



HID SPOT LIGHT

21W&35W/4"/7"/11"



Features & Specs

- High Intensity Discharge Super Bright Xenon Spot Light
- The super HID spot light can be used in many applications, such as searching, rescuing, camping, hunting and other outdoor activities
- Ballast & Starter integrated into the housing
- H3/35W/6000K/Xenon Bulb
- Harden Glass Lens
- Water and Dust Proof
- FAR DISTANCE White light can be seen for miles
- LONG LIFE 2500 hours life-10 times longer than halogen bulbs
- ENERGY SAVING 50% less energy consumption
- SUPER BRIGHT 3 times brighter than the same powered halogen bulb



1



HID SPOT LIGHT

21W&35W/4"/7"/11"



21W 3161



21W 3171



35W 3174

Product Specification


1.Power	21W+/-3W	21W+/-3W	35W+/-3W
2.Input Current	1.9A+/-0.1A	1.9A+/-0.1A	2.9A+/-0.1A
3.Max. Input Current	≤5A+/-1A	≤5A+/-1A	≤5A+/-1A
4.Adaptor	13.5V DC/0.3A/120V AC	13.5V DC/0.3A/120V AC	13.5V DC/0.5A/120V AC
5.Battery	12V/1.3Ah Sealed Lead Acid	12V/2.6Ah Sealed Lead Acid	12V/5Ah Sealed Lead Acid
6.Operation Voltage for Ballast	9V-16V DC	9V-16V DC	9V-16V DC
7.Output Voltage for Ballast	85V+/-17V	85V+/-17V	85V+/-17V
8.Candle Power	250,000CD	250,000CD	250,000CD
9.Bulb	H3/6000K/Xenon Bulb	H3/6000K/Xenon Bulb	H3/6000K/Xenon Bulb
10.Charging Time	5-6 hours	10-11 hours	10-11 hours
11.Continuous Work	15-20 minutes	45 minutes	60 minutes
12.Diameter of Lens	4 inch	4 inch	4 inch

General Specifications

Part number	3161	3171	3174
Unit dimensions(L*W*H) (Inch)	9.17*6.92*4.52	9.49*4.96*6.8	9.6*4.96*7.28
Unit weight (Pound)	4.4	4.4	6.16
Warranty	1 Year	1 Year	1 Year

Packaging Specifications

Packaging	Color Box	Color Box	Color Box
Packaging Dimension(L*W*H) (Inch)	10.63*8.54*6.3	10.63*8.54*6.3	10.63*8.54*6.3



2



HID SPOT LIGHT

21W&35W/4"/7"/11"



35W 3152



35W 3515

Product Specification


1.Power	35W+/-3W	35W+/-3W
2.Input Current	3.15A-3.3A	3.15A-3.3A
3.Max. Input Current	7.5A-8.5A	7.5A-8.5A
4.Adaptor	13.5V DC/0.5A/120V AC	13.8V DC/0.75A/120V AC
5.Battery	12V/5Ah Sealed Lead Acid	12V/5Ah Sealed Lead Acid
6.Operation Voltage for Ballast	9V-16V DC	9V-16V DC
7.Output Voltage for Ballast	85V+/-17V	85V+/-17V
8.Candle Power	500,000CD	1,000,000CD
9.Bulb	H3/6000K/Xenon Bulb	H3/6000K/Xenon Bulb
10.Charging Time	10-11 hours	7-8 hours
11.Continuous Work	60 minutes	60 minutes
12.Diameter of Lens	7 inch	11 inch

General Specifications

Part number	3152	3515
Unit dimensions(L*W*H) (Inch)	11.8*8.1*8.7	16.7*11*11.65
Unit weight (Pound)	8.8	12.76
Warranty	1 Year	1 Year

Packaging Specifications

Packaging	Color Box	Color Box
Packaging Dimension(L*W*H) (Inch)	13.92*9.92*10.43	18.7*12.44*13.78



3