

# 用户管理接口文档

# Overview

请勿随意测试删除类接口

## Version information

*Version* : V1.0.0

## Contact information

*Contact* : Clark

*Contact Email* : [1554711952@qq.com](mailto:1554711952@qq.com)

## License information

*License* : Apache

*License URL* : <http://www.apache.org/licenses/>

*Terms of service* : null

## URI scheme

*Host* : localhost:8081

*BasePath* : /seller

## Tags

- LogAPI : 日志相关
- LoginAPI : 用户登录相关
- PermissionAPI : 用户权限相关
- RoleAPI : 用户角色相关
- userAPI : 用户管理相关

## Paths

### 获取验证码

GET /seller/getCode

## Description

验证码在返回JSON中的msg部分

## Parameters

Type	Name	Description	Schema
Query	<b>username</b> <i>required</i>	用户名	string

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LoginAPI

## Example HTTP request

### Request path

```
/seller/getCode
```

### Request query

```
{
  "username" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除用户

POST /seller/log/deleteById

### Description

需要管理员权限

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data:id必须填写,其他的空缺	<a href="#">SysLogBean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

### Produces

- `application/json; charset=UTF-8`

### Tags

- LogAPI

## Example HTTP request

### Request path

```
/seller/log/deleteById
```

### Request header

```
"string"
```

### Request body

```
{
  "createTimeEnd" : "string",
  "createTimeStart" : "string",
  "id" : 0,
  "idList" : [ 0 ],
  "ip" : "string",
  "method" : "string",
  "param" : "string",
  "result" : "string",
  "timeUsed" : "string",
  "url" : "string",
  "user" : "string",
  "userAgent" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除用户组

```
POST /seller/log/deleteByIdList
```

## Description

需要管理员权限

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data:idList必须填写,其他空缺	<a href="#">SysLogBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- LogAPI

## Example HTTP request

### Request path

```
/seller/log/deleteByIdList
```

### Request header

```
"string"
```

### Request body

```
{
  "createTimeEnd" : "string",
  "createTimeStart" : "string",
  "id" : 0,
  "idList" : [ 0 ],
  "ip" : "string",
  "method" : "string",
  "param" : "string",
  "result" : "string",
  "timeUsed" : "string",
  "url" : "string",
  "user" : "string",
  "userAgent" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 组织列表

POST /seller/log/search

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	data:pageIndex, pageSize	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>postData</b> <i>required</i>	postData	PageRequestBean« SysLogBean»	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysLogBean»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LogAPI

## Example HTTP request

### Request path

```
/seller/log/search
```

### Request header

```
"string"
```

### Request body



```

{
  "data" : {
    "createTimeEnd" : "string",
    "createTimeStart" : "string",
    "id" : 0,
    "idList" : [ 0 ],
    "ip" : "string",
    "method" : "string",
    "param" : "string",
    "result" : "string",
    "timeUsed" : "string",
    "url" : "string",
    "user" : "string",
    "userAgent" : "string"
  },
  "pageIndex" : 0,
  "pageSize" : 0
}

```

## Example HTTP response

### Response 200

```

{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "createTimeEnd" : "string",
      "createTimeStart" : "string",
      "id" : 0,
      "idList" : [ 0 ],
      "ip" : "string",
      "method" : "string",
      "param" : "string",
      "result" : "string",
      "timeUsed" : "string",
      "url" : "string",
      "user" : "string",
      "userAgent" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}

```

# 数据清理

POST /seller/log/shrink

## Description

需要管理员权限

## Parameters

Type	Name	Description	Schema	Default
Header	Authorization required	Authorization	string	"UTF-8"
Header	Token required	登录成功时从服务获得的Token	string	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LogAPI

## Example HTTP request

### Request path

/seller/log/shrink

## Request header

```
"string"
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 登录

```
POST /seller/login
```

## Description

返回的Header中Token需要保存，用于其他操作的Authorization

## Parameters

Type	Name	Description	Schema
Body	<b>loginBean</b> <i>required</i>	用户名,密码,验证码	<a href="#">LoginBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- LoginAPI

## Example HTTP request

### Request path

```
/seller/login
```

### Request body

```
{
  "code" : "string",
  "oldPassword" : "string",
  "password" : "string",
  "username" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 忘记密码重设

```
POST /seller/password/forget
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>loginBean</b> <i>required</i>	data:用户名,新密码,验证码	<a href="#">LoginBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LoginAPI

## Example HTTP request

### Request path

```
/seller/password/forget
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "oldPassword" : "string",
  "password" : "string",
  "username" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 修改密码

POST /seller/password/update

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>loginBean</b> <i>required</i>	data:用户名,旧密码,新密码	<a href="#">LoginBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LoginAPI

## Example HTTP request

### Request path

```
/seller/password/update
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "oldPassword" : "string",
  "password" : "string",
  "username" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除权限

```
POST /seller/permission/delete
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的空缺	<a href="#">SysPermissionBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/delete
```

### Request header

```
"string"
```



## Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "rank" : 0,
  "status" : 0,
  "sysPermissionGroupId" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除权限组

POST /seller/permission/group/delete

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的空缺	<a href="#">SysPermissionGroup Bean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content

HTTP Code	Description	Schema
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/group/delete
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 增加权限组

POST /seller/permission/group/insert

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: 名字必须填写,其他的可以空缺	<a href="#">SysPermissionGroup Bean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

### Produces

- `application/json; charset=UTF-8`

### Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/group/insert
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 权限组列表

```
GET /seller/permission/group/list
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	Authorization <i>required</i>	Authorization	string	"UTF-8"

Type	Name	Description	Schema	Default
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«ArrayList«SysPermissionGroupBean»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/group/list
```

### Request header

```
"string"
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ {
    "code" : "string",
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string"
  } ],
  "msg" : "string"
}
```

## 更新权限组信息

POST /seller/permission/group/update

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的可以空缺	<a href="#">SysPermissionGroup Bean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/group/update
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 增加权限

```
POST /seller/permission/insert
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data: 权限名,编码,祖ID必须填写,其他的可以空缺	<a href="#">SysPermissionBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/insert
```

### Request header



```
"string"
```

## Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "rank" : 0,
  "status" : 0,
  "sysPermissionGroupId" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 查询权限列表

```
POST /seller/permission/list
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	data:pageIndex, pageSize	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>postData</b> <i>required</i>	postData	<a href="#">PageRequestBean«SysPermissionBean»</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysPermissionBean»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/list
```

### Request header

```
"string"
```

### Request body

```
{
  "data" : {
    "code" : "string",
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "rank" : 0,
    "status" : 0,
    "sysPermissionGroupId" : 0
  },
  "pageIndex" : 0,
  "pageSize" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "code" : "string",
      "description" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "rank" : 0,
      "status" : 0,
      "sysPermissionGroupId" : 0
    } ],
    "total" : 0
  },
  "msg" : "string"
}
```

## 权限列表

GET /seller/permission/listAll

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«ArrayList«SysPermissionBean»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/listAll
```

### Request header

```
"string"
```

## Example HTTP response

### Response 200

```

{
  "code" : 0,
  "data" : [ {
    "code" : "string",
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "rank" : 0,
    "status" : 0,
    "sysPermissionGroupId" : 0
  } ],
  "msg" : "string"
}

```

## 权限组内权限列表

GET /seller/permission/listByGroupId

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>groupId</b> <i>required</i>	权限组Id	integer (int64)

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«ArrayList«SysPermissionBean»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/listByGroupId
```

### Request header

```
"string"
```

### Request query

```
{  
  "groupId" : 0  
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ {
    "code" : "string",
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "rank" : 0,
    "status" : 0,
    "sysPermissionGroupId" : 0
  } ],
  "msg" : "string"
}
```

## 角色权限ID列表

GET /seller/permission/listByRole

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>roleId</b> <i>required</i>	Role Id	integer (int64)

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«long»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/listByRole
```

### Request header

```
"string"
```

### Request query

```
{  
  "roleId" : 0  
}
```

## Example HTTP response

### Response 200

```
{  
  "code" : 0,  
  "data" : [ 0 ],  
  "msg" : "string"  
}
```

## 更新权限信息

```
POST /seller/permission/update
```

## Description

Header中必须包含Token



## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的可以空缺	<a href="#">SysPermissionBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- PermissionAPI

## Example HTTP request

### Request path

```
/seller/permission/update
```

### Request header

```
"string"
```

## Request body

```
{
  "code" : "string",
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "rank" : 0,
  "status" : 0,
  "sysPermissionGroupId" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除角色

POST /seller/role/deleteById

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的空缺	<a href="#">UserRolePermission Bean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content

HTTP Code	Description	Schema
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/deleteById
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "permissionCodes" : [ "string" ],
  "permissionGroups" : [ 0 ],
  "rank" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 增加角色

POST /seller/role/insert

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization required</b>	Authorization	string	"UTF-8"
Header	<b>Token required</b>	登录成功时从服务获得的Token	string	
Body	<b>data required</b>	data: 名称必须填写,其他的可以空缺	<a href="#">UserRolePermissionBean</a>	

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

### Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/insert
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "permissionCodes" : [ "string" ],
  "permissionGroups" : [ 0 ],
  "rank" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 角色列表

```
POST /seller/role/list
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>postData</b> <i>required</i>	data:pageIndex, pageSize	<a href="#">PageRequestBean«SysUserBean»</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysRoleBean»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/list
```

### Request header

```
"string"
```

### Request body

```
{
  "data" : {
    "address" : "string",
    "birth" : "string",
    "createBy" : "string",
    "createTime" : "string",
    "email" : "string",
    "enName" : "string",
    "id" : 0,
    "loginName" : "string",
    "organizationId" : 0,
    "password" : "string",
    "permissionIds" : [ 0 ],
    "phone" : "string",
    "sex" : 0,
    "updateBy" : "string",
    "updateTime" : "string",
    "zhName" : "string"
  },
  "pageIndex" : 0,
  "pageSize" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "createBy" : 0,
      "createTime" : "string",
      "description" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "organizationId" : [ 0 ],
      "rank" : 0,
      "status" : 0,
      "sysPermissionIds" : [ 0 ],
      "updateBy" : 0,
      "updateTime" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}
```

## 基于当前用户的角色列表

GET /seller/role/listByUser

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«SysRoleBean»»</a>



HTTP Code	Description	Schema
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/listByUser
```

### Request header

```
"string"
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ {
    "createBy" : 0,
    "createTime" : "string",
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "organizationId" : [ 0 ],
    "rank" : 0,
    "status" : 0,
    "sysPermissionIds" : [ 0 ],
    "updateBy" : 0,
    "updateTime" : "string"
  } ],
  "msg" : "string"
}
```

## 角色列表

POST /seller/role/listSpecial

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>postData</b> <i>required</i>	data	<a href="#">UserRolePermissionBean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«UserRolePermissionBean»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content

HTTP Code	Description	Schema
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/listSpecial
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "permissionCodes" : [ "string" ],
  "permissionGroups" : [ 0 ],
  "rank" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ {
    "description" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "permissionCodes" : [ "string" ],
    "permissionGroups" : [ 0 ],
    "rank" : 0
  } ],
  "msg" : "string"
}
```

## 子组织列表

GET /seller/role/org/childrenList

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>id</b> <i>required</i>	current organization id	integer (int64)

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysOrganizationTree»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/childrenList
```

### Request header

```
"string"
```

### Request query

```
{  
  "id" : 0  
}
```

## Example HTTP response

### Response 200

```

{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "children" : [ {
        "children" : [ "..." ],
        "createBy" : 0,
        "createTime" : "string",
        "description" : "string",
        "fullName" : "string",
        "id" : 0,
        "isFinal" : 0,
        "name" : "string",
        "parentId" : 0,
        "rank" : 0,
        "status" : 0,
        "updateBy" : 0,
        "updateTime" : "string"
      } ],
      "createBy" : 0,
      "createTime" : "string",
      "description" : "string",
      "fullName" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "parentId" : 0,
      "rank" : 0,
      "status" : 0,
      "updateBy" : 0,
      "updateTime" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}

```

## 删除组织

POST /seller/role/org/delete

### Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的空缺	<a href="#">SysOrganizationList Bean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/delete
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "fullName" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "parentId" : 0,
  "rank" : 0,
  "roleIds" : [ 0 ],
  "roles" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 增加组织

POST /seller/role/org/insert

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data: 名称,全名必须填写,其他的可以空缺	<a href="#">SysOrganizationLi</a> <a href="#">stBean</a>	

## Responses



HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/insert
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "fullName" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "parentId" : 0,
  "rank" : 0,
  "roleIds" : [ 0 ],
  "roles" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 组织列表

POST /seller/role/org/list

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>postData</b> <i>required</i>	data:pageIndex, pageSize, id	<a href="#">PageRequestBean«SysUserBean»</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysOrganizationTree»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/list
```

### Request header

```
"string"
```

### Request body

```
{
  "data" : {
    "address" : "string",
    "birth" : "string",
    "createBy" : "string",
    "createTime" : "string",
    "email" : "string",
    "enName" : "string",
    "id" : 0,
    "loginName" : "string",
    "organizationId" : 0,
    "password" : "string",
    "permissionIds" : [ 0 ],
    "phone" : "string",
    "sex" : 0,
    "updateBy" : "string",
    "updateTime" : "string",
    "zhName" : "string"
  },
  "pageIndex" : 0,
  "pageSize" : 0
}
```

## Example HTTP response

### Response 200

```

{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "children" : [ {
        "children" : [ "..." ],
        "createBy" : 0,
        "createTime" : "string",
        "description" : "string",
        "fullName" : "string",
        "id" : 0,
        "isFinal" : 0,
        "name" : "string",
        "parentId" : 0,
        "rank" : 0,
        "status" : 0,
        "updateBy" : 0,
        "updateTime" : "string"
      } ],
      "createBy" : 0,
      "createTime" : "string",
      "description" : "string",
      "fullName" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "parentId" : 0,
      "rank" : 0,
      "status" : 0,
      "updateBy" : 0,
      "updateTime" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}

```

## 查询组织信息列表

GET /seller/role/org/listAll

### Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«SysOrganizationListBean»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/listAll
```

### Request header

```
"string"
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ {
    "description" : "string",
    "fullName" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "parentId" : 0,
    "rank" : 0,
    "roleIds" : [ 0 ],
    "roles" : "string"
  } ],
  "msg" : "string"
}
```

## 查询组织

POST /seller/role/org/listSpecial

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>postData</b> <i>required</i>	data:pageIndex, pageSize	<a href="#">PageRequestBean«SysOrganizationListBean»</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«PageInfo«SysOrganizationListBean»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/listSpecial
```

### Request header

```
"string"
```

### Request body

```
{
  "data" : {
    "description" : "string",
    "fullName" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "parentId" : 0,
    "rank" : 0,
    "roleIds" : [ 0 ],
    "roles" : "string"
  },
  "pageIndex" : 0,
  "pageSize" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "description" : "string",
      "fullName" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "parentId" : 0,
      "rank" : 0,
      "roleIds" : [ 0 ],
      "roles" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}
```

## 组织层级列表

GET /seller/role/org/ranks

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«long»»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content



## Consumes

- `application/json`

## Produces

- `application/json;charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/ranks
```

### Request header

```
"string"
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ 0 ],
  "msg" : "string"
}
```

## 查询组织信息

```
GET /seller/role/org/selectById
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>id</b> <i>required</i>	data:pageIndex, pageSize	integer (int64)

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«SysOrganizationTree»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/selectById
```

### Request header

```
"string"
```

### Request query

```
{
  "id" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : {
    "children" : [ {
      "children" : [ "..." ],
      "createBy" : 0,
      "createTime" : "string",
      "description" : "string",
      "fullName" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "parentId" : 0,
      "rank" : 0,
      "status" : 0,
      "updateBy" : 0,
      "updateTime" : "string"
    } ],
    "createBy" : 0,
    "createTime" : "string",
    "description" : "string",
    "fullName" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "parentId" : 0,
    "rank" : 0,
    "status" : 0,
    "updateBy" : 0,
    "updateTime" : "string"
  },
  "msg" : "string"
}
```

## 查询组织分层信息

```
GET /seller/role/org/tree
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	Authorization required	Authorization	string	"UTF-8"
Header	Token required	登录成功时从服务获得的Token	string	

## Responses

HTTP Code	Description	Schema
200	OK	ResultObject«List«SysOrganizationTree»»
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- application/json

## Produces

- application/json; charset=UTF-8

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/tree
```

### Request header

```
"string"
```

## Example HTTP response

## Response 200

```
{
  "code" : 0,
  "data" : [ {
    "children" : [ {
      "children" : [ "..." ],
      "createBy" : 0,
      "createTime" : "string",
      "description" : "string",
      "fullName" : "string",
      "id" : 0,
      "isFinal" : 0,
      "name" : "string",
      "parentId" : 0,
      "rank" : 0,
      "status" : 0,
      "updateBy" : 0,
      "updateTime" : "string"
    } ],
    "createBy" : 0,
    "createTime" : "string",
    "description" : "string",
    "fullName" : "string",
    "id" : 0,
    "isFinal" : 0,
    "name" : "string",
    "parentId" : 0,
    "rank" : 0,
    "status" : 0,
    "updateBy" : 0,
    "updateTime" : "string"
  } ],
  "msg" : "string"
}
```

## 更新组织信息

POST /seller/role/org/update

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的可以空缺	<a href="#">SysOrganizationListBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/update
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "fullName" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "parentId" : 0,
  "rank" : 0,
  "roleIds" : [ 0 ],
  "roles" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 查询用户组织层次列表

```
GET /seller/role/org/userInTree
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>id</b> <i>required</i>	organization Id	integer (int64)

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«List«long»»</a>
401	Unauthorized	No Content

HTTP Code	Description	Schema
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/org/userInTree
```

### Request header

```
"string"
```

### Request query

```
{
  "id" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : [ 0 ],
  "msg" : "string"
}
```



# 查询角色信息

GET /seller/role/selectById

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	Token <i>required</i>	登录成功时从服务获得的Token	string
Query	id <i>required</i>	data:pageIndex, pageSize	integer (int64)

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«SysRoleBean»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- application/json

## Produces

- application/json;charset=UTF-8

## Tags

- RoleAPI

## Example HTTP request

### Request path

/seller/role/selectById

## Request header

```
"string"
```

## Request query

```
{  
  "id" : 0  
}
```

## Example HTTP response

### Response 200

```
{  
  "code" : 0,  
  "data" : {  
    "createBy" : 0,  
    "createTime" : "string",  
    "description" : "string",  
    "id" : 0,  
    "isFinal" : 0,  
    "name" : "string",  
    "organizationId" : [ 0 ],  
    "rank" : 0,  
    "status" : 0,  
    "sysPermissionIds" : [ 0 ],  
    "updateBy" : 0,  
    "updateTime" : "string"  
  },  
  "msg" : "string"  
}
```

## 更新角色信息

```
POST /seller/role/update
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data: ID必须填写,其他的可以空缺	UserRolePermissionBean	

## Responses

HTTP Code	Description	Schema
200	OK	ResultMsg
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- application/json

## Produces

- application/json;charset=UTF-8

## Tags

- RoleAPI

## Example HTTP request

### Request path

```
/seller/role/update
```

### Request header

```
"string"
```

### Request body

```
{
  "description" : "string",
  "id" : 0,
  "isFinal" : 0,
  "name" : "string",
  "permissionCodes" : [ "string" ],
  "permissionGroups" : [ 0 ],
  "rank" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 删除用户

POST /seller/user/deleteByName

## Description

需要管理员权限

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data:用户名,必须填写,其他的可以空缺	<a href="#">LoginBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content

HTTP Code	Description	Schema
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

```
/seller/user/deleteByName
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "oldPassword" : "string",
  "password" : "string",
  "username" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

# 获取用户信息

GET /seller/user/info

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Query	<b>username</b> <i>required</i>	用户名	string

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«SysUserBean»</a>
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

/seller/user/info

## Request header

```
"string"
```

## Request query

```
{  
  "username" : "string"  
}
```

## Example HTTP response

### Response 200

```
{  
  "code" : 0,  
  "data" : {  
    "address" : "string",  
    "birth" : "string",  
    "createBy" : "string",  
    "createTime" : "string",  
    "email" : "string",  
    "enName" : "string",  
    "id" : 0,  
    "loginName" : "string",  
    "organizationId" : 0,  
    "password" : "string",  
    "permissionIds" : [ 0 ],  
    "phone" : "string",  
    "sex" : 0,  
    "updateBy" : "string",  
    "updateTime" : "string",  
    "zhName" : "string"  
  },  
  "msg" : "string"  
}
```

## 注册

```
POST /seller/user/insert
```

## Description

需要先获取验证码

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	data:用户名,密码,必须填写,其他的可以空缺	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>data</b> <i>required</i>	data	<a href="#">SysUserBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

```
/seller/user/insert
```

### Request header

```
"string"
```



## Request body

```
{
  "address" : "string",
  "birth" : "string",
  "createBy" : "string",
  "createTime" : "string",
  "email" : "string",
  "enName" : "string",
  "id" : 0,
  "loginName" : "string",
  "organizationId" : 0,
  "password" : "string",
  "permissionIds" : [ 0 ],
  "phone" : "string",
  "sex" : 0,
  "updateBy" : "string",
  "updateTime" : "string",
  "zhName" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 查询用户列表

POST /seller/user/list

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	data:搜索条件	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	
Body	<b>postData</b> <i>required</i>	postData	<a href="#">SysUserSearchBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultObject«Page Info«SysUserBean»»</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

```
/seller/user/list
```

### Request header

```
"string"
```

### Request body

```
{
  "address" : "string",
  "birth" : "string",
  "code" : "string",
  "createBy" : "string",
  "createTimeEnd" : "string",
  "createTimeStart" : "string",
  "email" : "string",
  "enName" : "string",
  "loginName" : "string",
  "pageIndex" : 0,
  "pageSize" : 0,
  "password" : "string",
  "phone" : "string",
  "sex" : 0,
  "updateBy" : "string",
  "updateTimeEnd" : "string",
  "updateTimeStart" : "string",
  "zhName" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "data" : {
    "pageSize" : 0,
    "rows" : [ {
      "address" : "string",
      "birth" : "string",
      "createBy" : "string",
      "createTime" : "string",
      "email" : "string",
      "enName" : "string",
      "id" : 0,
      "loginName" : "string",
      "organizationId" : 0,
      "password" : "string",
      "permissionIds" : [ 0 ],
      "phone" : "string",
      "sex" : 0,
      "updateBy" : "string",
      "updateTime" : "string",
      "zhName" : "string"
    } ],
    "total" : 0
  },
  "msg" : "string"
}
```

## 更新用户权限

POST /seller/user/permission/update

### Description

Header中必须包含Token

### Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>data</b> <i>required</i>	data:用户ID, 权限ID	<a href="#">SysUserPermissionBean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

```
/seller/user/permission/update
```

### Request header

```
"string"
```

### Request body

```
{
  "rolePermissionIds" : [ 0 ],
  "sysUserId" : 0
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 注册

POST /seller/user/registry

### Description

需要先获取验证码

### Parameters

Type	Name	Description	Schema
Body	<b>data</b> <i>required</i>	data:用户名,密码,验证码 必须填写,其他的可以空缺	<a href="#">UserRegistryBean</a>

### Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

### Consumes

- `application/json`

### Produces

- `application/json; charset=UTF-8`

### Tags

- userAPI

### Example HTTP request

## Request path

```
/seller/user/registry
```

## Request body

```
{
  "address" : "string",
  "birth" : "string",
  "code" : "string",
  "email" : "string",
  "enName" : "string",
  "loginName" : "string",
  "password" : "string",
  "phone" : "string",
  "sex" : 0,
  "zhName" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 更新用户信息

```
POST /seller/user/update
```

## Description

Header中必须包含Token

## Parameters

Type	Name	Description	Schema	Default
Header	<b>Authorization</b> <i>required</i>	Authorization	string	"UTF-8"
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string	

Type	Name	Description	Schema	Default
Body	<b>data</b> <i>required</i>	data:用户名 必须填写,其他的可以空缺	<a href="#">SysUserBean</a>	

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- userAPI

## Example HTTP request

### Request path

```
/seller/user/update
```

### Request header

```
"string"
```

### Request body



```
{
  "address" : "string",
  "birth" : "string",
  "createBy" : "string",
  "createTime" : "string",
  "email" : "string",
  "enName" : "string",
  "id" : 0,
  "loginName" : "string",
  "organizationId" : 0,
  "password" : "string",
  "permissionIds" : [ 0 ],
  "phone" : "string",
  "sex" : 0,
  "updateBy" : "string",
  "updateTime" : "string",
  "zhName" : "string"
}
```

## Example HTTP response

### Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

## 登出

POST /seller/userLogout

## Description

密码不需要

## Parameters

Type	Name	Description	Schema
Header	<b>Token</b> <i>required</i>	登录成功时从服务获得的Token	string
Body	<b>username</b> <i>required</i>	body: 用户名	<a href="#">LoginBean</a>

## Responses

HTTP Code	Description	Schema
200	OK	<a href="#">ResultMsg</a>
201	Created	No Content
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

## Consumes

- `application/json`

## Produces

- `application/json; charset=UTF-8`

## Tags

- LoginAPI

## Example HTTP request

### Request path

```
/seller/userLogout
```

### Request header

```
"string"
```

### Request body

```
{
  "code" : "string",
  "oldPassword" : "string",
  "password" : "string",
  "username" : "string"
}
```

## Example HTTP response

## Response 200

```
{
  "code" : 0,
  "msg" : "string"
}
```

# Definitions

## LoginBean

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : "string"	string
<b>oldPassword</b> <i>optional</i>	Example : "string"	string
<b>password</b> <i>optional</i>	Example : "string"	string
<b>username</b> <i>optional</i>	Example : "string"	string

## PageInfo«SysLogBean»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysLogBean" ]	< SysLogBean > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageInfo«SysOrganizationListBean»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysOrganizationListBean" ]	< SysOrganizationList Bean > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageInfo«SysOrganizationTree»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysOrganizationTree" ]	< SysOrganizationTree > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageInfo«SysPermissionBean»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysPermissionBean" ]	< SysPermissionBean > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageInfo«SysRoleBean»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysRoleBean" ]	< SysRoleBean > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageInfo«SysUserBean»

Name	Description	Schema
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>rows</b> <i>optional</i>	Example : [ "SysUserBean" ]	< SysUserBean > array
<b>total</b> <i>optional</i>	Example : 0	integer (int32)

## PageRequestBean«SysLogBean»

Name	Description	Schema
<b>data</b> <i>optional</i>	Example : " <a href="#">SysLogBean</a> "	<a href="#">SysLogBean</a>
<b>pageIndex</b> <i>optional</i>	Example : 0	integer (int32)
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)

## PageRequestBean«SysOrganizationListBean»

Name	Description	Schema
<b>data</b> <i>optional</i>	Example : " <a href="#">SysOrganizationListBean</a> "	<a href="#">SysOrganizationListBean</a>
<b>pageIndex</b> <i>optional</i>	Example : 0	integer (int32)
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)

## PageRequestBean«SysPermissionBean»

Name	Description	Schema
<b>data</b> <i>optional</i>	Example : " <a href="#">SysPermissionBean</a> "	<a href="#">SysPermissionBean</a>
<b>pageIndex</b> <i>optional</i>	Example : 0	integer (int32)
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)

## PageRequestBean«SysUserBean»

Name	Description	Schema
<b>data</b> <i>optional</i>	Example : " <a href="#">SysUserBean</a> "	<a href="#">SysUserBean</a>
<b>pageIndex</b> <i>optional</i>	Example : 0	integer (int32)
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)

## ResultMsg

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«ArrayList«SysPermissionBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "SysPermissionBean" ]	< SysPermissionBean > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«ArrayList«SysPermissionGroupBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "SysPermissionGroupBean" ]	< SysPermissionGroupBean > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«List«SysOrganizationListBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "SysOrganizationListBean" ]	< SysOrganizationListBean > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«List«SysOrganizationTree»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "SysOrganizationTree" ]	< SysOrganizationTree > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«List«SysRoleBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "SysRoleBean" ]	< SysRoleBean > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«List«UserRolePermissionBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ "UserRolePermissionBean" ]	< UserRolePermission Bean > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«List«long»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysLogBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysLogBean "	PageInfo«SysLogBean»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysOrganizationListBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysOrganizationListBean "	PageInfo«SysOrganizationListBean»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysOrganizationTree»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysOrganizationTree "	PageInfo«SysOrganizationTree»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysPermissionBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysPermissionBean "	PageInfo«SysPermissionBean»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysRoleBean»»



Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysRoleBean "	PageInfo«SysRoleBean»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«PageInfo«SysUserBean»»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "PageInfo SysUserBean "	PageInfo«SysUserBean»
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«SysOrganizationTree»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "SysOrganizationTree"	SysOrganizationTree
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«SysRoleBean»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "SysRoleBean"	SysRoleBean
<b>msg</b> <i>optional</i>	Example : "string"	string

## ResultObject«SysUserBean»

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : 0	integer (int32)
<b>data</b> <i>optional</i>	Example : "SysUserBean"	SysUserBean
<b>msg</b> <i>optional</i>	Example : "string"	string

## SysLogBean

Name	Description	Schema
<b>createTimeEnd</b> <i>optional</i>	Example : "string"	string
<b>createTimeStart</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>idList</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>ip</b> <i>optional</i>	Example : "string"	string
<b>method</b> <i>optional</i>	Example : "string"	string
<b>param</b> <i>optional</i>	Example : "string"	string
<b>result</b> <i>optional</i>	Example : "string"	string
<b>timeUsed</b> <i>optional</i>	Example : "string"	string
<b>url</b> <i>optional</i>	Example : "string"	string
<b>user</b> <i>optional</i>	Example : "string"	string
<b>userAgent</b> <i>optional</i>	Example : "string"	string

## SysOrganizationListBean

Name	Description	Schema
<b>description</b> <i>optional</i>	Example : "string"	string

Name	Description	Schema
<b>fullName</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string
<b>parentId</b> <i>optional</i>	Example : 0	integer (int64)
<b>rank</b> <i>optional</i>	Example : 0	integer (int64)
<b>roleIds</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>roles</b> <i>optional</i>	Example : "string"	string

## SysOrganizationTree

Name	Description	Schema
<b>children</b> <i>optional</i>	Example : [ "SysOrganizationTree" ]	< SysOrganizationTree > array
<b>createBy</b> <i>optional</i>	Example : 0	integer (int64)
<b>createTime</b> <i>optional</i>	Example : "string"	string (date-time)
<b>description</b> <i>optional</i>	Example : "string"	string
<b>fullName</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string
<b>parentId</b> <i>optional</i>	Example : 0	integer (int64)
<b>rank</b> <i>optional</i>	Example : 0	integer (int64)

Name	Description	Schema
<b>status</b> <i>optional</i>	Example : 0	integer (int32)
<b>updateBy</b> <i>optional</i>	Example : 0	integer (int64)
<b>updateTime</b> <i>optional</i>	Example : "string"	string (date-time)

## SysPermissionBean

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : "string"	string
<b>description</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string
<b>rank</b> <i>optional</i>	Example : 0	integer (int64)
<b>status</b> <i>optional</i>	Example : 0	integer (int32)
<b>sysPermissionGroupId</b> <i>optional</i>	Example : 0	integer (int64)

## SysPermissionGroupBean

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : "string"	string
<b>description</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string

## SysRoleBean

Name	Description	Schema
<b>createBy</b> <i>optional</i>	Example : 0	integer (int64)
<b>createTime</b> <i>optional</i>	Example : "string"	string (date-time)
<b>description</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string
<b>organizationId</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>rank</b> <i>optional</i>	Example : 0	integer (int64)
<b>status</b> <i>optional</i>	Example : 0	integer (int32)
<b>sysPermissionsIds</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>updateBy</b> <i>optional</i>	Example : 0	integer (int64)
<b>updateTime</b> <i>optional</i>	Example : "string"	string (date-time)

## SysUserBean

Name	Description	Schema
<b>address</b> <i>optional</i>	Example : "string"	string
<b>birth</b> <i>optional</i>	Example : "string"	string
<b>createBy</b> <i>optional</i>	Example : "string"	string
<b>createTime</b> <i>optional</i>	Example : "string"	string
<b>email</b> <i>optional</i>	Example : "string"	string

Name	Description	Schema
<b>enName</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>loginName</b> <i>optional</i>	Example : "string"	string
<b>organizationId</b> <i>optional</i>	Example : 0	integer (int64)
<b>password</b> <i>optional</i>	Example : "string"	string
<b>permissions</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>phone</b> <i>optional</i>	Example : "string"	string
<b>sex</b> <i>optional</i>	Example : 0	integer (int32)
<b>updateBy</b> <i>optional</i>	Example : "string"	string
<b>updateTime</b> <i>optional</i>	Example : "string"	string
<b>zhName</b> <i>optional</i>	Example : "string"	string

## SysUserPermissionBean

Name	Description	Schema
<b>rolePermissionIds</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>sysUserId</b> <i>optional</i>	Example : 0	integer (int64)

## SysUserSearchBean

Name	Description	Schema
<b>address</b> <i>optional</i>	Example : "string"	string
<b>birth</b> <i>optional</i>	Example : "string"	string

Name	Description	Schema
<b>code</b> <i>optional</i>	Example : "string"	string
<b>createBy</b> <i>optional</i>	Example : "string"	string
<b>createTimeEnd</b> <i>optional</i>	Example : "string"	string
<b>createTimeStart</b> <i>optional</i>	Example : "string"	string
<b>email</b> <i>optional</i>	Example : "string"	string
<b>enName</b> <i>optional</i>	Example : "string"	string
<b>loginName</b> <i>optional</i>	Example : "string"	string
<b>pageIndex</b> <i>optional</i>	Example : 0	integer (int32)
<b>pageSize</b> <i>optional</i>	Example : 0	integer (int32)
<b>password</b> <i>optional</i>	Example : "string"	string
<b>phone</b> <i>optional</i>	Example : "string"	string
<b>sex</b> <i>optional</i>	Example : 0	integer (int32)
<b>updateBy</b> <i>optional</i>	Example : "string"	string
<b>updateTimeEnd</b> <i>optional</i>	Example : "string"	string
<b>updateTimeStart</b> <i>optional</i>	Example : "string"	string
<b>zhName</b> <i>optional</i>	Example : "string"	string

## UserRegistryBean

Name	Description	Schema
<b>address</b> <i>optional</i>	Example : "string"	string

Name	Description	Schema
<b>birth</b> <i>optional</i>	Example : "string"	string
<b>code</b> <i>optional</i>	Example : "string"	string
<b>email</b> <i>optional</i>	Example : "string"	string
<b>enName</b> <i>optional</i>	Example : "string"	string
<b>loginName</b> <i>optional</i>	Example : "string"	string
<b>password</b> <i>optional</i>	Example : "string"	string
<b>phone</b> <i>optional</i>	Example : "string"	string
<b>sex</b> <i>optional</i>	Example : 0	integer (int32)
<b>zhName</b> <i>optional</i>	Example : "string"	string

## UserRolePermissionBean

Name	Description	Schema
<b>description</b> <i>optional</i>	Example : "string"	string
<b>id</b> <i>optional</i>	Example : 0	integer (int64)
<b>isFinal</b> <i>optional</i>	Example : 0	integer (int32)
<b>name</b> <i>optional</i>	Example : "string"	string
<b>permissionCodes</b> <i>optional</i>	Example : [ "string" ]	< string > array
<b>permissionGroups</b> <i>optional</i>	Example : [ 0 ]	< integer (int64) > array
<b>rank</b> <i>optional</i>	Example : 0	integer (int64)