

# Message Passing

CS511

# Erlang System

Message Passing

Exceptions


Links and Monitors

# Interaction Models

- ▶ Previously
  - ▶ Shared memory (low-level, non-structured)
  - ▶ Semaphores (low-level, non-structured)
  - ▶ Monitors (popular, structured, encapsulate synchronization)
- ▶ So what's the problem with monitors?
  - ▶ Highly centralized (un/blocking processes, maintaining queues of blocked processes, encapsulating data)
  - ▶ For modern, distributed architectures, need for less centralized solution
  - ▶ Turn to interaction through communication rather than sharing

# Erlang System

- Consists of a number of distributed Erlang runtime systems communicating with each other (instances of the VM)



# Nodes and Processes in Erlang

- ▶ Each such runtime system is called a **node**
  - ▶ node name is an atom `name@host`
    - ▶ `name` is the name given by the user
    - ▶ `host` is the full host name if long names are used, or the first part of the host name if short names are used
- ▶ The name of a node may be consulted using `node()`

```
1 1> node().  
2 nonode@nohost
```

# Processes and Communication in Erlang

- ▶ A **process** in a node has

- ▶ a process id (pid)

```
1 1> self().  
2 <0.78.0>
```

- ▶ its own memory (a mailbox, a heap and a stack); and
  - ▶ a process control block (PCB) with information about the process.
- ▶ Message passing between processes at different nodes, as well as links and monitors, are transparent when pids are used
    - ▶ Registered names, however, are local to each node.
  - ▶ Format of a PID:
    - ▶ node id where process lives; 0 if node is local
    - ▶ process index itself (index into process table)
    - ▶ serial which increases every time MAXPROCS has been reached.

Erlang System

Message Passing

Exceptions

Links and Monitors

# The Message Passing Model

- ▶ No shared memory
  - ▶ A process sends a message
  - ▶ Another process receives the message

- ▶ Operations:

```
receive(Var);  
send(PID,msg);
```

- ▶ `receive` blocks until a message is available in the mailbox
  - ▶ `send(PID,msg)` is non-blocking; it sends message `msg` to process `PID`
- ▶ This model is the **asynchronous communication model** and is the one used in Erlang



# A Simple Echo Server

- ▶ Process `echo` will receive a message and then send it back to the sender
- ▶ After that it will continue to wait for a new message
- ▶ It may be stopped by sending it the `stop` message

```
1 echo() ->
2   receive
3     {From, Msg} ->
4       From ! {Msg},
5       echo();
6   stop -> true
7 end.
```

- ▶ Processes are created using `spawn/1` and `spawn/3`

# A Simple Echo Server (cont.)

```
1 -module(echo).
2 -export([start/0]).
3
4 echo() ->
5     receive
6         {From, Msg} ->
7             From ! {Msg},
8             echo();
9         stop -> true
10    end.
11
12 start() ->
13     Pid = spawn(fun echo/0), % Returns pid of a new process
14         % started by the application of echo/0 to []
15     Token = "Hello Server!", % Sending tokens to the server
16     Pid ! {self(), Token},
17     io:format("Sent ~s~n",[Token]),
18     receive
19         {Msg} ->
20             io:format("Received ~s~n", [Msg])
21     end,
22     Pid ! stop. % Stop server
```

# A Simple Echo Server

```
1 1> echo:start( ).
2 Sent Hello Server!
3 Received Hello Server!
4 stop
```

If we export `echo/0` we can spawn from the interpreter:


```
1 59> X=spawn(fun echo:echo/0).
2 <0.198.0>
3 60> X!{self(), "hello"}.
4 {<0.60.0>, "hello"}
5 61> X.
6 <0.198.0>
```

Note: the value of a send is the value of the message

# Reacting to Multiple Messages


- ▶ Erlang “listens” for messages from different senders
- ▶ In which order will they be processed?
- ▶ Can we force an order?
- ▶ A receive statement tries to find a match as early in the mailbox as it can

```
1 receive  
2     msg3 -> 42  
3 end
```



# Reacting to Multiple Messages


```
1 receive
2   msg4 -> 42
3 end
```



# Reacting to Multiple Messages

Waiting for multiple messages


```
1 receive
2   msg4 -> 42;
3   _    -> 41
4 end
```



- The oldest message is tried against every pattern of the receive until one of them matches

# Sources of Multiple Messages

Multiple messages can come from different processes



- ▶ How do we know who sent a message?
- ▶ Distinguish the source by Pids

# Sources of Multiple Messages

```
1 -module(echo2).  
2 -export([start/0]).  
3  
4 echo() ->  
5     receive  
6         {From, Msg} ->  
7             timer:sleep(rand:uniform(100)),  
8             From ! {Msg},  
9             echo();  
10        stop ->  
11            true  
12    end.  
13  
14 % continued on next slide...
```

- ▶ `timer:sleep(N)` sleeps a process for `N` milliseconds
- ▶ `rand:uniform(N)` produces a random integer between 1 and `N`



# Sources of Multiple Messages

```
1 start() ->
2     PidB = spawn(fun echo/0),
3     PidC = spawn(fun echo/0),
4
5     % sending tokens
6     Token = 42,
7     PidB ! {self(), Token},
8     io:format("Sent~w~n",[Token]),
9     Token2 = 41,
10    PidC ! {self(), Token2},
11    io:format("Sent~w~n",[Token2]),
12
13    % receive message
14    receive
15        {Msg} ->
16            io:format("Received ~w~n", [Msg])
17    end,
18
19    % stop echo-servers
20    PidB ! stop,
21    PidC ! stop.
```

# Sources of Multiple Messages

- ▶ How do we know who sent a message?
- ▶ Distinguish the source by Pids

```
1 -module(echo2).  
2 -export([start/0]).  
3  
4 echo() ->  
5     receive  
6         {From, Msg} ->  
7             timer:sleep(rand:uniform(100)),  
8             From ! {self(), Msg},  
9             echo();  
10        stop ->  
11            true  
12    end.  
13  
14 % continued on next slide...
```

# Sources of Multiple Messages

```
1 start() ->
2     PidB = spawn(fun echo/0),
3     PidC = spawn(fun echo/0),
4
5     % sending tokens
6     Token = 42,
7     PidB ! {self(), Token},
8     io:format("Sent ~w~n", [Token]),
9     Token2 = 41,
10    PidC ! {self(), Token2},
11    io:format("Sent ~w~n", [Token2]),
12
13    % receive messages
14    receive
15        {PidB, Msg} ->
16            io:format("Received from B: ~w~n", [Msg]) ;
17        {PidC, Msg} ->
18            io:format("Received from C: ~w~n", [Msg])
19    end,
20
21    % stop echo-servers
22    PidB ! stop,
23    PidC ! stop.
```

# Sources of Multiple Messages

```
1 11> echo2:start().
2 Sent42
3 Sent41
4 Received from B: 42
5 stop
6 12> echo2:start().
7 Sent42
8 Sent41
9 Received from B: 42
10 stop
11 13> echo2:start().
12 Sent42
13 Sent41
14 Received from C: 41
15 stop
16 14> echo2:start().
17 Sent42
18 Sent41
19 Received from B: 42
20 stop
```

# Sources of Multiple Messages

Multiple messages can come from the same processes

- ▶ Send several messages of the same shape and continue computing
- ▶ When receiving the responses, how can the code match them to the appropriate request?
- ▶ BIF `make_ref` provides globally unique reference objects (references for short) different from every other object in the Erlang system including remote nodes
- ▶ References can be used to uniquely identify messages

# Sources of Multiple Messages

```
1 -module(echo3).  
2 -export([start/0]).  
3  
4 echo() ->  
5     receive  
6         {From, Ref, Msg} ->  
7             From ! {self(), Ref, Msg},  
8             echo();  
9         stop ->  
10            true  
11     end.  
12  
13 % continues in next slide...
```

# Sources of Multiple Messages

```
1 start() ->
2   PidB = spawn(fun echo/0),
3   % sending tokens
4   Token = 42,
5   Ref = make_ref(),
6   PidB ! {self(), Ref, Token},
7   io:format("Sent~w~n",[Token]),
8   Token2 = 41,
9   Ref2 = make_ref(),
10  PidB ! {self(), Ref2, Token2},
11  io:format("Sent~w~n",[Token2]),
12  % receive messages
13  receive
14    {PidB, Ref2, Msg} ->
15      io:format("Received 41? ~w~n", [Msg]) ;
16    {PidB, Ref, Msg} ->
17      io:format("Received 42? ~w~n", [Msg])
18
19  end,
20
21  % stop echo-servers
22  PidB ! stop.
```

# Selective Receive

- ▶ Clauses can have guards
- ▶ Guards must be composed of terminating functions (BIFs)

```
1 receive
2   {Pid, Ref, N} when N>0 -> ...
```



# Timeouts

```
1 f(Pid) ->
2   receive
3     {Pid, Msg} -> Msg
4   after 3000 ->
5     timeout
6 end.
```

- ▶ The after part will be triggered if 3000 milliseconds have passed without receiving a message that matches the pattern.
- ▶ Other uses

```
1 sleep(T) ->
2   receive
3   after T ->
4     ok
5 end.
6
7 flush() ->
8   receive
9     _ -> flush()
10  after 0 ->
11    ok
12 end.
```

# Exercise

- ▶ Implement a semaphore
- ▶ Use the `when` clause

Template that you can start from:

```
1 -module(semaphore).  
2 -compile(export_all).  
3  
4 make_semaphore(Permits) ->  
5 spawn(?MODULE, semaphore, [Permits]).  
6  
7 % complete
```

- ▶ `?MODULE`: macro that refers to the name of the current module

# A Semaphore

```
1 -module(semaphore).
2 -compile(export_all).
3
4 make_semaphore(Permits) ->
5     spawn(?MODULE, semaphore, [Permits]).
6
7 semaphore(0) ->
8     receive
9         {From, Ref, release} ->
10             semaphore(1)
11     end;
12 semaphore(P) when P>0 ->
13     receive
14         {From, Ref, release} ->
15             From!{self(), Ref, ok},
16             semaphore(P+1);
17         {From, Ref, acquire} ->
18             From!{self(), Ref, ok},
19             semaphore(P-1)
20     end.
```

- semaphore could be specified as a FSM

## Semaphore - Print "a" before "b"

```
1 start() ->
2     S = make_semaphore(0),
3     spawn(?MODULE,p1,[S]),
4     spawn(?MODULE,p2,[S]).
5
6 release(S) -> % could be included in semaphore module
7     R = make_ref(),
8     S!{self(),R,release},
9     receive
10         {S,R,ok} ->
11             done
12     end.
13
14 p1(S) ->
15     io:format("a"),
16     release(S).
17
18 p2(S) -> % acquire is inlined
19     R = make_ref(),
20     S!{self(),R,acquire},
21     receive
22         {S,R,ok} ->
23             io:format("b")
24     end.
```

Erlang System

Message Passing

Exceptions

Links and Monitors

# Three Kinds of Exceptions

- ▶ Errors
  - ▶ Ends the execution in the current process and includes a stack trace of the last functions
  - ▶ Errors are the means for a function to stop its execution when you can't expect the calling code to handle what just happened
- ▶ Throws
  - ▶ Used for cases that the programmer can be expected to handle (`try...catch`).
- ▶ Exits
  - ▶ Same as errors except used to signal abnormal termination between processes.
  - ▶ More lightweight than errors in that stack trace not included

Note: `try...catch` actually can catch them all

## Errors – Example

```
1 1> erlang:error(badarith).
2 ** exception error: bad argument in an arithmetic expression
3 2> erlang:error(custom_error).
4 ** exception error: custom_error
5 3> catch(1+a).
6 {'EXIT',{badarith,[{erlang,'+',[1,a],[]},
7     {erl_eval,do_apply,6,[{file,"erl_eval.erl"},{line,681}]}},
8     {erl_eval,expr,5,[{file,"erl_eval.erl"},{line,434}]}},
9     {shell,exprs,7,[{file,"shell.erl"},{line,686}]}},
10    {shell,eval_exprs,7,[{file,"shell.erl"},{line,642}]}},
11    {shell,eval_loop,3,[{file,"shell.erl"},{line,627}]}}]}
```

Erlang System

Message Passing

Exceptions

Links and Monitors



# Links

- ▶ Pid1 can be linked to Pid2 by calling `link(Pid2)`
  - ▶ Creates a two-way link
- ▶ Terminating processes emit exit signals to all linked processes, which can terminate as well or handle the exit in some way.
- ▶ This feature can be used to build hierarchical program structures where some processes are supervising other processes, for example, restarting them if they terminate abnormally.

Note: Some comments on monitors are present at the end of these set of slides

# Example

```
1 -module(linkmon).
2 -compile(export_all).
3
4 myproc() ->
5     timer:sleep(2000),
6     exit(reason).
```

In the shell:

```
1 > c(linkmon).
2 {ok,linkmon}
3 > self().
4 <0.79.0>
5 > spawn(fun linkmon:myproc/0).
6 <0.75.0>
7 > self().
8 <0.79.0>
9 > link(spawn(fun linkmon:myproc/0)).
10 true
11 ** exception error: reason
12 > self().
13 <0.83.0>
```

## Another Example

```
1 chain(0) ->
2   receive
3     _ -> ok
4   after 2000 ->
5     exit("chain dies here")
6   end;
7
8 chain(N) ->
9   Pid = spawn(fun() -> chain(N-1) end),
10  link(Pid),
11  receive
12    _ -> ok
13  end.
```

In the shell:

```
1 1> c(linkmon).
2 {ok,linkmon}
3 2> link(spawn(linkmon, chain, [3])).
4 true
5 ** exception error: "chain dies here"
```

## Another Example (cont.)

```
[shell] == [3] == [2] == [1] == [0]
[shell] == [3] == [2] == [1] == *dead*
[shell] == [3] == [2] == *dead*
[shell] == [3] == *dead*
[shell] == *dead*
*dead, error message shown*
[shell] <-- restarted
```

- ▶ After the process running `linkmon:chain(0)` dies, the error is propagated down the chain of links until the shell process itself dies because of it.
- ▶ The crash could have happened in any of the linked processes
  - ▶ because links are bidirectional, you only need one of them to die for the others to follow suit.

# On Number of Links and Linking

- ▶ Links cannot be stacked.
  - ▶ Calling `link/1` multiple times for the same two processes, will still create only one link between them
  - ▶ A single call to `unlink/1` will be enough to tear it down.
- ▶ `link(spawn(Function))` or `link(spawn(M,F,A))` happens in more than one step. In some cases, it is possible for a process to die before the link has been set up and then provoke unexpected behavior.
  - ▶ `spawn_link/1-3` spawns and links as an atomic operation

# Trapping Exit Signals

- ▶ In order to be reliable, an application needs to be able to both kill and restart a process quickly.
  - ▶ Links convenient for the killing part but restarting is missing.
- ▶ When a linked process terminates, it terminates with an `exit reason` that is sent through a special message known as an `exit signal`
  - ▶ Eg. exit signal with exit reason `"chain dies here"`

```
exit("chain dies here")
```

# Trapping Exit Signals

- ▶ The default behaviour when a process receives an **exit signal** with an **exit reason** other than normal, is to terminate and in turn emit exit signals with the same exit reason to its linked processes.
- ▶ **System processes**: normal processes, except they can convert exit signals to regular messages.
  - ▶ Done by calling `process_flag(trap_exit, true)` in a running process.
- ▶ Allows a process to react to exit signals

# Chain Example Revisited

Chain example with a system process at the beginning

```
1 1> process_flag(trap_exit, true).
2 true
3 2> spawn_link(fun() -> linkmon:chain(3) end).
4 <0.49.0>
5 3> receive X -> X end.
6 {'EXIT', <0.49.0>, "chain dies here"}
```

Description of behavior:

```
[shell] == [3] == [2] == [1] == [0]
[shell] == [3] == [2] == [1] == *dead*
[shell] == [3] == [2] == *dead*
[shell] == [3] == *dead*
[shell] <-- {'EXIT',Pid,"chain dies here"} -- *dead*
[shell] <-- still alive!
```




# Kill Reason

- ▶ Acts as a special signal that can't be trapped.
- ▶ Ensures any process you terminate with it will be dead.
  - ▶ A last resort, when everything else has failed.
- ▶ As the kill reason can never be trapped, it needs to be changed to `killed` when other processes receive the message.
  - ▶ Otherwise, every other process linked to it would in turn die for the same kill reason and would in turn kill its neighbors, and so on.
  - ▶ This explains why `exit(kill)` looks like `killed` when received from another linked process.

```
1 > spawn_link(fun() -> exit(kill) end).  
2 ** exception exit: killed
```

# MSC for Critic Example



# Restarting Processes

```
1 start_critic() ->
2     spawn(?MODULE, critic, []).
3
4 judge(Pid, Band, Album) ->
5     Pid ! {self(), {Band, Album}},
6     receive
7         {Pid, Criticism} -> Criticism
8         after 2000 ->
9             timeout
10    end.
11
12 critic() ->
13    receive
14        {From, {"Rage Against the Turing Machine", "Unit Testify"}} ->
15            From ! {self(), "They are great!"};
16        {From, {"System of a Downtime", "Memoize"}} ->
17            From ! {self(), "They're not Johnny Crash but they're good."}
18        {From, {"Johnny Crash", "The Token Ring of Fire"}} ->
19            From ! {self(), "Simply incredible."};
20        {From, {_Band, _Album}} ->
21            From ! {self(), "They are terrible!"}
22    end,
23    critic().
```

# Restarting Processes


```
1 1> c(linkmon).
2 {ok,linkmon}
3 2> Critic = linkmon:start_critic().
4 <0.47.0>
5 3> linkmon:judge(Critic, "Genesis", "The Lambda Lies Down on Broad
6 "They are terrible!"
```

We now kill the Critic process

```
1 4> exit(Critic, solar_storm).
2 true
3 5> linkmon:judge(Critic, "Genesis", "A trick of the Tail Recursion
4 timeout
```

We need a “supervisor” process to keep critics alive

## MSC for Critic Example



# Restarting Processes

```
1 start_critic2() ->
2 spawn(?MODULE, restarter, []).
3
4 restarter() ->
5     process_flag(trap_exit, true),
6     Pid = spawn_link(?MODULE, critic, []),
7     receive
8         {'EXIT', Pid, normal} -> % not a crash
9         ok;
10        {'EXIT', Pid, shutdown} -> % manual termination, not a crash
11        ok;
12        {'EXIT', Pid, _} ->
13    restarter()
14 end.
```

Problem: Pid of the critic is part of internal state, it is not known

```
1 1> c(linkmon).
2 {ok,linkmon}
3 2> linkmon:start_critic2().
4 <0.48.0>
5 3> linkmon:judge(?????, "Genesis", "The Lambda Lies Down on Broadw
```

# Restarting Processes

- ▶ We can name a process, using an atom, rather than use its pid via `erlang:register/2`
- ▶ If a process dies, it will automatically lose its name or you can also use `unregister/1`
- ▶ You can get a list of all registered processes with `registered/0` or a more detailed one with the shell command `regs()`.

```
1 restarter() ->
2   process_flag(trap_exit, true),
3   Pid = spawn_link(?MODULE, critic, []),
4   register(critic, Pid),
5   receive
6     {'EXIT', Pid, normal} -> % not a crash
7       ok;
8     {'EXIT', Pid, shutdown} -> % manual termination, not a crash
9       ok;
10    {'EXIT', Pid, _} ->
11      restarter()
12  end.
```

What about the judge?

# Restarting a Process

```
1 judge2(Band, Album) ->
2   critic ! {self(), {Band, Album}},
3   Pid = whereis(critic),
4   receive
5     {Pid, Criticism} -> Criticism
6   after 2000 ->
7     timeout
8   end.
```



# Restarting a Process

```
1 1> linkmon:start_critic2().
2 <0.58.0>
3 2> whereis(critic).
4 <0.59.0>
5 3> linkmon:judge2("Genesis", "A trick of the Tail Recursion").
6 "They are terrible!"
7 4> exit(whereis(critic),solar_storm).
8 true
9 5> linkmon:judge2("Genesis", "A trick of the Tail Recursion").
10 "They are terrible!"
11 6> whereis(critic).
12 <0.63.0>
```

# Race Conditions due to Shared State

- ▶ `critic` is stored in a `shared` registry
- ▶ There are processes that read it such as `judge2`
- ▶ And processes that write to it such as `restarter`
- ▶ Race conditions are therefore possible

# Race Conditions due to Shared State – Example 1

1. critic ! Message
2. critic receives
3. critic replies
4. critic dies
5. whereis fails
6. critic is restarted
7. code crashes

```
1 judge2(Band, Album) ->
2   critic ! {self(), {Band, Album}},
3   %% critic dies at this point
4   %% register still not updated
5   Pid = whereis(critic), %% fails (returns undefined)
6   receive
7     {Pid, Criticism} -> Criticism %% undefined!=Pid
8   after 2000 ->
9     timeout
10  end.
```

## Race Conditions due to Shared State – Example 2

1. critic ! Message
2. critic receives
3. critic replies
4. critic dies
5. critic is restarted
6. whereis picks up wrong pid
7. message never matches

```
1 judge2(Band, Album) ->
2   critic ! {self(), {Band, Album}},
3   %% critic dies at this point
4   %% register updated with new Pid
5   Pid = whereis(critic), %% successful (but different Pid)
6   receive
7     {Pid, Criticism} -> Criticism %% no match
8   after 2000 ->
9     timeout
10  end.
```

- Both may be solved by replacing the use of `whereis` (and `Pid` matching) to that of reference matching

# Adding References to Messages

```
1 judge2(Band, Album) ->
2   Ref = make_ref(),
3   critic ! {self(), Ref, {Band, Album}},
4   receive
5     {Ref, Criticism} -> Criticism
6   after 2000 ->
7     timeout
8   end.
9
10 critic2() ->
11   receive
12     {From, Ref, {"Rage Against the Turing Machine", "Unit Testify"
13       From ! {Ref, "They are great!"};
14     {From, Ref, {"System of a Downtime", "Memoize"}} ->
15       From ! {Ref, "They're not Johnny Crash but they're good."};
16     {From, Ref, {"Johnny Crash", "The Token Ring of Fire"}} ->
17       From ! {Ref, "Simply incredible."};
18     {From, Ref, {_Band, _Album}} ->
19       From ! {Ref, "They are terrible!"}
20   end,
21   critic2().
```

Appendix: More on Exceptions

Appendix: Monitors

# Revisiting Exceptions – How Processes Trap Them

- ▶ `spawn_link(fun() ->ok end)`
  - ▶ Untrapped Result: Nothing
  - ▶ Trapped Result: `{'EXIT', <0.61.0>, normal}`
  - ▶ The process exited normally, without a problem.
- ▶ `spawn_link(fun() ->exit(reason) end)`
  - ▶ Untrapped Result: `** exception exit: reason`
  - ▶ Trapped Result: `{'EXIT', <0.55.0>, reason}`
  - ▶ The process has terminated for a custom reason.
- ▶ `spawn_link(fun() ->exit(normal) end)`
  - ▶ Untrapped Result: Nothing
  - ▶ Trapped Result: `{'EXIT', <0.58.0>, normal}`
  - ▶ Emulates process terminating normally.

# Revisiting Exceptions

- ▶ `spawn_link(fun() ->1/0 end)`
  - ▶ Untrapped Result:  
Error in process <0.44.0> with `exit` value: `{badarith, [{erlang, '/']}`
  - ▶ Trapped Result:  
`{'EXIT', <0.52.0>, {badarith, [{erlang, '/'}, [1,0]]}}`
- ▶ `spawn_link(fun() ->erlang:error(reason) end)`
  - ▶ Untrapped Result:  
Error in process <0.47.0> with `exit` value: `{reason, [{erlang, apply,`
  - ▶ Trapped Result:  
`{'EXIT', <0.74.0>, {reason, [{erlang, apply, 2}]}}`
  - ▶ Similar to 1/0.
- ▶ `spawn_link(fun() ->throw(rocks) end)`
  - ▶ Untrapped Result:  
Error in process <0.51.0> with `exit` value: `{{nocatch, rocks}, [{erlang,`
  - ▶ Trapped Result:  
`{'EXIT', <0.79.0>, {{nocatch, rocks}, [{erlang, apply, 2}]}}`
  - ▶ Because the throw is never caught by a try ... catch, it bubbles up into an error, which in turn bubbles up into an EXIT.  
Without trapping exit, the process fails.



## Revisiting Exceptions – the `exit/2` case

Allows a process to kill another one from a distance, safely

- ▶ `exit(self(), normal)`
  - ▶ Untrapped Result: `** exception exit: normal`
  - ▶ Trapped Result: `{'EXIT', <0.31.0>, normal}`
  - ▶ When not trapping exits, `exit(self(), normal)` acts the same as `exit(normal)`.
- ▶ `exit(spawn_link(fun() ->timer:sleep(50000) end), normal)`
  - ▶ Untrapped Result: `nothing`
  - ▶ Trapped Result: `nothing`
- ▶ `exit(spawn_link(fun() ->timer:sleep(50000) end), reason)`
  - ▶ Untrapped Result: `** exception exit: reason`
  - ▶ Trapped Result: `{'EXIT', <0.52.0>, reason}`

## Revisiting Exceptions – the `exit/2` case

- ▶ `exit(spawn_link(fun() ->timer:sleep(50000) end), kill)`
  - ▶ Untrapped Result: `** exception exit: killed`
  - ▶ Trapped Result: `{'EXIT', <0.58.0>, killed}`
- ▶ `exit(self(), kill)`
  - ▶ Untrapped Result: `** exception exit: killed`
  - ▶ Trapped Result: `** exception exit: killed`
- ▶ `spawn_link(fun() ->exit(kill) end)`
  - ▶ Untrapped Result: `** exception exit: killed`
  - ▶ Trapped Result: `{'EXIT', <0.67.0>, kill}`

# Monitors

- ▶ Special type of link with two differences
  - ▶ they are unidirectional,
  - ▶ can monitor via a registered name, and
  - ▶ they can be stacked.
- ▶ Allows a process to, unobtrusively, monitor another one
- ▶ Useful for when you have multiple libraries that you call and they all need to know whether a process is alive or not
  - ▶ You can stack links and remove them individually

# Example

`erlang:monitor/2` sets up a monitor, where the first argument is the atom `process` and the second one is the pid

```
1 1> erlang:monitor(process, spawn(fun() -> timer:sleep(500) end)).
2 #Ref<0.0.0.77>
3 2> flush().
4 Shell got {'DOWN', #Ref<0.0.0.77>, process, <0.63.0>, normal}
5 ok
```

- ▶ When monitored process goes down, send message to monitor: `{'DOWN', MonitorReference, process, Pid, Reason}`.
- ▶ The reference allows you to demonitor the process.
  - ▶ Monitors are stackable, so it's possible to take more than one down.
  - ▶ References allow you to track each of them in a unique manner.

# Example

Atomic function to spawn process while monitoring it:

```
1 3> {Pid, Ref} = spawn_monitor(fun() -> receive _ -> exit(boom) end  
2 {<0.73.0>, #Ref<0.0.0.100>}  
3 4> erlang:demonitor(Ref).  
4 true  
5 5> Pid ! die.  
6 die  
7 6> flush().  
8 ok
```

- ▶ We demonitored the other process before it crashed hence no trace of it dying.