

Attendances External API changes

This document details the most important changes to our external API following the update to our attendances flow. For full documentation please refer to the Swagger docs: [Swagger UI](#)

Get training(s)

API call:

Type call	API path	Params	Response
GET	/trainings/{id}	• Integer id	Training
GET	/trainings/team	<i>see Swagger docs</i>	Page<Training>

Models:

Important notes

The **trainers** field has been removed from these endpoints. To fetch the trainers (= staff) of a training, use the **/trainings/{id}/availablepresences** endpoint below.

Training

- Integer id
- AttendanceStatusEnum defaultAttendanceStatusPlayers *(new)*
- AttendanceStatusEnum defaultAttendanceStatusStaff *(new)*
- List<Member> trainers *(removed)*

Get available training presences

API call:

Type call	API path	Params	Response
GET	/trainings/{id}/availablepresences	• String from • String to	List of TrainingPresencePlayer or TrainingPresenceStaff objects, depending

		• Integer id • String teamGroupIds • Integer type • String memberStatus <i>(new)</i> ◦ PLAYER ◦ STAFF	on the memberStatus parameter.
--	--	--	--------------------------------

Models:

Important notes

The **attending** boolean was replaced by the new **attendanceStatus** field. This status can have one of the following 3 values:

- ABSENT
- UNANSWERED
- PRESENT

The new **attendanceChangedDate** field refers to the date a player- or staffmember changed their own attendance status.

TrainingPresence

- Integer id
- Integer trainingId *(new)*
- Training selectedTraining
- Integer memberId *(new)*
- Member player
- AttendanceStatusEnum attendanceStatus *(new)*
- String attendanceChangedDate *(new)*
- boolean extra

TrainingPresencePlayer

- fields of **TrainingPresence**
- String remarks
- boolean injury

- Member trainer
- Member other
- Integer testPeriodId
- Intensity playerIntensity
- Integer minutes
- boolean customMinutes
- EventScheduleStatus eventScheduleStatus

TrainingPresenceStaff

- fields of **TrainingPresence**

Get Game(s)

API call:

Type call	API path	Params	Response
GET	/games/{id}	• Integer id • boolean includeGameSelections <i>(new)</i>	Game
GET	/games/teams/{teamId}/seasons/{seasonId}	see Swagger docs	Page<Game>

Models:

Important notes

The `gameSelections` field still exists on the Game object, but is only filled in if the `includeGameSelections` parameter is true. It's highly recommended to use the GET `/games/{id}/gameSelections` endpoint instead.

Game

- Integer id

- AttendanceStatusEnum defaultAttendanceStatusPlayers *(new)*
- AttendanceStatusEnum defaultAttendanceStatusStaff *(new)*
- List<GameSelectionPlayer> gameSelections *(only filled in when includeGameSelections parameter is true)*
- ...

Get player gameSelection(s)

API call:

Type e call	API path	Params	Response
GET	/games/{id}/game selections	• Integer id	List<GameSelectionWithMemberPositionsD TO>

Models:

Important notes

The **player** field has been renamed to **member** .

GameSelectionWithMemberPositionsDTO

- Integer id
- AttendanceStatusEnum attendanceStatus *(new)*
- Member player ⇒ Member member *(property name changed)*
- ...

Get staff gameSelection(s)

API call:

Type e call	API path	Params	Response

GET	/games/{id}/game selections-staff	- Integer id - Integer teamId	List<GameSelectionStaff>
GET	/games/info/{infoId}	Integer id	GameInformation

Models:

Important notes

staff field on GameInformation objects is removed, use **/games/{id}/game selections-staff** instead.

GameInformation

- staff *(removed)*

GameSelectionStaff *(new)*

- Integer id
- Game game
- AbsenceReason absenceReason
- Absence absencePeriod
- AttendanceStatusEnum attendanceStatus
- String attendanceChangedDate
- Member member
- Team team
- SportiveRole sportiveRole

Get Calendar Event absences

API call:

Typ e call	API path	Params	Response
GET	/agenda/{id}/presences/{status}	- Integer id - ScheduleEventSearchStatus status	Page< ScheduleEventPresence >

- | | | | |
|--|--|---|--|
| | | <ul style="list-style-type: none">• MemberStatusEnum memberStatus | |
|--|--|---|--|

Models:

Important notes

The **absences** field on CalendarEvent objects has been removed. If you need to fetch the absences of a specific activity, use the **/agenda/{id}/presences/{status}** endpoint with the **status** parameter set to ABSENT.

present boolean field on ScheduleEventPresence has been replaced by **attendanceStatus**.

CalendarEvent

- List<CalendarEventAbsence> absences *(removed)*

ScheduleEventPresence

- boolean present *(removed)*
- AttendanceStatusEnum attendanceStatus *(new)*