

REMOVE HR Haze Removers

APPLICATIONS

Removes stains, haze and ghost images from mesh for screen recycling.

GENERAL CHARACTERISTICS

Remove HR1

- One part, ready-to-use gel
- Mesh safe - can be left on screen overnight.

Remove HR2

- One part, ready-to-use liquid
- Is able to remove the toughest stains
- Works in minutes.

Remove HR3

- One part, ready-to-use paste
- Is able to remove the toughest stains
- Works in minutes.

Remove HR5

- One part, ready-to-use gel
- Let sit on screen for a few minutes
- Fast application

Remove HR8

- One part, ready-to-use (cream)
- Let sit on screen for a few minutes
- Application with coating through

DIRECTIONS FOR USE

Remove HR1

After ink and stencil removal, apply gel and spread the screen with a stiff brush. Let dry - may be left overnight. The gel will not harm mesh. Rinse the screen with a high pressure wash.

Remove HR2

After ink and stencil removal, spray or pour liquid on screen and spread with a stiff brush. Let sit for approximately 10 minutes - a longer time may weaken mesh. Rinse screen with a pressure wash.

Remove HR3

After ink and stencil removal, spread paste on screen with a stiff brush. Let sit for approximately 10 minutes - a longer time may weaken mesh. Rinse screen with a pressure wash.

Remove HR5

After ink and stencil removal, apply gel on screen with a squeegee or brush. Let sit for maximum 5 minutes - a longer time may harm mesh. Rinse screen with a pressure wash.

Remove HR8

After ink and stencil removal, apply cream on screen with a coating through. Let sit for maximum 5 minutes ; a longer time may harm mesh Rinse screen with a pressure wash.

HEALTH AND SAFETY

Before using, refer to appropriate safety data sheets.

STORAGE

When sealed in the original container and stored in cool conditions, REMOVER HR will maintain original properties for 24 months from the date of production.

PACKAGING

Available in 1 and 5 kilogram containers.
 In North America, available in ¼ , 1, 5, and 50 US gallon containers

WARRANTY AND LIMITED REMEDY

The directions, recommendations and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: all Saatichem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in Saatichem applicable Product Bulletin. Saatichem will replace or refund the price of any Saatichem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall Saatichem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.