

H I G H P E R F O R M A N C E T R A N S M I S S I O N P A R T S

BENEFITS

- Offers largest apply area of any AOD servo
- Optional cushion springs allow maximum holding power while reducing excessive harshness
- Springs minimize 3-4 shift timing concerns that can occur when installing a larger overdrive servo
- Special servo pin with o-ring seals prevent oil leaks at the case pin bore



Part No.

76890-17K/17KP

"Super Hold" Servo Kits

4 Conical Washers

1 D-Ring Piston Seal

1 Spacer

1 Return Spring

1 Servo Pin

1 "E" Clip

1 Servo Piston

1 Servo Cover

-17K is non-anodized
-17KP is purple anodized

4 O-Rings

2 Washers

1 Gauge Tool

PART SUMMARY

In high performance applications where a larger servo is desired, the Sonnax "Super Hold" servo, **76890-17K** or **76890-17KP**, provides the largest apply area of any available AOD servo. The Sonnax servo is calibrated to progressively increase band apply force as line pressure increases. At lower line pressures, the apply force is close to the Ford "A" servo. At mid-to-high line pressure, the apply force is significantly higher than with any other AOD servo.

Also Available:

Part No.

76890-15K

Replacement Pin Kit

1 Servo Pin

1 "E" Clip

2 O-Rings

1 Gauge Tool

Part No.

76890-17SK

Replacement Seal Kit

1 D-Ring Piston Seal

4 O-Rings