

Algoritmos y Estructuras de Datos II

Primer Cuatrimestre de 2015

Departamento de Computación
Facultad de Ciencias Exactas y Naturales
Universidad de Buenos Aires

Trabajo Práctico 1

Especificación

Integrante	LU	Correo electrónico
BENITEZ, Nelson	945/13	nelson.benitez92@gmail.com
ROIZMAN, Violeta	273/11	violeroizman@gmail.com
VÍZQUEZ, Jéssica	318/13	jesis_93@hotmail.com
ZAVALLA, Agustín	670/13	nkm747@gmail.com

Reservado para la cátedra

Instancia	Docente	Nota
Primera entrega		
Segunda entrega		

Índice

1. TAD AS	3
2. TAD CAMPUS	9

1. TAD AS

TAD AS

géneros as

igualdad observacional

$$(\forall dc, dc' : \text{dcnet}) (dc =_{\text{obs}} dc' \iff ())$$

usa CAMPUS

exporta

observadores básicos

campus : as \rightarrow campus

seguridad : as \rightarrow conj(seguridad)

hayEst? : as $a \times \text{pos } p \rightarrow \text{bool}$

$$\{posValida(campus(a), p)\}$$

hayHippie? : as $a \times \text{pos } p \rightarrow \text{bool}$

$$\{posValida(campus(a), p)\}$$

#capturas : as $a \times \text{seg } s \rightarrow \text{nat}$

$$\{s \in seguridad(a)\}$$

#sanciones : as $a \times \text{seg } s \rightarrow \text{nat}$

$$\{s \in seguridad(a)\}$$

generadores

nueva : campus \times conj(seguridad) \rightarrow as

$$\{(\forall segs:e) posValida(c, pos(e)) \wedge (\forall segs:s, s1) id(s) \neq id(s1) \Rightarrow pos(s) \neq pos(s1)\}$$

moverEst : as $a \times \text{pos } pe \times \text{pos } pd \rightarrow$ as

$$\left\{ \begin{array}{l} posValida(campus(a), pe) \wedge_L hayEst?(a, pe) \wedge adyacente(campus(a), pe, pd) \wedge \\ posValidaPersona(as, pd) \end{array} \right\}$$

nuevoHippie : as $a \times \text{pos } p \rightarrow$ as

$$\{posIngreso(campus(a), p) \wedge posValidaPersona(a, p)\}$$

nuevoEst : as $a \times \text{pos } p \rightarrow$ as

$$\{posIngreso(campus(a), p) \wedge posValidaPersona(a, p)\}$$

sacarEst : as $a \times \text{pos } p \rightarrow$ as

$$\{posValida(campus(a), p) \wedge_L hayEst?(a, p) \wedge posIngreso(a, p)\}$$

otras operaciones

haySeg? : as $a \times \text{pos } p \rightarrow \text{bool}$

posValidaPersona : as $a \times \text{pos } p \rightarrow \text{bool}$

posIngreso : as $a \times \text{pos } p \rightarrow \text{bool}$

moverTodos : as $a \times \text{conj(seguridad) } segs \rightarrow \text{conj(seguridad)}$

moverSeg : as $a \times \text{seguridad } seg \times \text{pos } posSig \rightarrow \text{seguridad}$

proximasPosiciones : as $a \times \text{conj(pos) } minPos \times \text{pos } posAct \rightarrow \text{conj(pos)}$

$$\{\neg(emptyset?(minPos)) \wedge_L posValida(campus(a), posAct) \wedge posicionesValidas(campus(a), minPos)\}$$

hippiesMasCerca : as $a \times \text{seguridad } seg \rightarrow \text{conj(pos)}$

$$\{seg \in seguridad(a) \wedge hayHippies(a)\}$$

encerrado : as $a \times \text{pos } p \rightarrow \text{bool}$

$$\{hayEst?(p)\}$$

#hippies : as $a \rightarrow \text{nat}$

#estudiantes : as $a \rightarrow \text{nat}$

#masVigilante : as $a \rightarrow \text{nat}$

contarHippies : as $a \times \text{conj(pos) } poss \rightarrow \text{nat}$

contarEstudiantes : as $a \times \text{conj(pos) } poss \rightarrow \text{nat}$

#masCapturas : as $a \times \text{conj(seg) } segs \rightarrow \text{conj(seg)}$

$$\{(\forall segs:s) s \in seguridad(a)\}$$

#maxCapturas : as $a \times \text{conj(seg) } segs \rightarrow \text{nat}$

$$\{(\forall segs:s) s \in seguridad(a)\}$$

$\text{captura?} : \text{as } a \times \text{pos } p \longrightarrow \text{bool}$

axiomas

$\text{campus}(\text{nueva}(c, \text{segs}))$	$\equiv c$
$\text{campus}(\text{moverEst}(a, p_1, p_2))$	$\equiv \text{campus}(a)$
$\text{campus}(\text{nuevoEst}(a, p_1))$	$\equiv \text{campus}(a)$
$\text{campus}(\text{nuevoHippie}(a, p_1))$	$\equiv \text{campus}(a)$
$\text{campus}(\text{sacarEst}(a, p_1))$	$\equiv \text{campus}(a)$
$\text{seguridad}(\text{nueva}(c, \text{segs}))$	$\equiv \text{segs}$
$\text{seguridad}(\text{moverEst}(a, p_1, p_2))$	$\equiv \text{moverTodos}(a, \text{seguridad}(a))$
$\text{seguridad}(\text{nuevoEst}(a, p_1))$	$\equiv \text{moverTodos}(a, \text{seguridad}(a))$
$\text{seguridad}(\text{nuevoHippie}(a, p_1))$	$\equiv \text{seguridad}(a)$
$\text{seguridad}(\text{sacarEst}(a, p_1))$	$\equiv \text{seguridad}(a)$
$\text{hayEst?}(\text{nueva}(c, \text{segs}), p)$	$\equiv \text{False}$
$\text{hayEst?}(\text{nuevoEst}(a, p_1), p)$	$\equiv \text{if } p_1 = p \text{ then True else hayEst?}(a, p) \text{ fi}$
$\text{hayEst?}(\text{moverEst}(a, p_1, p_2), p)$	$\equiv \text{if } p_1 = p \text{ then False else}$ $\quad \text{if } p_2 = p \text{ then True else hayEst?}(a, p) \text{ fi}$
$\text{hayEst?}(\text{nuevoHippie}(a, p_1), p)$	$\equiv \text{hayEst?}(a, p)$
$\text{hayEst?}(\text{sacarEst}(a, p_1), p)$	$\equiv \text{if } p_1 = p \text{ then False else hayEst?}(a, p) \text{ fi}$
$\text{hayHippie?}(\text{nueva}(c, \text{segs}), p)$	$\equiv \text{False}$
$\text{hayHippie?}((\text{nuevoHippie}(a, p_1), p)$	$\equiv \text{if } p_1 = p \text{ then True else hayHippie?}(a, p) \text{ fi}$
$\text{hayHippie?}(\text{nuevoEst}(a, p_1), p)$	$\equiv \text{hayHippie?}(a, p)$
$\text{hayHippie?}(\text{sacarEst}(a, p_1), p)$	$\equiv \text{hayHippie?}(a, p)$
$\# \text{capturas}(\text{nueva}(a, \text{segs}), s)$	$\equiv 0$
$\# \text{capturas}(\text{moverEst}(a, p_1, p_2), s)$	$\equiv \# \text{capturas}(a, s)$
$\# \text{capturas}(\text{nuevoHippie}(a, p_1), s)$	$\equiv \text{if } (\text{adyacente}(a, p_1, \text{posSeg}(a, s)) \wedge \text{encerrado}(a, p_1)) \text{ then}$ $\quad 1 + \# \text{capturas}(a, s)$ else $\quad \# \text{capturas}(a, s)$ fi
$\# \text{capturas}(\text{nuevoEst}(a, p_1), s)$	$\equiv \# \text{capturas}(a, s)$
$\# \text{capturas}(\text{sacarEst}(a, p_1), s)$	$\equiv \# \text{capturas}(a, s)$
$\# \text{capturas}(a, \text{moverSeg}(a, s, p_1))$	$\equiv \beta(\text{posValida}(\text{campus}(a), < \pi_1(p_1) + 1, \pi_2(p_1) >) \wedge_L (\text{hayHippie?}(a, < \pi_1(p_1) + 1, \pi_2(p_1) >) \wedge_L \text{encerrado}(a, < \pi_1(p_1) + 1, \pi_2(p_1) >))) +$ $\beta(\text{posValida}(\text{campus}(a), < \pi_1(p_1) - 1, \pi_2(p_1) >) \wedge_L (\text{hayHippie?}(a, < \pi_1(p_1) - 1, \pi_2(p_1) >) \wedge_L \text{encerrado}(a, < \pi_1(p_1) - 1, \pi_2(p_1) >))) +$ $\beta(\text{posValida}(\text{campus}(a), < \pi_1(p_1), \pi_2(p_1) + 1 >) \wedge_L (\text{hayHippie?}(a, < \pi_1(p_1), \pi_2(p_1) + 1 >) \wedge_L \text{encerrado}(a, < \pi_1(p_1), \pi_2(p_1) + 1 >))) +$ $\beta(\text{posValida}(\text{campus}(a), < \pi_1(p_1), \pi_2(p_1) - 1 >) \wedge_L (\text{hayHippie?}(a, < \pi_1(p_1), \pi_2(p_1) - 1 >) \wedge_L \text{encerrado}(a, < \pi_1(p_1), \pi_2(p_1) - 1 >))) + \# \text{capturas}(a, s)$

#capturas(moverEst(a, p_1, p_2), s)

```

≡ if (PosValida(campus(a), <  $\pi_1(posSeg)+1, \pi_2(posSeg) >$ 
)) then
  if (hayHippie(a, <  $\pi_1(posSeg) + 1, \pi_2(posSeg) >))$ 
  then
    if (captura?(a, <  $\pi_1(posSeg) + 1, \pi_2(posSeg) >))$ 
    then
      1
    else
      0
    fi
  else
    0
  fi
else
  0
fi

+

if (PosValida(campus(a), <  $\pi_1(posSeg)-1, \pi_2(posSeg) >$ 
)) then
  if (hayHippie(a, <  $\pi_1(posSeg) - 1, \pi_2(posSeg) >))$ 
  then
    if (captura?(a, <  $\pi_1(posSeg) - 1, \pi_2(posSeg) >))$ 
    then
      1
    else
      0
    fi
  else
    0
  fi
else
  0
fi

+

if (PosValida(campus(a), <  $\pi_1(posSeg), \pi_2(posSeg)+1 >$ 
)) then
  if (hayHippie(a, <  $\pi_1(posSeg), \pi_2(posSeg) + 1 >))$ 
  then
    if (captura?(a, <  $\pi_1(posSeg), \pi_2(posSeg) + 1 >))$ 
    then
      1
    else
      0
    fi
  else
    0
  fi
else
  0
fi

+

if (PosValida(campus(a), <  $\pi_1(posSeg), \pi_2(posSeg)-1 >$ 
)) then
  if (hayHippie(a, <  $\pi_1(posSeg), \pi_2(posSeg) - 1 >))$ 
  then
    if (captura?(a, <  $\pi_1(posSeg), \pi_2(posSeg) - 1 >))$ 
    then
      1
    else
      0
  fi
else
  0
fi

```

<code>#sanciones(nueva(a, segs),s)</code>	$\equiv 0$
<code>#sanciones(moverEst(a, p₁, p₂),s)</code>	$\equiv \#sanciones(a, s)$
<code>#sanciones(nuevoHippie(a, p₁),s)</code>	$\equiv \text{if } (cercanos?(a, p_1, posSeg(a, s)) \wedge_L$ $(hayEst?(casilleroEnComun(a, p_1, posSeg(a, s))) \wedge$ $encerrado(casilleroEnComun(a, p_1, posSeg(a, s))))$ then $1 + \#sanciones(a, s)$ else $\#sanciones(a, s)$ fi
<code>#sanciones(nuevoEst(a, p₁),s)</code>	$\equiv \#sanciones(a, s)$
<code>#sanciones(sacarEst(a, p₁),s)</code>	$\equiv \#sanciones(a, s)$
<code>#sanciones(a,moverSeg(a, s, p₁))</code>	$\equiv \beta(posValida(campus(a), < \pi_1(p_1) + 1, \pi_2(p_1) >) \wedge_L$ $(hayEst?(a, < \pi_1(p_1) + 1, \pi_2(p_1) >) \wedge_L encerrado(a, <$ $\pi_1(p_1) + 1, \pi_2(p_1) >))) +$ $\beta(posValida(campus(a), < \pi_1(p_1) - 1, \pi_2(p_1) >) \wedge_L$ $(hayEst?(a, < \pi_1(p_1) - 1, \pi_2(p_1) >) \wedge_L encerrado(a, <$ $\pi_1(p_1) - 1, \pi_2(p_1) >))) +$ $\beta(posValida(campus(a), < \pi_1(p_1), \pi_2(p_1) + 1 >) \wedge_L$ $(hayEst?(a, < \pi_1(p_1), \pi_2(p_1) + 1 >) \wedge_L encerrado(a, <$ $\pi_1(p_1), \pi_2(p_1) + 1 >))) +$ $\beta(posValida(campus(a), < \pi_1(p_1), \pi_2(p_1) - 1 >) \wedge_L$ $(hayEst?(a, < \pi_1(p_1), \pi_2(p_1) - 1 >) \wedge_L encerrado(a, <$ $\pi_1(p_1), \pi_2(p_1) - 1 >))) + \#sanciones(a, s)$
<code>moverTodos(a,segs)</code>	$\equiv \text{if } (\emptyset?(segs)) \text{ then}$ \emptyset else $\text{if } (hayHippies?(a)) \text{ then}$ $Ag(moverTodos(a, sinUno(segs)),$ $moverSeg(a, dameUno(segs),$ $dameUno(proxPosiciones$ $(hippiesMasCerca(a, dameUno(segs)))))$ else $moverIngreso(a, segs)$ fi fi
<code>moverIngreso(a,segs)</code>	$\equiv \text{if } \emptyset?(segs) \text{ then}$ \emptyset else $\text{if } (alto(campus(a)) - 1) - \pi_2(dameUno(segs)) >$ $\pi_2(dameUno(segs)) \text{ then}$ $ag(moverIngreso(a, sinUno(segs)), mover(dameUno(segs), <$ $(\pi_1(dameUno(segs)), \pi_2(segs) - 1) >))$ else $\text{if } (alto(campus(a)) - 1) - \pi_2(dameUno(segs)) <$ $\pi_2(dameUno(segs)) \text{ then}$ $ag(moverIngreso(a, sinUno(segs)), mover(dameUno(seg,$ $(\pi_1(dameUno(segs)), \pi_2(segs) + 1) >))$ else $ag(moverIngreso(a, sinUno(segs)), mover(dameUno(seg,$ $dameUno(\{< (\pi_1(dameUno(segs)), \pi_2(segs) -$ $1) >, < (\pi_1(dameUno(segs)), \pi_2(segs)+1) >\}))$ fi fi fi

moverSeg(a,seg,nPos)

≡ **if** ($distMan(campus(a), \pi_2(seg), nPos) \geq 2$
 $\vee \neg(posValida(campus(a), nPos))$) **then**
 seg

else
 if $\#sanciones(a, seg) < 3$ **then**
 $< \pi_1(seg), nPos >$

else
 seg

fi

proximasPosiciones(hscerca, posSeg)

≡ **if** $\emptyset?(hscerca)$ **then**
 \emptyset

else

if $\pi_1(dameUno(hscerca)) > \pi_1(posSeg)$ **then**

if $\pi_2(dameUno(hscerca)) > \pi_2(posSeg)$ **then**

$\{< \pi_1(posSeg) + 1, \pi_2(posSeg) >,$

$< \pi_1(posSeg), \pi_2(posSeg) + 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

else

if $\pi_2(dameUno(hscerca)) < \pi_2(posSeg)$ **then**

$\{< \pi_1(posSeg) + 1, \pi_2(posSeg) >,$

$< \pi_1(posSeg), \pi_2(posSeg) - 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

else

$\{< \pi_1(posSeg) + 1, \pi_2(posSeg) >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

fi

fi
else

if $\pi_1(dameUno(hscerca)) < \pi_1(posSeg)$ **then**

if $\pi_2(dameUno(hscerca)) > \pi_2(posSeg)$ **then**

$\{< \pi_1(posSeg) - 1, \pi_2(posSeg) >,$

$< \pi_1(posSeg), \pi_2(posSeg) + 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

else

if $\pi_2(dameUno(hscerca)) < \pi_2(posSeg)$

then

$\{< \pi_1(posSeg) - 1, \pi_2(posSeg) >,$

$< \pi_1(posSeg), \pi_2(posSeg) - 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

else

$\{< \pi_1(posSeg) - 1, \pi_2(posSeg) >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

fi

fi
else

if $\pi_2(dameUno(hscerca)) > \pi_2(posSeg)$ **then**

$\{< \pi_1(posSeg), \pi_2(posSeg) + 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

else

$\{< \pi_1(posSeg), \pi_2(posSeg) - 1 >\}$

$\cup proxPosiciones(sinUno(minPos), posSeg)$

fi

fi
fi

fi

hippiesMasCerca(a,seg)

≡ $minDistsPos(campus(a), \pi_2(seg), posHippies(a))$

$\#hippies(a)$

≡ $contarHippies(a, conjPos(campus(a), 0, 0))$

$\#estudiantes(a)$

≡ $contarEstudiantes(a, conjPos(campus(a), 0, 0))$

contarHippies(a,poss)

```

≡ if ¬(∅?(poss)) then
    if posValida(campus(a), dameUno(poss)) then
        if hayHippie(a, dameUno(poss)) then
            1 + contarHippies(a, sinUno(poss))
        else
            contarHippies(a, sinUno(poss))
    fi
else
    contarHippies(a, sinUno(poss))
fi
else
    0
fi

```

contarEstudiantes(a,poss)

```

≡ if ¬(∅?(poss)) then
    if posValida(campus(a), dameUno(poss)) then
        if hayEst?(a, dameUno(poss)) then
            1 + contarEstudiantes(a, sinUno(poss))
        else
            contarEstudiantes(a, sinUno(poss))
    fi
else
    contarEstudiantes(a, sinUno(poss))
fi
else
    0
fi

```

masVigilante(a)

```

≡ dameUno(masCapturas(a, seguridad(a)))

```

masCapturas(a,segs)

```

≡ if ¬(∅?(segs)) then
    if #capturas(a, dameUno(segs)) ≥ maxCapturas(a, segs)
    then
        ag(masCapturas(a, sinUno(segs)), dameUno(segs))
    else
        masCapturas(a, sinUno(segs))
    fi
else
    ∅
fi

```

maxCapturas(a,segs)

```

≡ if ∅?(segs) then
    0
else
    if #capturas(a, dameUno(segs)) ≥
        maxCapturas(a, sinUno(segs))
    then
        #capturas(a, dameUno(segs))
    else
        maxCapturas(a, sinUno(segs))
    fi
fi

```


$\text{captura?}(a, p)$

\equiv **if** ($\text{posValida}(\text{campus}(a), < \pi_1(p) + 1, \pi_2(p) >)$ **then**
 ($\text{hayObstaculo?}(\text{campus}(a), < \pi_1(p) + 1, \pi_2(p) >) \vee$
 $\text{haySeg?}(a, < \pi_1(p) + 1, \pi_2(p) >)$)
else
 $\neg(\text{hayEst?}(a, < \pi_1(p), \pi_2(p) >))$
fi
 \wedge
if ($\text{posValida}(\text{campus}(a), < \pi_1(p) - 1, \pi_2(p) >)$ **then**
 ($\text{hayObstaculo?}(\text{campus}(a), < \pi_1(p) - 1, \pi_2(p) >) \vee$
 $\text{haySeg?}(a, < \pi_1(p) - 1, \pi_2(p) >)$)
else
 $\neg(\text{hayEst?}(a, < \pi_1(p), \pi_2(p) >))$
fi
 \wedge
if ($\text{posValida}(\text{campus}(a), < \pi_1(p), \pi_2(p) + 1 >)$ **then**
 ($\text{hayObstaculo?}(\text{campus}(a), < \pi_1(p), \pi_2(p) + 1 >) \vee$
 $\text{haySeg?}(a, < \pi_1(p), \pi_2(p) + 1 >)$)
else
 True
fi
 \wedge
if ($\text{posValida}(\text{campus}(a), < \pi_1(p), \pi_2(p) - 1 >)$ **then**
 ($\text{hayObstaculo?}(\text{campus}(a), < \pi_1(p), \pi_2(p) - 1 >) \vee$
 $\text{haySeg?}(a, < \pi_1(p), \pi_2(p) - 1 >)$)
else
 True
fi

Fin TAD

2. TAD CAMPUS

TAD CAMPUS

géneros campus

usa CAMPUS

exporta

observadores básicos

$\text{alto} : \text{campus} \rightarrow \text{nat}$

$\text{ancho} : \text{campus} \rightarrow \text{nat}$

$\text{obstaculos} : \text{campus} \rightarrow \text{conj}(\text{pos})$

generadores

$\text{nuevo} : \text{nat } \text{ancho} \times \text{nat } \text{alto} \times \text{conj}(\text{pos}) \text{ obst} \rightarrow \text{campus}$

$\{1 \leq \text{ancho} \wedge 1 \leq \text{alto} \wedge (\forall p:\text{pos}) p \in \text{obst} \Rightarrow_{\text{L}} \text{posValida}(c, p)\}$

otras operaciones

$\text{adyacente} : \text{as } a \times \text{pos } pe \times \text{pos } pd \rightarrow \text{bool}$

$\{\text{posValida}(c, pe) \wedge \text{posValida}(c, pd)\}$

$\text{posValida} : \text{as } a \times \text{pos } p \rightarrow \text{bool}$

$\text{posIngreso} : \text{as } a \times \text{pos } p \rightarrow \text{bool}$

$\text{minDistsPos} : \text{campus } c \times \text{pos } p \times \text{conj}(\text{pos}) \text{ posiciones} \rightarrow \text{conj}(\text{pos})$

$\{\neg(\emptyset?(\text{posiciones}))\}$

$\text{minDist} : \text{campus } c \times \text{pos } p \times \text{conj}(\text{posiciones}) \text{ posiciones} \rightarrow \text{nat}$

$\{\neg(\emptyset?(\text{posiciones}))\}$

$\text{distMan} : \text{campus } c \times \text{pos } p1 \times \text{pos } p2 \longrightarrow \text{nat}$	
$\text{restaAbs} : \text{nat} \times \text{nat} \longrightarrow \text{nat}$	
$\text{conjPos} : \text{campus} \times \text{nat} \times \text{nat} \longrightarrow \text{conj}(\text{pos})$	
axiomas $\forall \text{ alto}:\text{nat}, \forall \text{ ancho}:\text{nat}, \forall \text{ obst}:\text{conj}(\text{pos})$ $\forall p_1:\text{pos} \forall p_2:\text{pos}$	
$\text{alto}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}))$	$\equiv \text{alto}$
$\text{ancho}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}))$	$\equiv \text{ancho}$
$\text{obstaculos}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}))$	$\equiv \text{obst}$
$\text{posValida}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}), p_1)$	$\equiv \pi_1(p_1) < \text{ancho} \wedge \pi_2(p_1) < \text{alto}$
$\text{adyacente}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}), p_1, p_2)$	$\equiv (\pi_1(p_1) = \pi_1(p_2) - 1 \vee \pi_1(p_1) = \pi_1(p_2) + 1) \wedge$ $(\pi_2(p_1) = \pi_2(p_2) - 1 \vee \pi_2(p_1) = \pi_2(p_2) + 1)$
$\text{posValida}(\text{nuevo}(\text{ancho}, \text{alto}, \text{obst}), p_1)$	$\equiv \pi_2(p_1) = \text{alto} - 1 \vee \pi_2(p_1) = 0$
$\text{minDistsPos}(c, p, \text{posiciones})$	$\equiv \text{if } \emptyset?(\text{sinUno}(\text{posiciones})) \text{ then}$ $\text{dameUno}(\text{posiciones})$ else if $\text{distMan}(c, p, \text{dameUno}(\text{posiciones})) \leq$ $\text{minDist}(c, p, \text{posiciones})$ then $\text{Ag}(\text{minDistsPos}(c, \text{sinUno}(\text{posiciones})),$ $\text{dameUno}(\text{posiciones}))$ else $\text{minDistsPos}(c, \text{seg}, \text{sinUno}(\text{posiciones}))$ fi fi
$\text{minDist}(c, p, \text{posiciones})$	$\equiv \text{if } \emptyset?(\text{sinUno}(\text{posiciones})) \text{ then}$ $\text{distMan}(c, p, \text{dameUno}(\text{posiciones}))$ else if $\text{distMan}(c, p, \text{dameUno}(\text{posiciones})) \leq$ $\text{minDist}(c, p, \text{sinUno}(\text{posiciones}))$ then $\text{distMan}(c, p, \text{dameUno}(\text{posiciones}))$ else $\text{minDist}(c, p, \text{sinUno}(\text{posiciones}))$ fi fi
$\text{distMan}(c, p_1, p_2)$	$\equiv \text{restaAbs}(\pi_2(p_1), \pi_2(p_2)) + \text{restaAbs}(\pi_1(p_1), \pi_1(p_2))$
$\text{restaAbs}(n1, n2)$	$\equiv \text{if } n2 > n1 \text{ then } n2 - n1 \text{ else } n1 - n2 \text{ fi}$
$\text{conjPos}(c, x, y)$	$\equiv \text{if } x \geq \text{ancho}(c) \text{ then}$ \emptyset else if $y \geq \text{alto}(c)$ then $\text{conjPos}(c, x + 1, 0)$ else $\text{ag}(\text{conjPos}(c, x, y + 1), < x, y >)$ fi fi

Fin TAD