

# ZYRO

## ZYRO Air

Integrated FPV Airborne Video Link / Product Brief



Product image

### Beyond Distance, In Real Time

#### 01 Product Overview

ZYRO Air is a lightweight airborne video transmission unit that combines a camera, video encoding, and wireless transmission in a compact form factor. It is designed for drones, FPV platforms, and portable real-time video backhaul applications where weight, wiring simplicity, and installation efficiency matter.

#### 02 Key Features

Integrated airborne design

High-efficiency H.265 encoding

|                                                                                                                                        |                                                                                                                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera, encoder, and wireless transmission are combined in one compact module for faster deployment and cleaner installation.          | Delivers strong image quality while reducing link load and bandwidth pressure.                                                                     |
| <b>4K30 and 1080P90 support</b><br>Supports up to 3840 × 2160 @ 30fps and high-frame-rate 1920 × 1080 @ 90fps modes for FPV operation. | <b>Wide-angle visual coverage</b><br>Equipped with a 2.1 mm lens and 170° ultra-wide field of view for immersive FPV and low-altitude observation. |
| <b>Flexible power input</b><br>Supports 2S-6S input and integrates easily with common airborne power systems.                          | <b>Optimized antenna layout</b><br>Dual tail-antenna arrangement helps reduce mutual interference during installation.                             |

### 03 Technical Specifications

| Parameter           | Value                                                |
|---------------------|------------------------------------------------------|
| Mounting size       | 30 × 30 × 14 mm                                      |
| Camera size         | 19 × 19 mm                                           |
| Total weight        | Approx. 30 g                                         |
| Power consumption   | 10 W                                                 |
| Input voltage       | 2S-6S                                                |
| Operating frequency | 5.18-5.845 GHz                                       |
| Transmit power      | 29 dBm                                               |
| Image sensor        | Sony IMX415, up to 3840 × 2160                       |
| Encoding            | H.265 by default                                     |
| Video modes         | 1920 × 1080 @ 90fps to 3840 × 2160 @ 30fps           |
| Lens                | 2.1 mm, 170° ultra-wide, for 1/2.8-inch image sensor |

### 04 Installation & Setup

## 产品功能指示



请参照示意图进行安装，此布局为最佳天线配置方式。

### *Installation reference and antenna routing*

- Keep the two tail antennas separated to reduce mutual interference.
- Angle the antennas upward when possible and avoid blockage by the airframe or battery.
- Recommended settings: Channel 60 and H.265 codec.
- APP installation information is available from after-sales support.

## 05 Typical Applications

- FPV drones and lightweight airborne platforms
- Portable real-time video transmission systems
- Compact integrated payloads requiring low wiring complexity