



# Sketch-BERT

: Learning Sketch Bidirectional Encoder Representation  
from Transformers by Self-supervised Learning of Sketch Gestalt

손수현

- Sketch image를 활용한 task

## 1. Recognition


: sketch 그림의 category(label)을 예측하는

## 2. Retrieval

: query sketch가 주어졌을 때, 그와 같은 category의 sketch를 예측하는

## 3. Sketch Gestalt \*본 논문에서 처음으로 제안한 task

: masked된 부분을 예측하여 realistic sketch image를 생성하는





→ Sketch is stored as a sequence of data points, a vector format representation

기존의 모델(SketchRNN)이 학습하는 representation은 generation task에서만 중요했고,  
다른 task에서는 크게 도움을 주지 못함



SketchBERT

: NLP의 BERT 구조에서 embedding과 pretraining algorithm에 변화를 주어 다양한 sketch task를 수행하도록

→ Sequential data를 modeling할 때 적합한 구조

sketch can be represented as a list of points, where each point contains 5 attributes

$$(\Delta x, \Delta y, p_1, p_2, p_3)$$

위치정보  $\Delta x, \Delta y$  : relative offsets between current point and previous point

$p_1 = 1$  : represents the other sequential points of sketches

상태정보  $p_2 = 1$  : indicates the ending of one stroke

$p_3 = 1$  : means the ending of the whole sketch

sketch can be represented as a list of points, where each point contains 5 attributes


$$(\Delta x, \Delta y, p_1, p_2, p_3)$$

$\Delta x, \Delta y$  : relative offsets between current point and previous point

$p_1 = 1$  : represents the other sequential points of sketches

$p_2 = 1$  : indicates the ending of one stroke

$p_3 = 1$  : means the ending of the whole sketch



# Self-Supervised Learning by Sketch Gestalt




- Sketch Gestalt (sGesta)
  - : 본 논문에서 제안한 새로운 self-supervised learning process
  - : recovering the masked points in sketches
    - ↳ 이를 수행하는 SGM(Sketch Gestalt Model) 제안
- SGM
  - : 5개의 key information으로 표현된 point는 SGM에 의해 mask되고 predict된다.
  - : 2가지의 mask strategies 제안 (15%)
    - 1) positional offset
    - 2) state information

$$(\Delta x, \Delta y, p_1, p_2, p_3)$$

# Self-Supervised Learning by Sketch Gestalt

1. Mask Position Prediction
  - $\Delta x, \Delta y$  값을 0으로 함으로써 masking
2. Mask State Prediction
  - p1,p2,p3값을 0으로 함으로써 masking



(a) Sketch-BERT for Sketch Gestalt

downstream tasks after the pre-training procedure

Sketch Recognition  
Sketch Retrieval  
Sketch Gestalt

- 2가지 Dataset을 사용하여 training & test
  - : QuickDraw dataset  
(50 million, 345 classes of common object)
  - : TU-Berlin dataset  
(보다 quality가 좋은, 250개의 category, 각 category 별 80개의 sketches)

Models	QuickDraw			TU-Berlin		
	Top-1 (%)	Top-5 (%)	mAP (%)	Top-1 (%)	Top-5 (%)	mAP(%)
Bi-LSTM [9]	70.91	89.52	60.11	31.40	59.60	23.71
Sketch-a-Net [27]	74.88	90.10	65.13	37.25	63.50	26.18
DSSA [22]	78.16	91.04	68.10	38.45	66.10	28.77
ResNet18 [8]	80.34	91.71	70.98	41.45	67.10	29.33
ResNet50 [8]	82.41	92.52	74.84	51.80	74.45	36.94
TCNet [20]	83.59	92.57	76.38	55.30	79.45	38.78
Sketch-BERT (w./o.)	63.13	84.70	55.10	32.50	57.90	24.14
Sketch-BERT (w.)	<b>85.47</b>	<b>93.49</b>	<b>78.87</b>	<b>57.25</b>	<b>81.50</b>	<b>41.54</b>

sketch gestalt  
포함 유무



