

Driver Vigilance Monitoring System with Smart Alert and Rescue Mechanism



L OVELY
P ROFESSIONAL
U NIVERSITY

Submitted By:

- ☐ **Naman Tiwari 01 (12508806)**
- ☐ **Nishant 02 (12509031)**
- ☐ **Sonu Kumar 20 (12515603)**

Dept. of Computer Science and Engineering
Lovely Professional University, Phagwara, India
Section: 325UX

Abstract :-

The development of an intelligent Driver Vigilance Monitoring System represents a significant advancement in vehicular safety and accident prevention technology. Road accidents caused by driver fatigue, drowsiness, and lack of attention have become a major global issue, often leading to tragic loss of life and property. This paper presents a detailed implementation of a monitoring device capable of identifying early signs of driver drowsiness and providing immediate haptic and auditory feedback. The system integrates an ESP32/ Raspberry Pi microcontroller with Eye Blink sensors, Camera modules, and Accelerometers to create a reliable detection and rescue system. Challenges such as precision in variable lighting, real-time data processing, and hardware/software integration are addressed through modular design and iterative testing. Experimental results confirm that the integration of GPS and GSM modules for automatic rescue significantly

improves emergency response times.

Keywords— Driver Vigilance, Drowsiness Detection, ESP32, GPS Tracking, Emergency Rescue, IoT Safety, Eye Aspect Ratio, Accelerometer.

I. INTRODUCTION :-

In modern technological landscapes, the development of efficient and reliable driver safety systems holds significant importance across various domains of transportation and logistics. Radar and vision systems play a crucial role in object detection, yet monitoring the human element—the driver—is equally vital for collision avoidance. This project focuses on the design and implementation of a vigilant monitoring system for precise drowsiness detection and rapid response. The motivation behind this project stems from the critical need for a robust and cost-effective system that can be utilized in diverse scenarios, including commercial trucks, public

transport, and autonomous vehicle support. Traditional vehicle systems often lack the intelligence to detect physiological fatigue or sudden distraction. The primary objective of this project is to design a system that accurately monitors driver behavior and provides appropriate responses based on detected fatigue levels.




Fig. 1. Block diagram for the Driver Vigilance Monitoring System illustrating Input, Processing, and Output stages.

II. LITERATURE REVIEW :-

After reading several papers on the implementation of driver safety systems, it is clear that the concept of automated vigilance monitoring is a highly sought-after field in global IoT research. Existing systems can

be categorized into camera-based vision systems and sensor-based physiological monitors. Current literature on vision-based systems highlights effective ways to integrate OpenCV for Eye Aspect Ratio (EAR) calculations, yet these often omit rescue mechanisms. Conversely, standalone GPS trackers provide location data but lack real-time physiological insights. The conclusion from our review is that while individual components exist, a low-cost, single-node solution combining automation, monitoring, and an emergency rescue mechanism remains a vital gap this project aims to fill.

III. PROBLEM STATEMENT :-

The purpose of this project is to demonstrate the integrated use of multiple sensors via the ESP32 board to mitigate road accidents. Traditional systems lack the ability to detect driver drowsiness, head movement, or distraction in real-time. Furthermore, when accidents do occur, there is often a fatal delay in emergency response

due to a lack of automated location reporting. This project addresses these deficiencies by creating a prototype that provides real-time alerts and autonomous rescue notifications.




Fig. 2. ESP32 Microcontroller acting as the central processing unit for sensor fusion and IoT connectivity

IV. SYSTEM DESIGN :-

A. Methodology of Model Development :-

The development involves sensor integration where Eye Blink sensors and Accelerometers are connected to the ESP32. The Eye Blink sensor monitors the frequency of eyelid closure, providing crucial data about the driver's alertness. The ESP32 acts as

the central unit, collecting and processing this data using the EAR algorithm. This algorithm calculates the duration of eye closure; if it exceeds a threshold, the system triggers a buzzer. Simultaneously, the processed data is transmitted to an IoT dashboard (Blynk/Firebase), allowing for real-time monitoring of the surroundings. Users can interact with the system to set alert thresholds and receive notifications during emergencies.




Fig. 3. IR-based Eye Blink Sensor used for detecting blinking patterns and fatigue.

B. Hardware Module Design :-

The hardware system consists basically of six components: the ESP32 Controller, Camera Module, Eye Blink Sensor,

Accelerometer, GPS, and GSM Module. The eye blink sensor is mounted to monitor the driver's face, while the accelerometer detects sudden impacts indicative of a crash. Both are powered and controlled by the ESP32.

V. HARDWARE DESCRIPTION :-

A. Eye Blink Sensor :-

The Eye Blink sensor is a device that uses infrared sound/ light waves to detect the position of the eyelid. It works on the principle of measuring the reflection from the eye; when the eye is closed, the reflection changes, outputting a digital signal. This allows the sensor to determine fatigue with good accuracy.

B. GPS and GSM Modules :-

The GPS module provides real-time latitude and longitude coordinates. The GSM module (SIM900) is packed with components necessary to send emergency SMS alerts to saved contacts when an accident or drowsiness threshold is breached.




Fig. 5. Integrated GPS and GSM modules for location tracking and distress signal transmission.




Fig. 4. Accelerometer (ADXL345) for real-time impact and accident detection.

VI. HARDWARE WORKING :-

The system operates on the principle of sensor fusion. The sensors continuously emit/receive signals that travel to the driver and bounce back. These waves are captured by the sensors, and the ESP32 processes this to determine

distance and alertness. If the driver does not respond to the initial buzzer, a stronger alarm is activated via a vibration motor, and the rescue mechanism begins.




Fig. 6. Output actuators: Piezoelectric buzzer and Vibration motor for driver alerts.

VII. SOFTWARE OVERVIEW

:-

The software is developed using the Arduino IDE and Python. It provides a user-friendly platform for writing and uploading code. We use OpenCV for sophisticated image processing to calculate the Eye Aspect Ratio. The platform has inbuilt tools for debugging and modifying the code in the environment.

VIII. SOFTWARE IMPLEMENTATION :-

The code consists of an important function that measures EAR: $EAR = (\text{Eye Height}) / (\text{Eye Width})$. If EAR falls below the threshold, the driver is classified as drowsy. Another major part of the code involves the IFELSE statements used for triggering the GSM module when the accelerometer registers a force greater than the threshold (Impact Detection: $A = \Delta v / \Delta t$).

IX. EXECUTION OF MODEL :-

First, the sensors scan the driver at a proximity conducive to cabin settings. Upon detecting an object/drowsiness, the alert targets the driver, and the distance/angle of closure is shown on the computer screen. The real-time input is fed via Serial ports, outlining the status as either 'Vigilant' or 'Alert Required'.




Fig. 8. Final hardware prototype illustrating successful sensor integration and communication.

X. ADVANTAGES :-

One significant advantage is the independence from manual monitoring. The system is resilient to environmental factors and ensures consistent performance regardless of external light conditions. It is easy to design into existing vehicles at a low cost, making safety accessible without breaking the bank.

XI. APPLICATION :-

While observing military technology in aviation, where vigilance is critical, the concept of this rescue mechanism came to us. It is applicable for fleet management, public transport, and long-haul logistics where safety is paramount.

XII. CONCLUSION :-

In this project, we successfully designed and implemented a Driver Vigilance Monitoring System. This system can accurately sense fatigue and impact, providing a visual and haptic representation for effective decision-making. The combination of IoT, sensors, and intelligent rescue mechanisms ensures driver safety and timely rescue, potentially saving countless lives.

REFERENCES :-

- [1] A. Bocharé and M. Saini, "Short range monitoring system using Arduino," IRJET, vol. 4, no. 6, 2017.
- [2] S. Mehta and S. Tiwari, "Vigilance system using ESP32," IJNRD, vol. 3, no. 4, 2018.
- [3] "Driver Vigilance Monitoring System Synopsis," Section 325UX, Lovely Professional University.
- [4] Research papers on Driver Drowsiness Detection and IoT Security.
- [5] OpenCV Documentation and ESP32 Datasheets.