All the Best!!!

Binary Tree



Binary Tree Node Class

```
class Node{
    public:
        int data;
        Node*left;
        Node*right;

    Node(int d){
        data = d;
        left = right = NULL;
    }
};
```

Build Tree :-

3 4 -1 -1 5 -1 -1




```
void buildTree(){
    // input data
    int d;
    cin >> d;

    // if input is -1 then simply return NULL
    if(d==-1)
        return NULL;

    // create a new Tree Node with data d
    root = new Node(d);

    // recursion call to left and right subtree
    root->left = buildTree();
    root->right = buildTree();

    // at the end return root
    return root;
}
```

Print Tree :- Pre-Order Traversal

```
void PreOrder(Node*root){
    if(root==NULL)
        return;

    cout << root->data << " ";
    PreOrder(root->left);
    PreOrder(root->right);
}
```

1 2 3 4 5 6



In-Order Traversal

```
void InOrder(Node*root){
    if(root==NULL)
        return;
    InOrder(root->left);
    cout << root->data << " ";
    InOrder(root->right);
}
```

Inorder

X → NULL



1
10
9
6
7
8
3
13
4

Post Order Traversal :-

```
void PostOrder(Node*root){
    if(root==NULL)
        return;
    PostOrder(root->left);
    PostOrder(root->right);
    cout << root->data << " ";
}
```

Post Order



1
9
7
6
10
13
4
3
8

Pre-Order Iterative :-

```
iterativePreorder(node)


if (node = null)
  return
s -> empty stack
s.push(node)
while (not s.isEmpty())
  node -> s.pop()
  visit(node)
  if (node.right != null)
    s.push(node.right)
  if (node.left != null)
    s.push(node.left)
```

```cpp
void PreOrderIterative(Node*root){
    if(root==NULL)
        return;

    // create a stack
    stack<Node*> stack;
    stack.push(root);

    while(!stack.empty()){
        Node*curr = stack.top();
        stack.pop();
        cout << curr->data << " ";

        // if right subtree is present
        // then fill into the stack
        if(curr->right)
            stack.push(curr->right);
        // if left subtree is present
        // then fill into the stack
        if(curr->left)
            stack.push(curr->left);
    }
}
```



Stack

10 |
~~10~~ | 2 | 8 |
2 | ~~8~~ | 5 | 3 |
2 | ~~5~~ | ~~3~~ |
~~2~~ | 6 |
~~6~~ |

O/P:- 10 8 3 5 2 6

In Order Traversal Iterative :-

Algo :-

```
iterativeInorder(node)


  s -> empty stack
  while (not s.isEmpty() or node != null)
    if (node != null)
      s.push(node)
      node -> node.left
    else
      node -> s.pop()
      visit(node)
      node -> node.right
```



O/P:- 3, 8, 5, 10, 6, 2

Stack

10 | 8 | ~~3~~
10 | ~~8~~ | 5
10 | ~~5~~ |
~~10~~ | 2 | 6
2 | ~~6~~
~~2~~

```cpp
void InOrderIterative(Node*root){
    // create a stack
    stack<Node*> stack;

    // assign root to curr node
    Node*curr = root;

    while(curr!=NULL || !stack.empty()){
        if(curr!=NULL){
            stack.push(curr);
            curr = curr->left;
        }
        else{
            curr = stack.top();
            cout << curr->data << " ";
            stack.pop();
            curr = curr->right;
        }
    }
}
```

PostOrder Iterative Traversal

Algorithm

```
iterativePostorder(node)


s -> empty stack
t -> output stack
while (not s.isEmpty())
  node -> s.pop()
  t.push(node)

  if (node.left <> null)
    s.push(node.left)

  if (node.right <> null)
    s.push(node.right)

while (not t.isEmpty())
  node -> t.pop()
  visit(node)
```

for storing

for O/P



O/P:- 3, 8, 5, 10, 6, 2

Stack	ans
~~10~~ | 8 | 2	10 |
8 | ~~2~~ | 6	10 | 2
8 | ~~6~~	10 | 2 | 6
~~8~~ | 3 | 5	10 | 2 | 6 | 8
3 | ~~5~~	10 | 2 | 6 | 8 | 5
~~3~~	10 | 2 | 6 | 8 | 5 | 3

3 5 8 6 2 10

reverse

```
void PostOrderIterative(Node*root) {
    if (root == NULL)
        return;

    stack<Node*>s;
    s.push(root);
    // answer stack will be the int type
    stack<int> ans;

    while (!s.empty()) {

        Node*curr = s.top();
        s.pop();
        ans.push(curr->data);

        // if any node present in left, then push into the stack
        if (curr->left)
            s.push(curr->left);
        // if any node presnet in right, then push into the stack
        if (curr->right)
            s.push(curr->right);
    }
    // now print the answer stack
    while (ans.empty() == false) {
        cout << ans.top() << " ";
        ans.pop();
    }
}
```