

Usage Guideline

HSBC_pain.002.001.03_PaymentStatus- ReportFileLevel_Core

HSBC_pain.002.001.03_PaymentStatusReportFileLevel_Core

This document describes a usage guideline restricting the base message **MX pain.002.001.03**. You can also consult [this information online](#).

Published by HSBC Direct Channels and generated by [MyStandards](#).

15 April 2014

Table of Contents

Message Functionality	3
1 Restriction summary	4
2 Structure	5
3 Rules	6
4 Message Building Blocks	7
5 Message Components	9
6 Message Datatypes	18
7 Restriction appendix	23
Legal Notices	24

Message Functionality

Overview

Scope

The CustomerPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction.

Usage

The CustomerPaymentStatusReport message is exchanged between an agent and a non-financial institution customer to provide status information on instructions previously sent. Its usage will always be governed by a bilateral agreement between the agent and the non-financial institution customer.

The CustomerPaymentStatusReport message can be used to provide information about the status (e.g. rejection, acceptance) of the initiation of a credit transfer, a direct debit, as well as on the initiation of other customer instructions.

The CustomerPaymentStatusReport message refers to the original instruction(s) by means of references only or by means of references and a set of elements from the original instruction.

The CustomerPaymentStatusReport message can be used in domestic and cross-border scenarios.

Outline

The HSBC_pain.002.001.03_PaymentStatusReportFileLevel_Core /

HSBC_pain.002.001.03_PaymentStatusReportFileLevel_Core message is composed of 2 building blocks

a. GroupHeader

Set of characteristics shared by all individual transactions included in the status report message.

b. OriginalGroupInformationAndStatus

Original group information concerning the group of transactions, to which the status report message refers to.

1 Restriction summary

This Usage Guideline restricts the pain.002.001.03 message.

Restriction Type	See page
Removed elements	See appendix on page 23
Make mandatory	10, 11, 13, 13, 16
Reduce Multiplicity	n.a.
Ignore	See appendix on page 23
Text rules	n.a.
Conditional rules	n.a.
Fixed values	n.a.
Comments	9, 10, 11, 12, 13, 13, 13, 14, 16, 17
Annotations	n.a.
Changed datatypes	n.a.
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.0	GroupHeader	<GrpHdr>		[1..1]		7
1.1	MessageIdentification	<MsgId>		[1..1]		9
1.2	CreationDateTime	<CreDtTm>		[1..1]		9
1.3	InitiatingParty	<InitgPty>		[0..1]	 	10
1.4	ForwardingAgent	<FwdgAgt>		[0..1]		
1.5	DebtorAgent	<DbtrAgt>		[0..1]		
1.6	CreditorAgent	<CdtrAgt>		[0..1]		
2.0	OriginalGroupInformationAndStatus	<OrgnlGrpInfAndSts>		[1..1]		7
2.1	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		12
2.2	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		12
2.3	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		
2.4	OriginalNumberOfTransactions	<OrgnlNbOfTxS>		[0..1]	 	12
2.5	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		13
2.6	GroupStatus	<GrpSts>		[0..1]	 	13
2.7	StatusReasonInformation	<StsRsnInf>		[0..*]		14
2.13	NumberOfTransactionsPerStatus	<NbOfTxSPerSts>		[0..*]		
3.0	OriginalPaymentInformationAndStatus	<OrgnlPmtInfAndSts>		[0..*]		

3 Rules

R1 **GroupStatusAcceptedRule** ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to ACTC, ACCP, ACSP, ACSC or ACWC, then OriginalPaymentInformationAndStatus/PaymentInformationStatus must be different from RJCT.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00063
- *Error Text:* Invalid message content for group and payment information statuses.

R2 **GroupStatusPendingRule** ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to PDNG, then OriginalPaymentInformationAndStatus/PaymentInformationStatus must be different from RJCT.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00064
- *Error Text:* Invalid message content for group and payment information statuses.

R3 **GroupStatusRejectedRule** ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to RJCT, then OriginalPaymentInformationAndStatus/PaymentInformationStatus, if present, must be equal to RJCT.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00065
- *Error Text:* Invalid message content for group and payment information statuses.

R4 **GroupStatusReceivedRule** ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to RCVD, then OriginalPaymentInformationAndStatus/PaymentInformationStatus is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00066
- *Error Text:* Invalid message content for group and payment information statuses.

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CustomerPaymentStatusReportV03 message definition.

4.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the status report message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader36__1" on page 9 for details)

🛑 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	9
1.2	CreationDateTime	<CreDtTm>		[1..1]		9
1.3	InitiatingParty	<InitgPty>		[0..1]	M ⚠	10
1.4	ForwardingAgent	<FwdgAgt>		[0..1]	✦	
1.5	DebtorAgent	<DbtrAgt>		[0..1]	✦	
1.6	CreditorAgent	<CdtrAgt>		[0..1]	✦	

4.2 OriginalGroupInformationAndStatus

XML Tag: OrgnlGrpInfAndSts

Presence: [1..1]

Definition: Original group information concerning the group of transactions, to which the status report message refers to.

The **OrgnlGrpInfAndSts** block contains the following elements (see datatype "OriginalGroupInformation20__1" on page 11 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		12
2.2	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]	⚠	12
2.3	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]	✦	
2.4	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]	M ⚠	12
2.5	OriginalControlSum	<OrgnlCtrlSum>		[0..1]	⚠	13
2.6	GroupStatus	<GrpSts>		[0..1]	M ⚠	13
2.7	StatusReasonInformation	<StsRsnInf>		[0..*]	⚠	14
2.13	NumberOfTransactionsPerStatus	<NbOfTxPerSts>		[0..*]	✦	

5 Message Components

Note The following chapter identifies the CustomerPaymentStatusReportV03 message components.

5.1 GroupHeader36__1

Definition: Set of characteristics shared by all individual transactions included in the message.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠️	9
1.2	CreationDateTime	<CreDtTm>		[1..1]		9
1.3	InitiatingParty	<InitgPty>		[0..1]	M ⚠️	10
1.4	ForwardingAgent	<FwdgAgt>		[0..1]	💡	
1.5	DebtorAgent	<DbtrAgt>		[0..1]	💡	
1.6	CreditorAgent	<CdtrAgt>		[0..1]	💡	

Used in element(s)

"GroupHeader" on page 7

5.1.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period.

Datatype: "Max35Text" on page 20

Usage Guideline details

- on pain.002.001.03/GroupHeader/MessageIdentification

Comment:

Here is the unique message reference generated from HSBC

5.1.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "ISODatetime" on page 19

5.1.3 InitiatingParty

XML Tag: InitgPty

Presence: [0..1]

Definition: Party that initiates the status message.

The **InitgPty** block contains the following elements (see datatype "PartyIdentification32__1" on page 15 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	💡	
9.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	
9.1.12	Identification	<Id>		[0..1]	M	15
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	

Usage Guideline details

- on pain.002.001.03/GroupHeader/InitiatingParty

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.002.001.03/GroupHeader/InitiatingParty

Comment:

Provide HSBC Connect Customer ID under /InitgPty/Id/OrgId/Othr/Id/. Alternatively, provide: BIC under /InitgPty/Id/OrgId/BICorBEI/ or SIRET ID under /InitgPty/Id/OrgId/Othr/Id/

5.2 OrganisationIdentification4__1

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICorBEI	<BICorBEI>		[0..1]	M ⚠	11
9.1.15	Other	<Othr>		[0..*]	💡	

Used in element(s)

"OrganisationIdentification" on page 14

5.2.1 BICOrBEI

XML Tag: BICOrBEI

Presence: [0..1]

Definition: Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "AnyBICIdentifier" on page 18

Usage Guideline details

- on pain.002.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/BICOrBEI

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.002.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/BICOrBEI

Comment:

This is used to identify the sender of the message. That is HSBC in a status message.

5.3 OriginalGroupInformation20__1

Definition: Set of elements used to provide information on the original group, to which the message refers.

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		12
2.2	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]	⚠	12
2.3	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]	💡	
2.4	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]	M ⚠	12
2.5	OriginalControlSum	<OrgnlCtrlSum>		[0..1]	⚠	13
2.6	GroupStatus	<GrpSts>		[0..1]	M ⚠	13
2.7	StatusReasonInformation	<StsRsnInf>		[0..*]	⚠	14
2.13	NumberOfTransactionsPerStatus	<NbOfTxPerSts>		[0..*]	💡	

Rules

R6 StatusReasonInformationRule ✓

If GroupStatus is present and is different from RJCT or PDNG then StatusReasonInformation/AdditionalInformation must be absent.

Error handling:

- *Error severity*: Fatal
- *Error Code*: X00078
- *Error Text*: Invalid message content for additional status reason.

Guidelines

1. NumberOfTransactionPerStatusGuideline

OriginalGroupInformationAndStatus/NumberOfTransactionsPerStatus should only be present if GroupStatus equals 'PART'.

Used in element(s)

"OriginalGroupInformationAndStatus" on page 7

5.3.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.

Datatype: "Max35Text" on page 20

5.3.2 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "Max35Text" on page 20

Usage Guideline details

- on pain.002.001.03/OriginalGroupInformationAndStatus/OriginalMessageNameIdentification

Comment:

For example, if it is Credit Transfer Initiation, it is pain.001.001.03. If it is Direct Debit Initiation, it is pain.008.001.02

5.3.3 OriginalNumberOfTransactions

XML Tag: OrgnlNbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the original message.

Datatype: "Max15NumericText" on page 20

Usage Guideline details

- **on pain.002.001.03/OriginalGroupInformationAndStatus/OriginalNumberOfTransactions**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.002.001.03/OriginalGroupInformationAndStatus/OriginalNumberOfTransactions**

Comment:

The value will be zero if it is rejected at file level.

5.3.4 OriginalControlSum

XML Tag: OrgnlCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the original message, irrespective of currencies.

Datatype: "DecimalNumber" on page 18

Usage Guideline details

- **on pain.002.001.03/OriginalGroupInformationAndStatus/OriginalControlSum**

Comment:

Original hash total contained in the original customer submission.If present in the inbound file.

Please note: Where this was not provided in the original Inbound file, this would NOT be included in the PSR return.

5.3.5 GroupStatus

XML Tag: GrpSts

Presence: [0..1]

Definition: Specifies the status of a group of transactions.

Datatype: "TransactionGroupStatus3Code" on page 21

Usage Guideline details

- **on pain.002.001.03/OriginalGroupInformationAndStatus/GroupStatus**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.002.001.03/OriginalGroupInformationAndStatus/GroupStatus**

Comment:

Required if reporting on a group level or consolidated (combined group and transaction levels).

ACCP: (Accepted) Group only and/or Consolidated
 RJCT: (Rejected) Group only and/or Consolidated

5.3.6 StatusReasonInformation

XML Tag: StsRsnInf

Presence: [0..*]

Definition: Set of elements used to provide detailed information on the status reason.

The **StsRsnInf** block contains the following elements (see datatype "[StatusReasonInformation8__1](#)" on [page 16](#) for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.8	Originator	<Orgtr>		[0..1]	⬠	
2.9	Reason	<Rsn>		[0..1]		17
2.12	AdditionalInformation	<AddtlInf>		[0..*]	⚠	17

Usage Guideline details

- on [pain.002.001.03/OriginalGroupInformationAndStatus/StatusReasonInformation](#)

Comment:

Additional status reason provided only if file being rejected

5.4 Party6Choice__1

Definition: Nature or use of the account.

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]		14
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	⬠	

Used in element(s)

"[Identification](#)" on [page 15](#)

5.4.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification4__1" on page 10 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICOrBEI	<BICOrBEI>		[0..1]	M ⚠	11
9.1.15	Other	<Othr>		[0..*]	💡	

5.5 PartyIdentification32__1

Definition: Set of elements used to identify a person or an organisation.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	💡	
9.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	
9.1.12	Identification	<Id>		[0..1]	M	15
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	

Used in element(s)

"InitiatingParty" on page 10

5.5.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party6Choice__1" on page 14 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]		14
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	💡	

Usage Guideline details

- on pain.002.001.03/GroupHeader/InitiatingParty/Identification

This element is now mandatory, the minimum occurrence has been changed to : 1

5.6 StatusReason6Choice__1

Definition: Specifies the reason for the status of the transaction.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.10	Code	<Cd>	{Or	[1..1]	⚠	16
2.11	Proprietary	<Prtry>	Or}	[1..1]	🚫	

Used in element(s)

"Reason" on page 17

5.6.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the status, as published in an external reason code list.

Datatype: "ExternalStatusReason1Code" on page 19

Usage Guideline details

- on pain.002.001.03/OriginalGroupInformationAndStatus/StatusReasonInformation/Reason/Code

Comment:

Code showing here is originated from the ISO Code list

5.7 StatusReasonInformation8__1

Definition: Set of elements used to provide information on the status reason of the transaction.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.8	Originator	<Orgtr>		[0..1]	✦	
2.9	Reason	<Rsn>		[0..1]		17
2.12	AdditionalInformation	<AddtlInf>		[0..*]	⚠	17

Rules**R7 StatusReasonRule** ✓

If Reason/Code is equal to NARR, then AdditionalInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional status reason.

Used in element(s)

"StatusReasonInformation" on page 14

5.7.1 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "StatusReason6Choice_1" on page 16 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.10	Code	<Cd>	{Or	[1..1]	⚠️	16
2.11	Proprietary	<Prtry>	Or}	[1..1]	🚫	

5.7.2 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the status reason.

Usage: Additional information can be used for several purposes such as the reporting of repaired information.

Datatype: "Max105Text" on page 19

Usage Guideline details

- on pain.002.001.03/OriginalGroupInformationAndStatus/StatusReasonInformation/Additional-Information

Comment:

HSBC error code and description

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the CustomerPaymentStatusReportV03 message.

6.1 AnyBICIdentifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Rules

R5 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters comprising the first three or all four of the following components: INSTITUTION CODE, COUNTRY CODE, LOCATION CODE, BRANCH CODE. The institution code, country code and location code are mandatory, while the branch code is optional.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC

Used in element(s)

"BICOrBEI" on page 11

6.2 DecimalNumber

Definition: Number of objects represented as a decimal number, eg, 0.75 or 45.6.

Type: Quantity

Format

totalDigits 18

fractionDigits 17

Used in element(s)

"OriginalControlSum" on page 13

6.3 ExternalStatusReason1Code

Definition: Specifies the status reason, as published in an external status reason code list. External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

"Code" on page 16

6.4 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"CreationDateTime" on page 9

6.5 Max105Text

Definition: Specifies a character string with a maximum length of 105 characters.

Type: Text

Format

minLength	1
maxLength	105

Used in element(s)

"AdditionalInformation" on page 17

6.6 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern [0-9]{1,15}

Used in element(s)

"OriginalNumberOfTransactions" on page 12

6.7 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength 1
maxLength 35

Used in element(s)

"MessageIdIdentification" on page 9, "OriginalMessageIdIdentification" on page 12, "OriginalMessageNameIdentification" on page 12

6.8 PaymentStatusCode

Definition: Indicates the status of a single payment transaction or of a group of payment transactions.

Type: Code

Code	Name	Definition
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACCR	AcceptedCancellationRequest	Cancellation is accepted.
ACPT	Accepted	Request is accepted.
ACSC	AcceptedSettlementCompleted	Settlement on the debtor's account has been completed. Usage : this can be used by the first agent to report to the debtor that the transaction has been completed. Warning : this status is provided for transaction status reasons, not for financial information. It can only be used after bilateral agreement
ACSP	AcceptedSettlementInProgress	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.

Code	Name	Definition
ACTC	AcceptedTechnicalValidation	Authentication and syntactical and semantical validation are successful.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PACR	PartiallyAcceptedCancellationRequest	Cancellation is partially accepted.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved 'accepted' status.
PDCR	PendingCancellationRequest	Cancellation request is pending.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RCVD	Received	Payment initiation has been received by the receiving agent.
RJCR	RejectedCancellationRequest	Cancellation request is rejected
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

Is restricted by

"TransactionGroupStatus3Code" on page 21

6.9 TransactionGroupStatus3Code

Definition: Specifies the status of a group of payment instructions.

Type: Code

Code	Name	Definition
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACSC	AcceptedSettlementCompleted	Settlement on the debtor's account has been completed. Usage : this can be used by the first agent to report to the debtor that the transaction has been completed. Warning : this status is provided for transaction status reasons, not for financial information. It can only be used after bilateral agreement
ACSP	AcceptedSettlementInProgress	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACTC	AcceptedTechnicalValidation	Authentication and syntactical and semantical validation are successful.

Code	Name	Definition
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved 'accepted' status.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RCVD	Received	Payment initiation has been received by the receiving agent.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

Used in element(s)

"GroupStatus" on page 13

Restricts

"PaymentStatusCode" on page 20

7 Restriction appendix

This appendix provides an overview of the 'Removed' and/or 'Ignored' elements in the Usage Guideline which the user has chosen not to generate as part of this document. Be aware, the 'Ignored' restriction type could be applied to mandatory elements, however, these fields have been filtered from this document.

Removed

pain.002.001.03/OriginalGroupInformationAndStatus/StatusReasonInformation/Reason/Proprietary

Ignored

pain.002.001.03/GroupHeader/CreditorAgent

pain.002.001.03/GroupHeader/DebtorAgent

pain.002.001.03/GroupHeader/ForwardingAgent

pain.002.001.03/GroupHeader/InitiatingParty/ContactDetails

pain.002.001.03/GroupHeader/InitiatingParty/CountryOfResidence

pain.002.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other

pain.002.001.03/GroupHeader/InitiatingParty/Identification/PrivateIdentification

pain.002.001.03/GroupHeader/InitiatingParty/Name

pain.002.001.03/GroupHeader/InitiatingParty/PostalAddress

pain.002.001.03/OriginalGroupInformationAndStatus/NumberOfTransactionsPerStatus

pain.002.001.03/OriginalGroupInformationAndStatus/OriginalCreationDateTime

pain.002.001.03/OriginalGroupInformationAndStatus/StatusReasonInformation/Originator

pain.002.001.03/OriginalPaymentInformationAndStatus

Legal Notices

Copyright

SWIFT SCRL © 2014. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.