Supplementary Material

Blind loci and sensor layout for influence-area bridge weigh-in-motion on continuous girders

Quoc-Bao Nguyen, Thai-Son Vu

This document accompanies the main text. Equation, table, figure and section numbers without the prefix S refer to the main text; references are to the main-text reference list, cited here by author and year.

Contents: S1 Nomenclature; S2 Closed forms for two- and three-span beams; S3 General channels, finite element verification and invariant weighting functions; S4 Multi-channel estimation and placement; S5 Identifiability, sensitivities and Möbius law; S6 Laboratory test; S7 Public field records; S8 Mây Bridge; S9 Dynamics and baseline handling; S10 Error budget and design checklist; S11 Scripts, console output and derived data.

S1. Nomenclature

Table S1. Nomenclature.

Symbol	Meaning
A^+	positive part of the area under an influence line
a	vector of channel weights of a multi-channel estimator
b	relative bias of the load caused by a residual offset, Eq. (10)
B_m	boundary sensitivity $\lvert \partial \ln C_m / \partial \ln \kappa \rvert$
C_0, C_∞	integral constant for pinned and for fixed piers at $\alpha = 1$, Eq. (13)
C_m	integral constant of the channel at m, Eq. (2) (m²/kN for deflection); called “the constant” in the text
$C_\varepsilon, C_\theta, C_V$	integral constant of a strain, rotation and shear channel
c	distance of the gauged fiber from the neutral axis (m)
d_i	distance of axle i behind the first axle (m)
EI, EI_{mid}, EI_{ref}	flexural rigidity; design value at mid main span; reference rigidity used to normalize N_w (kN m²)
F_A	end-support reaction (kN)
f_1, T_1	fundamental frequency and period of the girder
$g(x)$	weighting function applied along a record
h	girder depth (m)
I	second moment of area

Symbol	Meaning
J_m	record integral of the channel at m over a complete crossing, in space
k, k_g	rotational stiffness of a monolithic pier; girder stiffness against the pier-rotation pattern $\theta_6 = -\theta_7$ (kN m/rad)
$\hat{k}$	pier stiffness relative to the side-span rigidity, $k L_{side}/E I_{side}$
K_g, K_p	girder and pier parts of the stiffness matrix
L	length of the span containing the sensor, including the span of the laboratory beam (m)
L_p	length of the loaded path (m)
L_{tot}	length of the integration record (m)
M_q	bending moment under a uniform load q_0 over the whole path
$\acute{M}_l$, $\acute{M}_r$	normalized end moments $-8M/\left(q_0 L^2\right)$ at the left and right ends of a span (positive for hogging)
N_w, N_M	deflection and strain (moment) indicators, Eqs. (8) and (7)
N_θ, N_V, N_F	rotation, shear and end-reaction indicators (Section 2.2, Section S3)
P_{tot}, P_0	total load of a crossing; weighed reference load (kN)
P_t, J_t, J_0	load and record integral of a target crossing; record integral of the reference crossing
P_δ	offset-equivalent load $\delta_0 L_{tot}/C$ (kN)
R	cancellation ratio C/A^+
r_{87}	measured-to-model ratio at gauge N8 divided by that at gauge N7; $r_{87}=1$ when one model fits both gauges
S_α, S_k	logarithmic sensitivities $\partial \ln C_m/\partial \ln \alpha$, $\partial \ln C_m/\partial \ln k$ (Section S5)
t_{cr}	duration of a crossing (s)
w, w_q	deflection; deflection under the uniform load q_0 over the whole path
α	ratio of effective to design girder rigidity
β	main-to-side span ratio L_{main}/L_{side} (three spans)
γ	rigidity ratio: $E I_2/E I_1$ (two spans, span 1 instrumented); $E I_{main}/E I_{side}$ (three spans)
δ_0	residual zero offset after re-zeroing before and after a crossing, in the units of the channel (mm for deflection)
ζ	position in the main span from the pier, as a fraction of the main span
η_m	influence line of the channel at m
κ	scaled pier stiffness k/α (kN m/rad, since α is dimensionless)
λ	span ratio L_2/L_1 of the adjacent to the instrumented span (two spans)
μ	interior-moment parameter, $\mu = -8M_B/\left(q_0 L^2\right)$ with $L=L_1$ (two spans) or L_{side} (three spans); Eqs. (4), (14)
r^2	coefficient of determination
ρ	common-mode fraction of the offset or noise between channels
Σ	covariance matrix of the channel integrals

Symbol	Meaning
σ, Δx	standard deviation of the white noise of a record; sampling interval along the record
$\sigma_{P,noise}$	standard deviation of the load estimate caused by white noise
τ	tolerance on the static misfit of a gauge
ξ	sensor position as a fraction of its span
BPM	beam-property method: load = record integral / modeled constant
SLM	standard-load method: constant taken from a crossing of known weight
WIM, BWIM, NOR	weigh-in-motion; bridge weigh-in-motion; Nothing-on-Road (no sensors on the road surface)
CI, CV, MAE, SD	confidence interval; coefficient of variation; mean absolute error; standard deviation
FE	finite element
GLS	generalized least squares
GUM	Guide to the Expression of Uncertainty in Measurement
GVW	gross vehicle weight
LOO, LOTO	leave-one-run-out and leave-one-truck-out cross-validation
TOST	two one-sided tests of equivalence
N7, N8	deflection gauges at mid main span and at $0.4L$ of a side span (Mây Bridge)
T5–T8	supports of the main unit of the Mây Bridge: T5, T8 end supports, T6, T7 inner piers (Section 5.1)

S2. Closed forms for two- and three-span beams

For unequal spans the uniform-load support moment of a two-span beam is $M_B = -q_0\left(L_1^3/EI_1 + L_2^3/EI_2\right)/\left[8\left(L_1/EI_1 + L_2/EI_2\right)\right]$. Superposing the simply supported uniform-load deflection of span 1 and the deflection due to M_B, evaluating at x_m and dividing by q_0 gives Eq. (5) with $\mu = -8M_B/\left(q_0 L_1^2\right)$, which is $\mu_{2\,span}$ of Eq. (4). Because $1 - 2\xi^2 + \xi^3 = (1-\xi)\left(1 + \xi - \xi^2\right)$, setting $F = 0$ gives Eq. (6). With uniform rigidity, the blind condition for a mid-span sensor is $3\lambda^2 - 3\lambda - 2 = 0$, and maximizing F over ξ at $\mu = 1$ gives $8\xi^2 - \xi - 1 = 0$. Hence, for a mid-span sensor on two spans of equal rigidity, the blind span ratio and, for equal spans, the optimal sensor position are

$$\lambda_{crit} = \frac{3+\sqrt{33}}{6} = 1.4574\,,\quad \xi^* = \frac{1+\sqrt{33}}{16} = 0.4215\,.$$

In units of $L_1^4/\left(192\,EI_1\right)$, the positive contribution of the instrumented span varies only between 1.50 and 2.00 for λ from 0.5 to 2.0, whereas the negative contribution of the adjacent span sweeps from −0.125 to −4.00; the cancellation is driven almost entirely by the adjacent span.

For the symmetric three-span beam the three-moment equation gives $M_B = M_C = -q_0 L_{side}^2 \mu/8$ with $\mu_{3\,span}$ of Eq. (4). Three equal spans give $\mu = 4/5$. For a mid side-span sensor and uniform rigidity, the blind ratio is the positive root of $6\beta^3 - 15\beta - 4 = 0$,

$$\beta_{crit} = \sqrt{10/3}\cos\left[1/3\arccos\left(2/5\sqrt{6/5}\right)\right] = 1.7006\,.$$

The blind locus over all side-span positions ends at $\beta = 2\cos(\pi/9) = 1.8794$. The optimal side-span position solves $8\xi^3 - (12 - 3\mu)\xi^2 + (2 - \mu) = 0$ (Table S2). For the threshold 0.2, the near-blind band at mid side span, $1.621 < \beta < 1.775$, runs from the root of $30\beta^3 - 69\beta - 16 = 0$ (1.621) to that of $10\beta^3 - 27\beta - 8 = 0$ (1.775). A mid main-span deflection sensor is blind at $\beta = 0.9647$. For a sensor at $\zeta = x/L_{main}$ in the main span, $192\,E\,I_{main}\,C_m/L_{main}^4 = 8\left[\zeta\left(1 - 2\zeta^2 + \zeta^3\right) - \nu\,\zeta\,(1 - \zeta)\right)$ with $\nu = 3\left(\gamma + \beta^3\right)/\left[\beta^2(2\gamma + 3\beta)\right)$. For $\beta = 1.636$ the strain blind point in the main span lies at $\zeta_0 = 0.177$ from the pier.

Table S2. Symmetric three-span beam, uniform rigidity: optimal side-span position ξ^* and deflection indicator N_w (Eq. (8); 2.5 for a simply supported mid-span).

β	μ	ξ^*	N_w at ξ^*	N_w at $\xi = 1/2$
1.0	0.800	0.4460	1.322	1.300
1.2	0.9743	0.4251	1.076	1.039
1.4	1.208	0.3875	0.7585	0.6884
1.5	1.346	0.3582	0.5807	0.4808
1.636 (= 90/55)	1.558	0.2994	0.3316	0.1632
1.7	1.666	0.2608	0.2202	0.0015

Asymmetric three-span beams. For arbitrary spans L_1, L_2, L_3 and rigidities $E\,I_1, E\,I_2, E\,I_3$, the two support moments follow from the three-moment equations at the inner supports, solved symbolically; the sensor deflection under a uniform load then follows by superposition, as above. The general expressions are long and are given in the scripts. Four asymmetric cases agree with FE to a relative error of at most 9.2×10^{-12}. With the sensor at mid-span of span 1 and uniform rigidity, the blind ratio L_1/L_2 is 0.589774, 0.591969, 0.587260, 0.565712, 0.525757 and 0.461410 for L_3/L_2 = 0.3, 0.5, 0.6, 0.8, 1.0 and 1.2 (main-text Fig. 2b).

Strain blind-locus maps. Figures S1 and S2 map the strain indicator N_M over the sensor position and the span ratio for two-span and symmetric three-span beams. For two equal spans the strain near-blind band is $0.676 < \xi < 0.812$, that is, 0.19–0.32 of the span from the interior support.




Figure S1. Two-span beam: (a) strain indicator N_M over the sensor position and the span ratio λ, with the strain and deflection blind loci and the near-blind band; (b) blind positions against λ.




Figure S2. Symmetric three-span beam: strain indicator N_M (a) in the side span and (b) in the main span measured from the pier, over the span ratio β, with the blind loci, the near-blind band and the Mây Bridge span ratio.

Threshold sensitivity. The threshold 0.2 is a design convention (Section 2.3). Table S3 gives the near-blind bands of three gauges for thresholds of 0.1, 0.2 and 0.3 (script `s06_threshold_sensitivity.py`).

Table S3. Near-blind bands against the threshold on the indicator magnitude; prismatic beams of uniform rigidity. Strain: two equal spans, distance from the interior support as a fraction of the span. Deflection: mid-span gauge on two spans (span ratio λ) and mid side-span gauge on a symmetric three-span beam (span ratio β).

Threshold	Strain, two equal spans	Deflection, mid-span, two spans: λ	Deflection, mid side span, three spans: β
0.1	0.218–0.285	1.422–1.492	1.662–1.738
0.2	0.188–0.324	1.385–1.525	1.621–1.775
0.3	0.161–0.369	1.347–1.557	1.580–1.811

S3. General channels, finite element verification and invariant weighting functions

For a prismatic span with end-moment parameters $\acute{M}_l$, $\acute{M}_r$ and $\xi = x/L$, the indicators are $N_w = 8\,\Phi$ with $\Phi = \xi\left(1 - 2\xi^2 + \xi^3\right) - \acute{M}_l/2\left(2\xi - 3\xi^2 + \xi^3\right) - \acute{M}_r/2\left(\xi - \xi^3\right)$, $N_\theta = 24\,E\,I\,C_\theta/L^3 = \Phi'(\xi)$, N_M of Eq. (7) and $N_V = 2C_V/L = 1 - 2\xi + \left(\acute{M}_l - \acute{M}_r\right)/4$. N_θ, N_M and N_V equal 1 for the simply supported reference (end rotation, mid-span moment, end shear). N_w equals 2.5 at a simply supported mid-span and 1 at mid-span of each span of an equal two-span beam. For the two-span beam, $\left(\acute{M}_l, \acute{M}_r\right) = (0, \mu)$ in span 1 and $\left(\mu/\lambda^2, 0\right)$ in span 2; for the symmetric three-span beam, $(0, \mu)$ in the side span and $\left(\mu/\beta^2, \mu/\beta^2\right)$ in the main span with pinned piers; with pier springs, μ follows from Eq. (14) and the main-span values from $\acute{M}_{main}$ in Section 2.5. Strain zeros solve $4\xi^2 - \left(4 + \acute{M}_l - \acute{M}_r\right)\xi + \acute{M}_l = 0$.

All closed forms of Section 2.2 agree with FE evaluations of Eq. (2) in 981 checks, with a maximum error of 8.1×10^{-11} on the normalized indicators. The verification covered two-span, symmetric and asymmetric three-span and four-span beams, zero-moment positions, ten blind configurations, the identity for a two-truck convoy on piecewise-prismatic girders with elastic pier springs (relative error 2.8×10^{-9}), and the haunched Mây Bridge FE against an independent force-method solution (5.4×10^{-10}). Truncating the record when the first axle leaves changed the integral by up to 59 % (rotation) and 10 % (moment) on the two-span example.

For the most general linear estimator $\hat{P} = \sum_j \int g_j(x)\, y_j(x)\, dx$, with weighting functions g_j along the records y_j, the mean is $\sum_i P_i \psi(s_i)$, with s_i the position of axle i and $\psi(s) = \sum_j \int g_j(x)\, \eta_j(x - s)\, dx$. If ψ must be constant in s for every set of influence lines supported on $[0, L_p]$, then $\int_0^{L_p} \left[g(u+s) - g(u+s')\right)\eta(u)\, du = 0$ for every admissible η, so $g(u+s) = g(u+s')$ almost everywhere. Each g_j is therefore constant, and the only freedom lies across channels. SLM relies on this invariance. An estimate built on the absolute value of the record (Deng et al., 2025) is not linear in the axle loads, so it loses this invariance whenever contributions of opposite sign overlap.

The same argument links SLM to transmissibility-based weighing (Yan et al., 2022): a transmissibility is a ratio of response spectra, and at zero frequency it equals the ratio of

record integrals. A record integrated uniformly in time weights space by $1/v(x)$, so the integral must be taken in space; at constant speed v the time integral is J_m/v.

When the influence line is known, other invariant weighting functions exist; for two equal spans their white-noise variance is lower by a factor of 1.5–6.6, but a 20 % rigidity error in the adjacent span then produces configuration-dependent errors of −1.1 % to +2.0 % (Fig. S3).




Figure S3. Structure-aware weighting functions for two equal spans (Section S3): (a) weighting functions along the record, (b) white-noise variance relative to uniform weighting against the range of entry shift, (c) invariance defect, (max − min)/mean of the constant over the axle configurations, under a 20 % rigidity error in the adjacent span or a 0.5 m sensor-position error.

S4. Multi-channel estimation and placement

For one channel, Eq. (11) returns $\hat{P}=J/C$ with variance $\sigma_{P,noise}^2+P_\delta^2$, where $\sigma_{P,noise}$ is the standard deviation of the load estimate caused by white noise. For two channels the zero-sum weights are $a=(1,-1)/(C_1-C_2)$, and a second sensor over a support ($C_2=0$) gives the familiar differential measurement against a reference. The white-noise variance then rises by the factor $2C_1^2/(C_1-C_2)^2$, which is 1.65–2.0 on the beams studied. This price is small, because for the long-span parameters of Section 5.3 with $\Delta x=0.1$ m the white-noise term of Eq. (12) is only about 5 × 10^{-6} of $\delta_0^2 L_{tot}^2$, and 5 × 10^{-5} of the offset term at $\rho=0.9$ (σ = 0.01 mm, δ_0 = 0.1 mm, L_{tot} = 220 m, that is, the 200 m unit plus a 20 m convoy allowance). Strain and deflection channels need separate zero-sum constraints.

Which extreme of $C(x)$ to use depends on the offsets. With independent offsets, every sensor should sit as close as possible to the maximum, because the GLS variance then falls with the sum of the squared constants. With correlated offsets, one sensor should sit at the minimum, because a common offset cancels in the difference of two channels and the variance of Eq. (12) falls with the spread of the constants. The placement rule was verified by a brute-force

search over 96 cases, which found no design better than the vertex design, and by a Monte Carlo study with 10^5 random axle configurations per case, which confirmed that the estimators are unbiased and that Eqs. (11) and (12) hold to within 0.6 %. Figure S4 shows the gain over the best single sensor under the assumed noise model, Fig. S5 the extremes of $C(x)$ that the rule selects, and Fig. S6 the Monte Carlo verification. For the Mây Bridge girder, the single-gauge standard deviation of the load at mid main span is 22.5 % for a 200 m record under the assumptions of Section 5.3 (ρ = 0.9, calibration A), against 24.8 % for the 220 m record.




Figure S4. Multi-channel estimation under the assumed noise model: (a) variance with two or three optimally placed sensors relative to the best single sensor, against the common-mode fraction ρ of the offset; (b) standard deviation of the load against the offset level for single sensors and three-sensor designs; (c) zero-sum pair at $\rho = 1$ against the white-noise level. Line style: (a) two sensors solid, three sensors dashed; (b) ρ = 0 dotted, 0.9 solid, 1 dashed; thick light lines: single sensor.




Figure S5. Uniform-load response $C(x)$ along six girders (two-span, three-span and the Mây Bridge girder under calibrations A and B), with the maximum and minimum selected by the placement rule.




Figure S6. Monte Carlo verification: distribution of the load error for a single gauge, GLS and the zero-sum estimator with three gauges, (a) on a 30 + 60 + 30 m beam and (b) on the Mây Bridge girder (calibration A), and (c) Monte Carlo standard deviation relative to theory against the number of axles (circles: beam of (a); squares: girder of (b)).

S5. Identifiability, sensitivities and Möbius law

Let $G = K^{-1}$ with $K = \alpha K_g + k K_p$, where K_p has a unit entry on each inner-pier rotational degree of freedom, and $C_m = e_m^T G q$ with q the consistent uniform load. Then $dC_m/dk = -\sum_i \theta_{m,i}\theta_{q,i}$, where $\theta_{m,i}$ and $\theta_{q,i}$ are the pier rotations under a unit load at the gauge and under the uniform load. The logarithmic sensitivities $S_\alpha = \partial \ln C_m / \partial \ln \alpha$ and $S_k = \partial \ln C_m / \partial \ln k$ satisfy $S_\alpha + S_k = -1$ by Euler's theorem, because C_m is homogeneous of degree -1 in (α, k). Mirror symmetry decouples the two pier-rotation patterns, $\theta_6 = \theta_7$ and $\theta_6 = -\theta_7$; the mirror-symmetric uniform load excites only the pattern $\theta_6 = -\theta_7$, and the Sherman–Morrison formula gives the linear-fractional (Möbius) law of Eq. (13) with $1/k_g$ the pier flexibility of the girder in this pattern at $k = 0$. For the Mây Bridge model the law holds to a relative error of 5×10^{-6} over $k = 10^5$–10^{12} kN m/rad, and Eq. (14) agrees with FE to 4.4×10^{-7} (Fig. S7).




Figure S7. Mây Bridge proportions, prismatic beam: (a) deflection indicators of the side-span and main-span gauges against the relative pier stiffness $\hat{k}$, closed form against FE; (b) boundary sensitivity

B_m. Dotted line in (b): $\hat{k} = 3 + 2/\beta = 4.22$, the girder's own pier stiffness in the pattern $\theta_6 = -\theta_7$, $k_g L_{side}/E I_{side}$.

Because every static response has the form $f(\kappa)/\alpha$, the ratio of two static readings carries all the information about κ; once κ is chosen, either reading gives α. With two static readings the Fisher matrix has a determinant proportional to $(S_{y8} - S_{y7})^2$, where S_{y8} and S_{y7} are the logarithmic sensitivities of the N8 and N7 readings to κ; this determinant vanishes at the minimum of the misfit ratio, that is, at calibration B. A frequency adds a row with the mass as nuisance parameter; a pier rotation adds a row without a nuisance parameter. Unequal pier stiffnesses would bring in the pattern $\theta_6 = \theta_7$, which Eq. (13) does not cover.

S6. Laboratory test

The specimen is a steel hollow square tube on three supports forming two equal spans of 2500 mm. Deflection at mid-span of the first span was measured with a linear variable differential transformer of 0.005 mm resolution. The measured single-load influence line of the beam is shown in Fig. S8. The SLM deviations match the growth of the measured-to-analytical integral ratio (1.010, 1.016 and 1.017 for one, two and three loads), which the data cannot assign to either support seating or the stated masses. Table S4 compares the identified total loads with direct weighing, and Table S5 lists the mid-span deflection for all three load configurations; the order of the three-load group is the best-fitting order discussed in Section 3. On the 250 mm grid the trapezoidal rule underestimates the exact single-load integral by 0.500 %. It is used throughout, because Simpson's rule loses its advantage when the kinks of trailing loads fall inside its panels.




Figure S8. Laboratory two-span beam: measured and analytical influence line of the mid-span deflection of the first span for the single 40.64 N load (Table S5).

Table S4. Identified total loads against direct weighing (trapezoidal rule). BPM: $P = J / C_m$ with the analytical constant; SLM: $P_t = P_0 J_t / J_0$ with the single-load record as reference.

Configuration	Weighed (N)	BPM (N)	BPM deviation	SLM (N)	SLM deviation
Two loads	66.99	67.73	+1.10 %	67.40	+0.61 %
Three loads	125.08	126.57	+1.19 %	125.95	+0.70 %

Table S5. Mid-span deflection of the first span (mm), mean of three cycles. Single load 40.64 N; analytical values from the closed-form influence line.

x (mm)	Analytical, single	Measured, single	Two loads	Three loads
0	0.0000	0.0000	0.0000	0.0000
250	0.8874	0.8844	0.4625	0.5525
500	1.6968	1.6975	1.8813	1.0450
750	2.3501	2.3525	3.1413	2.5413
1000	2.7693	2.7738	4.0988	4.8700
1250	2.8764	2.8827	4.6350	6.7588
1500	2.6253	2.6363	4.6238	7.9350
1750	2.0980	2.1100	4.0688	8.2775
2000	1.4087	1.4213	3.1375	7.6825
2250	0.6713	0.6838	1.9600	6.2800
2500	0.0000	0.0000	0.7715	4.3725
2750	−0.5132	−0.5069	−0.2689	2.2975
3000	−0.8644	−0.8556	−1.0063	0.3021
3250	−1.0715	−1.0600	−1.4988	−1.2588
3500	−1.1526	−1.1438	−1.7813	−2.3650
3750	−1.1255	−1.1200	−1.8600	−3.0363
4000	−1.0085	−1.0013	−1.7738	−3.3300
4250	−0.8194	−0.8175	−1.5525	−3.2663
4500	−0.5763	−0.5816	−1.2213	−2.9450
4750	−0.2971	−0.3019	−0.8125	−2.4125
5000	0.0000	0.0000	−0.3325	−1.7088
5250			0.0000	−1.0713
5500				−0.3650
5750				0.0000

S7. Public field records

Data. The strain transducers of the Virginia Smart Road Bridge lie 158.5 m from the first abutment, at longitudinal stations about 2 m apart under the wheel path. Day 1 has 12 channels in three groups: four wheel-path gauges with clear axle spikes (ch4, ch5, ch11, ch12), a partner gauge at each of these four stations, and four further gauges without axle spikes (ch1, ch2, ch8, ch9). The bridge depth is about 3.8 m at mid-span and 9.5 m at the piers. Sampling was 100 Hz on day 1 and 200 Hz on day 2. The day-1 driver-reported gross

weights were 21.2–22.8 t for the runs used. Errors are given as a percentage of the gross vehicle weight (GVW). Because the weights vary by only a few percent within each day, a predictor that always returns the mean calibration weight already has a mean absolute error (MAE) of 2.0 % on day 2 and 2.2 % on day 1, and the field data test the scatter and invariance of the integral constant rather than the ability to discriminate weights.

Processing. Speeds were obtained from the axle spikes and the measured wheelbase and agree with the dataset authors' processing script within 1.4 % on average (at most 4.6 % for a single run). A low-pass fit of the records gives lane-A speeds 1.139 times the spike speeds (median; SD 0.124; 22 runs). Lane-B speeds were taken from the lag between gauges. Records were integrated over the whole time the truck was on the bridge plus 5 s at each end. Three day-1 runs with two trucks on the bridge and four passes without documented weights were excluded. Vehicle-free noise windows were at least 70 s from any detected vehicle.

Invariance and speed. On day 1, eight of the 12 gauges have a coefficient of variation (CV) of 5.8–13.5 %, consistent with the noise (χ^2 p = 0.13–0.71; Table S6), but only ch11 shows equal constants for both trucks within ±10 % (main-text Fig. 5a); each equivalence test wrongly declares equivalence with probability at most 5 %, so chance alone would produce at most about 0.6 passes in 12 tests, and one pass is weak evidence. The first truck ran at 10.4–12.8 m/s and the second at 19.1–19.8 m/s, so speed and truck are almost perfectly confounded (correlation 0.98). Day-2 speeds were 13–28 m/s; no speed effect was resolved (+6 % per 10 m/s, 95 % CI −23 to +35 %), but the confidence interval of the slope is too wide to call the constant speed-independent (Fig. S9). Equivalence was tested by two one-sided tests (TOST; Table S7); for the day-2 gauge average, the 90 % CI used for the equivalence test is 0.76–1.27, so differences of up to about 27 % cannot be excluded. Day-2 noise amplitudes at the median speed were 13.7–32.8 με m.




Figure S9. NOR-BWIM: integral constant against speed for the day-1 gauge average, gauge ch1 and the day-2 gauge average, by truck; the panel titles give the fitted slope per 10 m/s with its 95 % CI.

Lanes, superposition and gauges. In lane B, all channels have CV 31–40 %, and st36, st31 and the gauge average fail the χ^2 test (χ^2 p = 0.016–0.027). The st36 constant in lane B is 0.64 of that in lane A (95 % CI 0.47–0.81). The two-truck runs gave 0.92 and 0.92 of the summed single-truck predictions (pooled 95 % CI 0.77–1.06); the GLS combination gave 0.82 (95 % CI 0.73–0.91). A one-dimensional beam model predicts ch11/ch8 ratios of 0.978–1.003. The ratio of st36 to st40 constants is 3.24 ± 0.56 in lane A against 1.82 ± 0.10 in lane B (± one standard error), about 2.5 standard errors apart. For the gauge average the lane-B constant is 0.79 of that in lane A (95 % CI 0.59–1.00), so the lane effect is resolved only for st36. Lane-B speeds came from the lag between gauges, so the lane ratios also contain any difference between the two speed estimates.

Estimators. Table S8 gives all out-of-sample errors, including leave-one-truck-out (LOTO) and the four wheel-path gauges of day 1; Fig. S10 also shows in-sample results. On day 2, GLS with the measured covariance was significantly worse than the gauge average (paired difference +8.5 percentage points, 95 % CI +2.3 to +15.1); on day 1 the estimators cannot be told apart, and on both days every estimator is worse than the mean-weight predictor. Table S9 and Fig. S11 give the correlations behind this result, and Table S10 shows that the covariance of the crossing residuals, unlike the vehicle-free covariance, predicts the observed order of GLS and gauge average. The day-2 per-crossing SD predicted by the vehicle-free covariance (% of GVW) is 16.2 for the best single gauge, 32.5 for the worst single gauge, 19.8 for the gauge average, 19.4 for GLS with diagonal Σ, 12.7 for GLS with measured Σ, 13.3 for the zero-sum estimator with measured Σ and 16.1 for the zero-sum estimator with Σ = identity. The GLS weights with the measured Σ are st40 +0.16 and st36 −0.35. GLS with Σ estimated from the crossing residuals has a mean absolute error of 8.5 % of GVW in sample and 23.4 % out of sample (root-mean-square errors 10.4 % and 28.4 %), that is, it over-fits with eight runs.




Figure S10. NOR-BWIM: mean absolute error of the gross weight for single-gauge, gauge-average, GLS, zero-sum and mean-weight predictors, with 95 % bootstrap confidence intervals: in sample (IN), leave-one-run-out (LOO) and leave-one-truck-out (LOTO). (a) Day 2, 4 gauges; (b) day 1, 4 wheel-path gauges; (c) day 1, 12 gauges (multi-gauge estimators use all 12; only the single gauges ch5 and ch11 are shown). GLS-diag: diagonal covariance; zero-sum-eq: zero-sum estimator with equal noise (Σ = identity matrix); GLS-resid: covariance from crossing residuals.




Figure S11. NOR-BWIM: correlation matrices of the integrated vehicle-free noise between gauges, for windows of crossing length: (a) day 1 (12 gauges) and (b) day 2 (4 gauges); T: window length.

Beam model and limits. The beam model of the five-span girder (Euler–Bernoulli, parabolic haunch, second moment proportional to h^2) gives r^2 = 0.79–0.94 against the strain histories; zeros of the uniform-load moment in span 2 at 121.6 m and 190.8 m; a strain constant of the gauges 0.69 of the largest on the girder (0.56–0.93 across rigidity laws); a cancellation ratio R = 0.51; and contributions of span 2 of about 170 % of the net integral and of the adjacent spans −26 % and −66 % (Fig. S12). Figure S13 shows the synthetic records of the dataset authors processed with the same integration. The tests rest on four trucks, two axle counts and seven or eight runs per day. The gauge calibration factors and exact positions are not published, so absolute constants cannot be checked. The dataset authors reported a mean

absolute GVW error of 4.6 % for their influence-line system on this bridge (Moghadam et al., 2023a); it was obtained on different runs and is not compared directly with the results of the main text.




Figure S12. Five-span girder, beam model with uniform rigidity and two haunch laws: (a) uniform-load moment and (b) strain constant along the girder, normalized at the gauges, and (c) the single-gauge error expected from the measured noise for a 25 t truck. Red line: gauge position; dotted lines: zero-moment points.




Figure S13. Synthetic strain records of the dataset authors: integral per unit gross weight (a) by truck and lane, and (b) for a 3-axle truck against speed.

Table S6. Integral constant C and its scatter over the runs, lane A unless stated. CV expected: coefficient of variation predicted from the measured vehicle-free noise. For ch1, ch2, ch8 and ch9 the residual variance is 2.9–5.1 times the vehicle-free noise variance.

Day, channel	Runs	C (με m/t), 95 % CI	CV observed (%)	CV expected (%)	χ^2 p
1, ch11 (best)	7	−5.85 (−6.17, −5.53)	5.8	6.8	0.60
1, gauge average (4 wheel-path gauges)	7	−4.03 (−4.24, −3.82)	5.6	6.1	0.53
1, ch1, ch2, ch8, ch9	7	−1.49 to −2.38	17.2–19.1	7.8–11.0	≤ 0.012
2, st36	8	−5.97 (−6.57, −5.38)	12.0	16.5	0.73
2, gauge average (4 gauges)	8	−4.12 (−4.62, −3.63)	14.4	20.2	0.79
2, lane B, average	8	−3.27 (−4.19, −2.35)	33.7	23.2	0.027

Table S7. Ratio of the integral constants of two trucks, lane A unless stated. Day 1: second to first truck, both 3-axle; day 2: 5-axle to 3-axle truck. Equivalence by two one-sided tests (TOST) at the 5 % level: the 90 % CI of the ratio lies inside the stated margin (for ch11, 0.904–1.098), so a 95 % CI can extend beyond a margin that is shown.

Day, channel	Ratio (95 % CI)	Equivalence
1, ch11 (best)	0.996 (0.874–1.136)	shown within ±10 %
1, gauge average (4 wheel-path gauges)	0.955 (0.863–1.057)	shown only within ±11.8 %
1, ch1, ch2, ch8, ch9	0.740–0.783	invariance rejected (CIs exclude 1)
2, st36	1.005 (0.735–1.375)	not shown
2, gauge average (4 gauges)	0.978 (0.697–1.374)	shown only within ±26.7 %
2, lane B, average	0.749 (0.440–1.276)	– (constants fail the χ^2 test, Table S6)

Table S8. Mean absolute error of the gross weight (% of GVW), out of sample, with 95 % bootstrap CIs over the test runs (8 on day 2, 7 on day 1). LOTO: calibrated on one truck, tested on the other. The leave-one-run-out columns contain every row of the estimator table of the main text (Table 2).

Estimator	Day 2, leave-one-run-out	Day 2, LOTO	Day 1, 12 gauges	Day 1, 4 wheel-path gauges
Best single gauge (chosen after the fact)	8.4 (2.9–15.3)	7.6	4.8 (1.8–7.9)	4.8 (1.8–7.9)
Worst single gauge	27.9 (12.9–44.5)	24.3	17.6 (11.0–23.4)	12.1
Gauge average	11.9 (6.0–18.6)	11.1	5.3 (2.5–7.8)	5.4 (3.3–7.4)
GLS, diagonal Σ	11.4 (6.0–18.0)	10.8	5.3 (2.5–8.0)	5.2 (3.3–7.1)
GLS, measured Σ	20.4 (12.3–28.8)	17.7	5.8 (3.5–8.1)	4.9 (3.0–6.9)
Zero-sum, measured Σ	20.3 (12.4–28.6)	18.0	6.0 (2.9–9.3)	8.3 (3.9–13.4)
Zero-sum, Σ = identity matrix	12.3 (6.1–20.2)	10.8	13.0 (7.1–19.0)	8.4 (4.6–12.9)
Mean-weight predictor (mean of the calibration runs)	2.0 (1.9–2.0)	3.4	2.2 (1.1–3.5)	2.2 (1.1–3.5)

Table S9. Correlation between gauges of the integrated strain: means over gauge pairs, with 95 % bootstrap CIs in parentheses. Vehicle-free windows: 1227 on day 2 and 3405 on day 1. Crossing residual: deviation of a crossing's integral from its calibrated value. –: not computed.

Correlation of	Day 2, 4 gauges	Day 1, 12 gauges
vehicle-free noise, non-overlapping windows	0.92 (0.83–0.96)	0.42 (0.26–0.54)
vehicle-free noise, window length of each crossing	0.90	–
crossing residuals	0.63	–
crossing residuals, st40 with its neighbors	0.30–0.37	–

Table S10. Day 2: per-crossing standard deviation (SD) of the gross weight predicted by two covariance models, and the observed error (% of GVW). SD and MAE are different measures; the table compares the order of the two estimators, not magnitudes. Row 1 is the mean of the leave-one-run-out predictions; on the all-run basis of row 2, the vehicle-free value for GLS is 12.8.

Quantity	GLS, measured Σ	Gauge average
SD predicted from the vehicle-free covariance	12.7	19.8
SD predicted from the covariance of the crossing residuals	21.0	14.6
Observed MAE, leave-one-run-out (main text Table 2)	20.4	11.9

S8. Mây Bridge

Bridge and test. The bridge carries provincial road ĐT389. In the June 2020 acceptance test, four trucks stood in the side span (gauge N8) and six in the main span (gauge N7). The trucks were 3-axle, nominally 5 + 10 + 10 t, with a mean weighed gross weight of 25.06 t (Table S11). Mitutoyo dial gauges, mounted on independent frames fixed to the ground, read the peak deflection under central and eccentric transverse positions at three measuring points across each section (Table S12). The readings across one section differ by up to 2.05 mm in the eccentric N7 case, about 13 % of the mean reading.

Model. Design sections: depth 2.40 m (mid-span) to 5.40 m (piers), second moments 5.482 m⁴ and 59.61 m⁴, E_c = 36 057 MPa. Model-form variants: L_v = 40 and 45 m (base 44 m), exponents 2.5 and 3.2 (base 2.943), rigid pier zone ±1.5 m. The misfit ratio r_{87} is 1.126 at κ = 10^7 kN m/rad, has its minimum 1.058 at κ = 1.68 × 10^8 kN m/rad (calibration B) and is 1.091 for fixed piers.

Tolerance. The six readings of each section have a standard deviation of 4.7–5.0 % about their mean (Table S12), so the standard error of the mean is 1.9–2.0 %. Dividing the six-reading SD by $\sqrt{6}$ treats the transverse readings as independent samples; this is an assumption, because the scatter comes from the transverse positions and the readings are not replicates. The model-form standard uncertainty of 1.75 % is half the spread of ln of the predicted N8-to-N7 ratio across the model-form variants at the minimum of the misfit ratio (κ = 1.68 × 10^8 kN m/rad), divided by $\sqrt{2}$ to give a per-gauge value (script `ident_static.py`). Combined in quadrature with the pooled standard error of the mean, it gives 2.64 % for each section mean and τ = 5.3 % at two standard deviations.

Admissible sets (Table S13). The conclusions depend on the tolerance, so Table S13 gives the admissible set at τ = 3, 4 and 5.3 %. At τ = 3 % the admissible set shrinks and excludes the design rigidity, α = 1. The ratio of the largest to the smallest C_8 over the admissible set is 1.5 at τ = 3 %, 3.4 at 4 % and 6.6 at 5.3 %, and 2.4 at 5.3 % with the prior α = 0.9–1.3; for C_7 the same ratios are 1.1, 1.4, 1.5 and 1.1. The upper end of C_8 at 5.3 % needs $\alpha \approx 0.5$ with κ toward fixity.

Frequencies. The measured vertical frequencies (3.43–3.64 Hz; Table S14) would narrow the admissible set further if they belonged to the third vertical mode. This interpretation is conditional: Fig. S14 shows the predicted vertical frequencies against the scaled pier stiffness

κ, and Fig. S15 the static misfit over the plane of α and k with contours of the third vertical frequency. The acceptance test reports only one frequency per span, so the first frequency is not identified, and the Cramér–Rao bound of 0.24 on the standard deviation of $\ln C_8$ that the first and third frequencies would give assumes a measurement that was not made. The bounds of Section 5.3 are evaluated at the design pier stiffness, $\kappa = 2.75 \times 10^7$ kN m/rad, with α refitted to $\alpha^* = 1.07$ (Fig. 7b).




Figure S14. Mây Bridge: first, second and third vertical frequencies against the scaled pier stiffness κ, for low, base and high mass, with the measured band. Curves for $\alpha = 1$ with the dynamic modulus equal to the static modulus; frequencies scale with $\sqrt{\alpha}$.




Figure S15. Mây Bridge: static misfit over the rigidity factor α and the pier stiffness k, with contours of the third vertical frequency equal to the measured values: dashed 3.43 Hz, solid 3.64 Hz; green, red and blue for low, base and high mass. Yellow: first-frequency contours (base mass). White dotted line: best static fit $\alpha^{*}(\kappa)$. Open circle A: calibration A; filled circle A′: best static α at the design k; square B: calibration B. Gray scale: maximum static misfit; the 5.27 % level is τ.

Indicators and channels (Table S15). In the base model, going from pinned to fixed piers multiplies the N8 constant by 14.0 but reduces the N7 constant to 0.59 of its pinned value. The design stiffness sits at $\kappa/k_g = 0.63$, near the steepest part of the Möbius curve, where B_m is 0.51 at N8 and 0.12 at N7. Calibrating to the N8 reading does not fix the N8 constant either: the ratio of C_m to the modeled N8 deflection varies by a factor of 6.5 over the admissible set, against 1.5 for N7. A rotation reading at the end bearing T8 adds little, because its sensitivity duplicates that of N8. At calibration B the two-reading Fisher matrix is singular, so the deflections alone cannot bound $\ln C_8$ (Section S5); with the pier tiltmeter the bound is 0.04.

Strain and end-reaction channels. The haunches move every zero-moment point toward mid-span; the side-span zero lies 26.0–33.3 m from the end support, so a strain gauge at mid side span would be practically blind under calibration A ($N_M = 0.048$) and would change sign with pinned piers. At mid main span the small strain indicator reflects restraint (R_ε = 0.65–1.00). By N_M alone the best strain locations in all haunched models are 5–10 m from the piers ($|N_M| \geq 0.39$), but their gain c/EI is about one quarter to one third of that at mid-span, and one

fifth at the pier face (main-text Fig. 6c). Load cells under the end bearings ($N_F = \xi_0$ = 0.47–0.61) cannot be blind unless the side span loses its sagging zone.

Test-load positions. The longitudinal axle positions of the static test load, taken from the test plan (the test report gives them as drawings), are listed in Table S16 (script `wp3_run.py`).

Table S11. Weighed 3-axle test trucks: gross weight and axle spacings (front to middle axle; middle to rear axle) and track width. Mean gross weight 25.06 t.

Truck	Gross weight (t)	Front axle spacing (m)	Rear axle spacing (m)	Track (m)
1	24.7	3.45	1.35	1.9
2	25	3.65	1.45	1.85
3	25.66	3.45	1.35	1.85
4	25.06	3.85	1.35	1.85
5	25.05	3.45	1.35	1.85
6	25.3	3.65	1.45	1.85
7	25.1	3.7	1.45	1.9
8	25.5	3.65	1.45	1.9
9	24.6	3.65	1.45	1.85
10	24.6	3.6	1.45	1.85

Table S12. Mây Bridge acceptance test (June 2020): measured peak deflection (mm, downward positive) at the two gauge sections, at three measuring points across each section, under central and eccentric truck arrangements.

Section	Measuring point	Central	Eccentric
N8, side span, 0.4L from T8	right edge	5.32	5.91
N8, side span, 0.4L from T8	centerline	5.56	5.55
N8, side span, 0.4L from T8	left edge	5.76	5.22
N7, mid main span	right edge	14.68	14.62
N7, mid main span	centerline	15.24	15.51
N7, mid main span	left edge	15.83	16.67

Table S13. Admissible set of the Mây Bridge model (base model, L_v = 44 m) against the tolerance τ on the misfit of each gauge. Max/min: ratio of the largest to the smallest constant in the set.

Tolerance, prior	κ (kN m/rad)	α	N8 indicator, $\alpha E I_{mid}$	N8 indicator, design $E I_{mid}$	C_8 (m²/kN)	C_8 max/min	C_7 (m²/kN)	C_7 max/min
τ = 3 %	1.0–3.0 × 10^8	0.64–0.80	0.30–0.37	0.38–0.58	9.1 × 10^{-5}–1.4 × 10^{-4}	1.5	3.8–4.3 × 10^{-4}	1.1

Tolerance, prior	κ (kN m/rad)	α	N8 indicator, $\alpha E I_{mid}$	N8 indicator, design $E I_{mid}$	C_8 (m²/kN)	C_8 max/ min	C_7 (m²/kN)	C_7 max/ min
τ = 4 %	4.2 × 10^7–2.0 × 10^9	0.54–0.98	0.22–0.41	0.23–0.77	5.5 × 10^{-5}–1.9 × 10^{-4}	3.4	3.5–4.8 × 10^{-4}	1.4
τ = 5.3 %	≥ 1.8 × 10^7	0.51–1.15	0.14–0.42	0.12–0.82	3.0 × 10^{-5}–2.0 × 10^{-4}	6.6	3.3–5.0 × 10^{-4}	1.5
τ = 5.3 %, prior $\alpha \in$ [0.9, 1.3]	1.8–6.7 × 10^7	0.90–1.15	0.14–0.27	0.12–0.30	3.0 × 10^{-5}–7.2 × 10^{-5}	2.4	3.3–3.6 × 10^{-4}	1.1

Table S14. Vertical natural frequencies of the main-bridge spans reported in the acceptance test.

Span	Vertical frequency (Hz)
Side span T5–T6 (55 m; T6 is the other inner pier)	3.43
Main span T6–T7 (90 m)	3.64
Side span T7–T8 (55 m)	3.63

Table S15. Deflection indicator N_w (Eq. (8)), cancellation ratio R (Eq. (9)) and boundary sensitivity B_m of the Mây Bridge gauges, including the mid side-span position. $E I_{ref}$ = design $E I_{mid}$ and L the span containing the gauge. Calibration A and the pinned-pier and fixed-pier rows have $\alpha = 1$, calibration B has $\alpha = 0.716$, and the admissible set spans α = 0.51–1.15; the haunched pinned-pier and fixed-pier rows give the extreme values over the haunch-length variants (L_v = 40–45 m). B_m at the design stiffness, with $k_g = 4.36 \times 10^7$ kN m/rad. –: not computed.

Model	N_w, N8 at 0.4 L (installed)	N_w, N8 at mid side span	N_w, N7 (installed)	R, N8 at 0.4L	R, N8 at mid side span	R, N7
Prismatic beam, pinned piers	0.287	0.163	0.755	0.14	0.08	0.70
Haunched, calibration A	0.181	0.105	0.209	0.18	0.11	0.59
Haunched, calibration B	0.476[a]	0.377	0.234	0.56	0.49	0.77
Haunched, admissible set (τ = 5.3 %)	0.124–0.822[b]	–	0.190–0.286	0.13–1.00	–	0.56–1.00
Haunched, pinned piers	0.023	−0.066	0.263	–	–	–
Haunched, fixed piers	0.446	0.375	0.145	–	–	–
B_m at the design stiffness	0.51	–	0.12	–	–	–

[a] Above the fixed-pier value because calibration B has α = 0.716; normalized by the effective rigidity $\alpha E I_{mid}$ it is 0.341. [b] The upper part of this range requires $\alpha \approx 0.5$; normalized by the effective rigidity, the range is 0.144–0.422.

Table S16. Longitudinal axle positions of the static test load (model positions from the test plan). Each longitudinal row consists of two 3-axle trucks side by side, so the axle loads per row are 10, 20 and 20 t (5, 10 and 10 t per truck). x is measured from T5, with T8 at x = 200 m.

Scheme	Axle positions x (m), with axle load per row (t)	Distance from T8 (m)
N8, side span (2 rows)	163.45 (10), 167.05 (20), 168.40 (20); 174.40 (10), 178.00 (20), 179.35 (20)	36.55, 32.95, 31.60; 25.60, 22.00, 20.65
N7, main span (3 rows)	87.70 (20), 89.05 (20), 92.65 (10); 98.65 (20), 100.00 (20), 103.60 (10); 109.60 (20), 110.95 (20), 114.55 (10)	–

S9. Dynamics and baseline handling

For a constant force moving across the laboratory beam, the quasi-static error is at most about 1 % when the ratio of the crossing time to the fundamental period, t_{cr}/T_1, is at least 8, and it exceeds 15 % below 2.5 (Frýba, 1999). This bound omits vehicle–bridge interaction and road roughness. The moving-force analysis is reproduced by `s05_moving_force.py`; its console output (`s05_moving_force.log`) lists the quasi-static error against t_{cr}/T_1, the effect of damping and the axle-configuration spread under dynamics.

The authors' deflection records from two simply supported bridges showed post-minus-pre level differences of up to 0.23 mm. Linear re-zeroing removes such differences, so this value bounds the drift before re-zeroing, not δ_0. Figures S16 and S17 show these records, which illustrate the baseline handling and the low-pass filtering recommended in Section S10.




Figure S16. Deflection records of two simply supported bridges (Gie Cục I and Phương Độ): deviation of the event integral from a linear pre/post baseline for several baseline treatments and high-pass filters.




Figure S17. The same records: (a) deflection relative to the linear baseline, unfiltered and low-pass filtered at 2 Hz; (b) dynamic residual removed by the low-pass filter.

S10. Error budget and design checklist

The budget below is indicative, not an evaluation according to the Guide to the Expression of Uncertainty in Measurement (GUM): several entries are scenario ranges and the correlations

between terms are not quantified. To first order, the relative error of BPM is the sum of the relative errors of the rigidity, the gain, the speed and the offset term of Eq. (10), plus four times the relative error of the span length for deflection (two times for strain). SLM removes the structural terms, because they belong to C. Every other term survives as the difference between the target and the reference crossings.

Speed enters twice. It affects the response itself, and it enters again through its measurement, because the space integral is the time integral times the speed measured at the gauges; a speed error therefore passes one-to-one into the weight. Speed variation over a 605 m crossing was not measured. On lane A, speeds from a low-pass fit of the records were 1.139 times those from the axle spikes (SD 0.124, 22 runs), so the choice of speed estimator alone can shift the weight by more than 10 %.

Table S17 evaluates Eq. (10) for the Mây Bridge gauges over the admissible set, with $L_{tot}=200$ m and a truck of the mean weighed gross weight, 25.06 t. The smaller offsets in Table S17 are typical of displacement transducers. Absolute deflection on a 90 m span over water would usually come from a non-contact technique, whose residual offset after re-zeroing has to be established on site, since environmental effects act over the same window (Sohn, 2007; Cross et al., 2013). At $\delta_0=0.1$ mm a single main-span gauge biases a 25 t truck by 16–25 %, and a single side-span gauge by 41–271 %. The zero-sum pair addresses this term only to the extent that the offset is common-mode during crossings.

Transverse position and multiple presence add further terms; Table S18 collects all terms. On the five-span girder the far-lane constant was 0.79 of the near-lane value. At the Mây Bridge the readings across one section differ by up to 2.05 mm in the eccentric N7 case, about 13 % of the mean reading. Several vehicles on the structure return their combined weight; on the five-span girder the two-truck events gave 0.92 of the prediction. A crossing of the 200 m Mây Bridge unit, plus the wheelbase, takes 12.4 s at 60 km/h, and every crossing that overlaps another vehicle in that window must be discarded or treated as a group. The fraction of usable isolated crossings was not quantified. In the laboratory, the reference record and the load-dependent growth of the integral ratio cause the SLM deviations of 0.6–0.7 %. In the field, the noise, the lane and the gauge position dominate, and the weight errors of single crossings, 5–12 % on these records, exceed the spread of the reference weights.

Table S17. Bias of a single-channel estimate caused by a residual offset δ_0, Eq. (10), for a 25.06 t truck; L_{tot} = 200 m. Ranges over the admissible set (τ = 5.3 %).

Gauge	C (m²/kN)	0.02 mm	0.05 mm	0.1 mm	0.2 mm	0.5 mm
N7, mid main span	$3.3–5.0 \times 10^{-4}$	3.3–5.0 %	8–12 %	16–25 %	33–50 %	82–124 %
N8, $0.4L$	3.0×10^{-5}–2.0×10^{-4}	8–54 %	21–136 %	41–271 %	82–543 %	206–1356 %

Table S18. Indicative sensitivity budget of influence-area weighing. Values are those measured or assumed in this study; they are not combined.

Term	Sensitivity	Cancels in SLM?	Value in this study
Flexural rigidity EI	1	yes	BPM only; Mây Bridge N8 constant varies 6.6-fold over the admissible set
Span length	4 (deflection), 2 (strain)	yes	BPM only
Gain	1	if not recalibrated between crossings	not evaluated
Reference weighing P_0	1	no	laboratory: International Organization of Legal Metrology (OIML) class M1 weights; field: day-1 weights driver-reported
Residual offset, drift δ_0	L_{tot}/J per unit offset	only if common-mode during crossings	Table S17; field per-crossing SD of the gauge average predicted 19.8 % (day 2), 5.3 % (day 1)
Speed effect	1	no	day 2: +6 % per 10 m/s (95 % CI −23 to +35 %), not resolved
Speed measurement	1	no	1.4 % on average (at most 4.6 %) against the dataset speeds; a second estimator differs by a factor of 1.139 (SD 0.124)
Dynamics	1	partly	≤ 1 % for $t_{cr}/T_1 \geq 8$ (constant force)
Transverse position	lane-dependent C	no, unless lane-specific	field lane ratio 0.79; Mây Bridge range 2.05 mm across a section
Multiple presence	group weight	–	two-truck events 0.92 of prediction
Linearity, seating	1	no	laboratory integral ratio 1.010 → 1.017

Design checklist. The results combine into the following procedure for designing load-monitoring channels on a continuous girder before installation.

1. Constants. For each candidate channel and position, compute C from one static analysis under a uniform unit load on each lane, Eq. (2). Use Eqs. (4)–(7), (S1) and (S2) for prismatic two- and three-span beams.

2. Blindness. Locate the blind loci of Table 1. Keep strain gauges out of the near-blind band $|N_M| < 0.2$ around every zero-moment point, including gauges set back from a pier. Keep deflection gauges out of the near-blind bands $|N_w| < 0.2$, for example $1.385 < \lambda < 1.525$ for a mid-span gauge on two spans and $1.621 < \beta < 1.775$ for a mid side-span gauge on three spans.

3. Conditioning. Report N_M for strain, N_w with its EI_{ref} for deflection (or the absolute constant), and R for both. A small indicator with R near 1 is restraint, not cancellation.

4. Boundary robustness. Evaluate C over the plausible range of pier stiffness; for a symmetric girder, Eq. (13) gives the whole curve from the pinned and fixed constants. Avoid locations with large C_∞ / C_0 or B_m, or plan the measurement that identifies κ: a tiltmeter on a monolithic pier, an identified first frequency, or an integral ratio between two gauges.

5. Placement. Place sensors at the extremes of $C(x)$ of each channel type: w_q for deflection and $c M_q / EI$ for strain.

6. Estimator. Use SLM with weighed vehicles of clearly different weights, several reference crossings and lane-specific constants. For GLS or zero-sum weights, vehicle-free windows are not enough to estimate Σ; they misled on the field records (Section 4.3). Residuals of calibration crossings are the better basis but were not sufficient on the field records: with eight runs, Σ estimated from them over-fitted (mean absolute error 8.5 % in sample against 23.4 % out of sample; Section S7). Combine channels only with enough calibration crossings and an out-of-sample check against the gauge average. Use BPM only where the location is well conditioned and the structure is known; on box girders with deck-mounted gauges, a beam model does not give the constant.

7. Offset and dynamics. Evaluate P_δ, Eq. (10), for the residual offset that the instrumentation achieves after re-zeroing, and compare it with the lightest vehicle to be screened. Check $t_{cr} / T_1 \geq 8$ with the measured fundamental frequency $f_1 = 1/T_1$.

8. Processing. Integrate in space over the complete crossing, re-zero before and after each crossing, remove dynamics with a low-pass filter whose cutoff is well below the fundamental frequency f_1 and never with a high-pass filter, and discard overlapping crossings.

Influence-area weighing is a simplified alternative to influence-line BWIM, not a competitor. It returns the gross weight of a vehicle or group from one scalar constant per channel and one weighted sum. Its natural role is low-cost screening across many continuous structures, with influence-line BWIM or enforcement weighing for the vehicles it flags.

S11. Scripts, console output and derived data

The archive `scripts.zip` contains the analysis scripts and the console output of every run. `README.md` in the archive maps every table and figure of the article and this document to a script and a log file. `run_all.sh --all` reruns the closed forms and their FE verification, the multi-channel placement study and Monte Carlo simulation, the identifiability analysis of the in-service girder, the processing of the public field records and the laboratory evaluation. Every equation and numerical output was checked independently against an analytical, finite element or convergence-based route. The derived data behind every figure and table are provided as CSV files in the same archive. The raw field records are not redistributed; they are available from the NOR-BWIM dataset (https://doi.org/10.7294/26880898.v1).