```
#Date: 2026-09-11
#By: Divyam Sood
#Exam Eligibility

.data
name: .space 20
tot: .word 0
num: .word 0
p1: .asciiz "Enter your name please:"
p2: .asciiz "Enter total number of classes:"
p3: .asciiz "Enter number of classes you attended:"
sorry: .asciiz "You cannot attend more classes than total classes!"
pass: .asciiz " is allowed to sit in the exam"
fail: .asciiz " is not allowed to sit in the exam"
newline: .asciiz "\n"

.globl main
.text

main:
    #Get player name
    li $v0, 4
    la $a0, p1
    syscall
    li $a1, 21
    la $a0, name
    li $v0, 8
    syscall


    #now to remove the enter character (ASCII 10) from input
    la $t7, name
    li $s1, 10

remove:
    addi $t7, $t7, 1
    lb $t6, 0($t7)
    bne $t6, $s1, remove
    beq $zero, $zero, continue


continue:
    sb $zero, 0($t7) #change the \n character
    #Get total classes
    li $v0, 4
    la $a0, p2
    syscall
    li $v0, 5
    syscall
    move $t0, $v0
    #$t0 now has total classes

    #Get attended classes
    li $v0, 4
    la $a0, p3
    syscall
    li $v0, 5
    syscall
    move $t1, $v0
    #$t1 now has attended classes

    bgt $t1, $t0, fool #Case of total classes less than attended

    li $t3, 100
    mul $t1, $t3, $t1
    div $t1, $t0
    mflo $t2 #Quotient
    mfhi $t4 #Remainder
    li $t6, 75
```

```
    bge $t2, $t6, yes
    blt $t2, $t6, no



yes:
    li $v0, 4
    la $a0, name
    syscall
    li $v0, 4
    la $a0, pass
    syscall
    beq $zero, $zero, end

no:
    li $v0, 4
    la $a0, name
    syscall
    li $v0, 4
    la $a0, fail
    syscall
    beq $zero, $zero, end

fool:
    li $v0, 4
    la $a0, sorry
    syscall
    beq $zero, $zero, end

end:
    # exit program
    li  $v0, 10         # system call code for exit = 10
    syscall             # call operating system
```