

The Physics and Mathematics Behind Quantum Computing (2025): Theory, Architecture, Institutions, and Innovations

Theoretical Foundations: Quantum Mechanics and Information

Quantum computing's extraordinary computational promise arises from its steadfast grounding in the principles of quantum mechanics. Unlike classical computation, whose logical basis rests on deterministic bit manipulations, **quantum computation leverages the superposition, entanglement, and probabilistic measurement properties of quantum states**. This section details these principles, the mathematical formalism underpinning them, and sketches the key historical and institutional developments that gave rise to quantum computing today.

Quantum Superposition: Linear Combinations of States

Quantum superposition is perhaps the most fundamental departure from classical logic. In its purest form, if (

Origins and Formulation: Superposition traces directly to **Erwin Schrödinger's** and **Paul Dirac's** formal developments of quantum mechanics^[6]. The implications of superposition for information processing were independently recognized in the late 20th century by theorists such as **Richard Feynman**, whose 1982 lecture argued for a quantum device capable of simulating physics to surpass the limits of classical hardware^{[8][9]}. His insight catalyzed the quantum computing field by linking **exponential classical resource demands** to the unique scaling properties of quantum systems in superposition.

Quantum Entanglement: Nonlocal Correlations and Tensor Products

The **entanglement** phenomenon further sets quantum computing apart. In technical terms, the state space of multipartite quantum systems is the tensor product of the subsystems (e.g., $H_1 \otimes H_2$ for two qubits). States that cannot be factorized, such as $\frac{1}{\sqrt{2}}(|0\rangle|1\rangle + |1\rangle|0\rangle)$, are called **entangled**.

Entanglement ensures that measurement results on one qubit instantaneously affect correlated outcomes of others, regardless of spatial separation, revealing "nonlocal" information^{[11][12]}.

Mathematical Rigor:

- For two systems (A) and (B) with Hilbert spaces H_A and H_B , the composite system is $H_A \otimes H_B$.
- A general two-qubit state is $|\Psi\rangle = \sum_{i,j} \alpha_{ij} |i\rangle \otimes |j\rangle$, with $(|i\rangle, |j\rangle \in \{|0\rangle, |1\rangle})$.
- The **Schmidt decomposition**: any pure bipartite state can be written as $\sum_k \lambda_k |u_k\rangle \otimes |v_k\rangle$.
- Entanglement is quantified using **von Neumann entropy**: $S(\rho_A) = -\text{Tr}(\rho_A \log \rho_A)$, where ρ_A is the reduced density matrix after partial trace over (B).

Historical Significance: The phenomenon of entanglement introduced deep philosophical debates, especially after the **Einstein-Podolsky-Rosen (EPR) paradox**^[11]. **John Bell's** inequalities and subsequent experimental violations established that local hidden variable theories could not account for quantum predictions.

Quantum Measurement: The Born Rule and State Collapse

Quantum measurement differs sharply from classical observation; it's an inherently **probabilistic and invasive process**. Consistent with the **Born rule**, the probability of a measurement outcome is given by: $P(a_n) = \langle \Psi | P_n | \Psi \rangle$, where $P_n = |\phi_n\rangle\langle\phi_n|$ is the projector onto eigenstate $(|\phi_n\rangle)$. After measurement yielding result (a_n) , the system **collapses** to $(|\phi_n\rangle)$ ^[6].

In the **density matrix formalism**, measurement generalizes naturally to mixed states, and non-projective measurements (POVMs) further broaden permissible quantum operations.

Circuit-Language Description: Measurement gates appear as final elements in quantum circuits, converting quantum amplitudes into definite outcomes, usually in the $\{|0\rangle, |1\rangle\}$

Operators, Hilbert Space, and Unitary Evolution

The backbone of quantum computing formalism is **linear operators** acting on finite- or infinite-dimensional **Hilbert spaces**. Qubits, gates, and algorithms are all realized as operations within this structure^{[5][13]}.

- **Hermitian Operators** correspond to observables and have real eigenvalues.
- **Unitary Operators** (e.g., quantum gates) preserve normalization: $U^\dagger U = U U^\dagger = I$
- **Spectral Theorem:** Any Hermitian (and unitary) operator admits a basis of orthonormal eigenstates, facilitating diagonalization and functional calculus.

Quantum gate circuits consist of sequential (and sometimes parallel) application of unitary operators to specified qubits, with the global system evolving as $|\Psi\rangle \rightarrow U|\Psi\rangle$, where (U) itself may be a tensor product or controlled operation acting nontrivially on subsets.

Mathematical Derivations: Formalizing Quantum Computation

Quantum Gates: Universal Sets and Circuit Construction

Elementary quantum gates-unitary operators acting on one or two qubits-are the functional primitives of quantum circuits. The theoretical universality of quantum computation emerges from the fact that *almost any two-qubit gate is universal*, allowing arbitrary circuits to be composed from such building blocks^{[15][16]}.

Single-Qubit Gates:

- **Pauli Gates:** (X, Y, Z) correspond to the canonical generators of $SU(2)$.
- **Hadamard Gate (H):** (H)

- **Phase (S), T ($\pi/8$):** Implement arbitrary rotations about the (Z)-axis.

Two-Qubit Gates:

- **CNOT (Controlled-NOT):** $|\text{c}\rangle|\text{t}\rangle = |\text{c}\rangle \oplus |\text{t}\rangle$
- **Controlled-Z (CZ):** (CZ)
- **Swap and Toffoli:** Enable universal reversible computation.

Universal Gate Theorem: Any unitary operation over (n) qubits can be approximated arbitrarily well by a sequence of gates from a universal set such as {CNOT, all one-qubit gates}^{[14][15]}.

Hilbert Space Representation:

For an (n)-qubit system, the **global state** is a vector in $(\mathbb{C}^{2^n})$, and any gate is a $(2^n \times 2^n)$ unitary.

Tensor Product Structure: The action of gate (G) on qubits (i,j) in (n) qubits: $[U = I^{\otimes (i-1)} \otimes G \otimes I^{\otimes (n-i-1)}]$

Quantum Algorithms: Mathematical Core

Shor's Factoring Algorithm

Shor's Algorithm bridges number theory and quantum parallelism to factor integers exponentially faster than the best-known classical algorithms. *Mathematical structure:*

- **Period finding** reduces factoring to extracting the order (r) of $(y \bmod N)$.
- Core quantum routine uses **quantum Fourier transform (QFT)** on the order-finding register.

Mathematical steps:

1. **Initialize qubits**-prepare superpositions with Hadamard gates.
2. **Modular exponentiation**-implemented as a sequence of controlled unitary transformations.
3. **Quantum Fourier Transform (QFT)**-applied to period-finding register. The QFT efficiently computes the discrete Fourier transform over $(\mathbb{Z}_q)$: $|\text{x}\rangle \mapsto \frac{1}{\sqrt{q}} \sum_{\text{y}} e^{2\pi i \text{x y}/q} |\text{y}\rangle$
4. **Measurement and continued fraction expansion**-the observed output is interpreted classically to deduce the period.

Algorithm complexity: Shor's algorithm runs in $(O((\log N)^3))$, drastically improving upon superpolynomial classical methods^[16].

Grover's Search Algorithm

Grover's algorithm employs **amplitude amplification** to find a marked element in an unstructured database of (N) items in $(O(\sqrt{N}))$ time^[19]. The key steps are:

1. **Prepare uniform superposition** by applying Hadamard gates.
2. **Oracle query** marks the solution with a phase flip.
3. **Diffusion operator** inverts about the mean; serves as a reflection operator.
4. Iterate steps 2 and 3 $(\approx \pi/4\sqrt{N})$ times.

Mathematical description involves alternating applications of the oracle and diffusion unitary: $G = D \cdot O$, where the state evolution after (k) iterations is a rotation in a two-dimensional space spanned by marked and unmarked states.

Quantum Error Correction

Quantum error correction employs codewords-entangled states of many physical qubits-to detect and correct the decoherence and gate errors endemic to physical quantum systems.

Stabilizer codes and **surface codes** are the leading families. In the *stabilizer* formalism^[20]:

- The codespace is defined as the +1 eigenspace of an abelian subgroup of the Pauli group.
- Repeated measurement of stabilizers reveals a “syndrome” from which error recovery operations can be prescribed.

Mathematically, for a code correcting (t) errors, the code must have distance ($d=2t+1$). The codes exploit redundancy by mapping one logical qubit to (n) physical qubits.

Protocol Descriptions: Quantum Circuits, MBQC, Fusion-Based, and Fault-Tolerance

Quantum Circuit Model

The standard **circuit model** lays out computation as a sequence of quantum gates and measurements, reminiscent of digital electronics. Each quantum algorithm can be decomposed into a sequence of unitary gates, and the universality of two-qubit gates ensures theoretical completeness.

Circuit diagrams describe time-evolution left-to-right, with horizontal lines for qubits, boxes for gates, and vertical lines for control/entanglement^{[15][18]}.

Measurement-Based Quantum Computing (MBQC)

Measurement-Based Quantum Computing (MBQC, also called “one-way quantum computation”) upends the gate model. Here, the computation is performed by preparing a highly entangled resource state-typically a **cluster state**-and then reading out the result via a sequence of single-qubit measurements^{[22][16]}.

- **Cluster states:** Graph-structured multi-qubit states stabilized such that measurement on one party steers the rest.
- **Computation:** Logical operations correspond to the measurement basis choices; measurement results, due to randomness, are adaptively processed with classical feed-forward for determinism.
- **MBQC universality:** Any unitary operation can be mapped to a measurement pattern over a suitable cluster.

Mathematical formulation (resource graph state (

Australian research impact: The **University of Queensland** and **University of New South Wales** (UNSW) have actively advanced experimental MBQC, especially in photonic cluster state generation.

Fusion-Based Quantum Computing (FBQC)

FBQC occupies a middle ground between MBQC and circuit models, focusing on the **fusion** (joint projective measurement) of small entangled resource states rather than maintaining large cluster states^{[25][16]}.

- **Fusion gates:** Perform two-qubit (or multi-qubit) Bell measurements, instantly "fusing" resource states and permanently consuming them.
- **Error correction:** The fusion process is compatible with surface codes and Floquet codes, offering high loss and noise tolerance.
- **Photonic hardware:** Recent advances in deterministic quantum dot photon sources have substantially improved resource efficiency in FBQC settings.

Mathematical derivation: Fusion measures operators like $(X_a X_b)$ and $(Z_a Z_b)$, projecting onto Bell states.

Protocol: Photonic resource states created deterministically are guided by adaptive feedforward logic, ensuring robust logical qubit error correction even under moderate photon loss and noise^[26].

Global contributors:

- Center for Hybrid Quantum Networks (Hy-Q), University of Copenhagen
- Sparrow Quantum
- Niels Bohr Institute
- University of Bristol
- PsiQuantum (industry leader)

Australian relevance: While much foundational FBQC work is European and US-led, Australia's quantum photonics community (UTS Centre for Quantum Software and Information, University of Sydney) is a vital global player in photonic architectures.

Fault-Tolerant Quantum Computing and Error Correction Topologies

Quantum error correction and fault tolerance are required to overcome inevitable noise, decoherence, and error rates above the critical **fault-tolerance threshold**. **Surface codes**, **color codes**, and **topological codes** such as those based on **Majorana zero modes** are prominent.

Topological Quantum Computing and Majorana Qubits

Topological quantum computing exploits the non-Abelian statistics of particles such as **Majorana zero modes (MZMs)**, storing quantum information in globally robust degrees of freedom. Here:

- Majorana-based **tetrons**: Four-MZM islands implement "topological" qubits, enabling robust measurement of Pauli operators (X, Z) via interferometry.

- **Measurement-based braiding:** Logical gates are performed by measurement sequences contingently tracking the braiding of quasiparticle worldlines-no physical exchange is necessary.

Experimental milestone: Microsoft’s “Majorana 1” eight-qubit processor demonstrated the first topological quantum processor using MZMs for fault-tolerance^{[28][29]}.

Surface Codes and Fault-Tolerance Metrics

The **surface code** encodes logical qubits onto a 2D lattice of physical qubits, with local stabilizer measurements conferring high error thresholds (up to 1% per gate in some versions) and efficient error syndrome extraction. Logical operations are implemented by manipulating topological defects, with error rates suppressed exponentially in code distance^{[30][31]}.

Thresholds: Successful logic is achieved only if component error rates fall below the code’s threshold; thresholds depend on both physical noise characteristics and decoding algorithms.

Experimental and Theoretical Achievements (2024-2025)

Notable projects and breakthroughs:

- **Distributed Quantum Computing:** High-fidelity entangling gates between remote superconducting quantum processors (Beijing Academy of Quantum Information Sciences, Chinese Academy of Sciences) demonstrate CNOT and CZ over macroscopic distances (>30 cm) via cross-resonance effects, enabling scalable and modular quantum machines^{[33][34]}.
- **Superconducting Processors:** Google’s “Sycamore” 53- and 54-qubit processors establish quantum supremacy and accurate scalable control, laying the groundwork for NISQ and surface code demonstrations^[36].
- **Silicon Qubits:** The UNSW group built, controlled, and measured the world’s fastest two-qubit logic gates in silicon, providing a scalable path compatible with CMOS manufacturing^{[38][39]}.

Physicist Contributions and Global Institutional Leadership

Foundational Physicists

The quantum computing field has been seeded and sustained by the joint contributions of key theorists and experimenters:

Name	Contribution	Impact on Quantum Computing
Max Planck	Energy quantization, quantum hypothesis	Foundation for quantum mechanics
Albert Einstein	Photoelectric effect	Wave-particle duality, quantum information
Niels Bohr	Atomic model, Copenhagen interpretation	Measurement theory and quantum logic

Erwin Schrödinger	Schrödinger equation, wave mechanics	Evolution and representation of quantum states
Werner Heisenberg	Matrix mechanics, uncertainty principle	Measurement and non-commutativity
Paul Dirac	Formalism, delta function, canonical quantization	Quantum algorithm mathematics
John von Neumann	Hilbert space, measurement theory, density matrices	Mathematical architecture, measurement postulates
Richard Feynman	Path integrals, quantum electrodynamics, quantum simulation	Quantum computation as physical simulation
Peter Shor	Shor's algorithm, quantum error correction	Factoring, quantum error-correcting codes
Lov Grover	Grover's search algorithm, amplitude amplification	Search algorithms, quadratically faster solutions
David Deutsch	Computational universality, deterministic and Turing models	Quantum algorithms and circuit model

Recent Leaders and Experimental Pioneers (2024-2025):

- **Michelle Simmons (UNSW):** Atomically precise silicon qubits, fastest two-qubit gates^[37].
- **Chetan Nayak (Microsoft/UC Santa Barbara):** Majorana qubit architectures, topological quantum processors^[27].
- **Peter Lodahl (Niels Bohr Institute, Copenhagen):** Deterministic quantum dot photon sources, fusion-based computing^[25].
- **Juan Song, Wen-Gang Zhang, Fei Yan (Beijing Academy):** Remote high-fidelity superconducting entanglers^[32].
- **Google Quantum AI/IBM/QC Design:** Large-scale superconducting hardware, error correction blueprints^{[36][30]}.

Institutional Leadership: Global and Australian

Institution	Key Area	Notable Contributions
California Institute of Technology	Origin of simulation concepts	Feynman's universal quantum simulator
University of Oxford	Universal gate theory, algorithms	Deutsch, Barenco, Ekert
MIT, Harvard, IBM, Google, Microsoft	Algorithms, hardware, error correction	Shor's algorithm, surface code hardware
Beijing Academy of Quantum Information Sci.	Remote superconducting gates	Distributed quantum computing

University of Copenhagen/Hy-Q, Bristol	Photonic/fusion-based architectures	Deterministic quantum dot sources
UNSW, Sydney, University of Sydney	Silicon qubits, quantum control	Atom-precise silicon devices, MBQC
UTS Centre for Quantum Software & Information	Photonic quantum computation	Photonic error correction, theory

Australian Contributions:

- **UNSW Sydney:** Atomically engineered silicon quantum processors, two-qubit logic gates with record speed/fidelity^[38].
- **University of Sydney:** Error correction/quantum control, home to Microsoft's Station Q.
- **National initiatives:** Substantial funding (A\$1B+) for quantum R&D, with coordination through the Center of Excellence (CQC2T) and strong links to industry.

Experimental Implementations: Superconducting, Silicon, Photonic, and Topological Hardware

Superconducting Qubit Processors

Superconducting quantum processors remain prominent due to their tunability, scalability, and integration with planar circuit technologies.

- **Google Sycamore:** Achieved "quantum supremacy" using 53 superconducting qubits; depth and gate fidelity suffice for NISQ-scale experiments and error correction studies^[35].
- **IBM Nighthawk and Loon:** High-connectivity modular architectures (120-qubit processors), aiming for scalable fault-tolerant error correction using surface codes^[36].
- **Remote coupling:** High-fidelity entangling gates between spatially separated processors, facilitating distributed quantum computing architectures^[33].

Australian advances: Quantum-dot silicon spin qubits and integrated circuits at UNSW demonstrate high-speed logical gates and error correction, closing the gap with superconducting qubits in scalability and fabrication compatibility^[38].

Photonic Quantum Computing (Deterministic Quantum Dots)

Photonic qubits offer unique advantages in transmission, scalability, and room-temperature operation. Recent breakthroughs in deterministic quantum dot emitters have revolutionized cluster and fusion-based architectures^{[40][42]}.

Deterministic Entangled Photon Sources

- Quantum dots in nanowires and Bragg cavities produce near-perfect entangled photons on-demand, with record efficiencies, indistinguishability, and fidelities (e.g., >0.85 extraction efficiency, FEF > 0.90)^[42].

- These devices underpin **fusion-based quantum computing**, allowing low-overhead, loss-tolerant, and modular photonic computation.

GHZ, Cluster States, and Photonic Graphs

- **Graph and cluster states** produced by repeated deterministic photon emissions enable MBQC and FBQC protocols.
- Adaptive feedback and time-bin encodings reduce hardware complexity and boost tolerance to loss/error in large-scale networks.

Practical Fusion-Based Blueprints

A **blueprint** for scalable photonic quantum computing:

- Deterministic quantum dot EPS send entangled photons through unitary logic, switches, and fusion gates.
- Adaptive feedforward reconfigures sources based on measurement outcomes, constructing logical cluster states for error correction.
- **Floquet codes** and surface-code architectures implemented in photonic hardware support clock cycle error correction at microsecond timescales, exceeding fault-tolerance thresholds even with significant physical imperfections^[26].

Topological Quantum Computing and Majorana Devices

Topological quantum processors use **Majorana zero modes (MZMs)** to encode and manipulate quantum information in ways inherently immune to local noise^{[29][27]}.

- **Microsoft Station Q Majorana 1**: World's first eight-qubit topological processor demonstrated fault-tolerant gates and high-fidelity measurement-based Clifford operations using Majorana arrays.
- **Braiding and measurement protocols**: Logical operations (e.g., Hadamard, Phase) executed via measurement sequences, with error rates dominated by physical isolation and measurement fidelity.

Advantages: Exponential suppression of local error mechanisms, simplified measurement-based "digital" logic replacing fine-tuned pulses, and scalable architectures (proposed up to millions of logical qubits per wafer)^[27].

Summary Tables

Key Quantum Principles and Their Foundational Contributors

Principle	Description	Foundational Physicists
Superposition	States exist as linear combinations with complex coefficients	Schrödinger, Dirac, Feynman, Bohr

Entanglement	Nonlocal correlations, tensor product Hilbert spaces	Bell, Einstein, Schrödinger, Aspect
Measurement	Probabilistic, Born rule, collapse, decoherence	Von Neumann, Born, Wigner, Everett
Unitary Gates	Reversible computation by unitary, universal sets	Deutsch, Barenco, Ekert, DiVincenzo
Hilbert Space	Complex vector spaces, linear operators, tensor products	Dirac, Von Neumann, Hilbert

Experimental Benchmarks and Performance

Platform	Key Metric	Value	Reference
Google Sycamore	Qubit count	53 (2020)	[Google, 2019]
IBM Nighthawk	Qubit count	120 (2025 road)	[IBM, 2025]
UNSW Silicon Qubits	2-qubit gate time	0.8 ns	[UNSW, 2019]
UNSW 2-Qubit Gate Fidelity	Fidelity	>90%	[UNSW, 2019]
Determ. Photonic Sources	Extraction Efficiency	>0.69, up to 0.85	[Rota et al., 2024]
Majorana Qubit Array	Logical error suppression	$\exp(-\Delta/kT)$	[Aasen et al., 2025]
Distributed Superconduct.	Remote CNOT gate fidelity	99.15%	[Song et al., 2025]

Conclusion: State of Quantum Computing Physics and Mathematics, 2025

Quantum computing, as realized in 2025, stands atop a century-long tradition of quantum mechanics, mathematical formalism, and increasingly sophisticated experiments and devices. **The physics of quantum computation is deeply rooted in linear algebra, tensor products, and operator theory**, with superposition and entanglement driving powerful computational parallelism and communication protocols inaccessible to classical machines. **Quantum gates**, universal in their scope, rely on the mathematical clarity of unitary evolution; circuits, measurement-based, and fusion-based architectures each embody complementary strategies for harnessing quantum effects. **Fault-tolerance and error correction** increasingly shape hardware and algorithm design, with topological qubits and Majorana devices promising unprecedented robustness. The last five years have witnessed **global, collaborative acceleration**-from giant research labs in the US, China, Europe, and Australia to cross-border academic-industry consortia. Australia’s quantum hardware and silicon qubit breakthroughs, Denmark’s deterministic photonic sources,

China's distributed superconducting entanglers, and the US's surface codes and topological arrays, are all critical pillars in the field.

Looking forward, rigorous mathematical modeling, advances in materials science, new physical theories (including non-Abelian anyons and hybrid systems), and coordinated institutional leadership will be essential as the field strives relentlessly toward practical, scalable, and truly fault-tolerant quantum computers.

References (42)

1. *[quant-ph/0207183] Computational Model for the One-Way Quantum Computer*
<https://arxiv.org/abs/quant-ph/0207183>
2. *arXiv:2507.16152v1 [quant-ph] 22 Jul 2025.* <https://arxiv.org/pdf/2507.16152>
3. *Tailoring Fusion-Based Photonic Quantum Computing Schemes to Quantum*
<https://journals.aps.org/prxquantum/pdf/10.1103/PRXQuantum.6.020304>
4. *Roadmap to fault tolerant quantum computation using topological qubit*
<https://arxiv.org/html/2502.12252v1>
5. *Step-by-Step Explanation of Fault-Tolerant Topological Qubit Arrays.*
<https://ithy.com/article/fault-tolerant-qubits-df6ol3q9>
6. *Learn more about fault tolerance - QC Design.* <https://www.qc.design/learn>
7. *[2504.01897] Threshold for Fault-tolerant Quantum Advantage with the*
<https://arxiv.org/abs/2504.01897>
8. *High-fidelity entangling gates connect remote superconducting quantum*
<https://phys.org/news/2025-08-high-fidelity-entangling-gates-remote.html>
9. *Realization of high-fidelity perfect entangler between remote*
<https://arxiv.org/html/2407.20338v1>
10. *Quantum - IBM.* <https://www.ibm.com/roadmaps/quantum/2025/>
11. *The First Two-Qubit Logic Gate in Silicon - IEEE Spectrum.* <https://spectrum.ieee.org/a-first-two-qubit-logic-gate-in-silicon>
12. *UNSW builds world first two-qubit logic gate in silicon - ZDNET.*
<https://www.zdnet.com/article/unsw-builds-world-first-two-qubit-logic-gate-in-silicon/>
13. *200 times faster than ever before: the speediest quantum operation yet.*
<https://www.unsw.edu.au/newsroom/news/2019/07/200-times-faster-than-ever-before--the-speediest-quantum-operati>
14. *Topological quantum processor uses Majorana zero modes for fault*
<https://phys.org/news/2025-02-topological-quantum-processor-majorana-modes.html>
15. *Realization of High-Fidelity Perfect Entanglers between Remote*
<https://link.aps.org/doi/10.1103/npr7-b7kq>
16. *Quantum Supremacy Using a Programmable Superconducting Processor.*
<https://research.google/blog/quantum-supremacy-using-a-programmable-superconducting-processor/>

17. *A source of entangled photons based on a cavity-enhanced and strain*
<https://elicht.springeropen.com/articles/10.1186/s43593-024-00072-8>
18. *Quantum Superposition Principle Made Simple - My Brain Rewired.*
<https://mybrainrewired.com/quantum-physics/quantum-superposition-principle-simplified/>
19. *Fault-Tolerant Stabilizer Measurements in Surface Codes with Three*
<https://arxiv.org/pdf/2506.09029>
- 20.2. *Mathematical Formalism of Quantum Mechanics.* https://ocw.mit.edu/courses/22-51-quantum-theory-of-radiation-interactions-fall-2012/774a0d883fca9c660912cc029e58669e_MIT22_51F12_Ch2.pdf
- 21.9. *Operators on Hilbert spaces - Mathematics for Quantum Physics.*
<https://interactivetextbooks.tudelft.nl/mqp/operators.html>
22. *Mathematical Foundations of Quantum Mechanics - Wikipedia.*
https://en.wikipedia.org/wiki/Mathematical_Foundations_of_Quantum_Mechanics
23. *Feynman's "Simulating Physics with Computers".* <https://arxiv.org/html/2405.03366v1>
24. *Richard Feynman and Quantum Computing - EEJournal.*
<https://www.eejournal.com/article/richard-feynman-and-quantum-computing/>
25. *Master - Universitetet i Oslo.*
<https://www.uio.no/studier/emner/matnat/math/MAT4430/v24/lecture11.pdf>
- 26.1.2: *Operators in Hilbert Space - Physics LibreTexts.*
https://phys.libretexts.org/Bookshelves/Quantum_Mechanics/Advanced_Quantum_Mechanics_%28Kok%29/0
27. *circuit construction - Why is Deutsch's gate universal? - Quantum*
<https://quantumcomputing.stackexchange.com/questions/10216/why-is-deutschs-gate-universal>
28. *Quantum Computation and Quantum Information - almuhammadi.*
https://almuhammadi.com/sultan/books_2020/Nielsen_Chuang.pdf
29. *arXiv:quant-ph/9505018v1 24 May 1995.* <https://arxiv.org/pdf/quant-ph/9505018>
30. *Chapter 3: Quantum Entanglement.*
https://www1.spms.ntu.edu.sg/~ydchong/teaching/PH7024_03_entanglement.pdf
31. *Amplitude amplification - Wikipedia.* https://en.wikipedia.org/wiki/Amplitude_amplification
32. *Grover and The Search Problem - PhysLab.* https://physlab.org/wp-content/uploads/2023/04/Grover_24100096.pdf
33. *Quantum Dot Sources Generate Nearly Perfect Entangled Photons.*
https://www.photonics.com/Articles/Quantum_Dot_Sources_Generate_Nearly_Perfect/a69847