
Proving Necessity

Designing a Proof System for Necessary Conditions
Julian Mackay, James Noble, Sophia Drossopolou, Susan
Eisenbach

Traditional Specifications

Traditional Specifications: Correctness

- $\{P\} s \{Q\}$

Traditional Specifications: Correctness

- $\{P\} s \{Q\}$
 - if P is true before we execute s, then Q will be true after
-

Traditional Specifications: Correctness

- $\{P\}s\{Q\}$
- if P is true before we execute s, then Q will be true after
- e.g.

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
```

Traditional Specifications: Correctness

- $\{P\}s\{Q\}$
- if P is true before we execute s, then Q will be true after
- e.g.

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
```

```
{pwd = a.password}a.transfer(pwd,to,amt){a.balance_new = a.balance_old - amt}
```

Necessity Specifications

- open world

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
 - what are the necessary conditions for our balance to decrease?
-

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
- what are the necessary conditions for our balance to decrease?

if the balance decreases then

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
- what are the necessary conditions for our balance to decrease?

if the balance decreases then

- the password was correct?
-

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
- what are the necessary conditions for our balance to decrease?

if the balance decreases then

- the password was correct?
 - transfer was called? i.e. is there some other way to drain our account?
-

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
- what are the necessary conditions for our balance to decrease?

if the balance decreases then

- the password was correct?
 - transfer was called? i.e. is there some other way to drain our account?
 - someone knew our password?
-

```
class Account
  field balance
  field password
  method transfer(pwd, to, amt)
    if this.auth(pwd)
      this.balance -= amt
      to.balance += amt
  method send(amt)
    this.balance += amt
  ...
```

Necessity Specifications

- open world
- what are the necessary conditions for our balance to decrease?

if the balance decreases then

- the password was correct?
- transfer was called? i.e. is there some other way to drain our account?
- someone knew our password?

what if we wanted to specify the behaviour of arbitrary code?

Necessity Specifications

from A_1 **next** A_2 **onlyIf** A

from A_1 **to** A_2 **onlyIf** A

from A_1 **to** A_2 **onlyThrough** A

Necessity Specifications

from A_1 **next** A_2 **onlyIf** A

if A_1 is true, and A_2 is true in the **next** program state, then A must have **originally** been true too

- e.g. if $a.balance = 100$ and in the next visible program state $a.balance < 100$, then transfer have been called
-

Necessity Specifications

from A_1 **to** A_2 **onlyIf** A

if A_1 is true, and A_2 is true in **some future** program state, then A must have **originally** been true too

- e.g. if $a.\text{balance} = 100$ and in some future program state $a.\text{balance} < 100$, then someone must know our password
-

Necessity Specifications

from A_1 **to** A_2 **onlyThrough** A

if A_1 is true, and A_2 is true in **some future** program state, then A must have been true in **some intermediate** state


- e.g. if $a.balance = 100$ and in some future program state $a.balance < 100$, then someone have called transfer with the correct password in some intermediate program state
-

Necessity Specifications - Open World

- simple module system, i.e. just a set of classes
 - internal vs external
 - necessity specs describe the externally visible world, i.e. externally visible program states
-

Necessity Specifications - Modelling the Open World

- simple module system, i.e. just a set of classes
- internal vs external
- necessity specs describe the externally visible world, i.e. externally visible program states



Necessity Specifications

- necessity specs describe the externally visible world, i.e. externally visible program states

from A_1 to A_2 onlyIf A :




from A_1 next A_2 onlyIf A :



from A_1 to A_2 onlyThrough A :




Necessity Specifications - How we reason about necessity



Necessity Specifications - How we reason about necessity

we base our logic on top of two secondary proof systems

- assertion encapsulation: what assertions require internal library code to be invalidated
- functional specifications: proofs of traditional Hoare triples



Necessity Specifications - How we reason about necessity

our logic consists of 3 components:

1. per-call necessary preconditions
 - e.g. for a call to transfer to decrease the balance, the correct password must be given

```
from a.balance = bal && <_ calls a.transfer(pwd, _, _)>  
  next a.balance < bal  
  onlyIf pwd = a.password
```

we build this off traditional
specifications

Necessity Specifications - How we reason about necessity

```
from a.balance = bal && <_ calls a.transfer(pwd, _, _)>  
  next a.balance < bal  
  onlyIf pwd = a.password
```

equivalent to ...

```
{a.balance = bal && pwd <> a.password}  
  a.transfer(pwd, _, _)  
{a.balance = bal}
```

Necessity Specifications - How we reason about necessity

our logic consists of 3 components:

2. per-step necessary preconditions
 - e.g. for any arbitrary execution step to decrease the balance, that step must be a call to transfer with the correct password

```
from a.balance = bal
  next a.balance < bal
  onlyIf <_ calls a.transfer(pwd, _, _)> && pwd = a.password
```

we build this on top of assertion encapsulation ...

Necessity Specifications - How we reason about necessity

```
from a.balance = bal
next a.balance < bal
onlyIf <_ calls a.transfer(pwd, _, _)> && pwd = a.password
```

is true iff

- `a : Account`
 - `a.balance = bal` is “encapsulated”, i.e. requires internal computation to invalidate
 - there is no other way to decrease the balance internally
-

Necessity Specifications - How we reason about necessity

our logic consists of 3 components:

3. emergent behaviour

- e.g. for any execution of arbitrary length to decrease the balance, someone must first know the password

```
from a.balance = bal
to a.balance < bal
onlyIf exists x.[<x access a.password> && <external x>]
```

Necessity Specifications - How we reason about necessity

our logic consists of 3 components:

3. emergent behaviour
 - e.g. for any execution of arbitrary length to decrease the balance, someone must first know the password

```
from a.balance = bal
to a.balance < bal
onlyIf exists x.[<x access a.password> && <external x>]
```

note, the above spec does not specify any functions in the module interface, it only specifies a relationship between two fields. In fact, with ghost fields we are able to remove all mention of implementation details altogether

Necessity Specifications - How we reason about necessity

our logic consists of 3 components:

3. emergent behaviour
 - e.g. for any execution of arbitrary length to decrease the balance, someone must first know the password

```
from a.balance() = bal
to a.balance() < bal
onlyIf exists x.[<x access a.password> && <external x>]
```

note, the above spec does not specify any functions in the module interface, it only specifies a relationship between two fields. In fact, with ghost fields we are able to remove all mention of implementation details altogether

Necessity Specifications - How we reason about necessity ... some math stuff

$$\frac{M \vdash \{x : C \wedge P_1 \wedge \neg P\} \text{ res} = x.m(\bar{z}) \{ \neg P_2 \}}{M \vdash \text{from } P_1 \wedge x : C \wedge \langle _ \text{ calls } x.m(\bar{z}) \rangle \text{ next } P_2 \text{ onlyIf } P} \quad (\text{IF1-CLASSICAL})$$

$$\frac{M \vdash \{x : C \wedge \neg P\} \text{ res} = x.m(\bar{z}) \{ \text{res} \neq y \}}{M \vdash \text{from inside}(y) \wedge x : C \wedge \langle _ \text{ calls } x.m(\bar{z}) \rangle \text{ next } \neg \text{inside}(y) \text{ onlyIf } P} \quad (\text{IF1-INSIDE})$$

Necessity Specifications - How we reason about necessity ... some math stuff

$$\frac{\left[\begin{array}{l} \text{for all } C \in \text{dom}(M) \text{ and } m \in M(C).\text{mths}, \\ [M \vdash \text{from } A_1 \wedge x : C \wedge \langle _ \text{ calls } x.m(\bar{z}) \rangle \text{ next } A_2 \text{ onlyIf } A_3] \\ M \vdash A_1 \longrightarrow \neg A_2 \quad M \vdash A_1 \Rightarrow \text{Enc}(A_2) \end{array} \right]}{M \vdash \text{from } A_1 \text{ next } A_2 \text{ onlyIf } A_3} \quad (\text{IF1-INTERNAL})$$
$$\frac{M \vdash A_1 \longrightarrow A'_1 \quad M \vdash A_2 \longrightarrow A'_2 \quad M \vdash A'_3 \longrightarrow A_3 \quad M \vdash \text{from } A'_1 \text{ next } A'_2 \text{ onlyIf } A'_3}{M \vdash \text{from } A_1 \text{ next } A_2 \text{ onlyIf } A_3} \quad (\text{IF1-}\longrightarrow)$$
$$\frac{M \vdash \text{from } A_1 \text{ next } A_2 \text{ onlyIf } A \vee A' \quad M \vdash \text{from } A' \text{ to } A_2 \text{ onlyThrough false}}{M \vdash \text{from } A_1 \text{ next } A_2 \text{ onlyIf } A} \quad (\text{IF1-}\vee\text{E})$$
$$\frac{\forall y, M \vdash \text{from } ([y/x]A_1) \text{ next } A_2 \text{ onlyIf } A}{M \vdash \text{from } \exists x.[A_1] \text{ next } A_2 \text{ onlyIf } A} \quad (\text{IF1-}\exists_1)$$

Necessity Specifications - How we reason about necessity ... some math stuff

$$\begin{array}{c} \frac{M \vdash \text{from } A \text{ next } \neg A \text{ onlyIf } A'}{M \vdash \text{from } A \text{ to } \neg A \text{ onlyThrough } A'} \quad (\text{CHANGES}) \qquad \frac{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyThrough } A_3}{M \vdash \text{from } A_1 \text{ to } A_3 \text{ onlyThrough } A} \quad (\text{TRANS}_1) \\ \\ \frac{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyThrough } A_3}{M \vdash \text{from } A_3 \text{ to } A_2 \text{ onlyThrough } A} \quad (\text{TRANS}_2) \qquad \frac{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyIf } A}{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyThrough } A} \quad (\text{If}) \\ \\ M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyThrough } A_2 \quad (\text{END}) \end{array}$$

Necessity Specifications - How we reason about necessity ... some math stuff

$$\frac{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyThrough } A_3 \quad M \vdash \text{from } A_1 \text{ to } A_3 \text{ onlyIf } A}{M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyIf } A} \quad (\text{IF-TRANS})$$

$$M \vdash \text{from } x : C \text{ to } \neg x : C \text{ onlyIf false} \quad (\text{IF-CLASS}) \quad M \vdash \text{from } A_1 \text{ to } A_2 \text{ onlyIf } A_1 \quad (\text{IF-START})$$

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?



Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

$$A_1 \wedge \bigcirc \bar{A}_2 \longrightarrow A$$

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

$$A_1 \wedge \bigcirc \bar{A}_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyIf** A

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

$$A_1 \wedge \bigcirc \bar{A}_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyIf** A

$$A_1 \wedge \Diamond A_2 \longrightarrow A$$

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

$$A_1 \wedge \bigcirc A_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyIf** A

$$A_1 \wedge \Diamond A_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyThrough** A

Relationship with Temporal Logic

- These are proofs of temporal properties
- closely related to temporal logic, so how do they compare?

from A_1 **next** A_2 **onlyIf** A

$$A_1 \wedge \bigcirc \bar{A}_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyIf** A

$$A_1 \wedge \Diamond A_2 \longrightarrow A$$

from A_1 **to** A_2 **onlyThrough** A

??????????

Where to next?

- Modules are limited
 - If M1 is a dependency of M2, and satisfies our necessity spec, can we prove M1 also satisfies that necessity spec?
 - can we write specs about scopes, and not modules?
-

Where to next?

- Modules are limited
 - If M1 is a dependency of M2, and satisfies our necessity spec, can we prove M1 also satisfies that necessity spec?
 - can we write specs about scopes, and not modules?
 - we can use traditional specs to prove necessity specs, can we prove traditional specs from necessity specs?
 - i.e. if we know a module observes some behaviour, can we use that in proving post-conditions to functions
 - `from true to ~ A onlyIf false => A`
-

Where to next?

- Modules are limited
 - If M1 is a dependency of M2, and satisfies our necessity spec, can we prove M1 also satisfies that necessity spec?
 - can we write specs about scopes, and not modules?
 - we can use traditional specs to prove necessity specs, can we prove traditional specs from necessity specs?
 - i.e. if we know a module observes some behaviour, can we use that in proving post-conditions to functions
 - `from true to ~ A onlyIf false => A`
 - currently we do not allow external calls from internal code
 - we are currently working on an extension that allows unrestricted external calls and re-entrant code
-

Where to next?

- Modules are limited
 - If M1 is a dependency of M2, and satisfies our necessity spec, can we prove M1 also satisfies that necessity spec?
 - can we write specs about scopes, and not modules?
- we can use traditional specs to prove necessity specs, can we prove traditional specs from necessity specs?
 - i.e. if we know a module observes some behaviour, can we use that in proving post-conditions to functions
 - `from true to ~ A onlyIf false => A`
- currently we do not allow external calls from internal code
 - we are currently working on an extension that allows unrestricted external calls and re-entrant code
- currently assertion encapsulation is constructed from an ad-hoc system relying on a rudimentary type system, can we define a full fledged proof system for encapsulation?