

# XPath Selectors Cheat Sheet

**Application Used:** Demo Web Shop (Tricentis) URL: <https://demowebshop.tricentis.com/>

---

## 1. Absolute XPath (Full XPath)

| Type     | Description    | XPath                                             | What it Targets |
|----------|----------------|---------------------------------------------------|-----------------|
| Absolute | Search textbox | /html/body/div[4]/div[1]/div[2]/div[2]/form/input | Search input    |

**Note:** Not recommended; very fragile.

---

## 2. Relative XPath (Partial XPath)

| Type     | Description   | XPath                            | What it Targets |
|----------|---------------|----------------------------------|-----------------|
| Relative | Search box    | //input[@id='small-searchterms'] | Search input    |
| Relative | Login link    | //a[@href='/login']              | Login           |
| Relative | Register link | //a[@href='/register']           | Register        |

---

## 3. XPath with Single Attribute

| Description  | XPath                            | What it Targets |
|--------------|----------------------------------|-----------------|
| Search input | //input[@id='small-searchterms'] | Search box      |
| Newsletter   | //input[@id='newsletter-email']  | Email field     |
| Cart link    | //a[@href='/cart']               | Shopping cart   |

---

## 4. XPath with Multiple Attributes

| Description | XPath                                                      | What it Targets |
|-------------|------------------------------------------------------------|-----------------|
| Search box  | //input[@id='small-searchterms' and @name='q']             | Search          |
| Login link  | //a[@href='/login' and @class='ico-login']                 | Login           |
| Register    | //a[@href='/register' and contains(@class,'ico-register')] | Register        |

---

## 5. XPath with AND Operator

| Description  | XPath                                             | What it Targets |
|--------------|---------------------------------------------------|-----------------|
| Search input | //input[@type='text' and @id='small-searchterms'] | Search          |
| Newsletter   | //input[@type='text' and @id='newsletter-email']  | Email           |

---

## 6. XPath with OR Operator

| Description    | XPath                                    | What it Targets   |
|----------------|------------------------------------------|-------------------|
| Login/Register | //a[@href='/login' or @href='/register'] | Auth links        |
| Cart/Wishlist  | //a[@href='/cart' or @href='/wishlist']  | Cart and wishlist |

---

## 7. XPath with contains() Function

| Description    | XPath                                  | What it Targets |
|----------------|----------------------------------------|-----------------|
| Cart link      | //a[contains(@href,'cart')]            | Cart            |
| Product items  | //div[contains(@class,'product-item')] | Products        |
| Category links | //a[contains(@href,'category')]        | Categories      |

---

## 8. XPath with starts-with() Function

| Description    | XPath                                   | What it Targets |
|----------------|-----------------------------------------|-----------------|
| Books menu     | //a[starts-with(@href,'/books')]        | Books           |
| Poll options   | //input[starts-with(@id,'pollanswers')] | Poll            |
| Product blocks | //div[starts-with(@class,'product')]    | Products        |

---

## 9. XPath with text() Function

| Description | XPath                | What it Targets |
|-------------|----------------------|-----------------|
| Login link  | //a[text()='Log in'] | Login           |

| Description   | XPath                               | What it Targets |
|---------------|-------------------------------------|-----------------|
| Register link | <code>//a[text()='Register']</code> | Register        |
| Vote button   | <code>//input[@value='Vote']</code> | Vote            |

---

## 10. XPath with last() Function

| Description    | XPath                                                | What it Targets |
|----------------|------------------------------------------------------|-----------------|
| Last menu item | <code>((//ul[@class='top-menu']//li)[last()])</code> | Last category   |
| Last product   | <code>((//div[@class='item-box'])[last()])</code>    | Last product    |

---

## 11. XPath with position() Function

| Description   | XPath                                                      | What it Targets |
|---------------|------------------------------------------------------------|-----------------|
| First menu    | <code>((//ul[@class='top-menu']//li)[position()=1])</code> | Books           |
| Second menu   | <code>((//ul[@class='top-menu']//li)[position()=2])</code> | Computers       |
| Third product | <code>((//div[@class='item-box'])[position()=3])</code>    | Product         |

---

## 12. XPath Axes

### Parent Axis

| Description      | XPath                                                      | What it Targets |
|------------------|------------------------------------------------------------|-----------------|
| Parent of search | <code>//input[@id='small-searchterms']/parent::form</code> | Search form     |

---

### Child Axis

| Description | XPath                                          | What it Targets |
|-------------|------------------------------------------------|-----------------|
| Menu items  | <code>//ul[@class='top-menu']/child::li</code> | Categories      |

---

### Ancestor Axis

| Description       | XPath                                                                      | What it Targets |
|-------------------|----------------------------------------------------------------------------|-----------------|
| Product container | <code>//h2[@class='product-title']/ancestor::div[@class='item-box']</code> | Product card    |

---

### Descendant Axis

| Description         | XPath                                                    | What it Targets |
|---------------------|----------------------------------------------------------|-----------------|
| All links in header | <code>//div[@class='header-links']//descendant::a</code> | Header links    |

---

### Following Axis

| Description       | XPath                                    | What it Targets |
|-------------------|------------------------------------------|-----------------|
| Input after label | <code>//label/following::input[1]</code> | Next input      |

---

### Following-Sibling Axis

| Description         | XPath                                         | What it Targets |
|---------------------|-----------------------------------------------|-----------------|
| Input next to label | <code>//label/following-sibling::input</code> | Adjacent input  |

---

### Preceding Axis

| Description        | XPath                                                            | What it Targets |
|--------------------|------------------------------------------------------------------|-----------------|
| Label before input | <code>//input[@id='newsletter-email']/preceding::label[1]</code> | Previous label  |

---

### Preceding-Sibling Axis

| Description        | XPath                                                                 | What it Targets |
|--------------------|-----------------------------------------------------------------------|-----------------|
| Label before input | <code>//input[@id='newsletter-email']/preceding-sibling::label</code> | Label           |

---

### Top 10 XPath Selectors for Beginners

| #  | XPath                                            | Use           |
|----|--------------------------------------------------|---------------|
| 1  | <code>//input[@id='small-searchterms']</code>    | Search        |
| 2  | <code>//input[@value='Search']</code>            | Search button |
| 3  | <code>//a[@href='/register']</code>              | Register      |
| 4  | <code>//a[@href='/login']</code>                 | Login         |
| 5  | <code>//a[contains(@href,'cart')]</code>         | Cart          |
| 6  | <code>//ul[@class='top-menu']//li</code>         | Menu          |
| 7  | <code>//div[@class='product-item']</code>        | Products      |
| 8  | <code>//h2[@class='product-title']/a</code>      | Product name  |
| 9  | <code>//span[@class='price actual-price']</code> | Price         |
| 10 | <code>//input[@id='newsletter-email']</code>     | Email         |

---

### Notes for Beginners

- Prefer **Relative XPath** over **Absolute XPath**
  - Use **contains()** for dynamic elements
  - Combine attributes for better accuracy
  - Avoid long complex XPaths
  - Use axes when normal XPath is not enough
-