

Lab: CSS Locators

Objective

Learn how to use **CSS locators in Playwright** to identify elements, extract data, and validate user interface behavior.

Application URL

<https://demowebshop.tricentis.com/>

Lab Instructions

- Use **Playwright with TypeScript**
 - Focus on **CSS selectors**
 - Add assertions using `expect`
 - Print outputs using `console.log()`
-

Test Cases

Step 1: Open Application

Steps:

1. Launch the browser
2. Navigate to the application URL

Expected Result:

- The application should load successfully
-

Test 2: Verify Logo Visibility

Steps:

1. Locate the logo using a CSS attribute selector
2. Validate that the logo is visible

Expected Result:

- The logo should be visible on the page
-

Test 3: Find Products Containing "computer"

<https://www.pavanonlinetrainings.com>

<https://www.youtube.com/@sdetpavan>

Steps:

1. Locate elements using [href*="computer"]
2. Count the number of matching products

Expected Result:

- At least one matching product should be displayed
-

Test 4: Print Product Details**Steps:**

1. Print the first product name
2. Print the second product name
3. Print all product names

Expected Result:

- Product names should be displayed in the console
-

Test 5: Find Products Starting with "/build"**Steps:**

1. Use the [href^="/build"] selector
2. Count matching elements

Expected Result:

- At least one matching product should exist
-

Test 6: Verify Register Link**Steps:**

1. Locate the element using a[href="/register"]
2. Verify visibility

Expected Result:

- The register link should be visible
-

Test 7: Verify Last Social Media Link**Steps:**

1. Use :last-child

2. Capture the text content

Expected Result:

- The text should be **Google+**
-

Test 8: Verify Second Social Media Link

Steps:

1. Use :nth-child(2)
2. Capture the text content

Expected Result:

- The text should be **Twitter**
-

Key Learning Points

- CSS Attribute Selectors:
 - = — exact match
 - *= — contains
 - ^= — starts with
- Useful Methods:
 - .count()
 - .first()
 - .nth()
 - .allTextContents()
- CSS Pseudo-classes:
 - :last-child
 - :nth-child()