로그분석 1.

```
index=dnslog sourcetype=dnslog dpt=53 domain!="*.arpa" domain!="-"
| eval list="mozilla“
| `ut_parse(domain,list)`
| top showperc=f src, ut_netloc
```

로그분석 2.

```
index=dnslog sourcetype=dnslog domain!="-" rcode_name= "NXDomain"
| top showperc=f src, domain
```

로그분석 3.

```
index=dnslog sourcetype=dnslog domain!="-" rcode_name= "NXDomain"
| top showperc=f src, domain
```

로그분석 4.

```
index=networklog sourcetype=dnslog domain!="-"
| where NOT cidrmatch(domain, "0.0.0.0/0")
| eval list="mozilla"
| `ut_parse(domain, list)`
| where NOT match(domain,"(microsoft.com|akamaized.net|amazonaws.com)$")
| eval sub_len=len(ut_subdomain)
| search sub_len > 20
| table ut_domain, ut_subdomain, sub_len, ut_netloc
```

로그분석 5.

```
index=networklog sourcetype=dnslog (dst!="172.16.142.11" AND
dst!="172.16.142.12") (src!="172.16.142.11" AND src!="172.16.142.12")
| stats count by dst
| sort - count
```

로그분석 6.

```
index=httplog sourcetype=httplog domain!="(empty)"
| iplocation dst
| where NOT cidrmatch("0.0.0.0/0", domain)
| stats sum(request_body_len) as "Outbound", sum(response_body_len) as
"Inbound" by domain, Country
| eval Outbound=round(Outbound/(1024*1024),2)
| eval Inbound=round(Inbound/(1024*1024),2)
| sort Outbound desc
| head 10
```

로그분석 7.

```
index=httplog sourcetype=httplog uri!="-"
| top method limit=10 showperc=f
```

로그분석 8.

```
index=httplog sourcetype=httplog uri!="-" uri!="/"
(status_code >=400 AND status_code < 500)
| top domain, status_code limit=10 showperc=f
```

로그분석 9.

```
index=httplog sourcetype=httplog uri!="-" status_code >= 500
| top domain, status_code limit=10 showperc=f
```

로그분석 10.

```
index=httplog sourcetype=httplog domain!="(empty)" status_code!="-"
| top limit=10 showperc=f status_code
```