

Server and Data Feeds Restart

Translate: **EN** ▼

Server should be restarted after:

- a new [Data Center \(access point\)](#) has been added;
- a new [Users Group](#) has been added;
- new [financial instruments](#) have been added;
- changing the [margin settings](#) of a financial instrument;
- technical failures occur.

The server restart is performed in two steps: shutdown and repeated start. At the shutdown, all connections are broken, all feeders and requests to dealers are terminated. The restart initiates feeders, client bases, orders, and historical data.

You can restart server via "Services — Restart Server" menu command or  button of the toolbar.

Note: It is necessary to reconnect to the server after restarting. Since the server restart can take from several seconds to one minute, it is impossible to login to the server within this period of time.

Data Feeds Restart

The data feeds restart is applied when technical problems occur regarding quotes and news receiving. The server will stop operation of all data feeds and restart them should this occur.

You can reset them via the "Services — Reset Datafeeds" menu command or  button of the toolbar.

Note: When [adding a new feeder or changing the priority \(position in the list\)](#) of any data feed, the automatic resetting will start. It is not recommended to change the priorities of feeders unless absolutely necessary!

[Server Administration Commands](#)[Synchronization of Charts](#)

© 2000-2022, [MetaQuotes Ltd.](#) Copying or republishing in whole or in part is prohibited