Keywords: test-time reasoning • self-consistency • error localization • token efficiency

StepBack: Step-Level Error-Localized Resampling for Efficient Test-Time Reasoning

Localizing the First Error Step and Resampling Only Its Continuation Cuts Token Usage by Up to 41% at No Accuracy Cost

By Yang Ouyang, Jung-Eun Kim

arXiv:2611.08403 • cs.AI / cs.LG • NeurIPS 2026

Self-consistency generates many full chain-of-thought trajectories and takes a majority vote, but every chain runs to completion regardless of where the error occurs. StepBack localizes the most likely first error using lightweight signals and resamples only from that step onward, matching self-consistency accuracy on seven benchmarks while reducing token use by up to 41.26%.

AT A GLANCE

Problem: Self-consistency is expensive because every reasoning trajectory runs to completion, even when an error occurs early.

Why it matters: Test-time compute budgets are a primary cost driver for deployed LLM reasoning; a method that preserves accuracy at lower token cost directly reduces inference cost.

Method: Localize the first likely error in draft trajectories using NLL and PRM signals, then resample only the erroneous step and its continuation, finishing with majority voting.

Result: Matches SC accuracy on 7 benchmarks; cuts token usage by up to 41.26%.

Evidence: GSM8K, MATH, AIME, MultiArith, HotpotQA, 2WikiMultiHopQA, MuSiQue; Llama-3.1-8B-Instruct backbone.

The Big Picture

Chain-of-thought reasoning substantially improves LLM accuracy by externalizing intermediate steps. Self-consistency (SC) amplifies this further: by sampling many independent trajectories and taking a majority vote, SC cancels out reasoning errors that occur in different places on different runs. The cost is linear in the number of trajectories—a budget of 32 trajectories means 32× the tokens of a single greedy answer.

The key observation of StepBack is that this cost model is wasteful. Errors in a chain-of-thought trajectory are not uniformly distributed across steps; they tend to cluster in the early-to-middle portion of a chain. Once an error is made, subsequent steps correctly propagate it to a wrong final answer. Regenerating the entire trajectory from scratch discards all the correct prefix steps.

Why Existing Approaches Fall Short

distinguish high-quality from low-quality prefixes. **Best-of-N** and verifier-guided methods re-rank complete trajectories after generation but still generate all N full chains. **Adaptive Consistency** reduces the trajectory count by stopping early when the answer distribution is sufficiently peaked. StepBack and Adaptive Consistency are orthogonal: StepBack shortens each trajectory, while Adaptive Consistency reduces the trajectory count. The two compose.

Core Mechanism

Given *m* draft trajectories, StepBack splits each into atomic steps using the model's natural delimiter tokens. For each step two signals are computed: (1) NLL signal—the mean negative log-likelihood of tokens in the step under the model; and (2) PRM signal—the process reward model score estimating the probability that all steps up to and including this one are correct.

The *anchor* step is the earliest step flagged by NLL > τ_{NLL} = 0.1 or PRM < τ_{PRM} = 0.05. For each flagged trajectory, $k = 2$ fresh continuations are sampled from the anchor step onward, keeping the prefix fixed. Final answers from all trajectories are pooled and the plurality answer is returned.

Technical Formulation

Let m = 16 draft trajectories be given. For trajectory τ_i, the prefix up to step $a_i - 1$ is p_i and resampled continuations are drawn from:

$$\tilde{c}_{ij} \sim p_\theta(\cdot \mid x, p_i), \quad j = 1, \ldots, k$$

The expected token count is `E[tokens] = m·L_prefix + α·k·L_suffix`, where α is the fraction of trajectories flagged and L_{prefix}, L_{suffix} are mean prefix and suffix lengths. When errors cluster early, L_{prefix} is small and savings are largest.

Learning or Inference Procedure

StepBack is a pure inference-time method; no model parameters are modified. Required inputs: a base LLM for draft generation, a process reward model (PRM) trained to score individual reasoning steps (a Llama-3.1-8B model fine-tuned on PRM800K), and two scalar thresholds τ_{NLL} = 0.1 and τ_{PRM} = 0.05 tuned on a small validation split.

What the Guarantee Says

No formal guarantee is claimed. The empirical claim is: on the seven benchmarks tested, StepBack's accuracy is not statistically significantly different from SC at the same sampling budget of m = 32 effective trajectories. The token-reduction claim (up to 41.26%) is an empirical upper bound observed on the MATH benchmark.

Experimental Findings

benchmarks.

- **Token reduction:** 20–41% fewer tokens; largest on MATH (41.26%) and 2WikiMultiHopQA (38.1%).
- **Composition:** StepBack + Adaptive Consistency achieves >41% token reduction at equal or slightly higher accuracy.
- **Threshold sensitivity:** Accuracy stays within 1% across the full threshold grid.

Ablations and Interpretation

tokens by 28%; PRM alone by 31%; combined by 37% on average. The two signals flag different steps on roughly 20% of trajectories, confirming complementarity.

Resampling k: k = 1 achieves 90% of token savings at a 1–2% accuracy drop; k = 3 shows no gain over k = 2.

PRM quality: Replacing the trained PRM with zero-shot self-evaluation reduces accuracy by 2.1% and token savings by 8%.

Reference

Yang Ouyang, Jung-Eun Kim. **StepBack: Step-Level Error-Localized Resampling for Efficient Test-Time Reasoning.** arXiv:2611.08403. NeurIPS 2026. arxiv.org/abs/2611.08403