



Assignment

Assignment No. – 04

Submission date- 28 November, 2021

Course Title- Data Structure (Theory)

Course Code: CSE-2322

Submitted to-

Mohammed Shamsul Alam

Professor, Dept. of CSE, IIUC.

Cell: 01711941680, alam_cse@yahoo.com

Submitted by-

MD. SOROWAR MAHABUB RABBY

Matric ID: **C201032**, Section: **3AM**, Semester: **3rd**

Department of CSE (Computer Science and Engineering), IIUC

Cell: 01834756433, 01521564157, c201032@ugrad.iiuc.ac.bd

Problem No. & Statement	1. Write a program to sort n numbers using Insertion Sort algorithm.
------------------------------------	---

```
/*                                     Author: Sorowar Mahabub                                     */
/*                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int Array[201032],N;

void InsertionSort()
{
    int ptr,k,temp;

    Array[0]= -201032; //will be Infinity

    for(int k=2 ; k<=N; k++)
    {
        temp=Array[k];
        ptr=k-1;
        while(temp<Array[ptr])
        {
            Array[ptr+1]=Array[ptr];
            ptr--;
        }
        Array[ptr+1]=temp;
    }
}

// Author: Sorowar Mahabub, C201032

void DISPLAY()
{
    cout << endl;
    for(int i=1; i<=N; i++)
        cout<<Array[i]<<" ";
    cout << endl;
}

int main()
{
    cout<<"How many Elements: ";
    cin>>N;

    cout<<"Enter Elements: ";
```

```

    for(int i=1; i<=N; i++)
        cin>>Array[i];

    InsertionSort();
    DISPLAY();
    return 0;
}

```

Problem No. & Statement	2. Write a program to sort n numbers using Selection Sort algorithm.
------------------------------------	---

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

//#include <bits/stdc++.h>

#include<iostream>
using namespace std;

void SelectionSort(int *array, int size)
{
    int i, j, imin;
    for(i = 0; i<size-1; i++)
    {
        imin = i;
        for(j = i+1; j<size; j++)
            if(array[j] < array[imin])
                imin = j;

        int temp;
        temp = array[i];
        array[i] = array[imin];
        array[imin] = temp;
    }
}

int main()
{
    int n;
    cout << "Enter How many elements: ";
    cin >> n;
    int arr[n+32];
}

```

```

cout << "Enter your elements: ";
for(int i= 0; i<n; i++)
    cin >> arr[i];

//Author: Sorowar Mahabub, C201032

cout << endl;
cout << "Array is Sorted & sorted elements are: ";
SelectionSort(arr, n);

for(int i= 0; i<n; i++)
    cout << arr[i] << " ";
cout << endl;

return 0;
}

```

Problem No. & Statement	3. Write a program to sort n numbers using Quick Sort algorithm.
------------------------------------	---

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int compareTo(const void* first, const void* second)
{
    int* x = (int*) first;
    int* y = (int*) second;

    if (*x > *y)
    {
        return +1;
    }
    else if (*x < *y)
    {
        return -1;
    }
    else
    {
        return 0;
    }
}

```

```
// Author: Sorowar Mahabub, C201032
int main()
{
    int A[201032],N;

    cout<<"How many elements?: ";
    cin>>N;

    cout<<"Enter the array elements: ";
    for(int i=0; i<N; i++)
        cin>>A[i];

    qsort(A,N,sizeof(int),compareTo);

    cout << endl << "After sorting: ";
    for (int i=0; i<N; i++)
        cout << A[i] << " ";

    return 0;
}
```

Problem No. & Statement	4. Write a program to merge two sorted list.
------------------------------------	---

```
/*                                     Author: Sorowar Mahabub                                     */
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int A[1000], B[1000],C[1000000],N,R,S;

void display();
void MergingSort()
{
    int NA=1,NB=1,Ptr=1;
    while(NA<=R && NB<=S)
    {
        if(A[NA]< B[NB])
        {
            C[Ptr]=A[NA];
            Ptr++;
            NA++;
        }
        else
        {
            C[Ptr]=B[NB];

```

```

        Ptr++;
        NB++;
    }
}

if (NA>R)
{
    for(int k=0; k<=S-NB; k++)
    {
        C[Ptr+k]=B[NB+k];
    }
}
else
{
    for(int k=0; k<=R-NA; k++)
    {
        C[Ptr+k]=A[NA+k];
    }
}
display();
}

void display()
{
    N=R+S;
    cout<<"\nMerged Array Elements: ";
    for(int i=1; i<=N; i++)
        cout<<C[i]<<" ";

    cout << endl;
}

int main()
{
    cout<<"How Many elements (Array A) : ";
    cin>>R;
    cout<<"Enter sorted elements: ";
    for(int i=1; i<=R; i++)
        cin>>A[i];

    cout<<"How Many elements (Array B) : ";
    cin>>S;
    cout<<"Enter sorted elements : ";
    for(int i=1; i<=S; i++)
        cin>>B[i];

    MergingSort();
}

```

```

    return 0;
}

// Author: Sorowar Mahabub, C201032

```

Problem No. & Statement	5. Write a program to sort n numbers using Merge Sort algorithm.
------------------------------------	---

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

#include<bits/stdc++.h>
#include<iostream>
using namespace std;

int A[1000], B[1000], C[1000000], N, R, S;

void MergingSort()
{
    int NA=1, NB=1, Ptr=1;
    while(NA<=R && NB<=S)
    {
        if(A[NA]< B[NB])
        {
            C[Ptr]=A[NA];
            Ptr++;
            NA++;
        }
        //Author: Sorowar Mahabub, C201032
        else
        {
            C[Ptr]=B[NB];
            Ptr++;
            NB++;
        }
    }

    if(NA>R)
    {
        for(int k=0; k<=S-NB; k++)
        {
            C[Ptr+k]=B[NB+k];
        }
    }
    //Author: Sorowar Mahabub, C201032

```

```
        else
        {
            for(int k=0; k<=R-NA; k++)
            {
                C[Ptr+k]=A[NA+k];
            }
        }
    }

//Author: Sorowar Mahabub, C201032
void display()
{
    N= R+S;
    cout << "\nMerged Array Elements : ";
    for(int i=1; i<=N; i++)
        cout << C[i] << " ";
    cout << endl;
}

//Author: Sorowar Mahabub, C201032
int main()
{
    cout << "How Many elements (Array A): ";
    cin>>R;

    cout << "Enter sorted elements: ";
    for(int i=1; i<=R; i++)
        cin>>A[i];

    cout << "How Many elements (Array B): ";
    cin>>S;

    cout<<"Enter sorted elements: ";
    for(int i=1; i<=S; i++)
        cin>>B[i];

    //Author: Sorowar Mahabub, C201032
    MergingSort();
    display();
    return 0;
}
```


Problem No. & Statement

6. Write a program to create a Binary Search Tree of n elements and then display the elements (preorder, inorder and postorder) of the tree.

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

struct node
{
    int info;
    struct node *left;
    struct node *right;
};

node *root;

int insertNode(int Item)
{
    node *p , *newNode, *Back;

    p = root;
    Back=NULL;

    newNode = new node();
    newNode -> left = NULL;
    newNode -> right = NULL;
    newNode -> info = Item;

    while (p!=NULL)
    {
        Back=p;
        if (p->info > Item)
            p = p->left;
        else
            p = p->right;
    }

```

```
    if(Back == NULL)
        root = newNode;
    else if (Back->info > Item)
        Back->left = newNode;
    else Back->right = newNode;

    return 0;
}

void inOrder(node *p)
{
    if(p!=NULL)
    {
        inOrder(p->left);
        printf("%d  ",p->info);
        inOrder(p->right);
    }
}

void preOrder(node *p)
{
    if(p!=NULL)
    {
        printf("%d  ",p->info);
        preOrder(p->left);
        preOrder(p->right);
    }
}

void postOrder(node *p)
{
    if(p!=NULL)
    {
        postOrder(p->left);
        postOrder(p->right);
        printf("%d  ",p->info);
    }
}

int menu()
{
    int n;
```

```
    cout<<"\n\nMain Menu\n";
    cout<<"1. Insert\n";
    cout<<"2. Display\n";
    cout<<"3. Exit\n\n";
    cout<<"Enter Choice(1-3): ";
    cin>>n;
    cout<<"\n";
    return n;
}

void Display()
{
    if(root)
    {
        cout<<"\nTraverse Tree INorder\n";
        inOrder(root);
        cout<<"\nTraverse Tree PREorder\n";
        preOrder(root);
        cout<<"\nTraverse Tree POSTorder\n";
        postOrder(root);
    }
    else
        cout<<"\nBST IS NULL\n";
}

int main()
{
    node p;
    int VAL,n;

    n = menu();

    do
    {
        if(n==1)
        {
            cout<<"\nInsert a val :";
            cin>>VAL;
            insertNode(VAL);
        }
        if(n==2)
```

```

        {
            Display();
        }
        if(n==3)
        {
            cout<<"\n";
            break;
        }
        if(n>3)
            cout<<"\nWrong Choice\n";
        n = menu();

    } while(1);
    return 0;
}

// Author: Sorowar Mahabub, C201032

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

```

**Problem No. &
Statement**

7. Write a program to create a Binary Search Tree of n elements and then search an element from the tree.

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

struct nodeType
{
    int info;
    struct nodeType *left;
    struct nodeType *right;
};

typedef struct nodeType *nodeptr;
nodeptr root;
nodeptr loc, par, save;
//nodeType *root, *loc, *par, *save;
int insertNode(int Item)

```

```
{
    nodeptr p, newNode, back;

    p = root;
    back=NULL;

    newNode = (nodeType *) malloc(sizeof(nodeType));
    newNode -> left = NULL;
    newNode -> right = NULL;
    newNode -> info = Item;

    while (p!=NULL)
    {
        back=p;
        if (p->info > Item)
            p = p->left;
        else
            p = p->right;
    }

    if(back == NULL)
        root = newNode;
    else if (back->info > Item)
        back->left = newNode;
    else back->right = newNode;

    return 0;
}

void inOrder(nodeptr p)
{
    if (p!=NULL)
    {
        inOrder(p->left);
        printf("%d ",p->info);
        inOrder(p->right);
    }
}

void preOrder(nodeptr p)
{
    if (p!=NULL)
    {
        printf("%d ",p->info);
        preOrder(p->left);
        preOrder(p->right);
    }
}
```

```

void postOrder(nodeptr p)
{
    if(p!=NULL)
    {
        postOrder(p->left);
        postOrder(p->right);
        printf("%d  ",p->info);
    }
}

int menu()
{
    int n;

    printf("\n\nMain Menu\n");
    printf("1. Insert\n");
    printf("2. Display\n");
    printf("3. Exit\n\n");
    cout<<"4. search"<<endl;
    printf("Enter Choice(1-4): ");
    scanf("%d",&n);
    printf("\n");
    return n;
}

void Search(int item)
{
    nodeType *ptr;
    if (root==NULL)
    {
        loc = NULL;
        par = NULL;
        cout<<"\nTree is Empty ! \n";
        return;
    }
    if(item == root->info)
    {
        loc = root;
        par = NULL;
        cout << endl << item << " is Found  at Root." <<
endl;
        return;
    }

    if(item<root->info)
    {
        ptr = root->left;
        save=root;
    }
}

```

```
    }
    else
    {
        ptr= root->right;
        save=root;
    }

    while(ptr!=NULL)
    {
        if (item == ptr->info)
        {
            loc=ptr;
            par=save;

            cout << endl << item << " is Found at location:
" << loc << "! Search is Successful!\nChild of Parent: " <<
par->info << '!'<< endl;
            return;
        }
        if(item < ptr->info)
        {
            save=ptr;
            ptr=ptr->left;

        }
        else
        {
            save=ptr;
            ptr=ptr->right;
        }
    }

    loc=NULL;
    par=save;
    if(loc==NULL)
        cout << endl << "Opps, " << item << " is not Found!
Search Unsuccessful!!" << endl;

    return;
}

void Display()
{
    if(root)
    {
        printf("\nTraverse Tree INorder\n");
        inOrder(root);
    }
}
```

```

        printf("\nTraverse Tree PREorder\n");
        preOrder(root);
        printf("\nTraverse Tree POSTorder\n");
        postOrder(root);
    }
    else printf("\nBST IS NULL\n");
}

int main()
{
    nodeptr p;
    int VAL;

    root = NULL;

    char ch[11];
    int n = 2;

    n = menu();

    do
    {
        if(n==1)
        {
            printf("\nInsert a val :");
            scanf("%d",&VAL);
            insertNode(VAL);
        }

        if(n==2)
        {
            Display();
        }
        if(n==3)
        {
            printf("\n");
            break;
        }
        if(n==4)
        {
            cout << "Enter the item to search: ";
            int ok;
            cin >> ok;
            Search(ok);
        }
        if(n>4)
            printf("\nWrong Choice\n");
        n = menu();
    }

```



```

    } while(1);
    return 0;
}

// Author: Sorowar Mahabub, C201032

```

**Problem No. &
Statement**

8. Write a program to create a Binary Search Tree of n elements and then delete an element from the tree

```

/*                                     Author: Sorowar Mahabub                                     */
/*                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */
#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

struct node
{
    int info;
    struct node *left;
    struct node *right;
};

node *root, *loc, *par, *save, *child;

int insertNode(int Item)
{
    node *p, *newNode, *Back;

    p = root;
    Back=NULL;

    newNode = new node();
    newNode -> left = NULL;
    newNode -> right = NULL;
    newNode -> info = Item;

    while (p!=NULL)
    {

```

```
        Back=p;
        if (p->info > Item)
            p = p->left;
        else
            p = p->right;
    }

    if(Back == NULL)
        root = newNode;
    else if (Back->info > Item)
        Back->left = newNode;
    else Back->right = newNode;

    return 0;
}

void Find(int item)
{
    node *ptr;
    if (root==NULL)
    {
        loc = NULL;
        par = NULL;

        return;
    }
    if(item == root->info)
    {
        loc = root;
        par = NULL;

        return;
    }

    if(item<root->info)
    {
        ptr = root->left;
        save=root;
    }
    else
    {
        ptr= root->right;
```

```
        save=root;
    }

    while(ptr!=NULL)
    {
        if (item == ptr->info)
        {
            loc=ptr;
            par=save;
            return;
        }
        if(item < ptr->info)
        {
            save=ptr;
            ptr=ptr->left;

        }
        else
        {
            save=ptr;
            ptr=ptr->right;
        }
    }

    loc=NULL;
    par=save;

    return;
}

void CaseA(node *loc, node *par)    //No children
{
    if(loc->left == NULL && loc->right == NULL)
        child = NULL;
    else if(loc->left!=NULL)
        child = loc->left;
    else
        child = loc->right;

    if(par!=NULL)
    {
        if(loc == par->left)
            par->left = child;
    }
}
```

```
        else
            par->right = child;
    }
    else
        root = child;

    return;
}

void CaseB(node *loc, node *par) // N has two
children
{
    node *ptr, *SUC, *PARSUC;
    ptr = loc->right;
    save=loc;

    while(ptr->left!=NULL)
    {
        save=ptr;
        ptr=ptr->left;
    }
    SUC=ptr; //location of inorder successor
    PARSUC=save; //location of parent of inorder
successor

    CaseA(SUC, PARSUC);

    if(par!=NULL)
    {
        if(loc= par->left)
            par->left = SUC;
        else
            par->right = SUC;
    }
    else
        root=SUC;

    SUC->left= loc->left;
    SUC->right= loc->right;

    return;
```

```
}

void Delete(int item)
{
    Find(item);

    if(loc==NULL)
    {
        cout<<"Item not found";
        return;
    }
    if(loc->right!=NULL && loc->left!=NULL)
    {
        CaseB(loc, par);
    }

    else
    {
        CaseA(loc, par);
    }
    return;
}

void preOrder(node *p)
{
    if(p!=NULL)
    {
        printf("%d  ",p->info);
        preOrder(p->left);
        preOrder(p->right);
    }
}

void Display()
{
    if(root)
    {
        cout<<"\nTraverse Tree PREorder\n";
        preOrder(root);
    }
}
```

```

        else
            cout<<"\nBST IS NULL\n";
    }
int main()
{
    int Num,element,item;
    cout<<"How many elements for BST? " ;
    cin>>Num;
    cout<<"\nEnter elements: ";
    for (int i=0; i<Num; i++)
    {
        cin>>element;
        insertNode(element);
    }
    Display();

    cout<<"\nEnter an element to Delete : ";
    cin>>item;
    Delete(item);

    cout<<"After deleting "<<item<<" node : \n";
    Display();

    return 0;
}

// Author: Sorowar Mahabub, C201032

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

```

**Problem No. &
Statement**

9. Write a program to create a Maxheap of n elements and then display the elements of the heap..

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

```

```
int tree[201032],N;

void Insheap(int tree[],int N, int item)
{
    int ptr,PAR;

    N=N+1;
    ptr=N;
    while(ptr!=0)
    {
        PAR=float(ptr/2);
        //PAR=floor(ptr/2);
        if(item<=tree[PAR])
        {
            tree[ptr]=item;
            return;
        }
        tree[ptr]=tree[PAR];
        ptr=PAR;
    }
    tree[1]=item;

    return;
}

void Display()
{
    cout<<"Maxheap elements: ";
    for(int i=1; i<=N; i++)
        cout<<tree[i]<<" ";
}

int main()
{
    int element;
    cout<<"How many element? :";
    cin>>N;

    for(int i=1; i<=N; i++)
        cin>>tree[i];

    for(int j=1; j<N; j++)
    {
        Insheap(tree, j, tree[j+1]);
    }
}
```

```

    Display();

    return 0;

}

// Author: Sorowar Mahabub, C201032

```

Problem No. & Statement	10. Write a program to create a Maxheap of n elements and then delete an element from the heap.
------------------------------------	---

```

/*                                     Author: Sorowar Mahabub                                     */
/*                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */
#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int tree[201032],N;

void Insheap(int tree[],int N, int item)
{
    int ptr,PAR;

    N=N+1;
    ptr=N;
    while(ptr!=0)
    {
        PAR=float(ptr/2);
        //PAR=floor(ptr/2);
        if(item<=tree[PAR])
        {
            tree[ptr]=item;
            return;
        }
        tree[ptr]=tree[PAR];
        ptr=PAR;
    }
    tree[1]=item;
}

```



```
        return;
    }

void Delheap()
{
    int item;
    int ptr, left, right, last;

    item=tree[1];
    last=tree[N];
    N=N-1;
    ptr=1;
    left=2;
    right=3;
    while(right<=N || left<=N)
    {
        if(last>=tree[left] && last >=tree[right])
        {
            tree[ptr]=last;
            return;
        }
        if(tree[right]<=tree[left])
        {
            tree[ptr]=tree[left];
            ptr=left;
        }
        else
        {
            tree[ptr]=tree[right];
            ptr=right;
        }
        left=2*ptr;
        right=left+1;
    }
    if(left==N && last<tree[left])
    {
        ptr=left;
    }
    tree[ptr]=last;
    return;
}
```

```
void Display()
{
    cout<<"Maxheap elements: ";
    for(int i=1; i<=N; i++)
        cout<<tree[i]<<" ";
}

int main()
{
    int element;
    cout<<"How many element? :";
    cin>>N;

    for(int i=1; i<=N; i++)
        cin>>tree[i];

    for(int j=1; j<N; j++)
    {
        Insheap(tree, j, tree[j+1]);
    }

    cout<<"After deleting ";
    Delheap();

    Display();

    return 0;
}
```

// Author: Sorowar Mahabub, C201032

/*

Author: Sorowar Mahabub
ID: C201032, Section: 3AM, CSE, IIUC

*/

Problem No. & Statement	11. Write a program to sort n numbers using Heap sort algorithm.
------------------------------------	---

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int tree[201032],N, Size, Item;

void Insheap(int tree[],int N, int item)
{
    int ptr,PAR;

    N=N+1;
    ptr=N;
    while(ptr!=0)
    {
        PAR=float(ptr/2);
        //PAR=floor(ptr/2);
        if(item<=tree[PAR])
        {
            tree[ptr]=item;
            return;
        }
        tree[ptr]=tree[PAR];
        ptr=PAR;
    }
    tree[1]=item;

    return;
}

void Delheap()
{
    int ptr,left,right,last;

    Item=tree[1];
    last=tree[N];
    N=N-1;
    ptr=1;

```

```
left=2;
right=3;
while(right<=N || left<=N)
{
    if(last>=tree[left] && last >=tree[right])
    {
        tree[ptr]=last;
        return;
    }
    if(tree[right]<=tree[left])
    {
        tree[ptr]=tree[left];
        ptr=left;
    }
    else
    {
        tree[ptr]=tree[right];
        ptr=right;
    }
    left=2*ptr;
    right=left+1;
}
if(left==N && last<tree[left])
{
    ptr=left;
}
tree[ptr]=last;
return;
}

void heapsort()
{
    int val,j;
    for(j=1; j<N; j++)
    {
        val=tree[j+1];
        Insheap(tree,j, val);
    }
    while(N>1)
    {
        Delheap();
        tree[N+1]=Item;
```

```
    }
}
void Display()
{
    for(int i=1; i<=Size; i++)
        cout<<tree[i]<<" ";
}

int main()
{
    cout<<"How many Elements : ";
    cin>>N;
    Size=N;
    for(int i=1; i<=N; i++)
    {
        cin>>tree[i];
    }
    cout<<"Elements before Heapsort:"<<endl;
    Display();

    cout<<endl;
    heapsort();
    cout<<"After Heap sort:"<<endl;
    Display();

    return 0;
}

// Author: Sorowar Mahabub, C201032
/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */
```

Problem No. & Statement**12. Write a program to display the adjacency matrix of a graph.**

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

#define Max 32

int adj[ Max ][ Max ];
int n;
int main()
{
    int max_edges, n, i, j, origin, destin;
    char graph_type;

    cout<<"Enter number of nodes : ";
    cin>>n;
    cout<<"Enter type of graph, directed or undirected (d/u)
: ";
    fflush( stdin );
    cin>>graph_type;

    if ( graph_type == 'u' )
        max_edges = n * ( n - 1 ) / 2;
    else
        max_edges = n * ( n - 1 );

    for ( i = 1; i <= max_edges; i++ )
    {
        cout<<"Enter edge "<<i<<" ( 0 0 to quit ) : ";
        cin>>origin>>destin;

        if ( ( origin == 0 ) && ( destin == 0 ) )
            break;

        if ( origin > n || destin > n || origin <= 0 ||
destin <= 0 )
        {
            cout<<"Invalid edge!\n" ;
            i--;
        }
        else
        {
            adj[ origin ][ destin ] = 1;

```

```

        if ( graph_type == 'u' )
            adj[ destin ][ origin ] = 1;
    }
}

cout<<"The adjacency matrix is :\n" ;

for ( i = 1 ; i <= n; i++ )
{
    for ( j = 1; j <= n; j++ )
        printf( "%4d", adj[ i ][ j ] );

    cout<< "\n" ;
}
return 0;
}

// Author: Sorowar Mahabub, C201032

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

```

Problem No. & Statement	13. Write a program to display the path matrix of a graph from an adjacency matrix.
------------------------------------	--

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

#include<stdio.h>
#define MAX 1032

void display(int matrix[MAX][MAX]);
void pow_matrix(int p,int adjp[MAX][MAX] );
void multiply(int mat1[MAX][MAX],int
mat2[MAX][MAX],int mat3[MAX][MAX]);

void create_graph( );
int adj[MAX][MAX];
int n;

void create_graph()
{
    int i,max_edges,origin,destin;

```

```

printf("\nEnter number of vertices : ");
scanf("%d",&n);

max_edges = n*(n-1);

for( i=1; i<=max_edges; i++ )
{
    printf("\nEnter edge %d( -1 -1 ) to quit :
",i);
    scanf("%d %d",&origin,&destin);
    if( (origin == -1) && (destin == -1) )
        break;
    if( origin >= n || destin >= n || origin<0 ||
destin<0)
    {
        printf("\nInvalid edge!\n");
        i--;
    }
    else
        adj[origin][destin] = 1;
}
}

void pow_matrix(int p,int adjp[MAX][MAX])
{
    int i,j,k,tmp[MAX][MAX];

    for(i=0; i<n; i++)
        for(j=0; j<n; j++)
            adjp[i][j] = adj[i][j];

    for(k=1; k<p; k++)
    {
        multiply(adjp,adj,tmp);
        for(i=0; i<n; i++)
            for(j=0; j<n; j++)
                adjp[i][j] = tmp[i][j];
    }
}

```



```

}

void multiply(int mat1[MAX][MAX],int
mat2[MAX][MAX],int mat3[MAX][MAX])
{
    int i,j,k;

    for(i=0; i<n; i++)
        for(j=0; j<n; j++)
            {
                mat3[i][j] = 0;
                for(k=0; k<n; k++)
                    mat3[i][j] = mat3[i][j]+ mat1[i][k] *
mat2[k][j];
            }
}

void display(int matrix[MAX][MAX])
{
    int i,j;
    for(i=0; i<n; i++)
    {
        for(j=0; j<n; j++)
            printf("%4d",matrix[i][j]);
        printf("\n");
    }
    printf("\n");
}

int main()
{

    int adjp[MAX][MAX];
    int x[MAX][MAX],path[MAX][MAX],i,j,p;

    create_graph();

    printf("\nThe adjacency matrix is :\n");
    display(adj);

    /*Initialize all elements of matrix x to zero*/

```


**Problem No. &
Statement**

14. Write a program to display the path matrix of a graph using Warshall's algorithm.

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

#define Max 32

int adj[ Max ][ Max ];
int P[ Max ][ Max ] ;
int n;

int main()
{
    int max_edges, n, i, j, origin, destin;
    char graph_type;

    printf( "Enter number of nodes : " );
    scanf( "%d", &n );
    printf( "Enter type of graph, directed or undirected
(d/u) : " );
    fflush( stdin );
    getchar();
    scanf( "%c", &graph_type );

    if ( graph_type == 'u' )
        max_edges = n * ( n - 1 ) / 2;
    else
        max_edges = n * ( n - 1 );

    for ( i = 1; i <= max_edges; i++ )
    {
        printf( "Enter edge %d( 0 0 to quit ) : ", i );
        scanf( "%d %d", &origin, &destin );

        if ( ( origin == 0 ) && ( destin == 0 ) )
            break;

        if ( origin > n || destin > n || origin <= 0 ||
destin <= 0 )
        {

```

```

        printf( "Invalid edge!\n" );
        i--;
    }
    else
    {
        adj[ origin ][ destin ] = 1;

        if ( graph_type == 'u' )
            adj[ destin ][ origin ] = 1;
    }
}

for(int i=1; i<=n; i++)
{
    for(int j=1; j<=n; j++)
    {
        if(adj[i][j]==0)
        {
            P[i][j]=0;
        }
        else
            P[i][j]=1;
    }
}

for(int k=1; k<=n; k++)
{
    for(int i=1; i<=n; i++)
    {
        for(int j=1; j<=n; j++)
        {
            P[i][j]= P[i][j] || (P[i][k] && P[k][j]);
        }
    }
}

printf( "The adjacency matrix is :\n" );

for ( i = 1; i <= n; i++ )
{
    for ( j = 1; j <= n; j++ )
        printf( "%4d", adj[ i ][ j ] );

    printf( "\n" );
}

```

```

printf( "The Path matrix is :\n" );

for ( int i = 1; i <= n; i++ )
{
    for ( int j = 1; j <= n; j++ )
        printf( "%4d", P[ i ][ j ] );

    printf( "\n" );
}

return 0;
}

// Author: Sorowar Mahabub, C201032

```

Problem No. & Statement	15. Write a program to display the adjacency list of a graph.
-------------------------	---

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include <bits/stdc++.h>
using namespace std;
int main()
{
    int V,x,y,n;
    cin>>V>>n;
    vector<int> adj[V];
    for(int i=0; i<n; i++)
    {
        cin>>x>>y;
        adj[x].push_back(y);
        adj[y].push_back(x);
    }

    for (int d = 0; d < V; d++)
    {
        cout << endl << "Vertex " << d << ":";
        {
            for (auto i : adj[d])
                cout << "-> " << i;
            cout << endl;
        }
    }
}

```

```

    }

    return 0;
}

```

Problem No. & Statement	16. Write a program to traverse a graph using Breadth First Search.
------------------------------------	--

```

/*                                     Author: Sorowar Mahabub
                                     ID: C201032, Section: 3AM, CSE, IIUC                                     */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

#define MAX 100
#define initial 1
#define waiting 2
#define visited 3

int n;
int adj[MAX][MAX];
int state[MAX];
void create_graph();
void BF_Traversal();
void BFS(int v);

int Queue[MAX], Front = -1, Rear = -1;
void insert_queue(int vertex);
int delete_queue();
int isEmpty_queue();

void BF_Traversal()
{
    int v;
    for(v=0; v<n; v++)
        state[v] = initial;
    cout<<"Enter Start Vertex for BFS: \n";
    cin>>v;
    BFS(v);
}

void BFS(int v)
{
    int i;
    insert_queue(v);

```

```
state[v] = waiting;
while(!isEmpty_queue())
{
    v = delete_queue( );
    cout<<v;
    state[v] = visited;
    for(i=0; i<n; i++)
    {
        if(adj[v][i] == 1 && state[i] == initial)
        {
            insert_queue(i);
            state[i] = waiting;
        }
    }
    cout<<endl;
}

void insert_queue(int vertex)
{
    if(Rear == MAX-1)
        cout<<"Queue Overflow\n";
    else
    {
        if(Front == -1)
            Front = 0;
        Rear = Rear+1;
        Queue[Rear] = vertex ;
    }
}

int isEmpty_queue()
{
    if(Front == -1 || Front > Rear)
        return 1;
    else
        return 0;
}

int delete_queue()
{
    int delete_item;
    if(Front == -1 || Front > Rear)
    {
        cout<<"Queue Underflow\n";
        exit(1);
    }
    delete_item = Queue[Front];
```

```

    Front = Front+1;
    return delete_item;
}

void create_graph()
{
    int count,max_edge,origin,destin;

    cout<<"Enter number of vertices : ";
    cin>>n;
    max_edge = n*(n-1);

    for(count=1; count<=max_edge; count++)
    {
        cout<<"Enter edge "<<count<<"( -1 -1 to quit ) : ";
        cin>>origin>>destin;

        if((origin == -1) && (destin == -1))
            break;

        if(origin>=n || destin>=n || origin<0 || destin<0)
        {
            cout<<"Invalid edge!\n";
            count--;
        }
        else
        {
            adj[origin][destin] = 1;
        }
    }
}

int main()
{
    create_graph();
    BF_Traversal();
    return 0;
}

// Author: Sorowar Mahabub, C201032

```

Problem No. & Statement	17. Write a program to traverse a graph using Depth First Search.
------------------------------------	--

/*	Author: Sorowar Mahabub ID: C201032, Section: 3AM, CSE, IIUC	*/
----	---	----


```
#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int A[100][100], s[100], visited[100],n,i,j,top=0;

void DFS(int v)
{
    for(i=1; i<=n; i++)
    {
        if(A[v][i] && !visited[i])
        {
            s[++top]=i;
        }
    }

    if(top!=0)
    {
        visited[s[top]]=1;
        DFS(s[top--]);
    }
}

int main()
{
    int v;

    cout<<" Enter the number of nodes : ";
    cin>>n;
    cout<<" Enter the adjacency matrix : ";

    for(i=1; i<=n; i++)
    {
        for(j=1; j<=n; j++)
        {
            cin>>A[i][j];
        }
    }

    cout<<" Enter the starting node : ";
    cin>>v;

    for(i=1; i<=n; i++)
    {
        s[i]=0;
        visited[i]=0;
    }
}
```

```

    }

    DFS(v);

    cout<<" The reachable nodes are : ";

    for(i=1; i<=n; i++)
    {
        if(visited[i]!=0)
        {
            cout<<endl<<" The node "<<i<<" is reachable " ;
        }
        else
        {
            cout<<endl<<" The node "<<i<<" is not reachable
" ;
        }
    }

    return 0;
}

```

// Author: Sorowar Mahabub, C201032

Problem No. & Statement	
	<p>18. Write a program to implement a hash table using Division method & use linear probing for collision resolution.</p> <pre> /* Author: Sorowar Mahabub ID: C201032, Section: 3AM, CSE, IIUC */ #include<iostream> //#include<bits/stdc++.h> using namespace std; #define SIZE 10 int H[SIZE+1]; #define m 7 void Insert() { int key,index,n=0; cout<<"Enter key element to insert\n"; cin>>key; </pre>

```

    index = (key%m)+1;

    while(H[index]!= 0)
    {
        if(H[index] == 0)
            break;

        index++;
        n++;
        if(index==SIZE+1)
            index=1;
        if(n==SIZE+1)
            break;
    }

    if(n==SIZE+1)
    {
        cout<<"\nHash Table is full of elements\nNo Place to
insert this element\n\n";
    }

    else
        H[index] = key;
}

void Search()
{
    int key,index,n=0;

    cout<<"\nEnter the element you want to search\n";
    cin>>key;

    index = (key%m)+1;

    while(n!= SIZE)
    {
        if(H[index]==key)
        {
            cout<<"Element found at index "<<index<<"\n";
            break;
        }
        else
        {
            if(H[index] == 0)
            {
                cout<<"Element not found in Hash table\n";
            }
        }
    }
}

```

```

        break;
    }
    if(H[index] == -1)
    {
        index++;
    }
    n++;
    index++;
    if(index==SIZE)
        index=0;
}
}
if(n-- == SIZE)
    cout<<"Element not found in Hash table\n";
}
void display()
{
    int i;

    cout<<"Index\tValue\n";

    for(i=1; i<=SIZE; i++)
        printf("%d\t%d\n",i,H[i]);
}

int main()
{
    int choice;

    do
    {
        cout<<"Enter your choice\n";
        cout<<" 1. Insert\n 2. Search\n 3. Display\n 0.
Exit\n";
        cin>>choice;

        switch(choice)
        {
            case 1:
                Insert();
                display();
                break;

            case 2:
                Search();
                display();
                break;

            case 3:

```

```

        display();
        break;
    default:
        cout<<"Enter correct choice\n";
        break;
    }
}
while(choice);

return 0;
}

// Author: Sorowar Mahabub, C201032

```

Problem No. & Statement	19. Write a program to implement a hash table using Division method & use double hashing for collision resolution.
------------------------------------	---

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                                                */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

int table[12],SIZE;
#define m 7
#define SIZE 10

/*
Double hashing can be done using :
(hash1(key) + i * hash2(key)) % TABLE_SIZE

Here hash1() and hash2() are hash functions
and TABLE_SIZE is size of hash table.
(We repeat by increasing i when collision occurs)

First hash function is typically
    hash1(key) = key % TABLE_SIZE

A popular second hash function is :
    hash2(key) = PRIME - (key % PRIME)
where PRIME is a prime smaller
                    than the TABLE_SIZE.
*/

```

```

void display();
void Insert()
{
    int key,H1,H2,H,i=0,c=0;

    cout<<"Enter key element to insert\n";
    cin>>key;

    H1= (key%SIZE);
    cout<<"h1 " <<H1;
    H2= m-(key%m);
    cout<<" H2 " <<H2;

    while(i<SIZE)
    {
        H=((H1+ i*H2)%SIZE )+1 ;

        cout<<"H " <<H<<endl;

        if(table[H]==0)
        {
            table[H]=key;
            //c++;
            break;
        }
        else
        {
            i++;
        }
    }
    if(i==SIZE)
        cout<<"Hash table was full of elements\nNo Place to
insert this element\n\n";

    display();
}

void Search()
{
    int element,H1,H2,H,i=0;

    cout<<"Enter element you want to search\n";
    cin>>element;

    H1= element%SIZE;
    H2= m-(element%m);

```

```

while(1)
{
    H=((H1+ i*H2)%SIZE)+1;

    if(table[H]==0)
    {
        cout<<"Element not found in the table"<<endl;
        break;
    }

    if(table[H]==element)
    {
        cout<<"Element found at index : "<<H<<endl;
        break;
    }
    else
    {
        i++;
    }
}

}

void display()
{
    int i;

    printf("Index\tValue\n");

    for(i=1; i<=SIZE; i++)
        printf("%d\t%d\n",i,table[i]);
}

int main()
{
    int choice;

    do
    {
        cout<<"Enter your choice\n";
        cout<<" 1. Insert\n 2. Search\n 3. Display\n 0.
Exit\n";
        cin>>choice;

        switch(choice)
        {
            case 1:
                Insert();

```

```

        break;

    case 2:
        Search();
        break;
    case 3:
        display();
        break;
    default:
        cout<<"Enter correct choice\n";
        break;
    }
}
while(choice);

return 0;
}

```

// Author: Sorowar Mahabub, C201032

Problem No. & Statement	20. Write a program to implement a hash table using chaining method for collision resolution.
------------------------------------	--

```

/*
                                Author: Sorowar Mahabub
                                ID: C201032, Section: 3AM, CSE, IIUC
                                */

#include<iostream>
//#include<bits/stdc++.h>
using namespace std;

typedef struct node
{
    int data;
    struct node *next;
};

node *A[1032];

void Insert(int Size)
{
    int num;
    cout<<"Enter the elements : ";
    for(int i=0; i<Size; i++)
    {
        cin>>num;
    }
}

```



```
node *newNode = new node();
newNode->data = num;
newNode->next = 0;

int mod = num % Size;

if(A[mod] == 0)
{
    A[mod] = newNode;
}

else
{
    node *temp = A[mod];
    while(temp->next)
    {
        temp = temp->next;
    }

    temp->next = newNode;
}
}

void display(int Size)
{
    int i;

    for(i = 0; i < Size; i++)
    {
        node *temp = A[i];
        cout<<"Array"<<"["<<i<<"]"<<"-->";
        while(temp)
        {
            cout<<temp->data<<" -->";
            temp = temp->next;
        }
        cout<<0<<endl;
    }
}

int main()
{
    int i,Size;
```

```
cout<<" Enter the size : ";
cin>>Size;

A[Size];
for(i = 0; i < Size; i++)
    A[i] =0;

Insert(Size);
display(Size);

return 0;
}
// Author: Sorowar Mahabub, C201032
```

Submitted by-

MD. SOROWAR MAHABUB RABBY

Matric ID: **C201032**, Section: **3AM**

Department of CSE (Computer Science and Engineering)