

# RMD – Final Firestore Schema (Field by Field) & Sprint Plan

Versi FINAL – Zero Hole – Siap Implementasi

===== PART 1 – STRUKTUR COLLECTION  
FIRESTORE (FINAL) =====

## 1. users/{uid}

- uid (string)
- nama (string)
- role (admin | manager | branch\_manager | owner | sales\_canvas | sales\_to | supervisor)
- kodeSales (string | null)
- active (bool)
- createdAt (timestamp)

## 2. products/{kodeBarang}

- kodeBarang (string)
- namaBarang (string)
- satuan (array: ['dus', 'pcs', 'pack'])
- hargaBeli (number)
- hargaJual (number)
- aktif (bool)
- createdAt (timestamp)

## 3. outlets/{kodeOutlet}

- kodeOutlet (string, AUTO)
- namaToko (string)
- alamat (string)
- phone (string)
- lat (number)
- lng (number)
- levelHarga (A | B | C)
- creditLimit (number)
- statusBlok (bool)
- createdAt (timestamp)

## 4. sales\_routes/{kodeSales}

- kodeSales (string)
- route (array kodeOutlet)

- aktif (bool)

## 5. rps\_daily/{id}

- tanggal (YYYY-MM-DD)
- kodeSales (string)
- outlets (array: {kodeOutlet,namaToko,lat,lng,phone,status})
- generatedAt (timestamp)
- version (number)

## 6. noo/{id}

- noNoo (string, AUTO)
- kodeSales (string)
- namaToko (string)
- alamat (string)
- phone (string)
- lat (number)
- lng (number)
- fotoTokoUrl (string)
- ktpUrl (string)
- status (PENDING | APPROVED | REJECTED)
- createdAt (timestamp)
- approvedBy (string | null)

## 7. orders/{orderId}

- orderId (string)
- kodeOutlet (string)
- kodeSales (string)
- roleInput (sales\_canvas | sales\_to | supervisor)
- type (CANVAS | TO)
- items (array: {kodeBarang,namaBarang,qty,satuan,harga})
- total (number)
- status (WAIT | APPROVED | DELIVERED | FAILED)
- createdAt (timestamp)

## 8. invoices/{invoiceId}

- noFaktur (string, AUTO)
- orderId (string)
- kodeOutlet (string)
- kodeSales (string)
- total (number)
- jatuhTempo (date)
- status (OPEN | DUE | OVERDUE | LUNAS)
- createdAt (timestamp)

## 9. piutang/{noFaktur}

- noFaktur (string)
- kodeOutlet (string)
- kodeSales (string)
- total (number)
- sisa (number)
- jatuhTempo (date)
- status (OPEN | DUE | OVERDUE | LUNAS)

## 10. rrp/{id}

- noRrp (string, AUTO)
- tanggal (YYYY-MM-DD)
- kodeSales (string)
- fakturList (array: {noFaktur,kodeOutlet,sisa})
- totalTagihan (number)
- status (CREATED | SIGNED | REALIZED)
- createdAt (timestamp)

## 11. setoran/{id}

- noSetoran (string, AUTO)
- kodeSales (string)
- rrpId (string)
- nominal (number)
- metode (CASH | TRANSFER)
- selisih (number)
- createdAt (timestamp)

## 12. transfer\_payments/{id}

- transferId (string)
- kodeOutlet (string)
- kodeSales (string)
- nominal (number)
- buktiUrl (string)
- status (PENDING | VALID | REJECTED)
- createdAt (timestamp)

## 13. retur/{id}

- noRetur (string, AUTO)
- kodeOutlet (string)
- kodeSales (string)
- items (array: {kodeBarang,qty})
- kategori (JELEK | SALVAGE)

- alasan (string)
- fotoUrl (string)
- createdAt (timestamp)

## 14. back\_check/{id}

- noBackCheck (string, AUTO)
- noFaktur (string)
- kodeSupervisor (string)
- status (DIAKUI | TIDAK)
- catatan (string)
- createdAt (timestamp)

## 15. pbuc/{id}

- noPbuc (string, AUTO)
- kodeSales (string)
- items (array: {kodeBarang,qty})
- status (CREATED | APPROVED | DONE)
- createdAt (timestamp)

## 16. loading\_sheets/{id}

- noLoadingSheet (string, AUTO)
- tanggal (YYYY-MM-DD)
- items (array: {kodeBarang,totalQty})
- createdAt (timestamp)

## 17. deliveries/{id}

- noDeliveryNote (string, AUTO)
- driverName (string)
- fakturList (array noFaktur)
- status (ONROUTE | DELIVERED | FAILED)
- createdAt (timestamp)

## 18. purchase\_requests/{id}

- prNo (string, AUTO)
- items (array: {kodeBarang,qty})
- totalItem (number)
- status (DRAFT | SENT | CONFIRMED)
- createdAt (timestamp)

## 19. promos/{id}

- promoId (string)

- kodeSales (string)
- kodeOutlet (string)
- items (array: {kodeBarang,diskonPersen,diskonNominal})
- startDate (date)
- endDate (date)
- impactEstimation (number)
- status (PENDING|APPROVED\_MGR|APPROVED\_BM|REJECTED)
- approvedBy (string|null)

## 20. targets/{periode}

- periode (YYYY-MM)
- omzet (number)
- piutangMax (number)
- coverage (number)
- createdAt (timestamp)

## 21. kpi\_daily/{tanggal}

- tanggal (YYYY-MM-DD)
- omzet (number)
- piutang (number)
- overdue (number)
- coverage (number)
- strikeRate (number)
- returRate (number)
- selisih (number)

## 22. kpi\_monthly/{periode}

- periode (YYYY-MM)
- omzet (number)
- target (number)
- progress (number)
- piutang (number)
- overdue (number)
- coverage (number)

## 23. counters/{id}

- value (number)

## 24. logs/\* (audit, numbering, offline, promo, pr)

- type
- refId
- action

- by
- timestamp

===== PART 2 – SPRINT PLAN (UNTUK DEVELOPER)  
=====

===== SPRINT 1 – CORE FOUNDATION ===== 1. Firebase setup (Auth, Firestore, Storage, Functions) 2. Role system + users collection 3. Products & Outlets master 4. NOO flow + auto kodeOutlet 5. Security Rules 6. Auto numbering engine

Deliverable: Login, master data, NOO jalan

===== SPRINT 2 – TRANSAKSI INTI ===== 1. Orders (Canvas & TO) 2. Invoices + Piutang 3. Gate piutang & credit limit 4. RRP generation 5. Setoran & Transfer 6. Retur

Deliverable: Jual, piutang, nagih, setor

===== SPRINT 3 – GUDANG & DISTRIBUSI ===== 1. PBUC 2. Loading Sheet 3. Delivery + Driver flow 4. RPS harian 5. Sync Upload/Download 6. Offline mode + queue

Deliverable: Gudang & lapangan hidup

===== SPRINT 4 – MANAGEMENT & OWNER =====  
1. Promo + approval flow 2. Back Check 3. Laporan PDF + Email 4. Purchase Request ke pabrik 5. KPI Dashboard Owner 6. Closing Harian + Jurnal Koreksi

Deliverable: Sistem enterprise lengkap

===== STATUS: FINAL – SIAP DIJADIKAN ACUAN  
DEVELOPMENT =====