

CS2529 Computational Imaging - Project Proposal

Synthesis of brain tumor MRI images using GAN aggregation with style transfer

Sarah Hindawi, Sumant Bagri, Vignesh Edithal
{shindawi, sbagri, edithal}@cs.toronto.edu

November 14, 2022

1 Motivation

→ [6] **1**per identification of early stage brain tumors is crucial to prevent long term disability, severe cases such as High Grade Glioma may be fatal. Magnetic Resonance Imaging (MRI) is a powerful non invasive tool for obtaining the **2** brain scans. MRI scans can provide key information such as the location, shape, size, and growth stage of the brain tumor. To perform any medical image analysis using deep learning techniques, a sufficient volume of data with variability is required. However, due to constraints such as imaging time and privacy concerns, there is a lack of robust datasets. Traditional image augmentation methods (rotation, scale, etc.) create highly correlated images which are unable to capture the underlying features of the source images. In addition, they might change the pattern useful for diagnosis. **3** Class imbalance is another reason to apply augmentation. Synthetic data generation is a commonly used approach in the field of medical image analysis since there is no patient data handling or privacy concerns. Generative Adversarial Networks (**GAN**) have shown promising results in generating synthetic data with good generalization and anonymity on a large variety of images. We plan to use **AGGrGAN** [6] as it allows us to capture both the unique features of a source image using style transfer, and also the shared information among the different latent representations of multiple images using aggregation. **7**

2 Related works

→ [6] Han et al. [4] have applied DCGAN and WGAN separately on the BraTS **8** 2016 dataset to generate artificial MRI scans. **9** To validate their results, they conducted the Visual Turing test with 53% accuracy for VtGAN. **11** Nie et al. [7] have used Fully Convolutional Network (FCN) as generator and a basic CNN as the discriminator, they have proposed 3D FCN to estimate target image




Figure 1: Aggregate GAN (AggrGAN) architecture as implemented in [6] with our addition of U-Net GAN

from the corresponding source image, they have used ADNI dataset and have obtained a mean PSNR of 13.1. Emami et al. [3] have proposed a GAN based model where ResNet is used as the generator and discriminator is a CNN with five convolutional layers which classify the image as real or fake, they achieved a mean PSNR of 26.15 ± 1.2 for an IRB approved dataset.

3 Project overview

Our main goal is to understand how GAN models can help boost research in the medical imaging domain. We aim to implement the aggregated GAN (**AG-GrGAN**) as described in [6] and compare the performance with its component GANs (e.g. DCGAN, WGAN) using three metrics, SSIM, PSNR and KL divergence. Subsequently, we will implement style transfer as described in [6] to improve image resemblance and evaluate its performance both quantitatively (using aforementioned metrics) and qualitatively. We plan on introducing the following modifications to AGGrGAN. **1)** Adding a U-Net GAN [8]. **2)** Using two different weight initializations for each GAN (6 GANs in total). **3)** Modifying the aggregation algorithm to use images from all GANs instead of picking the top 2 (based on metrics) as mentioned in [6]. We will perform an ablation study to assess the performance impact of each of these modifications. If time permits we would like to implement a basic tumor classification network which will be trained on datasets using only real images, only fake images, combination of real and fake images, to show the effectiveness of the synthesized images. We will use the publicly available BraTS 2020 [5] [1] [2] dataset for our experiments.

4 Milestones

Week 1: Fetch dataset and analyze it for further processing

Week 2: Implement DCGAN, WGAN, U-Net GAN and aggregation models

Week 3: Implement Style transfer and perform evaluations on the dataset

Week 4: Prepare the project report and poster

References

- [1] Spyridon Bakas, Hamed Akbari, Aristeidis Sotiras, Michel Bilello, Martin Rozycki, Justin S. Kirby, John B. Freymann, Keyvan Farahani, and Christos Davatzikos. Advancing the cancer genome atlas glioma MRI collections with expert segmentation labels and radiomic features. *Scientific Data*, 4(1), September 2017.
- [2] Spyridon Bakas, Mauricio Reyes, and et al. Jakab. Identifying the best machine learning algorithms for brain tumor segmentation, progression assessment, and overall survival prediction in the brats challenge, 2018.
- [3] Hajar Emami, Ming Dong, Siamak P. Nejad-Davarani, and Carri K. Glide-Hurst. Generating synthetic CTs from magnetic resonance images using generative adversarial networks. *Medical Physics*, 45(8):3627–3636, July 2018.
- [4] Changhee Han, Hideaki Hayashi, Leonardo Rundo, Ryosuke Araki, Wataru Shimoda, Shinichi Muramatsu, Yujiro Furukawa, Giancarlo Mauri, and Hideki Nakayama. GAN-based synthetic brain MR image generation. In *2018 IEEE 15th International Symposium on Biomedical Imaging (ISBI 2018)*. IEEE, April 2018.
- [5] Bjoern H. Menze, Andras Jakab, and et al. Stefan Bauer. The multimodal brain tumor image segmentation benchmark (BRATS). *IEEE Transactions on Medical Imaging*, 34(10):1993–2024, October 2015.
- [6] Debadyuti Mukherjee, Pritam Saha, Dmitry Kaplun, Aleksandr Sinitca, and Ram Sarkar. Brain tumor image generation using an aggregation of GAN models with style transfer. *Scientific Reports*, 12(1), June 2022.
- [7] Dong Nie, Roger Trullo, Jun Lian, Li Wang, Caroline Petitjean, Su Ruan, Qian Wang, and Dinggang Shen. Medical image synthesis with deep convolutional adversarial networks. *IEEE Transactions on Biomedical Engineering*, 65(12):2720–2730, December 2018.
- [8] Edgar Schönfeld, Bernt Schiele, and Anna Khoreva. A u-net based discriminator for generative adversarial networks, 2020.