

ERP Deployment & Backup

SEPL ERP — Redis optimization layer (first production deploy). Staged: code first (fallback-safe), then Redis on.

1 · Pre-flight + backup (VPS)

```
cd /root/erp
node --version           # must be >= 18
git rev-parse --short HEAD # note this for rollback
git status               # MUST be clean (deploy.sh does a hard reset)
node server/scripts/backup-db.js # WAL-safe snapshot of erp.db + chat.db -> /root/erp-backups/
```

Use the script, not `cp` : SQLite runs in WAL mode, so a plain file copy can grab the DB mid-write and corrupt the backup. `backup-db.js` uses the native online-backup API (consistent snapshot while the server writes), backs up both DBs, and keeps the last 30.

2 · Deploy code (runs in fallback; Redis not on yet)

```
bash scripts/deploy.sh
pm2 status              # erp: online
```

Expected: the smoke test warns “Redis not reachable” at this stage — correct, Redis isn’t installed yet. The app serves the new code in fallback mode.

3 · Install Redis + configure .env

```
sudo bash scripts/setup-redis.sh
redis-cli ping                # -> PONG

nano /root/erp/.env          # APPEND the block below (do NOT overwrite)

grep -E 'JWT_SECRET|REDIS_URL' /root/erp/.env # confirm JWT_SECRET still present
```

Critical: append to `.env`, never overwrite. Overwriting drops `JWT_SECRET` and logs every user out.

4 · Restart on Redis + verify

```
pm2 restart erp --update-env
node server/scripts/redis-smoke.js # expect 4/4 PASS
redis-cli exists sepl:t:global:jobs:worker-alive # -> 1 (worker heartbeat)
pm2 save
```

.env block to append

```
# --- Redis optimization layer ---
REDIS_URL=redis://127.0.0.1:6379
REDIS_KEY_PREFIX=sepl
PRESENCE_TTL_SEC=30
ERP_DISABLE_REDIS=
ERP_DISABLE_JOB_QUEUE=
ERP_EMBED_WORKER=1
```

Rollback

```
# Disable Redis, keep new code (instant, no redeploy):
echo 'ERP_DISABLE_REDIS=1' >> /root/erp/.env && pm2 restart erp --update-env

# Full code rollback:
git reset --hard <commit-from-step-1>
npm install
pm2 startOrReload ecosystem.config.js
```

Databases (`data/erp.db` , `data/chat.db`), `.env` , `node_modules/` and `client/dist/` are gitignored — the hard reset in `deploy.sh` never touches them. Backups from step 1 are the belt-and-suspenders copy.