Conexão SSH

VirtualBox - AlpineLinux

Windows - Gitbash

```
Alunos@LMC1-PC08 MINGW64 ~ (master)

$ ssh user@10.112.3.157
The authenticity of host '10.112.3.157 (10.112.3.157)' can't be established.
ED25519 key fingerprint is SHA256:HLXVoRuypobh8XBD29E9hHvyVWbVGpkCVglg2whaTow.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.112.3.157' (ED25519) to the list of known hosts.
user@10.112.3.157's password:
Welcome to Alpine!

The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <a href="https://wiki.alpinelinux.org/">https://wiki.alpinelinux.org/</a>.

You can setup the system with the command: setup-alpine

You may change this message by editing /etc/motd.
localhost:~$ echo "Entrei no sistema :)" > /tmp/hi
localhost:~$
```

Chaves do servidor

```
localhost:"# cat /etc/ssh/ssh_host_ed25519_key
----BEGIN OPENSSH PRIVATE KEY-----
b3BlbnNzaC1rZXktdjEAAAAABG5vbmUAAAAEbm9uZQAAAAAAAAABAAAMwAAAAtzcZgtZW
QyNTUxOQAAACBTd9QU1LAxtJrbbQmaijMcXk4g3E1Swd6hIKVs31hCUQAAAJjE/JmUxPyZ
lAAAAAtzcZgtZWQyNTUxOQAAACBTd9QU1LAxtJrbbQmaijMcXk4g3E1Swd6hIKVs31hCUQ
AAAEA17Y4/uQ+pQfIBkGvtcOCOEHdnvGIQqSiEmji58wyAklN31BTUsDG0mtttCZqKMxxe
IiDcSVLB3qEgpWzfWEJRAAAADnJvb3RAbG9jYWxob3N0AQIDBAUGBw==
----END OPENSSH PRIVATE KEY-----
localhost:"# cat /etc/ssh/ssh_host_ed25519_key.pub
ssh-ed25519 AAAAC3NzaC11ZDI1NTE5AAAAIFN31BTUsDG0mtttCZqKMxxeTiDcSVLB3qEgpWzfWEJR root@localhost
localhost:"#
```

Conexão utilizando chaves

Criando chaves no cliente

```
lunos@LMC1-PC08 MINGW64 ~ (master)
$ ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/c/Users/Alunos/.ssh/id_rsa): chave
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
our identification has been saved in chave
our public key has been saved in chave.pub
The key fingerprint is:
SHA256:p619q4rgnSK9vmibsPoR3LaspxIqezxy7MPK8XEx9Ao Alunos@LMC1-PC08
The key's randomart image is:
 ---[RSA 3072]---
  oEoo .S .
0*.0+0 . .
 *0&**0 0 0 .
B%OX=++ 0.00..
    -[SHA256]--
```


Copiando chave publica do cliente para o servidor

```
Alunos@LMC1-PC08 MINGW64 ~ (master)
$ ssh-copy-id -i chave user@10.112.3.157
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "chave.pub"
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are alre ady installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install the new keys

Number of key(s) added: 1

Now try logging into the machine, with: "ssh 'user@10.112.3.157'"
and check to make sure that only the key(s) you wanted were added.
```

Chave pública do cliente já está no servidor



Logando utilizando a chave do cliente

```
Alunos@LMC1-PC08 MINGW64 ~ (master)
$ ssh user@10.112.3.157
Welcome to Alpine!

The Alpine Wiki contains a large amount of how-to guides and general information about administrating Alpine systems.

See <a href="https://wiki.alpinelinux.org/">https://wiki.alpinelinux.org/</a>.

You can setup the system with the command: setup-alpine

You may change this message by editing /etc/motd.

localhost:~$
```