


- 1.CAPACITY :---50TON. TO 1000 TON.
2.MAIN CYLINDER STROKE:-----4 INCH TO 25 INCH .
3.MAIN CYLINDER SINGLE ACTING OR DOUBLE ACTING.
4.OIL TANK 500 LTRS. TO 1000LTRS.
5.MAIN TABLE SIZE:----LEFT TO RIGHT , FRONT TO BACK .
6.MAIN CYLINDER DAYLIGHT :-----MM. OR INCH .
7.DIE CUSHION CAPACITY :---20TON. TO 600 TON.
8.DIE CUSHION STROKE:-----4 INCH TO 25 INCH .
9.DIE CUSHION TABLE SIZE:----LEFT TO RIGHT , FRONT TO BACK .
10.POWER PACK :----- 5HP TO 250 HP .
11.PUSH BUTTON, PLC , HMI.
12.POWER PACK SINGLE SPEED OR DOUBLE SPEED.
13.STROKE ADJUSTABLE THROUGH LIMIT SWITCH.
14.SAFETY FEATURES. :---PHOTO SENSORS.

ANGLE OF PROJECTION



DO NOT SCALE DRAWING

CHK'D

NAME

SIGNATURE

DATE

DRAWN

CHK'D

APPV'D

P.B.PATIL

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
SURFACE FINISH:
LINEAR:
ANGULAR:

EPITOME



EPITOME

UDYAMBAG-BELAGAVI
KARNATAKA-INDIA

sudhir.epitome@gmail.com.

DRAWING NO.

STRETCHED TIE ROD WITH DIE-CUSHION PRESS

MATERIAL:

WEIGHT:

sudhir.epitome@gmail.com