

EDP SERIES- E EPITOME D DOUBLE ACTING OIL RETURN P PLAIN RAM 10 CAPACITY -TON 150 STROKE -MM

D

Ε

RATED CAPACITY (TON)	CAPACITY @700 BAR (KN)	STROKE (MM)	MODEL	EFFECTIVE AREA (CM ²⁾	OIL CAP (CC)	A CLOSED HEIGHT (MM)	B CYLIINDER OD (MM)	C BORE DIA (MM)	D RAMDIA (MM)	WT (APPROX) (KG)
10	111	150	EDP 10-150	15.9	239	275	75	45	30	8
15	167	150	EDP 15-150	23.8	356	280	85	55	40	11
20	218	150	EDP 20-150	31.2	468	285	95	63	50	14
25	270	150	EDP 25-150	38.5	577	295	95	70	55	14.3
30	309	150	EDP 30-150	44.2	663	305	100	75	55	15.6
50	550	150	EDP 50-150	78.5	1178	305	130	100	70	26.3
75	792	150	EDP 75-150	113.1	1696	305	155	120	90	38.5
100	1077	150	EDP 100-150	153.9	2309	310	180	140	110	53.5
150	1589	150	EDP 150-150	227.0	3405	320	220	170	140	84
200	2199	150	EDP 200-150	314.2	4712	345	255	200	150	116
250	2661	150	EDP 250-150	380.1	5702	350	280	220	180	148
300	3167	150	EDP 300-150	452.4	6786	365	310	240	180	181
400	4008	150	EDP 400-150	572.6	8588	385	350	270	220	255

ANGLE OF PROJECTION DO NOT SCALE DRAWING CHK'D **DESCRIPTION** REVISION E SIGNATURE DATE NAME DRAWN PRADEEP 22.02.2022 **EPITOME** 22.02.2022 CHK'D PATIL APPV'D P.B.PATIL 22.02.2022 EDP-SERIES UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: **UDYAMBAG-BELAGAVI** MATERIAL: KARANATAKA-INDIA TOLERANCES: LINEAR: sudhir.epitome@gmail.com. weight: ANGULAR: sudhir.epitome@gmail.com EN EPITOME