

EDH SERIES - E EPITOME D DOUBLE ACTING OIL RETURN H HOLLOW RAM 10 CAPACITY - TON 75 STROKE -MM

RATED CAPACITY (TON)	CAPACIT Y @700 BAR (KN)	STROKE (MM)	MODEL	EFFECTIVE AREA (CM ²⁾	OIL CAP (CC)	HEIGHT	B CYLIINDER OD (MM)	C BORE DIA (MM)	DIA	D RAMDIA (MM)	WT (APPROX) (KG)
(1011)				(3.0.		(MM)			(MM)		
10	103	75	EDH 10-75	14.7	110	210	75	50	20	40	6
10	103	100	EDH 10-100	14.7	147	235	75	50	20	40	6.8
20	202	50	EDH 20-50	28.9	144	205	100	70	27	60	11.5
20	202	100	EDH 20-100	28.9	289	255	100	70	27	60	14
20	202	150	EDH 20-150	28.9	433	305	100	70	27	60	16.5
30	309	50	EDH 30-50	44.2	221	220	115	85	33	70	15.5
30	309	100	EDH 30-100	44.2	442	270	115	85	33	70	19
30	309	150	EDH 30-150	44.2	663	320	115	85	33	70	22
50	528	100	EDH 50-100	75.4	754	280	140	110	42	90	27
60	641	7 5	EDH 60-75	91.6	687	265	155	125	54	100	31
60	641	100	EDH 60-100	91.6	916	290	155	125	54	100	33.5
60	641	150	EDH 60-150	91.6	1373	340	155	125	54	100	38.5
100	1093	75	EDH 100-75	156.1	1171	295	210	170	77	130	60
100	1093	100	EDH 100-100	156.1	1561	320	210	170	77	130	64
150	1649	150	EDH 150-150	235.6	3534	375	245	200	80	150	104
200	2111	150	EDH 200-150	301.6	4524	400	290	220	80	160	164

ANGLE OF PROJECTION DESCRIPTION REVISION DO NOT SCALE DRAWING CHK'D E NAME SIGNATURE DATE EPITOME 03.06.2021 DRAWN PRADEEP 03.06.2021 CHK'D PATIL HYDRAULICS DRAWING NO. APPV'D P.B.PATIL 03.06.2021 UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: EDH-SERIES UDYAMBAG-BELAGAVI MATERIAL: **A2** KARANATAKA-INDIA TOLERANCES: LINEAR: sudhir.epitome@gmail.com. weight: ANGULAR: SHEET1 OF 1 sudhir.epitome@gmail.com ET EPITOME