

ESH SERIES: E EPITOME S SINGLE ACTING SPRING RETURN H HOLLOW 10 CAPACITY-TON 50 STROKE-MM

C

D

Ε

	RATED CAPACITY (TON)	CAPACITY @700 BAR (KN)	STROKE (MM)	MODEL	EFFECTIVE AREA (CM ²⁾	OIL CAP (CC)	A CLOSED HEIGHT (MM)	B CYLIINDER OD (MM)	C BORE DIA (MM)	D RAMDIA (MM)	WT (APPROX) (KG)
	10	110	50	ESH 10-50	15.7	7 9	165	75	60	50	4.6
-	10	110	75	ESH 10-75	15.7	118	190	75	60	50	5.3
	10	110	100	ESH 10-100	15.7	157	215	75	60	50	6
	20	231	50	ESH 20-50	33.0	165	170	105	85	7 5	10.5
	20	231	100	ESH 20-100	33.0	330	220	105	85	7 5	13.5
	20	231	150	ESH 20-150	33.0	495	270	105	85	75	16
	30	298	50	ESH 30-50	42.6	213	195	115	95	80	13
	30	298	75	ESH 30-75	42.6	320	220	115	95	80	14.5
	30	298	100	ESH 30-100	42.6	426	245	115	95	80	16
	30	298	150	ESH 30-150	42.6	639	295	115	95	80	19
	50	550	75	ESH 50-75	78.5	589	230	150	125	100	25
	50	550	100	ESH 50-100	78.5	785	255	150	125	100	27
	60	605	75	ESH 60-75	86.4	648	245	165	135	110	32
	60	605	100	ESH 60-100	86.4	864	270	165	135	110	35
	60	605	150	ESH 60-150	86.4	1296	320	165	135	110	40.5
	100	990	7 5	ESH 100-75	141.4	1060	270	215	180	150	58
	100	990	100	ESH 100-100	141.4	1414	295	215	180	150	62

ANGLE OF PROJECTION **DESCRIPTION** REVISION DO NOT SCALE DRAWING CHK'D E NAME SIGNATURE DATE DRAWN PRADEEP 22.02.2022 **EPITOME** CHK'D PATIL 22.02.2022 APPV'D P.B.PATIL 22.02.2022 UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: ESH-SERIES **UDYAMBAG-BELAGAVI** MATERIAL: KARANATAKA-INDIA TOLERANCES: LINEAR: sudhir.epitome@gmail.com. weight: ANGULAR: sudhir.epitome@gmail.com EN EPITOME