Metasploit Exploit Execution (Attacker Side)

Overview | Analysis | Sessions 1 | Campaigns | Web Apps | Modules | Tags | Reports | Tasks

Home > Metasploitable 2 > Tasks > Task 7

Task started

Launching	Complete (1 session opened) exploit/multi/samba/usermap_script	Complete

```
[+] [2012.07.12-20:56:01] Workspace:Metasploitable 2 Progress:1/2 (50%) Exploiting 10.10.10.30
[*] [2012.07.12-20:56:02] Started reverse double handler
[*] [2012.07.12-20:56:02] Accepted the first client connection...
[*] [2012.07.12-20:56:02] Accepted the second client connection...
[*] [2012.07.12-20:56:02] Command: echo lPOBBQKKXi4q89xL;
[*] [2012.07.12-20:56:02] Writing to socket A
[*] [2012.07.12-20:56:02] Writing to socket B
[*] [2012.07.12-20:56:02] Reading from sockets...
[*] [2012.07.12-20:56:03] Reading from socket B
[*] [2012.07.12-20:56:03] B: "lPOBBQKKXi4q89xL\r\n"
[*] [2012.07.12-20:56:03] Matching...
[*] [2012.07.12-20:56:03] A is input...
[+] [2012.07.12-20:56:03] Session 3 created for 10.10.10.30
[+] [2012.07.12-20:56:03] Workspace:Metasploitable 2 Progress:2/2 (100%) Complete (1 session opened) exploit/multi/samba/usermap_script
```

Metasploit Community 4.3.0 - Update 1 © 2010-2012 Rapid7 Inc, Boston, MA

root@kali: ~

File Edit View Search Terminal Help

```
root@kali:~# msfconsole -h
Usage: msfconsole [options]

Common options
    -E, --environment ENVIRONMENT    The Rails environment. Will use RAIL_ENV environment variable if that is set.  Defaults to production if
 neither option not RAILS_ENV environment variable is set.

Database options
    -M, --migration-path DIRECTORY   Specify a directory containing additional DB migrations
    -n, --no-database                Disable database support
    -y, --yaml PATH                  Specify a YAML file containing database settings

Framework options
    -c FILE                          Load the specified configuration file
    -v, --version                    Show version

Module options
        --defer-module-loads         Defer module loading unless explicitly asked.
    -m, --module-path DIRECTORY      An additional module path


Console options:
    -a, --ask                        Ask before exiting Metasploit or accept 'exit -y'
    -d, --defanged                   Execute the console as defanged
    -L, --real-readline              Use the system Readline library instead of RbReadline
    -o, --output FILE                Output to the specified file
    -p, --plugin PLUGIN              Load a plugin on startup
    -q, --quiet                      Do not print the banner on startup
    -r, --resource FILE              Execute the specified resource file (- for stdin)
    -x, --execute-command COMMAND    Execute the specified string as console commands (use ; for multiples)
    -h, --help                       Show this message
root@kali:~#
```

```
root@kali: ~
File  Edit  View  Search  Terminal  Help
root@kali:~# msfconsole

# cowsay++
 ____________
< metasploit >
 ------------
       \   ,__,
        \  (oo)____
           (__)    )\
              ||--|| *


       =[ metasploit v4.16.57-dev                         ]
+ -- --=[ 1767 exploits - 1007 auxiliary - 307 post       ]
+ -- --=[ 537 payloads - 41 encoders - 10 nops            ]
+ -- --=[ Free Metasploit Pro trial: http://r-7.co/trymsp ]

msf >
```