[TDDE09 2026] Lecture 2.2

Points: 2/5

✓ **Correct** 1/1 Points

1. Which of the following tasks do not usually lend themselves to the use of autoregressive language models?

- ○ machine translation
- ○ text summarisation
- ◉ document classification

✗ **Incorrect** 0/1 Points

2. Suppose we translate from Arabic (A) to Swedish (S). Which of the following quantities does a neural sequence-to-sequence model learn?

- ○ $P(A, S)$
- ○ $P(S \mid A)$
- ◉ $P(A \mid S)$

✓ **Correct** 1/1 Points

3. Which of the following resources do we need in order to train sequence-to-sequence translation models?

- ◉ parallel texts for the source language–target language pair

- ( ) word alignments between the words in the source language and target language
- ( ) a language model for the target language

✕ **Incorrect** 0/1 Points

4. Which of the following parameters does not impact the space complexity of beam search?

- ( ) width of the beam
- ( ) number of possible translations for the source sentence
- (●) lengths of the generated target sentences

✕ **Incorrect** 0/1 Points

5. Why do we use length normalisation together with beam search in decoding?

- ( ) We want to avoid numerical overflow.
- (●) We do not want to penalise short translations.
- ( ) We do not want to penalise long translations.

Microsoft 365

This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Microsoft Forms | AI-Powered surveys, quizzes and polls Create my own form

Privacy and cookies | Terms of use