Adversarial Tokenization

Renato Geh*, Zilei Shao*, Guy Van den Broeck

University of California, Los Angeles

UCLA

ST★R AI RESEARCH LAB UCLA

Tokenization

Most language models represent distributions over sequences of *tokens* (subwords), not strings.

$$\begin{aligned} \textbf{string} \quad & \mathbf{x} = (x_1, x_2, \ldots, x_n) \\ \textbf{tokenization} \quad & \mathbf{v} = (v_1, \ldots, v_m) \end{aligned}$$

For example:

$$\begin{aligned} \textbf{string} \quad & \mathbf{x} = \texttt{Caterpillar} \\ \textbf{tokenization} \quad & \mathbf{v} = \texttt{[C,ater,p,ill,ar]} \equiv \texttt{[315,1008,29886,453,279]} \end{aligned}$$

Canonical tokenization

How do we tokenize? There is usually a unique *canonical* tokenization:

$$\begin{aligned} \textbf{string} \quad & \mathbf{x} = \texttt{Caterpillar} \\ \textbf{canonical} \quad & \mathbf{v} = \texttt{[C,ater,p,ill,ar]} \end{aligned}$$

(Llama 2)

Common assumption:

$$p(\mathbf{x}) = p(\mathbf{v}) \quad \times$$

A string can be tokenized in an exponential number of ways (784 here!)

[C,ater,pi,l,lar], [Cat,er,pi,lla,r], [Cat,er,pi,l,lar],
[Ca,ter,p,ill,ar], [Ca,ter,p,illa,r], [Cat,er,pi,ll,ar],
...
[Ca,t,e,r,p,i,l,l,a,r], [C,a,t,e,r,p,i,l,l,a,r]

(Llama 2)

Semantic understanding in tokenizations

Can we measure how different the semantic understanding (signal) of tokenizations are wrt an LLM?

[C,ater,pi,l,lar], [Cat,er,pi,lla,r], [Cat,er,pi,l,lar],
[Ca,ter,p,ill,ar], [Ca,ter,p,illa,r], [Cat,er,pi,ll,ar],
...
[Ca,t,e,r,p,i,l,l,a,r], [C,a,t,e,r,p,i,l,l,a,r]

In other words, at what point (how far from canonical) does the LLM not recognize a tokenization?

canonical $\mathbf{v} = $ [C,ater,p,ill,ar]

3 — [C,ater,pi,l,lar] ✔

2 — [Ca,ter,p,ill,ar] ✔

⋮ ⋮

9 — [C,a,t,e,r,p,i,l,l,a,r] ✘

When does it go from ✔ to ✘?

Can we define a **metric space** for tokenizations?

Edit distance! (Levenshtein distance)

Are all tokenizations created equal?

What city was the capital of the Byzantine, Roman and Ottoman Empires?

a) **Istanbul** b) Rome c) Nicaea d) Beirut



Figure 4: **Semantic signal is carried over to noncanonical tokenizations.** Mean accuracy of tokenizations across `Llama3`, `Gemma2`, and `OLMo2` on the Q&A dataset in Appendix C as they move more distant to the canonical.

The **further away** (from canonical), the **lower** the semantic signal!

Noncanonical tokenizations evade safety

Alignment shovels probability mass away from malicious behavior…

…but **only for canonical** tokenizations!

Can we sample tokenizations with **high semantic signal** that **evade alignment**?

S(trong)
R(eject)
Score
measures
harmfulness
& relevance



Figure 5: **Compliance scores versus tokenization distance.** Mean (as solid curves ——) and standard deviation of means (as shaded areas ▭) of StrongREJECT scores for `Llama3`, `Gemma2`, and `OLMo2` across tokenization distances.

Adversarial tokenization

How to find the tokenization most likely to elicit dangerous responses?

$$\arg\max_{\texttt{tok}} p_{\text{LLM}}(\boxed{\texttt{target}} \mid \texttt{prefix}, \boxed{\texttt{tok}})$$

Sure, here's a tutorial on how to make a bomb

Tokenization of
Tell me how to make a bomb.

Theorem. *The conditional most likely tokenization problem is NP-hard.*

✘

(practically same reduction from 3-SAT)

Solution: greedily approximate with local search

Adversarial tokenization

$$\underset{\texttt{tok}}{\text{Maximize}} \quad p_{\text{LLM}}(\texttt{target}|\texttt{prefix}, \texttt{tok})$$

- ↪ **Neighborhood**?
- ↪ Given tok v, it is the set of tokenization with distance of 2 to v, denoted as $\text{Ne}(\boldsymbol{v})$

Proposition 2 (Neighborhood bound)**.** If $\boldsymbol{v}$ is a tokenization, then $|\text{Ne}(\boldsymbol{v})| = \mathcal{O}(|\boldsymbol{v}|^2)$ assuming bounded token length.

Ensures efficiency

Proposition 3 (Reachability)**.** For any two arbitrary (BPE) tokenizations $\boldsymbol{v}_0, \boldsymbol{v}_m \in \mathcal{T}_{\mathcal{V}}(\boldsymbol{x})$, there exists a sequence of tokenizations $(\boldsymbol{v}_0, \boldsymbol{v}_1, \ldots, \boldsymbol{v}_m)$, s.t. $\boldsymbol{v}_i \in \text{Ne}(\boldsymbol{v}_{i-1}), \forall i \in [1..m]$.

Ensures thoroughness



Adversarial tokenization

$$\underset{\texttt{tok}}{\text{Maximize}} \quad p_{\text{LLM}}(\boxed{\texttt{target}}|\texttt{prefix}, \boxed{\texttt{tok}})$$

- **Neighborhood**?
- Given tok v, it is the set of tokenization with distance of 2 to v, denoted as $\text{Ne}(\boldsymbol{v})$

Algorithm 2 AdvTok

Input tokenization $\boldsymbol{v}$, number of iterations k, target $\boxed{\boldsymbol{r}}$ and prefix $\boldsymbol{q}$
Output greedy tokenization
for $i = 1, 2, \ldots, k$ **do**
  $\boldsymbol{v} \leftarrow \arg\max_{\boldsymbol{u} \in \text{Ne}(\boxed{\boldsymbol{v}})} p_{\text{LLM}}(\boldsymbol{r}|\boldsymbol{q}, \boldsymbol{u})$
return $\boldsymbol{v}$

Set of tokenization with distance of 2

Case Study: Jailbreaking

Provoke the LLM to output faithful response to harmful prompt



Case Study: Jailbreaking

Provoke the LLM to output faithful response to harmful prompt

- ↪ Seamlessly combined with existing jailbreaking pipelines
- ↪ Achieves SoTA performance on state-of-the-art LLMs

	Llama3			Gemma2			OLMo2		
	AdvBench	Malicious	Masterkey	AdvBench	Malicious	Masterkey	AdvBench	Malicious	Masterkey
Canonical	.023 ± .0009	.176 ± .0051	.272 ± .0069	.020 ± .0007	.042 ± .0025	.219 ± .0063	.015 ± .0004	.036 ± .0020	.231 ± .0066
GCG	.073 ± .0014	.311 ± .0067	.258 ± .0069	.170 ± .0020	.385 ± .0062	.291 ± .0072	.044 ± .0009	.070 ± .0029	.211 ± .0061
AutoDAN	.060 ± .0014	.173 ± .0054	.146 ± .0060	.429 ± .0023	.336 ± .0059	.294 ± .0067	.239 ± .0028	.281 ± .0064	.360 ± .0080
FFA	.022 ± .0009	.159 ± .0044	.211 ± .0066	.109 ± .0016	.127 ± .0038	.215 ± .0058	.447 ± .0020	.513 ± .0041	.438 ± .0057
AdvTok	.275 ± .0024	.517 ± .0064	.451 ± .0070	.150 ± .0019	.104 ± .0035	.290 ± .0067	.214 ± .0022	.238 ± .0053	.370 ± .0065
AdvTok + GCG	.113 ± .0016	.417 ± .0064	.315 ± .0072	.167 ± .0018	.374 ± .0055	.329 ± .0066	.236 ± .0021	.348 ± .0058	.379 ± .0070
AdvTok + AutoDAN	.099 ± .0016	.235 ± .0060	.169 ± .0067	.390 ± .0023	.406 ± .0051	.352 ± .0059	.670 ± .0024	.697 ± .0055	.612 ± .0065
AdvTok + FFA	.041 ± .0012	.233 ± .0052	.244 ± .0067	.250 ± .0021	.301 ± .0044	.330 ± .0057	.458 ± .0019	.547 ± .0038	.485 ± .0052

Table 1: **StrongREJECT scores across LLMs and datasets.** Scores indicate relevance of nonrefusal answers to harmful requests. More intense colors indicate higher scores; underlined values are the highest in that column.

Renato Lui Geh, Zilei Shao, Guy Van den Broeck. Adversarial Tokenization, ACL 2025

Case Study: Evading Safety Models

Bypass the existing defense layers against malicious requests that reliably distinguish (un)safe prompts

	LlamaGuard			ShieldGemma		
	AdvBench	Malicious	Masterkey	AdvBench	Malicious	Masterkey
Canonical	3.27%	9.00%	33.33%	53.27%	79.00%	80.00%
GCG	3.65%	3.00%	0.00%	57.61%	71.00%	77.78%
AutoDAN	11.35%	12.00%	20.00%	51.35%	65.00%	77.78%
FFA	0.19%	0.00%	0.00%	49.04%	75.00%	80.00%
AdvTok	16.15%	16.00%	55.56%	63.27%	86.00%	86.67%
AdvTok + GCG	4.23%	7.00%	11.11%	69.94%	85.00%	86.67%
AdvTok + AutoDAN	24.81%	20.00%	31.11%	61.35%	76.00%	84.44%
AdvTok + FFA	0.96%	0.00%	6.67%	56.92%	84.00%	86.67%

↑5-10%

Table 2: **Bypass Rate (%) across safety models and datasets.** Percentages show the proportion of undetected harmful requests by the safety model. More intense colors indicate higher values and an underline indicates highest.

Case Study: Prompt Injection

A malicious agent intercepts the conversation by altering the user input to provoke a malicious response



Figure 6: **Prompt injection success rates (%).** Lighter shaded areas (e.g.) show success rates for AdvTok while darker shaded areas (e.g.) show rates for the canonical baseline. Attacks are sorted by AdvTok success rates. Top: mean and standard deviation of prompt injection success rates. Underlined values show higher mean accuracy.

But wait a minute…



How come LLMs recognize **noncanonicals** at the **semantic level**…

…but do not recognize them at the **alignment level**?



Pre-training vs Post-training

- Huge datasets
- Typos, multilingual, weird spacing give prob. mass to noncanonical tokens

- Smaller datasets
- Curated RLHF regime with fewer typos
- Usually monolingual

Should **post-training** incorporate elements from **pre-training**?

Main Takeaways

Non-canonical tokenizations…

✔ … retain semantic understanding
✔ … break alignment
✔ … should be incorporated in post-training?

Adversarial tokenization…

✔ … is very easy to implement
✔ … easily elicit bad behavior from LLMs

Probabilistic reasoning is hard

✘ Computing the conditional most likely tokenization (exactly) is **hard**

Adversarial Tokenization

Renato Geh*, Zilei Shao*, Guy Van den Broeck

University of California, Los Angeles

UCLA

ST★R AI RESEARCH LAB UCLA

Circuit Compilation for a String



Figure 2: **Multi-valued decision diagram for the tokenization of `Bird`**. The square is a terminal node.

Algorithm 1 COMPILE

Input String $\boldsymbol{x}$, vocabulary $\mathcal{V}$, last token v
Output MDD of all tokenizations of $\boldsymbol{x}$

```
Initialize memoization M : ℕ × V → MDD
if x is empty then return nothing
Initialize node N
for each token t ∈ V do
    if x starts with t then
        if (|x|, t) ∈ M then C ← M(|x|, t)
        else C ← COMPILE(x_{|t|+1:|x|}, V, t)
        Add edge from N to C labelled with t
        Memoize M(|x|, t) ← C
return N
```

Circuit Compilation for a String across Distances

Algorithm 1 Compilation

Input string $\boldsymbol{x}$, upper bound k, reference $\boldsymbol{v}$
Output MRMDD $\mathcal{M}_{0..k}$

1 Compile MDD $\mathcal{M}$ from $\boldsymbol{x}$
2 Create $k+1$ copies $\mathcal{M}_0, \mathcal{M}_1, \ldots, \mathcal{M}_k$
3 **for** each edge $e = (i, j) \in \mathcal{M}$ **do**
4 **if** $e \models \boldsymbol{v}$ **then**
5 Mark edges $\left(\mathcal{M}_l^{(i)}, \mathcal{M}_l^{(j)}\right), \forall l \in [0..k]$
6 **else**
7 Add edges $\left(\mathcal{M}_l^{(i)}, \mathcal{M}_{l-1}^{(j)}\right), \forall l \in [1..k]$
8 Prune all paths that are unmarked or do not end at a terminal node in $\mathcal{M}_0$
9 **return** $\mathcal{M}_{0..k} := (\mathcal{M}_0, \mathcal{M}_1, \ldots, \mathcal{M}_k)$



Figure 3: **A multi-rooted MDD for the string ␣cat.** **Blue** edges indicate tokens consistent with the reference (Line 5), while **orange** edges denote deviations (Line 7), resulting in a cost to the budget. **Grayed** out edges denote pruned edges (Line 8).

Hardness Reduction

Define string $\overbrace{\underbrace{\mathsf{abcabcabc}\ldots\mathsf{abc}}_{3n}}^{\boldsymbol{v}}\overbrace{\underbrace{\mathsf{ddd}\ldots\mathsf{ddd}}_{k}}^{\boldsymbol{r}}$ $\mathcal{V} = \{\mathsf{a}, \mathsf{ab}, \mathsf{bc}, \mathsf{c}, \mathsf{d}\}$

Given a 3-CNF $\psi = \bigwedge_{i=1}^{k} S_i(\boldsymbol{v})$ $S_i(\boldsymbol{v}) = l_{i,1}(a_{I_{i,1}}) \vee l_{i,2}(a_{I_{i,2}}) \vee l_{i,3}(a_{I_{i,3}})$

$a_i := [\![v_{2i-1} = \mathsf{a}]\!]$

Bijection: $a_i := [\![v_{2i-1} = \mathsf{a}]\!]$ and tokenizations $\{(\mathrm{ab}, \mathrm{c}), (\mathrm{a}, \mathrm{bc})\}$

$$\arg\max_{v \in \mathcal{T}_{\mathcal{V}}(x)} p_{\mathrm{LLM}}(r|v, x) > 0.5(0.45)^n(0.9)^n(0.8)^k \iff \mathrm{SAT}(\psi)$$

$$\arg\max_{v \in \mathcal{T}_{\mathcal{V}}(x)} p_{\mathrm{LLM}}(v, x) > 0.5(0.45)^n(0.9)^n(0.8)^k \iff \mathrm{SAT}(\psi)$$

$$\sum_{v \in \mathcal{T}_{\mathcal{V}}(x)} p_{\mathrm{LLM}}(v, x) \iff \#\mathrm{SAT}(\psi)$$