

```

import tensorflow as tf
import glob
import imageio
import matplotlib.pyplot as plt
import numpy as np
import os
import PIL
from tensorflow.keras import layers
import time

from IPython import display
(train_images, train_labels), (_, _) =
tf.keras.datasets.mnist.load_data()

Downloading data from https://storage.googleapis.com/tensorflow/tf-
keras-datasets/mnist.npz
11490434/11490434 [=====] - 0s 0us/step

train_images = train_images.reshape(train_images.shape[0], 28, 28,
1).astype('float32')
train_images = (train_images - 127.5) / 127.5 # Normalize the images
to [-1, 1]
BUFFER_SIZE = 60000
BATCH_SIZE = 256
# Batch and shuffle the data
train_dataset =
tf.data.Dataset.from_tensor_slices(train_images).shuffle(BUFFER_SIZE).
batch(BATCH_SIZE)

def make_generator_model():
    model = tf.keras.Sequential()
    model.add(layers.Dense(7*7*256, use_bias=False,
input_shape=(100,)))
    model.add(layers.BatchNormalization())
    model.add(layers.LeakyReLU())

    model.add(layers.Reshape((7, 7, 256)))
    assert model.output_shape == (None, 7, 7, 256) # Note: None is
the batch size

    model.add(layers.Conv2DTranspose(128, (5, 5), strides=(1, 1),
padding='same', use_bias=False))
    assert model.output_shape == (None, 7, 7, 128)
    model.add(layers.BatchNormalization())
    model.add(layers.LeakyReLU())

    model.add(layers.Conv2DTranspose(64, (5, 5), strides=(2, 2),
padding='same', use_bias=False))
    assert model.output_shape == (None, 14, 14, 64)
    model.add(layers.BatchNormalization())

```

```

model.add(layers.LeakyReLU())

model.add(layers.Conv2DTranspose(1, (5, 5), strides=(2, 2),
padding='same', use_bias=False, activation='tanh'))
assert model.output_shape == (None, 28, 28, 1)


return model

generator = make_generator_model()

noise = tf.random.normal([1, 100])
generated_image = generator(noise, training=False)

plt.imshow(generated_image[0, :, :, 0], cmap='gray')
<matplotlib.image.AxesImage at 0x7a9902561810>

```



```

def make_discriminator_model():
    model = tf.keras.Sequential()
    model.add(layers.Conv2D(64, (5, 5), strides=(2, 2),
padding='same',
input_shape=[28, 28, 1]))
    model.add(layers.LeakyReLU())
    model.add(layers.Dropout(0.3))

```

```

        model.add(layers.Conv2D(128, (5, 5), strides=(2, 2),
padding='same'))
        model.add(layers.LeakyReLU())
        model.add(layers.Dropout(0.3))

        model.add(layers.Flatten())
        model.add(layers.Dense(1))

    return model
discriminator = make_discriminator_model()
decision = discriminator(generated_image)
print (decision)

tf.Tensor([[ -0.00164985]], shape=(1, 1), dtype=float32)

cross_entropy = tf.keras.losses.BinaryCrossentropy(from_logits=True)
def discriminator_loss(real_output, fake_output):
    real_loss = cross_entropy(tf.ones_like(real_output), real_output)
    fake_loss = cross_entropy(tf.zeros_like(fake_output), fake_output)
    total_loss = real_loss + fake_loss
    return total_loss
def generator_loss(fake_output):
    return cross_entropy(tf.ones_like(fake_output), fake_output)

generator_optimizer = tf.keras.optimizers.Adam(1e-4)
discriminator_optimizer = tf.keras.optimizers.Adam(1e-4)

checkpoint_dir = './training_checkpoints'
checkpoint_prefix = os.path.join(checkpoint_dir, "ckpt")
checkpoint =
tf.train.Checkpoint(generator_optimizer=generator_optimizer,

discriminator_optimizer=discriminator_optimizer,
                        generator=generator,
                        discriminator=discriminator)

EPOCHS = 50
noise_dim = 100
num_examples_to_generate = 16
seed = tf.random.normal([num_examples_to_generate, noise_dim])

@tf.function
def train_step(images):
    noise = tf.random.normal([BATCH_SIZE, noise_dim])

    with tf.GradientTape() as gen_tape, tf.GradientTape() as
disc_tape:
        generated_images = generator(noise, training=True)

        real_output = discriminator(images, training=True)
        fake_output = discriminator(generated_images, training=True)

```

```

    gen_loss = generator_loss(fake_output)
    disc_loss = discriminator_loss(real_output, fake_output)

    gradients_of_generator = gen_tape.gradient(gen_loss,
generator.trainable_variables)
    gradients_of_discriminator = disc_tape.gradient(disc_loss,
discriminator.trainable_variables)

    generator_optimizer.apply_gradients(zip(gradients_of_generator,
generator.trainable_variables))

discriminator_optimizer.apply_gradients(zip(gradients_of_discriminator
, discriminator.trainable_variables))

def train(dataset, epochs):
    for epoch in range(epochs):
        start = time.time()

        for image_batch in dataset:
            train_step(image_batch)

        # Produce images for the GIF as you go
        display.clear_output(wait=True)
        generate_and_save_images(generator,
                                epoch + 1,
                                seed)

        # Save the model every 15 epochs
        if (epoch + 1) % 15 == 0:
            checkpoint.save(file_prefix = checkpoint_prefix)

        print ('Time for epoch {} is {} sec'.format(epoch + 1,
time.time()-start))

        # Generate after the final epoch
        display.clear_output(wait=True)
        generate_and_save_images(generator,
                                epochs,
                                seed)

def generate_and_save_images(model, epoch, test_input):
    # Notice `training` is set to False.
    # This is so all layers run in inference mode (batchnorm).
    predictions = model(test_input, training=False)

    fig = plt.figure(figsize=(4, 4))

    for i in range(predictions.shape[0]):
        plt.subplot(4, 4, i+1)
        plt.imshow(predictions[i, :, :, 0] * 127.5 + 127.5, cmap='gray')

```

```
plt.axis('off')  
  
plt.savefig('image_at_epoch_{:04d}.png'.format(epoch))  
plt.show()  
  
train(train_dataset, EPOCHS)
```

