

# Introduction to Computing

String operations, Preprocessors

# Recap

- Pointers
    - Value
    - Name
    - Address
    - Size and type of pointers
  - Array and pointers
  - Function and pointers
- Functions calling functions
  - Recursion
  - Passing Array to functions
    - Problems with sending size
  - Character Array
  - Strings

# Character Arrays and Strings

- Character arrays are very useful in storing data
  - Even though they are basically integers underlying, but the range of the values are limited
  - This allows to have some additional functionalities (for convenience, of course)
  - Strings are declared and defined the same way as any other array types
  - Since the values are in range of 0-127 (sometimes more, but still, limited), we have the convenience make some of the characters for special use such as:
    - newline(\n)
    - backspace (\b), etc.
  - In the case of character arrays we use a special character called the null character
    - Represented as '\0' (backslash-zero)
    - Ascii value of this character is 0
    - It prints nothing on the computer screen

# Character array and strings

- Character variable

- `char ch1, ch2 = 'a';`

- Character array

- `char ca1[10];`

- `char ca2[3] = {'S','D','B'};`

- `char ca3[5] = {'S','D','B'};`

A string is a character array for which the last valid character is the null character.

- `char ca4[10] = {'S','o','u','m','a','d','i','p','\0'};`

- `char ca5[10] = "Soumadip";`

- *Both the above statements are equivalent*

- This type of initialization makes sure that the null character is automatically appended at the end

You *can't do the following after declaration* though

`ca1 = "word1";` // **not allowed** – why?

`ca4 = "word2";` // **not allowed** – what is the type of `ca1` or `ca4`?

-- More on what can and can't be done, later

String is basically short for “a string of characters”

- A **single character** in C is written **within single quotes** e.g. `'a'`, `'3'`, `'Z'`, `'%'`, etc.
- A **string** is written in C **within double quotes**, e.g., `"a_string"`, `"with spaces"`, `"and with $"`, etc.

# Strings and scanf

- scanf also provides a shortcut for strings format **%s**
  - `scanf ("%s", ch_arr);` ⇒ this allows you to read a string from user **without spaces**
  - `scanf ("%[^\\n]*c", ch_arr);`
    - This is equivalent to **%s**; reads the characters until space ( ) or the newline character (\\n) is encountered

- `scanf ("%[^\\n]*c", ch_arr);`
  - reads a string with spaces until a newline (\\n); so, it can read strings **with spaces**

**Note:** *All the method discussed here will add a '\\0' to the end of the scanned characters - making it a string*

# String Operations

- Normal assignments **do not work** on strings (or any arrays for that matter)
  - You can define different operation on strings by writing your own functions
    - Compare two strings for equality
    - Copy one string to another
    - Concatenate two strings
    - Check if a input string is integer or float
- Alternatively, you can choose to #include a new header file called **string.h** and use built-in functions for such operations
    - strlen
      - `int strlen(const char *str)`
    - strcmp
      - `int strcmp(const char *str1, const char *str2, int n)`
    - strstr
      - `char* strstr(const char *haystack, const char *needle)`
    - strcat
      - `char* strcat(char *dest, const char *src)`
    - Check the [link](#) for more.

# Preprocessors

- Preprocessor is not a part of the compiler
- It is a step in the compilation process
- a C Preprocessor is just a text substitution tool
- It instructs the compiler to do required pre-processing before the actual compilation
- They are also known as **macro**

## Examples:

- `#include <string.h>`
- `#define SIZE 10`
- `#define SQUARE(x) ((x)*(x))`
- `#ifdef <macro>.. #endif`
- etc.