

Tutorial No. 08

Title: Introduction to React JS.

Batch: B1

Roll No.:16010420133

Tutorial No:8

Aim: To implement methods, functions to manipulate DOM element using React JS

Resources needed: Notepad++, Web Browser

__ Theory:

React JS

React is a declarative, efficient, and flexible JavaScript library for building user interfaces. It lets you compose complex UIs from small and isolated pieces of code called components”.

We use components to tell React what we want to see on the screen. When our data changes, React will efficiently update and re-render our components.

React does not manipulate the browser's DOM directly. Instead, React creates a virtual DOM in memory, where it does all the necessary manipulating, before making the changes in the browser DOM.

We will start with React .Component example

```
class ShoppingList extends React.Component {  
  render() {  
    return (  
      <div className="shopping-list">  
        <h1>Shopping List for {this.props.name}</h1>  
        <ul>  
          <li>Instagram</li>  
          <li>WhatsApp</li>  
          <li>Oculus</li>  
        </ul>  
      </div>  
    )  
  }  
}
```

```

    );
  }
}

```

Here, `ShoppingList` is a React component class, or React component type. A component takes in parameters, called props (short for “properties”), and returns a hierarchy of views to display via the render method.

The render method returns a description of what you want to see on the screen. React takes the description and displays the result. In particular, render returns a React element, which is a lightweight description of what to render.

Most React developers use a special syntax called “JSX” which makes these structures easier to write.

The `<div />` syntax is transformed at build time to `React.createElement('div')`.

The example above is equivalent to: `return`
`React.createElement('div', {className: 'shopping-list'},`
`React.createElement('h1', /* ... h1 children ... */),`
`React.createElement('ul', /* ... ul children ... */)`
`);`

The `createElement` is an inbuilt method. There are lots of methods and functions included in the `reactjs` API. see the details on reactjs.org API Reference.

JSX comes with the full power of JavaScript. You can put any JavaScript expressions within braces inside JSX. Each React element is a JavaScript object that you can store in a variable or pass around in your program.

Hello World Example

```

<!DOCTYPE html>
<html>
  <script src="https://unpkg.com/react@16/umd/react.production.min.js"></script>
  <script src="https://unpkg.com/react-dom@16/umd/react-dom.production.min.js"></script>
  <script src="https://unpkg.com/babel-standalone@6.15.0/babel.min.js"></script>
  <body>

    <div id="mydiv"></div>

    <script type="text/babel"> class Hello
      extends React.Component {
        render() {
          return <h1>Hello World!</h1>
        }
      }

```

```

    ReactDOM.render(<Hello    />,    document.getElementById('mydiv'))
  </script>
</body>
</html>

```

Setting up a React Environment

First of all you need to download NodeJs for your operating system version.
<https://nodejs.org/en/download/>


npm(node packet manager once you download NodeJs

Then follow the following commands:

- 1) **run the command** “C:\Users\Your Name>npm install -g create-react-app”
- 2) **run the command to create an application name helloworld**
 “C:\Users\Your Name>npx create-react-app Helloworld”
- 3) **run this command to get to the current directory** “C:\Users\Your Name>cd helloworld”
- 4) **run this command to start the react application**
 “C:\Users\Your

Name\helloworld >npm start”

A new browser window will pop up with your newly created React App! If not, open your browser and type localhost:3000 in the address bar.



Modify the React Application

Look in the helloworld directory, and you will find a src folder. Inside the src folder there is a file called App.js, open it and make changes to any HTML part.

You will be able to see the change on the newly opened browser **App.js**


File

```
import React, { Component } from
'react'; import logo from './logo.svg';
import './App.css';

class App extends Component {
  render() {
    return (
      <div className="App">
        <header className="App-header">
          <img src={logo} className="App-logo" alt="logo" />
          <p>
            Edit <code>src/App.js</code> and save to reload.
          </p>
        <p> Hi </p>
        <a    className="App-
          link"
          href="https://reactjs.org"
          target="_blank"
          rel="noopener noreferrer"
        >
          Learn React
        </a>
      </header>
    </div>
  );
}
} export default App; in the file “Hi” is
```

added inside paragraph tag. The result

browser screen is as follows



Activity: • Use React JS to change any of the HTML content.

Results: (Program printout with output)

```
import logo from './logo.svg';
import './App.css';

function App() {
  return (
    <div className="App">
      <header className="App-header">
        <img src={logo} className="App-logo" alt="logo" />
        <p>
          Hello World!!
        </p>
        <p>
          Soumen samanta 16010420133
        </p>
        <a
          className="App-link"
          href="https://reactjs.org"
```

```
        target="_blank"
        rel="noopener noreferrer"
      >
        Learn React
      </a>
    </header>
  </div>
);
}

export default App;
```



Hello World!!

Soumen samanta 16010420133

[Learn React](#)

Outcomes: CO 4 Implement web application using React JS, Json and CBOR

Conclusion: (Conclusion to be based on the outcomes achieved)

Successfully implemented Hello World in React Js

Grade: AA / AB / BB / BC / CC / CD /DD

Signature of faculty in-charge with date

__ References:

Books/ Journals/ Websites:

□ <http://www.w3schools.com>

□ https://www.tutorialspoint.com/angularjs/angularjs_tutorial.pdf

□ <https://angularjs.org>
