



Experiment No. 5

Title: To study optimization of String Searching problem using KMP algorithm



Batch: B1

Roll No: 16010420133

Experiment No.:5

Aim: To study optimization of string searching problem using KMP Algorithm

Resources needed: Text Editor, C/C++ IDE

Theory:

Pattern searching is an important problem in computer science. When we do search for a string in notepad/word file or browser or database, pattern searching algorithms are used to show the search results.

The naive method doesn't work well in cases where we see many matching characters followed by a mismatching character.

Consider following example, text

= "aaaaaab"

pattern = "aab"

Here if there are 'n' letters in text and 'm' letters in pattern then the time complexity of Naive method/Brute Force method is $O(m(n-m+1))$ where n is very large as compared to m. Hence the time complexity can be considered as $O(nm)$.

This is the drawback of Naive Method. So to overcome this problem the KMP method was introduced.

KMP Algorithm is one of the most popular patterns matching algorithms. KMP stands for Knuth Morris Pratt. KMP algorithm was invented by Donald Knuth and Vaughan Pratt together and independently by James H Morris in the year 1970. In the year 1977, all the three jointly published KMP Algorithm.

KMP algorithm was the first linear time complexity algorithm for string matching. KMP algorithm is one of the string matching algorithms used to find a "Pattern" in a "Text".

LPS Table (Longest proper Prefix which is also Suffix)

This algorithm compares character by character from left to right. But whenever a mismatch occurs, it uses a preprocessed table called "Prefix Table" to skip characters comparison while matching. Sometimes prefix table is also known as LPS Table. Here LPS stands for "Longest proper Prefix which is also Suffix". **Steps for creating LPS Table**

Step 1 - Define a one dimensional array with the size equal to the length of the Pattern. (LPS[size])

Step 2 - Define variables i and j. Set i = 0, j = 1 and LPS[0] = 0

Step 3 - Compare the characters at Pattern[i] and Pattern[j].

Step 4 - If both are matched, then

LPS[j] = i+1



i = i+1

j = j+1 and Goto to Step 3

Step 5 - If both are not matched then check the value of variable 'i'.

Case a) If it is '0' then set LPS[j] = 0 and increment 'j' value by one

Case b) If it is not '0' then set i = LPS[i-1]. Goto Step 3



Step 6- Repeat above steps until all the values of LPS[] are filled

Using LPS Table for searching Pattern in Text

We use the LPS table to decide how many characters are to be skipped for comparison when a mismatch has occurred. When a mismatch occurs, check the LPS value of the previous character of the mismatched character in the pattern. If it is '0' then start comparing the first character of the pattern with the next character to the mismatched character in the text. If it is not '0' then start comparing the character which is at an index value equal to the LPS value of the previous character to the mismatched character in pattern with the mismatched character in the Text.

Steps for searching Pattern in Text using LPS table

Step 1 – Initialize i and j pointers as $i = 0$ and $j = 0$. I pointer is used to iterate over characters 'n' in "Text" and j pointer is used to iterate over characters 'm' in "Pattern"

Step 2- Compare Text[i] and Pattern [j]

Step 3- If matched, then $i = i+1$, $j=j+1$ and Goto Step 2

Step 4 – If not matched, then check value of j

Case a) If $j \neq 0$, then $j = \text{lps}[j-1]$

Case b) If $j=0$, then $i=i+1$

Goto step 2

Step 4 – If $j = m$, then pattern found at (i-j), $j = \text{lps}[j-1]$ and goto Step 2

Step 5 – Repeat above steps until $i < n-m+1$

Activity:

Given 2 strings, P and T, find the number of occurrences of P in T.

Input format

First line contains string P, and second line contains the string T.

Output format

Print a single integer, the number of occurrences of P in T.

Constraints

$$1 \leq |P| \leq |T| \leq 10^5$$

Sample Input

sda sadasda

Sample Output

1

Program:

```

class
Main
{
    // Function to implement the KMP algorithm
    public static void KMP(String text, String pattern)
    {
        // base case 1: pattern is null or empty
        if (pattern == null || pattern.length() == 0)
        {
            System.out.println("The pattern occurs with shift 0");
            return;
        }

        // base case 2: text is NULL, or text's length is less than that of pattern's
        if (text == null || pattern.length() > text.length())
        {
            System.out.println("Pattern not found");
            return;
        }

        char[] chars = pattern.toCharArray();

        // next[i] stores the index of the next best partial match
        int[] next = new int[pattern.length() + 1];    for (int i = 1;
        i < pattern.length(); i++)
        {
            int j = next[i - 1];

            while (j > 0 && chars[j] != chars[i]) {
                j = next[j];
            }

            if (j > 0 || chars[j] == chars[i]) {
                next[i] = j + 1;
            }
        }

        for (int i = 0, j = 0; i < text.length(); i++)
        {
            if (j < pattern.length() && text.charAt(i) == pattern.charAt(j))
            {

```

```

        if (++j == pattern.length()) {
            System.out.println("The pattern occurs with shift " + (i - j + 1));
        }
    }
    else if (j > 0)
    {
        j
= next[j];
        i--; // since `i` will be incremented in the next iteration
    }
}
}
}

```

```

// Program to implement the KMP algorithm in Java
public static void main(String[] args)
{
    String text = "sadasda";
    String pattern = "sda";

    KMP(text, pattern);
}
}

```

Output:

```

sda
sadasda
1

```

Test Result:**RESULT: Sample Test Cases Passed** ?[? Refer judge environment](#)

Note: When you **Compile**, the code is run against sample inputs. When you **Submit code**, the code is run against sample input as well as multiple hidden test cases. In order to solve the problem, your code must pass all of the test cases.

Time (sec)	Memory (KiB)	Language
0.067335	3137132	Java

Input

```

sda
sadasda

```

Output

```

1

```

Expected Correct Output

```

1

```

Outcomes:

Learn effective computation and programming practices for numeric and string operations and computation geometry.

Conclusion: (Conclusion to be based on the objectives and outcomes achieved) Successfully studied and implemented optimization of string searching problem using KMP Algorithm.

References:

1. <https://www.hackerearth.com/practice/algorithms/string-algorithm/string-searching/tutorial/>
2. T.H. Cormen, C.E. Leiserson, R.L. Rivest, and C. Stein, " Introduction to algorithms", 3rd Edition 2009, Prentice Hall India Publication
3. Antti Laaksonen, "Guide to Competitive Programming", Springer, 2018
4. Gayle Laakmann McDowell, "Cracking the Coding Interview", CareerCup LLC, 2015
5. Steven S. Skiena Miguel A. Revilla, "Programming challenges, The Programming Contest Training Manual", Springer, 2006
6. Antti Laaksonen, "Competitive Programmer's Handbook", Hand book, 2018
7. Steven Halim and Felix Halim, "Competitive Programming 3: The Lower Bounds of Programming Contests", Handbook for ACM ICPC