Module 2: Collections, Loops, and Functions

PUBHLT 0411 · Python for Public Health Data Analysis

Soumik Purkayastha
Dept. of Biostatistics and Health Data Science, University of Pittsburgh

October 15, 2026

Forty-nine months.

We will examine 49 months of COVID-19 death data across all 67 counties in Pennsylvania.

Pennsylvania recorded COVID-19 deaths across 49 months and 67 counties

That is $49 \times 67 = 3,283$ county-months of data.


The question this session opens


Identifying the deadliest month requires examining every month and retaining the largest. Performed by hand, this is 49 comparisons for the state and 3,283 for the counties.

This session establishes the machinery that performs the comparison. A collection to hold the values, a loop to walk them, and a function to package the work for reuse.

Required from Module 1: `if` / `elif` / `else`, indentation, lists, `.append()`, `+=`.

Two views of the same 3,283 county-months





Source: PA DOH, monthly COVID-19 deaths by county

A dictionary maps keys to values

A list is indexed by position. A dictionary is indexed by a **key** chosen by the author.

Python Code | Start Over | Run Code

```
covid_deaths = {
    "2021-08": 555,
    "2021-09": 1248,
    "2021-10": 2035,
    "2021-11": 2117,
    "2021-12": 3365,
    "2022-01": 4294,
    "2022-02": 1819,
}

print(covid_deaths["2021-12"])
print(len(covid_deaths))
```

Each entry is a `key: value` pair. **Keys are unique**; assigning to an existing key replaces its value.

R analogue

A named list, or a two-column lookup table.

A missing key raises `KeyError`

Python Code | Start Over | Run Code

```
1 covid_deaths = {"2021-12": 3365, "2022-01": 4294}
2
3 try:
4     print(covid_deaths["2022-06"])
5 except KeyError as e:
6     print(f"{type(e).__name__}: {e}")
```

⚠ **`KeyError` — the key is not present**

```
KeyError: '2022-06'
```

Subscripting a dictionary with an absent key raises immediately rather than returning an empty value. The exception names the offending key.

Resolution: `.get(key, default)` returns the default instead of raising — `covid_deaths.get("2022-06", 0)` evaluates to `0`.

Python Code | Start Over | Run Code

```
1 covid_deaths = {"2021-12": 3365, "2022-01": 4294}
2
3 print(covid_deaths.get("2022-06", 0))
4 print(covid_deaths.get("2021-12", 0))
```

`for` walks every element of a collection

Python Code | Start Over | Run Code

```
covid_deaths = {
    "2021-11": 2117,
    "2021-12": 3365,
    "2022-01": 4294,
}

for month in covid_deaths:
    print(month, covid_deaths[month])
```

Iterating a dictionary yields its **keys**. The colon and the indented block follow the same rule as `if`.

Python Code | Start Over | Run Code

```
covid_deaths = {
    "2021-11": 2117,
    "2021-12": 3365,
    "2022-01": 4294,
}

for month, deaths in covid_deaths.items():
    print(f"{month}: {deaths} deaths")
```

`.items()` yields both parts at once, which is the idiomatic form.

Three views of a dictionary

`.keys()` yields the labels, `.values()` yields the quantities, `.items()` yields both.

`range()` generates a sequence of integers

Python Code Start Over Run Code

```
1 for i in range(5):
2     print(i)
```

Python Code Start Over Run Code

```
1 for year in range(2020, 2024):
2     print(year)
```

1. `range(n)` yields `0` through `n - 1` — **n values, starting at zero**
2. `range(a, b)` yields `a` through `b - 1` — the stop is excluded, as in slicing

> ⚠ **`range()` excludes its endpoint**
>
> `range(2020, 2024)` yields 2020, 2021, 2022, and 2023. Reaching 2024 requires `range(2020, 2025)`.

The accumulator pattern builds a result across iterations

Initialize a variable **before** the loop; update it **inside**.

Python Code | Start Over | Run Code

```python
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035, "2021-11": 2117,
    "2021-12": 3365, "2022-01": 4294, "2022-02": 1819,
}

total_deaths = 0

for month, deaths in covid_deaths.items():
    total_deaths += deaths

print(f"Total across {len(covid_deaths)} months: {total_deaths}")
print(f"Monthly average: {total_deaths / len(covid_deaths):.1f}")
```

Initialization belongs outside the loop

A counter initialized inside the loop resets on every iteration and finishes holding only the final value.

The maximum requires remembering the best so far

Python Code | Start Over | Run Code

```python
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035, "2021-11": 2117,
    "2021-12": 3365, "2022-01": 4294, "2022-02": 1819,
}

worst_month = ""
worst_deaths = 0

for month, deaths in covid_deaths.items():
    if deaths > worst_deaths:
        worst_deaths = deaths
        worst_month = month

print(f"Worst month: {worst_month} with {worst_deaths} deaths")
```

The loop retains a candidate and replaces it whenever a larger value appears. **This is the same procedure a person performs by hand, stated precisely.**

Checkpoint: the comparison is inside the wrong block

Objective: count the months exceeding 2,000 deaths.

Python Code | Start Over | Run Code

```
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035, "2021-11": 2117,
    "2021-12": 3365, "2022-01": 4294, "2022-02": 1819,
}

high_months = 0

for month, deaths in covid_deaths.items():
    if deaths > 2000:
        high_months += 1
        print(f"{month}: {deaths}")
        print(f"Running count: {high_months}")

print(f"Months above 2000: {high_months}")
```

⚠ **Indentation determines what runs when**

The final `print()` is outside the loop and reports the total once, correctly. The running count is inside the `if` and prints on every match.

Moving the final line inside the loop would report a partial count as though it were the answer — with no error raised.

`while` repeats until a condition fails

A `for` loop runs a known number of times. A `while` loop runs until something changes.

Python Code | Start Over | Run Code

```
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035, "2021-11": 2117,
    "2021-12": 3365, "2022-01": 4294, "2022-02": 1819,
}

months = list(covid_deaths.keys())
cumulative = 0
position = 0

while cumulative <= 10000:
    month = months[position]
    cumulative += covid_deaths[month]
    position += 1

print(f"Cumulative deaths passed 10,000 during {month}: {cumulative}")
```

⚠ A condition that never becomes false runs forever

Every `while` loop requires something inside it that moves the condition toward failure. Omitting `position += 1` produces a loop that never terminates.

`while True:` with `break` is an exit-controlled loop

Python Code | Start Over | Run Code

```python
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035,
    "2021-11": 2117, "2021-12": 3365, "2022-01": 4294,
}

months = list(covid_deaths.keys())
position = 0

while True:
    month = months[position]
    if covid_deaths[month] > 3000:
        print(f"First month above 3000: {month}")
        break
    position += 1
```

`break` exits the loop immediately. `continue` skips to the next iteration without leaving.

The loop that tests at the bottom

`while True:` with `break` runs the body first and decides afterward. This is Python's equivalent of a do-while loop, and it suits searches that stop at the first match.

Functions.

The same calculation, written once and reused — instead of copied and edited every time a new county arrives.

`def` packages a computation under a name

Python Code | Start Over | Run Code

```
1  def rate_per_100k(deaths, population):
2      """Return deaths per 100,000 people."""
3      return deaths / population * 100000
4
5
6  print(rate_per_100k(401, 143786))
7  print(rate_per_100k(208, 157795))
8  print(f"{rate_per_100k(4052, 1550542):.1f}")
```

1. `def` names the function; the parameters are named in parentheses
2. The **docstring** — a string on the first line — states what the function returns
3. `return` sends a value back to the caller

A function without `return` returns `None`

Printing a value inside a function displays it; it does not hand it back. Only `return` produces a value the caller can store or reuse.

A function may return more than one value

Python Code | Start Over | Run Code

```
def summarize_county(county, deaths, population):
    """Return the county's rate and a classification against the state rate."""
    rate = deaths / population * 100000
    if rate > 212.3:
        classification = "Above the state rate"
    else:
        classification = "At or below the state rate"
    return rate, classification


rate, label = summarize_county("Schuylkill", 401, 143786)

print(f"Schuylkill: {rate:.1f} per 100,000 — {label}")
```

Returning several values produces a **tuple**, and assigning to several names unpacks it.

A tuple is an immutable sequence

Python Code | Start Over | Run Code

```
1 county_record = ("Schuylkill", 401, 143786)
2
3 county, deaths, population = county_record
4
5 print(county, deaths, population)
6 print(county_record[0])
7 print(len(county_record))
```

Tuples index and slice exactly as lists do. **They cannot be modified after creation** — there is no `.append()`.

Tuples signal fixed structure

A list holds a variable number of similar things. A tuple holds a fixed number of related things — a record whose shape is known.

`sorted()` orders a collection, and `key=` chooses by what

Python Code | Start Over | Run Code

```
counties = [
    ("Philadelphia", 4052, 1550542),
    ("Allegheny", 2179, 1224825),
    ("Schuylkill", 401, 143786),
    ("Centre", 208, 157795),
    ("Fayette", 325, 123915),
]

by_deaths = sorted(counties, key=lambda record: record[1], reverse=True)

for county, deaths, population in by_deaths[:3]:
    print(f"{county}: {deaths} deaths")
```

`key=` receives a function returning the value to sort on. `lambda` writes that function inline.

Checkpoint: ranking by count answers a different question

Python Code | Start Over | Run Code

```python
counties = [
    ("Philadelphia", 4052, 1550542),
    ("Allegheny", 2179, 1224825),
    ("Schuylkill", 401, 143786),
    ("Centre", 208, 157795),
    ("Fayette", 325, 123915),
]

by_deaths = sorted(counties, key=lambda r: r[1], reverse=True)
by_rate = sorted(counties, key=lambda r: r[1] / r[2] * 100000, reverse=True)

print("Ranked by deaths:")
for county, deaths, population in by_deaths[:3]:
    print(f"   {county}: {deaths} deaths")

print("Ranked by rate:")
for county, deaths, population in by_rate[:3]:
    print(f"   {county}: {deaths / population * 100000:.1f} per 100,000")
```

Counts rank by population; rates rank by burden

The two orderings answer different questions. Ranking Pennsylvania's 67 counties by COVID death **count** returns the five largest counties. Ranking by **rate** returns five rural counties, and **the two lists share no members at all.**

A county appears at the top of a count ranking largely because many people live there.

Objects.

Why `.items()`, `.append()`, and `.strip()` all use a dot — one idea that explains every method met so far, and every one still to come.

Every value in Python is an object

An object carries **data** and the **operations** defined for it. The dot accesses both.

Python Code | Start Over | Run Code

```
1 county = "Schuylkill"
2 counties = ["Schuylkill", "Centre"]
3 covid_deaths = {"2022-01": 4294}
4
5 print(county.upper())
6 print(counties.count("Centre"))
7 print(covid_deaths.keys())
```

`"text".upper()`, `counties.append()`, and `covid_deaths.items()` are the same construction: **a value, a dot, and an operation that value supports.**

Methods belong to types

`.upper()` exists on strings and not on lists. Calling a method a type does not define raises `AttributeError`, which names both the type and the missing attribute.

A class defines a new kind of object

Python Code | Start Over | Run Code

```python
class County:
    """A Pennsylvania county with COVID-19 mortality data."""

    def __init__(self, name, deaths, population):
        self.name = name
        self.deaths = deaths
        self.population = population

    def rate_per_100k(self):
        """Return deaths per 100,000 residents."""
        return self.deaths / self.population * 100000


schuylkill = County("Schuylkill", 401, 143786)

print(schuylkill.name)
print(f"{schuylkill.rate_per_100k():.1f} per 100,000")
```

1. `__init__` runs when the object is created and stores its data
2. `self` refers to the object being operated on
3. An **attribute** holds data; a **method** performs an operation

Attributes and methods differ by the parentheses

`schuylkill.name` retrieves stored data. `schuylkill.rate_per_100k()` calls a function. Omitting the parentheses returns the function itself rather than its result.

The dot is the same idea everywhere

Python Code | Start Over | Run Code

```python
class County:
    def __init__(self, name, deaths, population):
        self.name = name
        self.deaths = deaths
        self.population = population

    def rate_per_100k(self):
        return self.deaths / self.population * 100000


counties = [
    County("Philadelphia", 4052, 1550542),
    County("Schuylkill", 401, 143786),
    County("Centre", 208, 157795),
]

for county in sorted(counties, key=lambda c: c.rate_per_100k(), reverse=True):
    print(f"{county.name}: {county.rate_per_100k():.1f} per 100,000")
```

What Module 4 introduces

`pandas` supplies an object holding an entire table. `df.head()` and `df.groupby()` use the construction on this slide — a value, a dot, an operation.

The worst month.

Putting the session together to answer the question it opened with - which month was the worst?

Exercise: find the deadliest month

Exercise | Start Over | Show Hint | Run Code

```
covid_deaths = {
    "2021-08": 555, "2021-09": 1248, "2021-10": 2035, "2021-11": 2117,
    "2021-12": 3365, "2022-01": 4294, "2022-02": 1819,
}

worst_month = ""
worst_deaths = 0

for month, deaths in covid_deaths._____():
    if deaths > worst_deaths:
        worst_deaths = deaths
        worst_month = month

print(f"Worst month: {worst_month} with {worst_deaths:,} deaths")
```

January 2022




Figure 1. Statewide COVID-19 deaths for each of the 49 months in the file. The series rises through late 2021 to a sharp peak of 4,294 deaths in January 2022, marked by a blue diamond, then falls away and stays low through 2023. Months before August 2021 are shaded and drawn as a dotted line because the file undercounts them — March 2020 reads zero.

4,294 Pennsylvanians died of COVID-19 in January 2022 — the deadliest month of the pandemic in this state.

Not March 2020. Not the first wave.

What the timing means

Session outcomes

1. Storing labelled data in a **dictionary**, and retrieving it with `[key]` and `.get()`
2. Iterating with `for`, over a collection and over `range()`
3. Walking key–value pairs with `.items()`
4. Building results with the **accumulator pattern**, initialized outside the loop
5. Repeating with `while`, and exiting with `while True:` plus `break`
6. Defining functions with `def`, `return`, and a docstring
7. Returning several values, and unpacking **tuples**
8. Ordering with `sorted(key=)`, and distinguishing **counts from rates**
9. Reading a small class: `__init__`, `self`, attributes, and methods

> **Preparation for the lab, Tuesday 10/20**
>
> The lab builds county-level dictionaries, writes functions returning several values, and ranks counties two ways.

Module 3 replaces these loops with arithmetic on whole arrays.

That’s all folks!

See you on Tuesday!