HDOC DAY – 75

1. Enumeration with explicit values starting from 10

Algorithm:

1. Start.
2. Define an enumeration Values.
3. Assign A = 10.
4. Since no values are assigned to B and C, they automatically become 11 and 12.
5. Print the values of A, B, and C.
6. Stop.

C PROGRAM:

```
#include <stdio.h>


enum Values
{
   A = 10,
   B,
   C
};


int main()
{
   printf("A=%d, B=%d, C=%d", A, B, C);
```

```
    return 0;
}
```

TEST CASE TABLE:

Test Case	Input	Expected Output
1	Nil	A=10, B=11, C=12

2. Enumeration for menu choices using switch

Algorithm:

1. Start.
2. Define an enumeration Operation containing ADD, SUBTRACT, and MULTIPLY.
3. Read the user's choice.
4. Read two numbers.
5. Use a switch statement:
    - If ADD, add the numbers.
    - If SUBTRACT, subtract the numbers.
    - If MULTIPLY, multiply the numbers.
6. Display the result.
7. Stop.

C PROGRAM:

```
#include <stdio.h>

enum Operation
{
```

```
    ADD = 1,
    SUBTRACT,
    MULTIPLY
};

int main()
{
    enum Operation choice;
    int a, b;

    printf("1. ADD\n");
    printf("2. SUBTRACT\n");
    printf("3. MULTIPLY\n");

    printf("Enter choice: ");
    scanf("%d", &choice);

    printf("Enter two numbers: ");
    scanf("%d %d", &a, &b);

    switch(choice)
    {
        case ADD:
            printf("%d", a + b);
            break;
```

```
        case SUBTRACT:
            printf("%d", a - b);
            break;

        case MULTIPLY:
            printf("%d", a * b);
            break;

        default:
            printf("Invalid choice");
    }

    return 0;
}
```

Test Case Table:

Test Case	Choice	Numbers	Expected Output
1	ADD (1)	10, 20	30
2	SUBTRACT (2)	20, 10	10
3	MULTIPLY (3)	10, 20	200