HDOC DAY – 74

Algorithm

1. Start.
2. Define an enumeration Month containing JAN to DEC.
3. Read the month from the user.
4. Compare the entered string with the month names.
5. Assign the corresponding enumeration value.
6. Use a switch statement:
    - JAN, MAR, MAY, JUL, AUG, OCT, DEC → print 31 days.
    - APR, JUN, SEP, NOV → print 30 days.
    - FEB → print 28 or 29 days.
7. If the month is invalid, print Invalid month.
8. Stop.

C PROGRAM:

```
#include <stdio.h>
#include <string.h>

enum Month
{
  JAN, FEB, MAR, APR, MAY, JUN,
  JUL, AUG, SEP, OCT, NOV, DEC
};

int main()
```

```
{
    char input[10];
    enum Month month;

    printf("Enter month: ");
    scanf("%s", input);

    if (strcmp(input, "JAN") == 0)
        month = JAN;
    else if (strcmp(input, "FEB") == 0)
        month = FEB;
    else if (strcmp(input, "MAR") == 0)
        month = MAR;
    else if (strcmp(input, "APR") == 0)
        month = APR;
    else if (strcmp(input, "MAY") == 0)
        month = MAY;
    else if (strcmp(input, "JUN") == 0)
        month = JUN;
    else if (strcmp(input, "JUL") == 0)
        month = JUL;
    else if (strcmp(input, "AUG") == 0)
        month = AUG;
    else if (strcmp(input, "SEP") == 0)
        month = SEP;
```

```
else if (strcmp(input, "OCT") == 0)
   month = OCT;
else if (strcmp(input, "NOV") == 0)
   month = NOV;
else if (strcmp(input, "DEC") == 0)
   month = DEC;
else
{
   printf("Invalid month");
   return 0;
}

switch (month)
{
   case JAN:
   case MAR:
   case MAY:
   case JUL:
   case AUG:
   case OCT:
   case DEC:
      printf("31 days");
      break;

   case APR:
```

```
        case JUN:
        case SEP:
        case NOV:
            printf("30 days");
            break;

        case FEB:
            printf("28 or 29 days");
            break;
    }

    return 0;
}
```

Test Case Table

Test Case	Input	Expected Output
1	FEB	28 or 29 days
2	JAN	31 days
3	APR	30 days
4	DEC	31 days
5	ABC	Invalid month