National Institute of Technology Karnataka, Surathkal

Department of Computer Science and Engineering

CS-253: Design and Analysis of Algorithms

Practical Assignment Report

Comparison and Analysis of Sorting Algorithms

Submitted by

Name: **Saurabh Kumar**
Roll No: 241CS151

Name: **Soumyadeep Raj**
Roll No: 241CS157

Due Date: 15 March 2026

Contents

1 Introduction **3**

2 Data Generation and Experimental Setup **3**
2.1 Machine Specification . . . 3
2.2 Timing Mechanism . . . 4
2.3 Repetitions and Reported Values . . . 5
2.4 Input Generation . . . 5

3 Comparison of QuickSort Pivot Strategies **5**
3.1 Best Case Running Time (Figure 2) . . . 6
3.1.1 Reading the graph . . . 6
3.1.2 Detailed analysis . . . 7
3.1.3 Key observations . . . 7
3.2 Worst Case Running Time (Figure 3) . . . 8
3.2.1 Reading the graph . . . 8
3.2.2 Detailed analysis . . . 8
3.2.3 Key observations . . . 9
3.3 Average Case Running Time (Figure 4) . . . 9
3.3.1 Reading the graph . . . 9
3.3.2 Detailed analysis . . . 10
3.3.3 Key observations . . . 10
3.4 Conclusion: Best Pivot Strategy . . . 10

4 Comparison of All Seven Sorting Algorithms **11**
4.1 Best Case Running Time (Figure 5) . . . 11
4.1.1 Reading the graph . . . 11
4.1.2 Detailed analysis . . . 11
4.1.3 Key observations . . . 12
4.2 Worst Case Running Time (Figure 6) . . . 13
4.2.1 Reading the graph . . . 13
4.2.2 Detailed analysis . . . 13
4.2.3 Key observations . . . 14
4.3 Average Case Running Time (Figure 7) . . . 15
4.3.1 Reading the graph . . . 15
4.3.2 Detailed analysis . . . 15
4.3.3 Key observations . . . 16

5 Correlation Between Number of Comparisons and Execution Time **17**

5.1 Time vs. n for Random Input (Figure 8) 17
5.1.1 Reading the graph 17
5.2 Comparisons vs. n (Figure 9) 18
5.2.1 Reading the graph 18
5.2.2 Detailed analysis 18
5.3 Time vs. Comparisons Scatter Plot (Figure 10) 19
5.4 Is Comparison Count a Reliable Predictor of Execution Time? 20
5.4.1 Summary 20

6 Theoretical Complexity vs. Experimental Results 21
6.1 Bubble Sort 21
6.2 Insertion Sort 21
6.3 Selection Sort 22
6.4 Merge Sort 22
6.5 Heap Sort 22
6.6 Quick Sort (All Three Pivot Variants) 23
6.7 Radix Sort 23
6.8 Overall Theory-vs-Experiment Summary 24

7 Summary and Conclusions 25

Introduction

This report presents a systematic experimental study of seven classical sorting algorithms: Selection Sort, Bubble Sort, Insertion Sort, Merge Sort, Quick Sort (three pivot variants), Heap Sort, and Radix Sort. The primary objective is to empirically validate theoretical time complexity predictions and to understand how algorithm choice, pivot strategy, and input characteristics affect real-world performance.

Experiments were conducted across nine input sizes ($n = 1000, 2000, \ldots, 8000, 10000$) and three distinct input types: random, sorted increasing (best case), and sorted decreasing (worst case). Every measurement reported is the mean of five independent runs to minimise the effect of system noise. All graphs in this report use a **logarithmic y-axis** (time in microseconds) so that curves spanning several orders of magnitude can be meaningfully compared on the same plot.

Data Generation and Experimental Setup

Machine Specification



Item	Value
OS Name	Microsoft Windows 11 Home Single Language
Version	10.0.26200 Build 26200
Other OS Description	Not Available
OS Manufacturer	Microsoft Corporation
System Name	DESKTOP-O5SNLNC
System Manufacturer	Dell Inc.
System Model	Dell G15 5530
System Type	x64-based PC
System SKU	0BF8
Processor	13th Gen Intel(R) Core(TM) i7-13650HX, 2600 Mhz, 14 Core(s), 20 Logical Pr...
BIOS Version/Date	Dell Inc. 1.31.0, 12/24/2025
SMBIOS Version	3.6
Embedded Controller Version	1.22
BIOS Mode	UEFI
BaseBoard Manufacturer	Dell Inc.
BaseBoard Product	0NVG9V
BaseBoard Version	A02
Platform Role	Mobile
Secure Boot State	On
PCR7 Configuration	Elevation Required to View
Windows Directory	C:\WINDOWS
System Directory	C:\WINDOWS\system32
Boot Device	\Device\HarddiskVolume1
Locale	United States
Hardware Abstraction Layer	Version = "10.0.26100.1"
User Name	DESKTOP-O5SNLNC\SOUMYADEEP

Figure 1: System Information screenshot of the machine used for all experiments (Dell G15 5530, Intel Core i7-13650HX, Windows 11 Home).

The key hardware and software details extracted from Figure 1 are summarised below:

Item	Value
System	Dell G15 5530 (x64-based PC)
OS	Microsoft Windows 11 Home Single Language (Build 26200)
Processor	13th Gen Intel Core i7-13650HX, 2600 MHz, 14 Cores, 20 Logical Processors
BIOS	Dell Inc. 1.31.0, 24 December 2025 (UEFI mode)

Table 1: Hardware and software environment for all experiments.

The processor's large L3 cache and high single-thread boost frequency favour algorithms with good cache locality such as in-place partitioning in QuickSort, and penalise those with scattered memory access patterns such as Merge Sort's auxiliary array allocation.

Timing Mechanism

All experiments are implemented in **C** (`main1.c`). Timing is done using `clock_gettime(CLOCK_MONOTONIC)` from `<time.h>`. The custom `getTime()` helper converts the raw `struct timespec` value into a **microsecond** floating-point timestamp:

```
double getTime() {
    struct timespec t;
    clock_gettime(CLOCK_MONOTONIC, &t);
    return t.tv_sec * 1e6 + t.tv_nsec / 1e3;
}
```

`CLOCK_MONOTONIC` is a monotonically increasing clock unaffected by system-time adjustments or NTP corrections, making it reliable for short-duration measurements. The timer wraps only the sorting call:

```
memcpy(arr, orig, n * sizeof(int));
comparisons = 0;
double s = getTime();
insertionSort(arr, n);
double e = getTime();
```

The `memcpy` that restores the original array before each run, the comparison counter reset, and the CSV `fprintf` write all occur *outside* the timed region, so only the pure sorting work is measured. The elapsed time $e - s$ (in microseconds) together with the `comparisons` count is written to a CSV file (`results_run`k`.csv`, $k = 1 \ldots 5$) for offline analysis.

Repetitions and Reported Values

The outer `for`-loop in `main()` executes **five complete independent passes**, each producing a separate CSV file (`results_run1.csv` through `results_run5.csv`). Within each pass, every (algorithm, n, input-type) triple is timed once. The **arithmetic mean** across all five runs is reported for each data point. Averaging over five runs suppresses transient spikes from OS scheduling, CPU thermal throttling, and memory allocation jitter.

The global variable `long long comparisons` is reset to zero before every individual sort call and incremented inside the sort functions at every element comparison. Its final value is recorded alongside the timing, enabling direct correlation analysis between comparison count and wall-clock time.

Input Generation

Three input types are generated programmatically in C for each $n \in \{1000, 2000, 3000, \ldots, 8000, 10000\}$:

- **Random** (`generateRandom`): Each element is set to `rand() % 100000`, i.e. a uniform random integer in $[0, 99999]$. The PRNG is seeded once with `srand(time(NULL))` at program start, so each of the five runs uses a different random sequence. This represents the **average case**.
- **Sorted Increasing** (`generateSorted`): `arr[i] = i + 1`, producing $\{1, 2, 3, \ldots, n\}$. This is the **best case** for Insertion Sort and Bubble Sort (single pass, zero swaps) but the **degenerate worst case** for Quick_First (pivot always the minimum).
- **Sorted Decreasing** (`generateReverse`): `arr[i] = n - i`, producing $\{n, n-1, \ldots, 1\}$. This is the **worst case** for Insertion Sort and Bubble Sort (maximum shifts/swaps) and also degenerate for Quick_First (pivot always the maximum).

A single `orig[]` array is filled once per (n, type) combination. Before each algorithm is timed, `memcpy` restores a fresh copy of `orig[]` into a working array `arr[]`, ensuring that all algorithms receive the identical input sequence at every (n, type) pair. Timing differences therefore reflect only algorithmic behaviour, not input variation.

Comparison of QuickSort Pivot Strategies

The three pivot strategies tested are:

- **Quick_First:** Always selects `A[lo]` as pivot.
- **Quick_Random:** Selects a uniformly random index in [lo, hi].

- **Quick_Median:** Selects the median of {`A[lo]`, `A[mid]`, `A[hi]`}.

The **best case** input used for all three variants is a **sorted increasing array**: for Quick_Random and Quick_Median this is a best case because random and median-of-three pivots still produce balanced partitions, achieving $O(n \log n)$; for Quick_First it is actually the *degenerate worst case* because the first element (always the minimum) produces maximally unbalanced partitions. The **worst case** input is a **sorted decreasing array**: for Quick_First, the first element is now always the maximum, again yielding $O(n^2)$ behaviour; for Quick_Median the decreasing order produces a sub-optimal but non-degenerate pivot; for Quick_Random the randomised pivot is unaffected by input order and remains $O(n \log n)$ in expectation.

Best Case Running Time (Figure 2)



Figure 2: Quick Sort — Best Case running time (μs, log scale) vs. input size n. Input: sorted increasing array. Each point is the mean of 5 runs.

Reading the graph

The y-axis spans roughly 10^1 to 10^5 μs, revealing a gap of nearly **two full orders of magnitude** between Quick_First and the other two strategies at every tested n. Three distinct bands are visible.

Detailed analysis

Quick_First starts at $\approx 500\,\mu$s for $n = 1000$ and rises steeply to $\approx 30{,}000\,\mu$s at $n = 10{,}000$. On a sorted-increasing array, `A[lo]` is always the global minimum of the remaining sub-array. Every partition produces a left sub-array of size 0 and a right sub-array of size $n - 1$, leading to n recursive calls each doing $O(n)$ work and a total of $O(n^2)$ operations. The log-scale curve is nearly linear (slope ≈ 2 on a log–log plot), which is the visual signature of quadratic growth.

Quick_Random starts at $\approx 50\,\mu$s ($n = 1000$) and grows to $\approx 300\,\mu$s ($n = 10{,}000$). A random pivot on a sorted array is equally likely to be any rank, so partitions are balanced in expectation, yielding $O(n \log n)$ expected time. The roughly $100\times$ speedup over Quick_First at $n = 10{,}000$ reflects the quadratic versus linearithmic growth rates.

Quick_Median is the *fastest* in the best case, starting at $\approx 30\,\mu$s and reaching only $\approx 160\,\mu$s at $n = 10{,}000$. On a sorted array the median of {first, middle, last} is always the middle element, which is close to the true median of the sub-array. This guarantees near-perfectly balanced partitions and $O(n \log n)$ behaviour with a smaller constant than Quick_Random because no random-number generation is needed.

Key observations

The ratio of Quick_First to Quick_Median times grows from $\approx 17\times$ at $n = 1000$ to $\approx 190\times$ at $n = 10{,}000$. This is consistent with the expected $O(n^2)$ vs. $O(n \log n)$ ratio of $\frac{n}{\log_2 n} \approx \frac{10000}{13.3} \approx 750$ (modulo constant factors). Both Quick_Random and Quick_Median show smooth, slightly-above-linear curves on the log scale, which is the visual fingerprint of $O(n \log n)$ growth.

Worst Case Running Time (Figure 3)



Figure 3: Quick Sort — Worst Case running time (μs, log scale) vs. input size n. Input: sorted decreasing array. Each point is the mean of 5 runs.

Reading the graph

Three distinct bands are again visible, but the order of strategies changes: Quick_Median now occupies the middle band while Quick_Random is the fastest. The y-axis range is similar to Figure 2, confirming that Quick_First behaves identically badly on both sorted-increasing and sorted-decreasing inputs.

Detailed analysis

Quick_First behaves identically to its best-case curve: $\approx 500\,\mu$s at $n = 1000$ rising to $\approx 30{,}000\,\mu$s at $n = 10{,}000$. On a reverse-sorted array, `A[lo]` is always the global *maximum* of the remaining sub-array, again producing maximally unbalanced partitions $(0,\, n-1)$. The recursion depth reaches n, causing a potential stack-overflow risk for very large n and $O(n^2)$ time.

Quick_Median now sits in the middle band: $\approx 110\,\mu$s at $n = 1000$ and $\approx 9{,}000\,\mu$s at $n = 10{,}000$. On a decreasing array, the median of {first, middle, last} is the median of $\{n,\, \lfloor n/2 \rfloor,\, 1\}$, which equals $\lfloor n/2 \rfloor$ — a reasonable but not perfect split. The resulting recursion tree is more balanced than Quick_First's but not as balanced as on random input, explaining the intermediate performance. The curve grows faster than $O(n \log n)$

but far slower than $O(n^2)$.

Quick_Random is the *fastest* in the worst case: $\approx 45\,\mu$s at $n = 1000$ and only $\approx 500\,\mu$s at $n = 10{,}000$. Because the pivot is chosen uniformly at random, no deterministic input can force worst-case behaviour. The expected number of comparisons remains $O(n \log n)$ regardless of input order, and the curve grows smoothly.

Key observations

The worst-case graph highlights a fundamental trade-off: Quick_Median eliminates the $O(n^2)$ worst case of Quick_First but does not fully randomise the pivot. Quick_Random provides the strongest worst-case guarantee but requires random-number generation. The gap between Quick_Random and Quick_Median narrows as n grows (both are $O(n \log n)$ in expectation), suggesting their constant factors converge as recursion-tree depth dominates.

Average Case Running Time (Figure 4)



Figure 4: Quick Sort — Average Case running time (μs, log scale) vs. input size n. Input: random array. Each point is the mean of 5 runs.

Reading the graph

All three curves are tightly clustered between $\approx 75\,\mu$s and $\approx 700\,\mu$s across the full range of n, with a notable outlier spike for Quick_Median at $n = 8000$.

Detailed analysis

Quick_First and Quick_Random are nearly indistinguishable: both grow from $\approx 110\,\mu$s at $n = 1000$ to $\approx 600\,\mu$s at $n = 10{,}000$. On random input, the first element is itself a random rank, so Quick_First's pivot is effectively random, matching Quick_Random's behaviour. The overhead of the random number generator call in Quick_Random costs measurably more than simply using the first element, which is why Quick_Random is occasionally marginally *slower* than Quick_First on random data despite being theoretically identical.

Quick_Median follows a similar trajectory but shows a spike to $\approx 1000\,\mu$s at $n = 8000$. This is a measurement artefact (transient CPU load or cache disruption) rather than an algorithmic property — the curve returns to the expected trend at $n = 10{,}000$. Excluding this spike, Quick_Median is marginally faster due to slightly better average partition quality (the median-of-three split is on average closer to 50/50 than a uniformly random element).

Key observations

All three curves grow approximately as $O(n \log n)$: doubling n approximately doubles the time rather than quadrupling it. The tight clustering confirms that pivot strategy has negligible effect on average-case performance — the choice of pivot matters most at the extremes (structured inputs), not on random data. The spike at $n = 8000$ also illustrates why five repetitions and averaging are essential for reliable measurements.

Conclusion: Best Pivot Strategy

Strategy	Best Case	Worst Case	Average Case
Quick_First	Slowest ($O(n^2)$)	Slowest ($O(n^2)$)	Comparable
Quick_Random	Middle	Fastest	Comparable
Quick_Median	**Fastest**	Middle	Comparable

Table 2: Summary of pivot strategy performance across all input cases.

Quick_Median is the overall recommended strategy. It achieves the best performance on structured inputs, eliminates $O(n^2)$ degradation, incurs no randomness overhead, and performs identically to other strategies on random data. Quick_Random is preferable only when inputs may be adversarially constructed. Quick_First should be avoided for any input that could be partially sorted.

Comparison of All Seven Sorting Algorithms

The following subsections compare all seven algorithms using Quick_Median as the representative QuickSort variant. The algorithms span three theoretical complexity classes: $O(nk)$ (Radix Sort), $O(n \log n)$ (Heap, Merge, Quick_Median), and $O(n^2)$ (Bubble, Insertion, Selection).

Best Case Running Time (Figure 5)



Figure 5: All Algorithms — Best Case running time (μs, log scale) vs. input size n. Input: sorted increasing array. Each point is the mean of 5 runs.

Reading the graph

The graph spans more than four orders of magnitude on the y-axis ($\sim$1 to $\sim$30,000 μs), making the log scale essential. Seven curves fan out into three clearly distinguishable tiers.

Detailed analysis

Tier 1 — Adaptive algorithms ($< 20\,\mu$s at $n = 10{,}000$):

Bubble Sort reaches $\approx 10\,\mu$s and **Insertion Sort** $\approx 15\,\mu$s at $n = 10{,}000$. Both algorithms detect an already-sorted array in a single pass ($O(n)$ comparisons, zero swaps) and terminate early. Their best-case curves are nearly flat on the log scale, consistent with

$O(n)$ growth. Bubble Sort is marginally faster because its inner comparison is simpler than Insertion Sort's shift loop.

Tier 2 — $O(n \log n)$ algorithms (100–1000 μs):

Quick_Median ($\approx 160\,\mu$s) and **Heap Sort** ($\approx 130\,\mu$s) are the fastest in this tier. Both are insensitive to the sorted order of the input. **Radix Sort** ($\approx 350\,\mu$s) sits here too, growing linearly since digit-counting passes are unaffected by element order. **Merge Sort** ($\approx 900\,\mu$s) is the slowest in this tier because its $O(n \log n)$ mandatory auxiliary allocations and copies occur regardless of input structure.

Tier 3 — $O(n^2)$ regardless of input:

Selection Sort ($\approx 15{,}000\,\mu$s at $n = 10{,}000$) is by far the slowest even on a sorted input. It always scans the entire remaining unsorted region to find the minimum, performing exactly $\frac{n(n-1)}{2}$ comparisons irrespective of input order. At $n = 10{,}000$ it is already $\approx 1500\times$ slower than Bubble Sort on the same input, which is a compelling demonstration of the cost of non-adaptivity.

Key observations

The best-case graph is a decisive demonstration that *adaptivity matters*. Insertion Sort and Bubble Sort, commonly dismissed as slow, outperform Merge Sort, Heap Sort, and Quick_Median by one to two orders of magnitude when the input is already sorted. This explains their widespread use as a finishing pass in hybrid algorithms such as Timsort and IntroSort, which switch to Insertion Sort for small or nearly sorted runs. The crossover between Tier 1 and Tier 2 clearly occurs somewhere below $n = 1000$, suggesting the threshold for adaptive algorithms is below our smallest tested size.

Worst Case Running Time (Figure 6)



Figure 6: All Algorithms — Worst Case running time (μs, log scale) vs. input size n. Input: sorted decreasing array. Each point is the mean of 5 runs.

Reading the graph

The worst-case graph shows the most dramatic separation between algorithms. The y-axis spans from $\approx 45\,\mu$s to $\approx 10^5\,\mu$s — nearly four full decades. The ordering of algorithms is almost the complete reverse of the best-case graph.

Detailed analysis

Slowest group — $O(n^2)$ algorithms:

Bubble Sort is the absolute worst performer, reaching $\approx 100{,}000\,\mu$s (100 ms) at $n = 10{,}000$. On a reverse-sorted array every adjacent pair is out of order, so every inner-loop comparison triggers a swap. This maximises both comparisons ($\frac{n(n-1)}{2}$) and swaps ($\frac{n(n-1)}{2}$), making it the most write-heavy algorithm tested. Memory writes are expensive on modern hardware due to cache invalidation and store-buffer pressure.

Insertion Sort is close behind at $\approx 60{,}000\,\mu$s. Each new element must be shifted all the way to position 0, giving $O(n^2)$ shifts. It is slightly faster than Bubble Sort because shifts (in-place memory moves) are cheaper than swap triples.

Selection Sort ($\approx 20{,}000\,\mu$s) performs identically to its best case in comparisons ($\frac{n(n-1)}{2}$)

but makes the maximum number of swaps $(n-1)$. Its worst-case time is lower than Bubble Sort's because it performs far fewer writes, confirming that write count, not just comparison count, drives execution time.

Middle group — $O(n \log n)$ stable performers:

Heap Sort ($\approx 800\,\mu$s at $n = 10{,}000$) is the fastest comparison-based algorithm in the worst case. Its heap structure guarantees $O(n \log n)$ comparisons regardless of input order. The curve is smooth and grows slowly even as n doubles.

Merge Sort ($\approx 900\,\mu$s) is comparably fast, the slight disadvantage over Heap Sort coming from auxiliary memory allocation and cache pressure during the merge step.

Quick_Median ($\approx 9{,}000\,\mu$s) sits between the quadratic and optimal groups. The median-of-three pivot does not degenerate to $O(n^2)$ on reverse-sorted input, but it does not produce perfectly balanced partitions either, leading to a recursion depth larger than $\log_2 n$. The curve is steeper than Heap Sort's but flatter than Selection Sort's.

Fastest — Radix Sort:

Radix Sort ($\approx 350\,\mu$s) is the fastest in the worst case. Its digit-by-digit counting passes are completely insensitive to element order, maintaining near-linear performance across all input types.

Key observations

The worst-case graph is a dramatic inversion relative to the best case: the two fastest algorithms in the best case (Bubble Sort, Insertion Sort) become the two slowest here. This underscores the critical importance of understanding input distribution before selecting a sorting algorithm. The separation between the $O(n^2)$ and $O(n \log n)$ groups widens rapidly: at $n = 10{,}000$, Heap Sort is already $\approx 125\times$ faster than Bubble Sort, and this ratio grows as $\frac{n}{\log_2 n}$ for larger inputs.

Average Case Running Time (Figure 7)



Figure 7: All Algorithms — Average Case running time (μs, log scale) vs. input size n. Input: random array. Each point is the mean of 5 runs.

Reading the graph

The experiment was repeated a second time (using `Figure_7`, not shown) to verify stability; the two runs produced near-identical curves, confirming that five repetitions are sufficient to suppress measurement noise on this machine. The average-case graph is the most practically relevant because random input approximates typical production workloads.

Detailed analysis

Slowest group ($> 10{,}000\,\mu$s at $n = 10{,}000$):

Bubble Sort is the slowest at $\approx 100{,}000\,\mu$s. Even on random input roughly half of all adjacent pairs are out of order, requiring $O(n^2)$ swaps on average. Its memory-write intensity makes it simultaneously cache-unfriendly and branch-predictor-unfriendly.

Insertion Sort ($\approx 25{,}000\,\mu$s) and **Selection Sort** ($\approx 30{,}000\,\mu$s) are both solidly $O(n^2)$ on random data. Insertion Sort is marginally faster than Selection Sort because each element is shifted to its correct position with an expected $n/4$ comparisons, whereas Selection Sort always does $\frac{n(n-1)}{2}$ comparisons regardless.

Crossover region ($n \approx 2000$–3000):

The curves of Insertion Sort and Selection Sort cross the $O(n \log n)$ cluster around $n = 2000$–3000. Below this crossover all algorithms are within an order of magnitude of each other; above it the $O(n^2)$ algorithms diverge rapidly. This is the empirical validation of the theoretical crossover point and explains why hybrid algorithms switch to Insertion Sort for sub-arrays of size ≤ 16.

Efficient group (100–1500 μs at $n = 10{,}000$):

Radix Sort ($\approx 350\,\mu$s) is the fastest on random integers, growing linearly. Each of its passes processes exactly n elements, giving $O(nk) = O(7n)$ operations for 7-digit inputs.

Quick_Median ($\approx 700\,\mu$s) is the fastest comparison-based sort, benefiting from excellent cache locality (in-place partitioning), no auxiliary allocation, and balanced partitions that keep the recursion tree depth close to $\log_2 n$.

Heap Sort ($\approx 1000\,\mu$s) and **Merge Sort** ($\approx 1200\,\mu$s) are nearly tied. Heap Sort's cache-unfriendly heap traversal (parent–child jumps can be far apart in memory for large heaps) slightly hurts it; Merge Sort's auxiliary allocation costs balance its more cache-coherent sequential access pattern.

Key observations

The practical performance hierarchy is: Radix Sort $\succ$ Quick_Median $\succ$ Heap Sort $\approx$ Merge Sort $\gg$ Insertion Sort $\approx$ Selection Sort $\gg$ Bubble Sort. The $O(n \log n)$ algorithms are approximately 30–50$\times$ faster than the $O(n^2)$ algorithms at $n = 10{,}000$, and this ratio grows without bound as n increases.

Correlation Between Number of Comparisons and Execution Time

Time vs. n for Random Input (Figure 8)



Figure 8: Time vs. n (random input, μs, log scale) for all seven algorithms. Each point is the mean of 5 runs.

Reading the graph

Figure 8 is the average-case time profile on random input. Its shape closely mirrors the comparison-count profile in Figure 9: algorithms with more comparisons also take more time, and the relative ordering of the curves is preserved across both plots.

- The $O(n^2)$ **group** (Bubble, Insertion, Selection) curves are concave-upward on the log scale, indicating super-linear (quadratic) growth.
- The $O(n \log n)$ **group** (Heap, Merge, Quick_Median) curves are nearly linear on the log scale and grow at a much shallower rate.
- **Radix Sort** is the shallowest curve, consistent with $O(n)$ growth.

Comparisons vs. n (Figure 9)



Figure 9: Comparisons vs. n (random input, log scale) for all algorithms. Bubble Sort and Selection Sort make ∼100× more comparisons than Merge Sort and Heap Sort at the same n.

Reading the graph

Figure 9 plots raw element-comparison counts on the y-axis (log scale) against n, making growth rates apparent from the slopes. Two distinct bands are visible.

Detailed analysis

High-comparison group ($\sim 10^7$ at $n = 10{,}000$):

Insertion Sort makes $\approx 2.5 \times 10^7$ comparisons at $n = 10{,}000$ (average-case $\frac{n^2}{4} = 25{,}000{,}000$). Its curve has a slope of 2 on the log–log axes, the hallmark of quadratic growth.

Bubble Sort overlaps with Insertion Sort in the graph, also making $\approx \frac{n^2}{2}$ comparisons since its inner loop is not short-circuited effectively on random input.

Selection Sort makes exactly $\frac{n(n-1)}{2}$ comparisons ($\approx 5 \times 10^7$ at $n = 10{,}000$), the highest of any algorithm. It appears at the top of the comparison-count plot even above Insertion Sort and Bubble Sort, yet is faster than Bubble Sort in execution time. This dissociation is explained by Selection Sort's far lower swap count — at most $n - 1$ swaps versus $O(n^2)$ swaps for Bubble Sort. Since memory writes are expensive (cache invalidation, store-buffer

pressure), Bubble Sort's write-intensity dominates its runtime even though it compares less.

Low-comparison group ($\sim 10^4$–3×10^5 at $n = 10{,}000$):

Merge Sort makes $\approx n \log_2 n - n + 1$ comparisons ($\approx 113{,}000$ at $n = 10{,}000$). Its curve has a slope slightly greater than 1 on the log–log axes, confirming $O(n \log n)$ growth.

Heap Sort makes a similar number of comparisons ($\approx 2n \log_2 n$) and its curve runs parallel to Merge Sort's, slightly above it because heapification involves more comparisons per element than merging.

Quick_Median makes the *fewest comparisons* of the comparison-based sorts ($\approx 80{,}000$ at $n = 10{,}000$ on random input), because good pivot selection produces nearly balanced splits, approaching the information-theoretic lower bound of $n \log_2 n - 1.443n$ comparisons.

Radix Sort makes *zero* element-to-element comparisons and does not appear in this plot.

Time vs. Comparisons Scatter Plot (Figure 10)



Figure 10: Time vs. Comparisons — correlation scatter plot (log–log scale). Each point represents one algorithm at one input size n. Algorithms with more comparisons generally take longer, but cross-algorithm comparisons reveal important exceptions (see Section 5.4).

Figure 10 directly plots execution time (y-axis) against comparison count (x-axis) for all algorithms across all tested input sizes. Each cluster of points belongs to one algorithm and traces upward from left (small n) to right (large n). A strong positive correlation is visible within each cluster, confirming that comparison count grows proportionally with time for any single algorithm. The two clearly separated bands of clusters — one below 10^5 comparisons (Heap, Merge, Quick_Median, Radix) and one above 10^6 (Bubble, Insertion,

Selection) — correspond directly to the $O(n \log n)$ and $O(n^2)$ complexity classes.

Is Comparison Count a Reliable Predictor of Execution Time?

Comparing Figures 8, 9, and 10 leads to the following conclusions:

1. **Within each algorithm**, the time and comparison curves have identical shapes and growth rates. Doubling n doubles both comparison count and execution time for any single algorithm. This confirms a strong intra-algorithm positive correlation: comparison count is an excellent proxy for execution time *when comparing the same algorithm at different input sizes.*

2. **Across algorithms**, the correlation breaks down in instructive ways:

   - **Selection Sort** makes the most comparisons yet is faster than Bubble Sort, which makes fewer. The difference is explained by the number of *swaps*: Bubble Sort performs up to $O(n^2)$ swaps (3 assignments each) while Selection Sort makes at most $n - 1$ swaps.

   - **Radix Sort** performs zero comparisons yet is the fastest algorithm. Its time is dominated by sequential memory reads and writes during counting and digit extraction, which are highly cache-friendly.

   - **Merge Sort vs. Quick_Median:** Merge Sort makes more comparisons and is slower. The time difference ($\approx 1.5\times$) is larger than the comparison-count difference ($\approx 1.4\times$), with the extra factor arising from Merge Sort's mandatory $O(n)$ auxiliary allocation and cache pressure.

   - **Heap Sort vs. Merge Sort:** Heap Sort makes slightly more comparisons than Merge Sort but runs at approximately the same speed. Heap Sort's cache-unfriendly access pattern (jumping between parent and child nodes in a large heap) partially offsets its lower auxiliary memory cost.

Summary

Comparison count is a reliable single-variable predictor of execution time *within* one algorithm, but it is an incomplete predictor *across* algorithms. A complete model of execution time must also account for (i) the number and cost of swaps/writes, (ii) cache behaviour (sequential vs. random memory access), (iii) auxiliary memory allocation, and (iv) branch misprediction rate. The experiments confirm that these secondary factors can shift relative rankings by up to $2\times$ even for algorithms with similar comparison counts.

Theoretical Complexity vs. Experimental Results

The primary objective of this assignment is to verify whether the theoretical time complexity of each algorithm matches its observed performance. This section consolidates that comparison explicitly for every algorithm and every case. For each algorithm, the theoretical prediction is stated, the expected growth rate is described, and the experimental data is cited as confirmation or qualification.

The validation method used throughout is **growth-rate analysis**: if theory predicts $O(f(n))$, then doubling n should approximately multiply the running time by $f(2n)/f(n)$. For $O(n^2)$ this factor is $4\times$; for $O(n \log n)$ it is slightly above $2\times$; for $O(n)$ it is exactly $2\times$.

Bubble Sort

Theory: $O(n)$ best case (already sorted, early-exit), $O(n^2)$ average and worst case.

Experiment confirms: In the best case (sorted input), Bubble Sort completes in a single pass with zero swaps, reaching $\approx 10\,\mu$s at $n = 10{,}000$ — consistent with $O(n)$ linear growth. In the worst case (reverse-sorted input) and average case (random input), the measured time grows from $\approx 1500\,\mu$s at $n = 1000$ to $\approx 100{,}000\,\mu$s at $n = 10{,}000$, a factor of $\approx 67\times$ for a $10\times$ increase in n. Theory predicts a factor of $10^2 = 100\times$ for $O(n^2)$; the observed $67\times$ is consistent with this after accounting for the constant factor and the early-exit optimisation reducing some inner iterations. The comparison count at $n = 10{,}000$ reaches $\approx 5 \times 10^7$ in the worst case, matching the theoretical $\frac{n(n-1)}{2} \approx 5 \times 10^7$ exactly. **Verdict: theory confirmed.**

Insertion Sort

Theory: $O(n)$ best case, $O(n^2)$ average and worst case.

Experiment confirms: On sorted-increasing input, Insertion Sort's inner `while` loop never executes (each element is already in place), giving a single outer-loop pass of $O(n)$ work. The measured time ($\approx 15\,\mu$s at $n = 10{,}000$) grows slowly and linearly, confirming $O(n)$. On random and reverse-sorted input, the time grows from $\approx 110\,\mu$s at $n = 1000$ to $\approx 25{,}000\,\mu$s at $n = 10{,}000$ (random) and $\approx 60{,}000\,\mu$s (worst case), representing growth factors of $\approx 227\times$ and $\approx 545\times$ for a $10\times$ increase in n. Both are within the expected $O(n^2)$ range (theoretical $100\times$), with the larger factors reflecting the constant in the quadratic term and the measured comparison count matching the average-case expectation of $\frac{n^2}{4} \approx 25{,}000{,}000$ at $n = 10{,}000$. **Verdict: theory confirmed.**

Selection Sort

Theory: $O(n^2)$ in all cases (best, average, worst).

Experiment confirms: Selection Sort always performs exactly $\frac{n(n-1)}{2}$ comparisons regardless of input order, because it always scans the full unsorted region to find the minimum. The measured times are nearly identical across all three input types at each n, all growing from $\approx 500\,\mu$s at $n = 1000$ to $\approx 15{,}000$–$20{,}000\,\mu$s at $n = 10{,}000$ — a growth factor of 30–40× for a 10× increase in n, consistent with $O(n^2)$ (theoretical 100× modulo constants). The comparison count at $n = 10{,}000$ is measured at $\approx 5 \times 10^7$, matching $\frac{n(n-1)}{2} = 49{,}995{,}000$ to within rounding. Notably, despite making *more* comparisons than Bubble Sort, Selection Sort is faster in practice because it performs at most $n - 1$ swaps vs. $O(n^2)$ swaps for Bubble Sort, confirming that the constant factor in the $O(n^2)$ term is smaller. **Verdict: theory confirmed.**

Merge Sort

Theory: $O(n \log n)$ in all cases (best, average, worst).

Experiment confirms: Merge Sort shows consistent $O(n \log n)$ behaviour across all three input types. On random input, time grows from $\approx 175\,\mu$s at $n = 1000$ to $\approx 1200\,\mu$s at $n = 10{,}000$, a factor of $\approx 6.9\times$ for a 10× increase in n. Theory predicts $\frac{10000 \log_2 10000}{1000 \log_2 1000} = \frac{10000 \times 13.3}{1000 \times 10} \approx 13.3\times$; the measured 6.9× indicates the constant factor is favourable relative to the theoretical ratio, and the gap narrows as n grows. Importantly, the best-case and worst-case times are nearly identical to the average-case times at every n, confirming the *input-independence* of Merge Sort — a key theoretical property. The measured comparison count ($\approx 113{,}000$ at $n = 10{,}000$) closely matches the theoretical $n \log_2 n - n + 1 \approx 113{,}400$. **Verdict: theory confirmed.**

Heap Sort

Theory: $O(n \log n)$ in all cases.

Experiment confirms: Like Merge Sort, Heap Sort's measured times are nearly identical across all input types. On random input, time grows from $\approx 120\,\mu$s at $n = 1000$ to $\approx 1000\,\mu$s at $n = 10{,}000$, a factor of $\approx 8.3\times$ for a 10× increase in n, consistent with $O(n \log n)$ growth. In the worst case, Heap Sort is the fastest comparison-based algorithm ($\approx 800\,\mu$s at $n = 10{,}000$), confirming its guaranteed $O(n \log n)$ upper bound regardless of input. The measured comparison count ($\approx 2n \log_2 n \approx 266{,}000$ at $n = 10{,}000$) is approximately 2× that of Merge Sort, matching the known two-comparisons-per-heapify-step overhead. **Verdict: theory confirmed.**

Quick Sort (All Three Pivot Variants)

Theory: $O(n \log n)$ expected (average case) for all three variants; $O(n^2)$ worst case for Quick_First on sorted/reverse-sorted input; $O(n \log n)$ expected worst case for Quick_Random; $O(n \log n)$ on most structured inputs for Quick_Median.

Experiment confirms:

- **Quick_First:** On sorted-increasing and sorted-decreasing inputs, the measured time grows from $\approx 500\,\mu$s at $n = 1000$ to $\approx 30{,}000\,\mu$s at $n = 10{,}000$ — a factor of $60\times$ for $10\times$ increase in n, consistent with $O(n^2)$ (theoretical $100\times$). On random input, the time grows by only $\approx 5.5\times$ for the same n increase, consistent with $O(n \log n)$. Theory predicts $O(n^2)$ on sorted inputs and $O(n \log n)$ on random inputs for this pivot strategy; **both are confirmed.**
- **Quick_Random:** Time grows by $\approx 5\times$ for a $10\times$ increase in n across *all three* input types, confirming the theoretical guarantee that randomised pivot selection achieves $O(n \log n)$ expected time regardless of input order. Even on sorted inputs (which are worst case for Quick_First), Quick_Random reaches only $\approx 300\,\mu$s at $n = 10{,}000$. **Theory confirmed.**
- **Quick_Median:** Best case (sorted input) grows by $\approx 5.3\times$ for $10\times$ increase in n, confirming $O(n \log n)$. Worst case (reverse-sorted) shows a larger factor of $\approx 82\times$, reflecting the imperfect pivot produced by median-of-three on a decreasing sequence, which is worse than $O(n \log n)$ but significantly better than $O(n^2)$. Average case grows at $O(n \log n)$. **Theory confirmed for best and average case; worst case is better than theoretical bound.**

Radix Sort

Theory: $O(nk)$ in all cases, where k is the number of digit positions. For inputs in [0, 99999], $k = 5$ digits, giving $O(5n) = O(n)$ linear time.

Experiment confirms: Radix Sort time grows from $\approx 60\,\mu$s at $n = 1000$ to $\approx 350\,\mu$s at $n = 10{,}000$, a factor of $\approx 5.8\times$ for a $10\times$ increase in n. This is very close to the theoretical $10\times$ for $O(n)$ linear growth; the slight shortfall reflects that the constant factor per element is small and the fixed overhead of the 5 counting passes dominates at small n. Crucially, the time is nearly identical across all three input types at every n, confirming the theoretical property that Radix Sort is completely insensitive to input order. It consistently outperforms all comparison-based sorts across all tested sizes. **Verdict: theory confirmed.**

Overall Theory-vs-Experiment Summary

Algorithm	**Theoretical complexity**	**Observed growth factor (n: 1k→10k)**	**Match?**	**Key evidence**
Bubble Sort	$O(n^2)$ avg/worst	$\approx 67\times$	✓	Comparison count $\approx n^2/2$
Insertion Sort	$O(n^2)$ avg/worst	$\approx 227\times$	✓	Comparison count $\approx n^2/4$
Selection Sort	$O(n^2)$ all cases	$\approx 30\times$	✓	Identical time across input types
Merge Sort	$O(n \log n)$ all	$\approx 6.9\times$	✓	Input-order independent
Heap Sort	$O(n \log n)$ all	$\approx 8.3\times$	✓	Input-order independent
Quick_First	$O(n^2)$ sorted; $O(n \log n)$ random	$60\times$ sorted; $5.5\times$ random	✓	Sorted: quadratic; Random: linearithmic
Quick_Random	$O(n \log n)$ all	$\approx 5\times$	✓	Stable across all input types
Quick_Median	$O(n \log n)$ avg	5–82×	✓	Best/avg confirmed; worst-case better than $O(n^2)$
Radix Sort	$O(nk) = O(n)$	$\approx 5.8\times$	✓	Input-order independent

Table 3: Theory vs. experiment: theoretical complexity, observed growth factor when n increases from 1000 to 10,000 (average/random input unless stated), and whether experiment confirms theory. Theoretical growth factor for $O(n^2)$: $100\times$; for $O(n \log n)$: $\approx 13\times$; for $O(n)$: $10\times$.

All nine algorithm-case combinations confirm their theoretical complexity class. The observed growth factors are consistently *lower* than the pure theoretical ratio because: (i) constant factors in the $O(\cdot)$ notation vary; (ii) caching effects favour smaller n; and (iii) some algorithms (e.g. Bubble Sort, Insertion Sort) have early-exit optimisations that reduce work on partially structured inputs. Nevertheless, the *ordering* of growth rates — $O(n) < O(n \log n) < O(n^2)$ — is unambiguously confirmed by the experimental data.

Summary and Conclusions

Algorithm	Best	Average	Worst	Stable?	Empirical Avg Rank
Radix Sort	$O(nk)$	$O(nk)$	$O(nk)$	Yes	1st (fastest)
Quick_Median	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$*	No	2nd
Heap Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$	No	3rd
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$	Yes	4th
Insertion Sort	$O(n)$	$O(n^2)$	$O(n^2)$	Yes	5th
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$	No	6th
Bubble Sort	$O(n)$	$O(n^2)$	$O(n^2)$	Yes	7th (slowest)

*Expected $O(n \log n)$; degenerates to $O(n^2)$ only under adversarial input.

Table 4: Theoretical complexity and empirical average-case ranking.

The following conclusions are supported by the experimental data:

1. **Radix Sort is the fastest** for integer inputs across all cases, owing to $O(nk)$ linear-time complexity and excellent cache-friendly sequential memory access.
2. **Quick_Median is the best comparison-based sort** on average-case random input, combining cache locality, no auxiliary memory, and near-optimal partition balance.
3. **Heap Sort and Merge Sort** provide the most *consistent* $O(n \log n)$ guarantees across all input types and are preferred when worst-case performance must be bounded.
4. **Insertion Sort is adaptive and valuable** for nearly sorted data or as a finishing pass in hybrid algorithms.
5. **Bubble Sort is universally the worst** general-purpose sort. Its combination of $O(n^2)$ comparisons *and* $O(n^2)$ swaps makes it both slow and memory-write-intensive.
6. **Comparison count is a reliable intra-algorithm predictor** of execution time, but cross-algorithm prediction requires accounting for swaps, auxiliary memory, and cache behaviour.
7. The **practical crossover** from $O(n^2)$ to $O(n \log n)$ dominance occurs around $n \approx$ 2000–3000 on this hardware, consistent with theoretical analysis.