

<https://swayam.gov.in>https://swayam.gov.in/nc_details/NPTEL

200801199@rajalakshmi.edu.in ▾

NPTEL (<https://swayam.gov.in/explorer?ncCode=NPTEL>) » Problem Solving Through Programming In C (course)



Click to register
for Certification
exam

(https://examform.nptel.ac.in/2023_10/exam_form/dashboard)

If already
registered, click
to check your
payment status

Course outline

How does an
NPTEL
online
course
work? ()

Week 0 : ()

Week 1 ()

Week 2 ()

Week 3 ()

Week 4 ()

Week 5 ()

Week 5 : Assignment 5

Your last recorded submission was on 2023-08-30, 20:04 Due date: 2023-08-30, 23:59 IST.
IST

- 1) The statement that transfers control to the beginning of the loop is called **1 point**
- ☐ a) break
 - ☒ b) continue
 - ☐ c) goto
 - ☐ d) None of the above
- 2) In C three way transfer of control is possible using **1 point**
- ☐ a) Unary operator
 - ☐ b) Logical operator
 - ☒ c) Ternary operator
 - ☐ d) None

Week 6 ()**DOWNLOAD
VIDEOS ()****Books ()****Text
Transcripts ()****Problem
Solving
Session -
July 2023 ()**

3) What is the output of the following code?

1 point

```
#include <stdio.h>
int main()
{
    int i=0;
    do
    {
        printf("while vs do-while\n");
    }while(i==0);
    printf("Out of loop");
    return 0;
}
```

- ☐ a) 'while vs do-while' once
- ☐ b) 'Out of loop' infinite times
- ☐ c) Both 'while vs do-while' and 'Out of loop' once
- ☒ d) 'while vs do-while' infinite times

4) What is the output of the following C program?

1 point

```
#include <stdio.h>
int main()
{
    int a = 0, i;
    for (i = 0; i < 5; i+=0.5)
    {
        a++;
        continue;
    }
    printf("%d", a);
    return 0;
}
```

- ☐ a) 5
- ☐ b) 10
- ☒ c) No output
- ☐ d) Compilation error

5) What is the output of the following C code?

1 point

```
#include <stdio.h>
int main()
{
    int a = 1;
    if (a--)
        printf("True\n");
    if (++a)
        printf("False\n");
    return 0;
}
```

- ☐ a) True
- ☐ b) False
- ☒ c) Both 'True' and 'False'
- ☐ d) Compilation error

6) What will be the output?

1 point

```
#include <stdio.h>
int main()
{
    int x=1;
    do
    {
        continue;
        printf("%d", x);
        x++;
        break;
    }while(x<=10);
    printf("\nAfter loop x=%d", x);
    printf("\n");
    return 0;
}
```

- ☐ a) After loop x=1
- ☐ b) 1
After loop x=2
- ☐ c) 1 2 3 4 5 6 7 8 9 10
- ☒ d) No output

7)

1 point

What will be the output?

```
#include <stdio.h>
int main()
{
    float k = 0;
    for (k = 0.5; k < 3; k++)
        printf("I love C\n");
    return 0;
}
```

- ☐ a) Error
- ☒ b) I love C - will be printed 3 times
- ☐ c) I love C - will be printed 6 times
- ☐ d) I love C - will be printed 5 times

8)

1 point

What will be the output?

```
#include <stdio.h>
int main()
{
    int x;
    x = 4 < 8 ? 5 != 1 < 5 == 0 ? 1 : 2 : 3;
    printf("%d", x);
    return 0;
}
```

- ☐ a) 1
- ☒ b) 2
- ☐ c) 3
- ☐ d) Error

9)

1 point

The following program is used to find the reverse of a number using C language. Find the missing condition inside while statement (indicated as 'xxxx').

```
#include <stdio.h>
int main()
{
    int n, reversedNumber = 0, remainder;

    printf("Enter an integer: ");
    scanf("%d", &n);

    while(xxxx)
    {
        remainder = n%10;
        reversedNumber = reversedNumber*10 + remainder;
        n /= 10;
    }

    printf("Reversed Number = %d", reversedNumber);

    return 0;
}
```

- ☒ a) n!=0
- ☐ b) n==0
- ☐ c) n%10==0
- ☐ d) n/10==0

10)

1 point

Compute the printed value of i & j of the C program given below

```
#include <stdio.h>
int main()
{
    int i = 0, j = 15;
    while (i<8, j >9)
    {
        i++;
        j--;
    }
    printf("%d, %d\n", i, j);
    return 0;
}
```

- ☐ a) 8,10
- ☐ b) 8,9
- ☒ c) 6, 9
- ☐ d) 7, 10

You may submit any number of times before the due date. The final submission will be considered for grading.

Submit Answers

