

TypeScript

Introduction to TypeScript -

1. TypeScript is a programming language, which was developed by Microsoft in the year 2012.
2. TypeScript is a superset of JavaScript which adds more features like static typing, error detection, and code readability.
3. JavaScript is flexible but sometimes it creates bugs because it does not check the type of the data.

// for example -

JavaScript:

```
let age = "20";  
  
console.log(age) // No error
```

TypeScript:

```
let age: Number;  
  
age = "20"  
  
console.log(age) // TypeError
```

Why TypeScript ? -

1. We use typescript because it detects errors at compile time.
2. TypeScript improves code readability and maintainability.
3. It provides strong typing and smart features like auto completion, auto suggestion, error checking.
4. TypeScript makes large projects easy to manage.
5. TypeScript helps testers to write reliable automation scripts.

Why not only JavaScript ? -

1. In JavaScript, most errors are found only when the program runs.
2. Using JavaScript, it is hard to handle big projects.
3. JavaScript does not have type safety (it doesn't check data types).
4. It becomes difficult to maintain large and complex automation frameworks in JavaScript.

// To solve these problems, we use TypeScript.

// TypeScript gives compile-time checking and type safety, so we can find errors early and manage projects easily.

History of TypeScript -

1. TypeScript was introduced in 2012, created by Microsoft and designed by Anders Hejlsberg .
2. The reason for the creation of TypeScript was that JavaScript is used for building large web applications but it had problems with

that, so to overcome those problems TypeScript was introduced which was more powerful, safer and maintainable as compared to JavaScript.

TypeScript Growth -

TypeScript become more popular because :

1. It supports the latest JavaScript features.
2. It makes code easy to read and understand.
3. It helps to write better quality code.
4. It helps testers write clean and readable automation scripts.
5. TypeScript works with frameworks like Angular, React, and Node.js. // When Angular adopted TypeScript, it became more popular.

Version of TypeScript -

// TypeScript updates its version regularly.

- 1. version 1:** The first version of TypeScript was released in the year 2012, which was the basic static typing.
- 2. version 2:** In this version , there was better type checking and optional parameters.
- 3. version 3:** In this version, they improved performance and introduced advanced types.

4. version 4: in this version, they introduced faster compilation and powerful type features.

5. version 5: In this version, they enhanced typescript performance and also supported the latest features of JavaScript.

// Currently we are using version 5.9 series.

What is a Transpiler ? -

A transpiler is a tool that converts code written in one programming language to another programming language.

Why do we need a Transpiler ? -

1. As browsers don't support the new JavaScript feature so for that we need a transpiler.
2. TypeScript cannot run on browsers directly.
3. We need a transpiler to convert the code that can work everywhere.

The Flow of Transpiler -



What is TSC ? -

1. TSC stands for TypeScript Compiler.
2. It is a command - line tool provided by TypeScript, to convert TypeScript code into JavaScript code.
3. It checks whether there is any error during compilation.
4. As browsers and Node.js cannot execute TypeScript code directly, TSC ensures that TypeScript code is validated, Type - checked and converted into a standard Javascript code that can run in every environment.

Installation process of TypeScript -

1. First create a new folder (Titled as TypseScript).
2. Open that folder and open cmd.
3. After opening cmd, check if your desktop / laptop is having node version or not (to check node version simply write node --version).
4. If your desktop / laptop is not having node then install node.js by downloading it through their official website <https://nodejs.org/en/download>.
5. After downloading proceed with the further steps.

6. If node is present in your desktop / laptop check npm (node package manager) (to check npm simply type `npm -v` command in the command prompt).
7. Install typescript package in your folder to install typescript package type (`npm install -g typescript`)
8. To check whether the compiler is properly installed in your desktop / laptop just type (`tsc -v`).
9. After that, open VS Code on your desktop / laptop.
10. After that, create two files, one `app.ts` and another file as `index.html`.

// To Compile a TSC file, just write in the terminal / cmd (`tsc file_name.ts`).

// To run the code in the terminal, we use (`node file_name.ts`).

Type Annotation -

1. A TypeAnnotation is a process in which we explicitly define the datatype of a variable, function, parameter return or an object in TypeScript.
2. In Type Annotation, it tells the compiler what kind / type of data will be present and helps to catch the error at the compile time

.

// Syntax for Type Annotation -

Variable_name : datatype = value; { The basic formula for type annotation is to add a colon(:) followed by datatype after that value.}

// Example - let age : number = 20;

```
let a : number;  
a = 500;  
console.log(a);
```

Why Type Annotation is needed ? -

1. Type Annotation prevents run time error.
2. It improves code readability.
3. Type Annotation provides compile - time safety.
4. It makes the code self - documented.

Common Type of Annotation -

1. **Primitive Types** - It is used for basic data like string, number, boolean, null and undefined.
2. **Array** - It specifies that an array should only contain a specific type. (for example - let score:number[]=[10,20])
3. **Object** - It explicitly defines the shape of an object. (for example - let user:{name:string,age:number}={name = "Ankita",age = 25})

When to use Type Annotation ? -

1. When a variable is declared without an initial value.
2. Functions have complex return logic.

Type Inference -

Type inference in TypeScript means the compiler automatically understands the data type based on the value you give, so you don't need to write the type manually, and your code stays safe.

Why is Type Inference useful ? -

1. Type Inference reduces the need for explicit type annotation.
2. It keeps the code clean and readable.
3. It maintains strong type safety.
4. It helps to catch an error at compile time.
5. It improves developer productivity.

//Syntax -

Let variable_name = value; { here, let is variable declaration type, variable_name is the name given to the variable and value is the data assigned to that variable.}

```
let data = 600
compiler version :- let data : number =
"TypeScript"
data = 100
console.log(data);

let a;      //!< with respect to type inference
a = 10;
a = "TypeScript"
```



```
console.log(a);

let a : number;    //! with respect to type
Annotation
a = 500;
console.log(a);
```

Difference between Type Annotation and Type Inference

type annotation


1. type annotation explicit provides the datatype to a particular variable.
2. the datatype is provided by the developer.
3. it is more controlled over declared type.

type inference

1. in type inference we are not providing explicitly the datatype to the variable.
2. the datatype is provided by the compiler.
3. it is less controlled over the declared type.

DataType in TypeScript -

Typescript datatype types us to define what kind of data is being stored in a variable.



In TypeScript, there are 4 types datatype in typescript : -

1. Primitive datatype - Primitive datatype in typescript stores single values that are immutable in nature that means we cannot change the type of the value.

There are different types in primitive datatype -

a. Number: number datatype is used to store numeric values (integer value and decimal value).

For example -

```
let num : number = 10; //! --> integer value
console.log(num);

let num : number = 15.60; //! --> decimal value
console.log(num);
```

```
let num : number = -250;    //! --> negative
value
console.log(num);
```

b. String: String datatype is used to store textual data (sentence, character, word). For representing string there are three ways :-

- Single quotes -

For example -

```
let a : string = 'hi everyone, a very
good morning after the session i will
be sending the notes.'
console.log(a);
```

- Double quotes -

For example -

```
let b :string = " let's go to a party."
console.log(b);
```

- Backticks (temporal literal) - A string interpolation is a concept in which we are accessing a value which is

assigned to a variable into a sentence. where we are using `` and \${}.

For example -

```
let age : number = 30
console.log(`my age is ${age}`);
```

- c. Bigint :** A bigint is a primitive datatype which is used to store a large number exceeding the limit of a normal number value and it is represented with the help of a letter at the n.

For example -

```
let num : bigint =
123456789000523698714581215221n
console.log(num);
```

- d. Boolean:** Boolean datatype is used to store true or false values. There are only two possible values either true or false.

For example -

```
let isPresent : boolean = true;
console.log(isPresent);
```

- e. Null:** Null datatype is used to represent an intentional empty value.

For example -

```
let data : null = null;  
console.log(data);
```

f. Undefined: Undefined datatype is a datatype where a variable is declared but not assigned any value.

For example -

```
let example : undefined  
example = undefined  
console.log(example);
```

2. Non - Primitive Datatype - Non - primitive datatype in typescript is used to store multiple values and they are mutable in nature.

➤ **Object** - An object is a real time entity which stores values in the form of key and pair.

```
///  
//? Type Annotation of an Object -  
  
//! first approach of assigning a value to an  
object. -  
  
let user : {  
    username : string,  
    usage : number,  
    isActive : boolean  
} = {
```

```
    username : "Ankita",
    usage : 35,
    isActive : false
}
console.log(user);

//! Second approach of assigning a value to an
object. -

let user : {
    username : string,
    usage : number,
    isActive : boolean
}
user = {
    username : "Lalitha",
    usage : 30,
    isActive : true
}
console.log(user);

//? Accessing and updating a value in an object -

let user : {
    username : string,
    usage : number,
    isActive : boolean
```

```
}
user = {
    username : "Lalitha",
    usage : 30,
    isActive : true
}
user.isActive = false
console.log(user);

//? Type Annotation of an object with optional
parameter / optional property-

//? optional parameter - An optional parameter is a
concept in typescript which is used to make a
particular property or a parameter as an optional
that means not mandatory. It is denoted with a ?.

let user : {
    username : string,
    usage : number,
    isActive ? : boolean
}
user = {
    username : "Lalitha",
    usage : 30,
}
console.log(user);
```

//? nested object - A nested object is defined as an object inside another object.

```
let user : {  
  username : string,  
  usage : number,  
  userIspresent : boolean,  
  userAddress : {  
    city : string  
  }  
}  
  
user = {  
  username : "Ankita",  
  usage : 30,  
  userIspresent : true,  
  userAddress : {  
    city : "Mumbai"  
  }  
}  
  
console.log(user.userAddress.city);
```