

7/27/26, 1:16 PM

Student Submissions — Level 1 - Viva

SIMATS Engineering • CSE • CSA0804 — Python Programming • 27-07-2026 • Category: Level 1 - Viva • Student Submissions Report

Student 36 **SOUNDHARYA S** 192421390RD

10 / 10 submitted

Q1. Operators in Python

ANSWER

Arithmetic operators
eg: (+,-,*,%)
Comparison operators
eg: (==, <=, >=)
Assignment operators
eg: (=, +=, -=)
logical operators
eg: (and, or, not)
Bitwise operators
eg: (&,)
Membership operators
eg: (in, not in)
Identity operators
eg: (is, not is)

Q2. Operators

ANSWER

```

** - exponentiation
a = 2
b = 4
print(a ** b)
% - modulus = 2 % 4
a = 2
b = 4
print(a % b)
// - for loop = 2 // 4
a = 2
b = 4
print(2 // 4)
/ - division = 2 / 4
a = 2
b = 4
print(2 / 4)

```

Q3. for and while loop

ANSWER

The for loop is used for, if the 1st statement is false we can able to go for an 2nd statement this can continue, when the statement is true till that we can get the for loop

Q4. range()

ANSWER

it helps to repeat the number
it can control the loop iteration

```

1) range(5)
it starts from 0 - end before 5
for i in range(5):
print(i)

2)range (1,6)
it starts from 1 - end before 6
for i in range(1, 6):
print(i)

3)range(1, 10, 2)
it starts
print from 1 - between it can increase by 2 - end before 10
for i in range(1, 10, 2):
print(i)

```

7/27/26, 1:16 PM

Student Submissions — Level 1 - Viva

SIMATS Engineering • CSE • CSA0804 — Python Programming • 27-07-2026 • Category: Level 1 - Viva • Student Submissions Report

Q5. String**ANSWER**

string is sequence of character and it has single quotes(' '), double(" ")
it is immutable.
it can contain number, space, symbol, letter
it can represent as "str"
it supports many built in methods upper(), lower(), split(), replace()

Q6. String Slice**ANSWER**

- 1) ytho
- 2) nohtyP
- 3) pto
- 4) hon

Q7. List**ANSWER**

A list in python is an ordered collection of values stored in a single variables.
it can contain multiple data types
list is mutable
string is a sequence of characters, and it cannot be changed directly if we want to change if we should not create a the string
list is created using square bracket[]

Q8. List Slice**ANSWER**

- 1) [30,40,50,60]
- 2) [10,20,30,40]
- 3) [10,30,50,70]
- 4) [70,60,50,40,30,20,10]
- 5) [40,50,60]

Q9. Index**ANSWER**

eg: "Python"
s[0] = 'P'
s[1] = 'y'
negative index starts at -1 from the end

Q10. length**ANSWER**

len(): return the number of element in an object that has length
count(): return the number of occurrences of a specific value inside a sequence