

Consolidated Energy Insulation

Consolidated Energy insulation are factory-formed glass fibre insulation batts bonded with a thermosetting resin binder and supplied as pre-cut batts. The range is designed to friction-fit between standard timber or steel framing members and recover to nominal thickness after unpacking for consistent cavity fill.

Product

Consolidated Energy Glasswool Batts

SDS Version

0.9 Interim

Issue Date
Review Date


GHS08

Class Carcinogenicity

Category Category 2

Signal word Warning

Code H351

Hazard statement:

H351 Suspected of causing cancer.

Additional effects:

Dust and airborne fibres may cause temporary mechanical irritation to the eyes, skin and upper respiratory tract.

Key precautions:

Obtain special instructions before use. Avoid generating dust. Wear gloves, eye protection and suitable respiratory protection where dust or fibres may be generated.

Important: This SDS is drafted as an interim GHS 7 SDS for an imported glasswool insulation product where **Note Q / biosolubility evidence has not yet been demonstrated**. It is therefore written on a conservative basis using **Carcinogenicity Category 2 (H351)**

Section 1 – Identification

Product Identifier	Consolidated Energy Glasswool Batts	
Other Names	Glasswool batts; glass fibre insulation batts; man-made vitreous fibre (MMVF) insulation batts	
Recommended Use	Thermal and acoustic insulation for wall, ceiling and other dry building cavity applications in residential and commercial construction.	
Restrictions on Use	Not for use as an exposed internal lining; not a water or vapour barrier; not for use where prolonged wetting, water exposure or persistent high humidity may occur.	
Australian supplier / importer	Consolidated Energy 1/58 Meakin Rd, Meadowbrook QLD 4131	Phone: 1300 560 944 Email: info@consolidatedenergy.com.au Website: www.consolidatedenergy.com.au
Emergency phone	000	
Poisons Information Centre	13 11 26 (Australia)	

Section 2 – Hazard(s) Identification

GHS classification (interim)

Carcinogenicity Category 2 – **H351 Suspected of causing cancer.**

Interim basis: Note Q / biosolubility evidence has not yet been demonstrated for this imported formulation. A conservative classification has therefore been adopted pending final assessment.

Label elements

Signal word	WARNING
Pictogram	Health hazard (GHS08)
Hazard statement	H351 Suspected of causing cancer.
Precautionary Statements	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves and eye protection. P284 - Wear respiratory protection where dust or fibres may be generated. P308 + P313 - If exposed or concerned: Get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/container in accordance with local regulations.
Other Hazards	Dust and airborne fibres may cause temporary mechanical irritation to skin, eyes and upper respiratory tract.

Section 3 – Composition and Information on Ingredients

This product is supplied as a manufactured batt/article and may release dust or fibres when cut, handled or damaged.

Ingredient	CAS No.	Proportion	Notes
Glass wool fibres (amorphous)	65997-17-3 (typical listing; confirm with supplier)	85–95% (TBC)	Main fibrous component
Thermosetting resin binder	Proprietary	3–10% (TBC)	Binder system
Additives / process aids / dust suppressants	Proprietary	0–2% (TBC)	Minor constituents

Section 4 – First Aid Measures

Inhalation

Remove affected person to fresh air. If irritation, coughing or discomfort persists, seek medical advice.

Eye contact

Flush cautiously with clean running water for at least 15 minutes. Remove contact lenses if present and easy to do. Seek medical advice if irritation persists.

Skin contact

Wash with mild soap and running water. Do not rub or scratch affected skin. Seek medical advice if irritation persists.

Ingestion

Rinse mouth and drink water. Ingestion is not an expected route of exposure. Seek medical advice if symptoms occur.

Most important symptoms/effects: Temporary mechanical irritation to eyes, skin and upper respiratory tract.

Section 5 – Firefighting Measures

Suitable extinguishing media	Use extinguishing media appropriate to the surrounding fire, such as water fog, foam, dry chemical or carbon dioxide.
Specific hazards	The glass fibres themselves are not readily combustible; however, packaging and organic binder components may burn in a sustained fire and produce smoke and decomposition products.
Protective equipment	Firefighters should wear self-contained breathing apparatus (SCBA) and full protective clothing in a sustained fire.

Section 6 – Accidental Release Measures

- Avoid generating dust or airborne fibres.
- Wear suitable PPE including respiratory protection if dust is present
- Collect material using a HEPA-filter vacuum or damp clean-up methods.
- Do not use compressed air or dry sweeping methods that may disperse fibres.
- Place waste in suitable bags or containers for disposal in accordance with local requirements.

Section 7 – Handling and Storage

Handling

- Minimise dust generation during cutting, fitting and clean-up.
- Use sharp hand tools where practicable; where power cutting is used, provide dust extraction or local exhaust ventilation.
- Wash hands after handling and before eating, drinking or smoking.
- Do not modify the product outside approved installation use.

Storage

- Store in original packaging in a dry, protected location.
- Protect from weather, moisture and physical damage.
- Keep sealed until required for use.
- Allow batts to recover to nominal thickness before installation.
- Store locked up where required under workplace procedures.

Section 8 – Exposure Controls and Personal Protection

Exposure standard	Apply relevant Australian workplace exposure standards and good occupational hygiene practice for mineral wool dust. Maintain exposures as low as reasonably practicable.
Engineering controls	Provide local exhaust ventilation, on-tool extraction or other dust capture where cutting or handling may generate airborne dust/fibres. Maintain good housekeeping.
Respiratory protection	Where dust or fibres may be generated, wear a suitable particulate respirator such as P2/N95 or higher as required by the workplace risk assessment and AS/NZS 1715/1716 practice.
Eye protection	Safety glasses or goggles in dusty environments.
Skin protection	Gloves and long-sleeved clothing to reduce mechanical irritation.
Hygiene measures	Wash exposed skin after handling. Launder contaminated work clothing before reuse. Do not use compressed air to remove fibres from skin or clothing.

Section 9 – Physical and Chemical Properties

Appearance	Fibrous batt
Colour	Yellow
Odour	Nil to slight
pH	Not applicable / TBC
Flash point	Not applicable
Flammability	Glass fibres are not readily combustible; packaging and binder may burn
Solubility	Insoluble in water

Section 10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions of storage and use.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: Moisture ingress, physical damage, unnecessary dust generation, temperatures above the product's service temperature.

Incompatible materials: Strong acids or strong alkalis may affect binder components.

Hazardous decomposition products: Smoke, carbon oxides and other combustion products may be generated in a sustained fire.

Section 11 – Toxicological Information

Likely routes of exposure: Inhalation of dust or fibres during cutting and installation; skin and eye contact.

Acute effects: Temporary mechanical irritation to the eyes, skin and upper respiratory tract.

Chronic effects: Interim classification as Carcinogenicity Category 2 has been adopted conservatively pending Note Q evidence for this formulation.

Carcinogenicity: H351 Suspected of causing cancer.

Section 12 – Ecological Information

- Not expected to present significant acute aquatic toxicity as supplied.
- Inert solid material with limited mobility as batt form; avoid unnecessary release of dust to the environment.
- Ecological data for the finished article are limited.

Section 13 – Disposal Considerations

Dispose of unused product, offcuts and contaminated packaging in accordance with local, state and territory regulations. Bag dusty waste to reduce airborne fibre release during handling and transport.

Section 14 – Transport Information

UN Number	Not regulated as Dangerous Goods
Proper shipping name	Not applicable
Dangerous Goods class	Not applicable
Packing group	Not applicable
Environmental hazards	Not classified as a marine pollutant

Section 15 – Regulatory Information

This SDS is intended to align with Australian WHS requirements for hazardous chemicals using the 16-section SDS format and GHS 7 hazard communication.

Section 16 – Other Information

UN Number	Not regulated as Dangerous Goods
Proper shipping name	Not applicable
Dangerous Goods class	Not applicable