

Consolidated Energy Insulation

Consolidated Energy insulation are factory-formed glass fibre insulation batts bonded with a thermosetting resin binder and supplied as pre-cut batts. The range is designed to friction-fit between standard timber or steel framing members and recover to nominal thickness after unpacking for consistent cavity fill.

Application and Intended Use

The product range is intended for use as bulk insulation installed within building cavities for thermal

and acoustic performance, including:



Ceilings/Roof Spaces



External and Internal Walls



**Underfloor Cavities
(where cavity conditions
are dry and protected)**

*This product is not intended to be used in commercial applications.

NCC 2022 Volume Two / Housing Provisions (Class 1 & 10)

Building fabric thermal insulation

Consolidated Energy Insulation tested and labelled in accordance with AS/NZS 4859.1 satisfy the requirements for thermal insulation materials used within building fabric under NCC Housing Provisions Part 13.2.2. When installed in accordance with installation guidelines, insulation is installed continuously and does not interfere with building services or fittings.



Evidence of Stability

Test Standard	Test Type	Result
AS/NZS 4859.1:2018	Thermal	Complies
AS/NZS 1530.3:1993	Fire (Indices)	AWTA Report 15-005343

Summary of Testing Results

NCC Clause(s)	Test Standard	Test Type	Requirement	Reported Value
Part 13.2.2	AS/NZS 4859.1:2018	Thermal	Classification	Refer to range table
	AS/NZS 1530.3:1993	Fire	Ignitability Index - 0 Spread of Flame Index - 0 Heat Evolved Index - 0 Smoke Development Index 0-1	

Walls



Product Code	Declared R-Value (m ² .K/W)	Density	Depth (mm)	Width (mm)	Length (mm)	Pieces / Pack	m ² / Pack	Packs / Bale
HNMWB009	1.5	12	75	430	1160	22	10.97	8
HNMWB010	1.5	12	75	580	1160	22	14.80	8
HNMWB003	2	21	75	430	1160	17	8.48	8
HNMWB004	2	21	75	580	1160	16	10.76	8
HNMWB001	2	13	90	430	1160	19	9.48	8
HNMWB002	2	13	90	580	1160	18	12.11	8
HNMWB005	2.5	22	90	430	1160	12	5.99	8
HNMWB006	2.5	22	90	580	1160	11	7.40	8
HNMWB007	2.7	31	90	430	1160	8	3.99	8
HNMWB008	2.7	31	90	580	1160	7	4.71	8

Ceilings



Product Code	Declared R-Value (m ² .K/W)	Depth (mm)	Width (mm)	Length (mm)	Pieces / Pack	m ² / Pack	Packs / Bale
HNMCB001	2.5	130	430	1160	17	8.48	8
HNMCB002	2.5	130	580	1160	16	10.76	8
HNMCB003	3.0	145	430	1160	16	7.98	8
HNMCB004	3.0	145	580	1160	15	10.09	8
HNMCB005	3.5	175	430	1160	10	4.99	8
HNMCB006	3.5	175	580	1160	9	6.06	8
HNMCB009	4.1	195	430	1160	9	5.99	8
HNMCB010	4.1	195	580	1160	9	7.40	8
HNMCB011	5.0	250	430	1160	8	3.99	8
HNMCB012	5.0	250	580	1160	8	5.38	8
HNMCB013	6.0	300	430	1160	7	3.49	8
HNMCB014	6.0	300	580	1160	7	4.71	8
HNMCB015	7.0	350	430	1160	6	2.99	8
HNMCB016	7.0	350	580	1160	6	4.04	8
HNMCB017	8.0	380	430	1160	6	2.99	8
HNMCB018	8.0	380	580	1160	5	3.36	8

Limitations of Use

Limitations of Use (compliance-relevant)

- **IMPORTANT:** Do not modify this product. Compliance with referenced evidence of suitability is only achieved by the listed product configuration and installation conditions.
- Product must not be exposed to weather or moisture at any time (before, during, or after installation). Install only in dry, protected cavities.
- High-density products (HD) must be installed in a cavity of the correct size with no obstructions. Installing in a cavity smaller than nominal thickness can cause deformation or detachment of rigid wall linings and may reduce performance.
- Unfaced glasswool is not a water barrier or vapor barrier and must not be relied upon for moisture/vapor control.
- Not suitable for use as an exposed internal wall or ceiling lining where a Group Number is required (AS ISO 9705 / AS 5637.1 pathways).
- Maximum service temperature for glasswool is typically 150°C (TBC for this range). Do not use above verified service temperature.

Conditions of Use

- Store in original packaging in a cool, dry area; protect from damage; keep sealed until installation; avoid prolonged UV exposure of packaging.
- Allow batts to fully recover to nominal thickness before installation; do not install crushed or permanently compressed material.
- Installation must comply with NCC 2022 and applicable Australian Standards and installation guidance.

Instructions for Design, Construction or Installation

- Confirm cavity size, stud spacing, and required installed thickness before selecting the appropriate product.
- Install insulation to form a continuous thermal barrier: abut or overlap adjoining insulation, avoid gaps around services and fittings, and maintain the product's full nominal thickness.
- Keep clearances around heat-producing fixtures and electrical equipment in accordance with manufacturer instructions and applicable regulations.

- Cutting and handling: minimize dust generation where practicable; use sharp tools and maintain clean work practices. Collect dust using suitable vacuum equipment or other dust-control measures.
- Personal protective equipment (PPE): When installing, cutting, or handling insulation, appropriate personal protective equipment should be worn in accordance with workplace safety practices. This may include protective clothing, gloves, safety glasses and respiratory protection where airborne dust or fibres may be generated.
- Respiratory protection: Where dust or airborne fibres may be generated during installation or cutting, suitable respiratory protection (such as a P1 or P2 particulate respirator compliant with AS/NZS 1716) should be used in accordance with Safe Work Australia guidance and workplace risk assessments.
- Wash hands after handling insulation products and before eating, drinking or smoking.

Maintenance Instructions

- No routine maintenance required when installed in dry, protected cavities.
- If insulation becomes wet or contaminated, remove and replace with dry product.

Support

Company: Consolidated Energy

Web: www.consolidatedenergy.com.au

Email: info@consolidatedenergy.com.au

Phone: 1300 560 944

Technical Support:

<https://www.consolidatedenergy.com.au/information-hub-downloads>

Specification

Product Name: Consolidated Energy Insulation, R[] m²K/W, thickness [] mm.

The insulation material shall be Consolidated Energy unfaced glasswool batts as supplied by Consolidated Energy and installed in accordance with NCC 2022, AS/NZS 4859.1 labelling/installation requirements, and the manufacturer's installation instructions. Evidence of suitability (thermal/fire and WHS documentation) shall be provided for the nominated SKUs.