ICICI Bank

Interface Specification Document

ICICI Bank

Table of Contents

Chapter 1: Introduction 3
Chapter 2: API Severity 4
Chapter 3: Initiate Sale 6
Chapter 4: Generate OTP 17
Chapter 5: Verify OTP 18
Chapter 6: Authorize 20
Chapter 7: Authorization Redirect Request 23
Chapter 8: Payment Advice 28
Chapter 9: Settlement Advice 30
Chapter 10: Generate QR 33
Chapter 11: Refund/Auth/Void 38
Chapter 12: Transaction Status 41
Chapter 13: Settlement Status 45
Chapter 14: Settlement Summary Request Parameters 48
Chapter 15: Settlement Details Request Parameters 51
Chapter 16: Get Card Bin 55
Chapter 17: UserCancel API 58
Chapter 18: Get Service Charges API 60
Sample HTML for Standard Mode Integration 63
Sample HTML for Direct Mode Integration 64
Payment Response 65
Refund/Auth Response 66
Transaction Status Response 66
Settlement Status Response 67
Hash Calculation 68
Hash Calculation (v2) 70
Sample API Request and Response 71
URLs 75

Chapter 1: Introduction

This document provides detailed integration process for Merchants to process payments through Payment Gateway. This integration will allow the consumers to select payment options, provide payment instrument credentials and process payments on the Merchant website.

Direct Integration mode

Step 1: All the payment details will be collected on the Merchant website for payment transaction.

Step 2: Merchant submits the details to sale URL in a server-to-server call (initiateSale API call). The initiateSale API responds back with response parameters as part of API Response. Browser is not involved in this step.

Step 3: Merchant handles API response and does the following:

1. Redirection (for 3DSecure on Card Issuer's domain)

When showOTPCapture is 'N' in the API Response, follow further steps:

1) Redirect to the redirect URI available in the initiateSale API Response with relevant parameters
2) Once Authentication and Authorization is done the response will be posted back (via browser POST) to the merchant's return URL.

2. Seamless

When showOTPCapturePage is 'Y' in the API Response, further Steps:

1) Merchant submits generateOTP GET request to the generateOTP URI available in the initiateSale response with relevant parameters. Response will be provided as json.
2) After successful generateOTP, merchant captures OTP on their domain and submits verifyOTP POST request to the verifyOTP URI available in the initiateSaleResponse with json request parameters.
3) Merchant can resend generateOTP requests up to 3 times and verify OTP.
4) After successful verifyOTP, merchant submits authorize POST request to the authorize URI available in the initiateSale Response with json request parameters. Response will be provided as json.

Chapter 2: API Severity

The APIs are categorized into severity levels based on the criticality or the sensitivity of the processing or data that it handles. The table below gives information on how severity is determined.

Severity Level	Guidelines for classifying an API at this level
High	1. APIs which are used for transaction generation using parameters coming from request. 2. APIs that can modify or add data in the system. 3. APIs that contain sensitive/PII data. If any of the above is true for an API, then it should fall under this severity.
Medium	1. APIs used for viewing transaction information 2. All inbound web API's that is not fitting in HIGH severity.
Low	1. Outbound APIs (e.g., Advice/Notifications) sent from system. 2. Any others

Below table provides the API wise severity level.

API Name	Severity
Initiate Sale	High
Generate OTP	High
Verify OTP	High
Authorize	High
Authorization Redirect Request	Medium
Payment Response	High
Payment Advice	Low
Settlement Advice	Low
Generate QR	High
MerchantCreditToCustomer Request	High

Refund/Auth/Void Request	High
Transaction Status Request	Medium
Settlement Status Request	Medium
Settlement Summary Request	Medium
Settlement Details Request	Medium
Get Card Bin Request	Medium
User Cancel	High
Get Service Charges	Medium

Chapter 3: Initiate Sale

The Sale Request is a json request.

The following URL can be used to initiate a sale:

URL - https://pgpay.icicibank.com/pg/api/v2/initiateSale

3.1 Initiate Sale Request Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant account ID	Numeric	20	Yes	Merchant account ID
merchantTxnNo	Txn ref Number	Alphanumeric	20	Yes	Unique ref no to identify the request. Should have only alphanumeric characters. No other characters allowed.
amount	Transaction amount	Numeric	9,2	No	9 significant and 2 decimal/precision e.g., nnnnnnnnn.nn
currencyCode	Transaction Currency	Numeric	3	Yes	356
payType	Possible values are 0, 1 Where, 0 = Standard (Redirection) 1 = Direct (Seamless)	Numeric	NA	Yes	Implemented for both '0' and '1'
customerEmailID	Email ID of customer	Alphanumeric (confirm special characters like @, #, $, %, etc)	48	Yes	Send notification emails to the customer email id.

transactionType	Type of Transaction • SALE	Alphanumeric	NA	Yes	Type of transaction. SALE
paymentMode	Payment instrument restriction list CSV, • CARD • NB • WALLET • UPI	Alphanumeric	NA	C	Can be used to restrict the payment options. For payType = 1, this field should indicate the exact paymentMode. For AADHAAR the payType has to be 1.
returnURL	Return URL after transaction completion	Alphanumeric (confirm special characters like @, #, $, %, etc)	128	C	Call back url on which response will be posted payment success/rejection. If available in request, the same would be used for response else the preconfigured URL of the merchant would be used. In case the transaction involves OTP capture on merchant page then the return URL is not used.
txnDate	Transaction Date	Numeric	14	Yes	YYYYMMDDHHMISS
cardNo	Card Number / Token Number (in case tokenized card)	Numeric	19	C	Mandatory, if payType is '1' and paymentMode is CARD
cardExpiry	Card expiration (YYYYMM)	Numeric	6	C	Mandatory, if payType is '1' and paymentMode is CARD
nameOnCard	Cardholder Name	Alphanumeric	45	C	Mandatory, if payType is '1' and paymentMode is CARD
cvv	Card verification value	Numeric	4	C	Mandatory, if payType is '1' and paymentMode is CARD. Optional in case token number is passed in cardNo field
tokenCryptogram	Cryptogram / TAVV received from TRG/T for transacting using	Alphanumeric	128	C	Can contain Alphanumeric & Base64 characters.

	token number				
tokenRefId	Token ReferenceID corresponding to the token number	Alphanumeric	64	No	Optional.
saveCardIndicator	Customer authorization to tokenize the card	Alpha	1	No	Y / N. Default is N Y – Indicates that the customer has opted to tokenize the card. Applicable only if the card passed is an actual card (not applicable for token card No)
authOnlyIndicator	Indicates the transaction as an authentication only transaction.	Alpha	1	No	Y / N. Default is N. Y – The transaction is on for authentication. Save card indicator would also need to be sent as for authOnly to work. This field is for supporting Rupay tokenization with Authentication (no authorization). Note: amount field is not required for authOnly transaction.
tokenizeOnAuth	Indicates whether to tokenize the card during Authentication Only transaction	Alpha	1	No	Y / N. Default is N. Y – Tokenize the card du the transaction. Auth only indicator would also need to be sent as Y for this to work. This field is for supporting Rupay tokenization with Authentication (no authorization).
panReferenceId	PAN reference Id of the card generated during the earlier tokenization call	Alpha	64	C	This will be used for authentication & tokenization. Either card number or panReferenceId should be present in the request.

					Auth Only indicator would also need to be Y for this work.
customerUPIAlias	Customer's Alias	Alphanumeric	45	C	If paymentMode is UPI then this field will be used to the payer's UPI Alias (VPA)
aggregatorID	Merchant Aggregator ID	Alphanumeric	20	C	Only applicable for Aggregator's
customerName	Customer Name	Alphanumeric	45	No	-
customerMobileNo	Customer Mobile No	Numeric	13	No	-
invoiceNo	Merchant Invoice No	Alphanumeric	32	No	-
addlParam1	Additional info 1	Alphanumeric	64	No	Additional information
addlParam2	Additional info 2	Alphanumeric	64	No	Additional information
country	Two-digit country code	Alphanumeric	2	No	e.g., IN, US
txnChannel	WEB, MOBILE	Alphanumeric	10	No	If nothing is sent, then WEB is taken by default.
terminalID	Terminal ID provided by acquirer	Alphanumeric	8	C	Contact support on how to use this field. Not for PG.
customerID	ID of customer as identified by Merchant	Alphanumeric	48	No	For Broker integration: customerID as registered in merchant account. For Nach debit request this field is mandatory and should match with the customerID sent in the registration of Nach request.
accountNo	The customer account number	Alphanumeric	16	No	For Broker integration: If merchant needs to validate the account from which payment is made. If not sent, then the registered

					account details of customerID would be used.
accountIFSC	The IFSC code	Alphanumeric	12	No	For Broker integration: The IFSC Code of the accountNo If not sent, then the registered account details of customerID would be used.
gstIn	GSTIN of the merchant	Alphanumeric	15	C	GSTIN of the merchant. Required if gst details are passed on by the merchant.
gst	GST amount	Numeric	9.2	C	The GST amount calculated by the merchant.
cgst	The CGST amount.	Numeric	9,2	C	The CGST amount.
Sgst	The SGST amount.	Numeric	9,2	C	The SGST amount.
igst	The IGST amount.	Numeric	9,2	C	The IGST amount.
cess	CESS amount	Numeric	9,2	C	CESS amount
gstIncentive	GST Incentive	Numeric	9,2	C	GST Incentive
gstPercentage	GST Percentage used.	Numeric	2	C	GST Percentage used.
udfFields	UDFFields Json Object to send user defined fields.	Json	NA	No	UDFFields Json Object which is used to pass user defined fields (like udf21, udf22, udf23, udf24,....., udf35).
billingData	Customer Data Json Object	Json	NA	No	Customer Data Json Object
shippingData	Customer Data Json Object	Json	NA	No	Customer Data Json Object
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Following fields are AADHAAR specific and mandatory for paymentMode of AADHAAR					
rdsId	Unique ID of the Registered device service	Alphanumeric	16	C	Provided by the registered device service
rdsVer	Registered device service version	Alphanumeric	12	C	-
dpId	Unique code assigned to RD provider	Alphanumeric	24	C	Provided by the register device (RD)
mi	Model of the registered device	Alphanumeric	12	C	Model of the registered device
mc	Public key certificate the registered device	Alphanumeric	2048	C	Public key certificate the registered device
dc	Unique device code of the registered biometric device	Alphanumeric	48	C	Unique device code of the registered biometric device
paymentInstID	Aadhaar Number	Alphanumeric	12	C	
bankiin	IIN of the bank		6	C	
Hmac	HMAC for the pidData		128	C	Provided by the RD
pidFormatType	X		1	C	Currently only “X” (XML) supported
pidData	Encrypted pid data		3000	C	Provided by the register device service
imageType	The fingerprint image type		3	C	Currently only “FMR” is supported
sessionKey	Session key used for pidData encryption		512	C	Provided by the RD

aadhaarCertificate	The certificateID of the UIDAI public certification used to encrypt the pidData		8		YYYYMMDD

UDF Fields JSON Object

Parameter	Description	Type	Size	Mandatory	Remarks
udf21	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf22	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf23	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf24	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf25	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf26	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf27	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf28	User Defined Field	Alphanumeric (All special	128	No	User Defined Field

		characters @, #, $, %, etc)			
udf29	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf30	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf31	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf32	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf33	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf34	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field
udf35	User Defined Field	Alphanumeric (All special characters @, #, $, %, etc)	128	No	User Defined Field

Customer Data JSON Object

These are an array of JSON objects, representing a customer record specific to business or transaction purposes.

Parameter	Description	Type	Size	Mandatory	Remarks
firstName	Customer first name	Alphanumeric	64	No	Customer First Name
lastName	Customer last name	Alphanumeric	64	No	Customer Last Name
address	Customer address	Alphanumeric (All special characters @, #, $, %, etc)	1500	No	Customer address
city	User Defined Field	Alphanumeric	64	No	User Defined Field
state	User Defined Field	Alphanumeric	64	No	User Defined Field
country	User Defined Field	Alphanumeric	64	No	User Defined Field
zipCode	User Defined Field	Numeric	12	No	User Defined Field
emailId	User Defined Field	Alphanumeric	64	No	User Defined Field
mobileNo	User Defined Field	Numeric	128	No	User Defined Field

3.2 Initiate Sale Response Parameters

The following Initiate Sale Response parameters will be available as json response.

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure	Alphanumeric	4	Yes	R1000 – Request Initiated successfully Any other value indicates failure.
responseDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantId	Merchant account ID	Numeric	20	Yes	Echo of request field
aggregatorID	Merchant aggregator ID	Numeric	20	C	Echo of request field (if available in request)
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	Echo of request field Should have only alphanumeric characters. No other characters allowed.
redirectURI	Redirection URL	Alphanumeric (All special characters @, #, $, %, etc)	128	C	Will be available in case merchant is required to redirect to complete payment authorization. Either this field or showOTPCapturePage field will be available in response.
generateOTPURI	generateOTPUrl	Alphanumeric (All special characters @, #, $, %, etc)		C	Will be available when showOTPCapturePage is 'Y'
verifyOTPURI	verifyOTPURL	Alphanumeric (All special characters @, #, $, %, etc)		C	Will be available when showOTPCapturePage is 'Y'

authorizeURI	authorizeURL	Alphanumeric (All special characters @, #, $, %, etc)		C	Will be available when showOTPCapturePage is 'Y'
showOTPCapturePage	Show OTP Page indicator	Alpha	1	C	Y / N Y – Merchant should display a page to for OTP. Please do contact integration team for OTP capture page requirements
tranCtx	The transaction context generated by the PG	Alphanumeric	512	C	Needs to be sent as is to the redirectURI / authorizeURI endpoint
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Chapter 4: Generate OTP

Merchant needs to send request if showOTPCapturePage is 'Y' in initiate sale

response. The generateOTP is a GET request.

<genearateOTP URI available in initiateSale Response>?tranCtx=<tranCtx available in sale Response>

4.1 Generate OTP Response Parameters

The Generate OTP Response parameters will be available as json response.

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure	Alphanumeric	4	Yes	0000 – Success
responseDescription	Response Description	Alphanumeric	NA	Yes	OTP Generated Successfully -
status	Status of transaction	Alphanumeric	-	Yes	Status of transaction
merchantId	Merchant account ID	Numeric	20	C	merchantId of original transaction
aggregatorID	Merchant aggregator ID	Numeric	20	C	aggregatorId of original transaction
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	merchantTxnNo of original transaction
secureHash	Hash value	Alphanumeric	64	C	Check Hash Calculation for logic

Chapter 5: Verify OTP

The Merchant needs to send request after generate OTP request is successful. The verifyOTP request is a POST request.

<verifyOTP URI available in initiateSale Response> Json Request Message as below:

5.1 Verify OTP Request Parameters

Will be sent as json request

Param	Description	Type	Size	Mandatory	Remarks
tranCtx	The transaction context generated by the PG	Alphanumeric	512	Yes	tranCtx sent in initiateSale Response
otp	OTP received by customer	Numeric	6	Yes	Merchant needs to provide OTP received by customer

5.2 Verify OTP Response Parameters

Will be available as json response

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure	Alphanumeric	4	Yes	0000 – Success
responseDescription	Response Description	Alphanumeric	NA	Yes	OTP verified successfully
status	Status of transaction	Alphanumeric	-	Yes	Status of transaction
merchantId	Merchant account	Numeric	20	C	merchantId of original transaction

aggregatorID	Merchant aggregator ID	Numeric	20	C	aggregatorId of original transaction
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	merchantTxnNo of original transaction
nwAuthRefNo	Network Auth reference	Alpha	64	C	Currently it is only applicable for Rupay card. This will be available if customer has opted for saveCard & authOnly as Y. This value needs to be used when initiating tokenization with RuPay's Token Server.
panReferenceId	Pan Reference ID the card number this token is generated	Alpha	64	C	It will be present in the response if tokenizeOnAuth was Y in the initiateSale request.
maskedCardNo	Masked Card number	Alpha	19	C	It will be present in the response if tokenizeOnAuth was Y in the initiateSale request.
tokenReferenceId	Token reference Id identify a token for a card number	Alphanumeric	64	C	It will be present in the response if tokenizeOnAuth was Y in the initiateSale request.
tokenReferenceIdHash	Token reference id hash to validate t token reference id	Alphanumeric	64	C	It will be present in the response if tokenizeOnAuth was Y in the initiateSale request.
cardExpiry	Card expiration (YYYYMM)	Numeric	6	C	It will be present in the response if tokenizeOnAuth was Y in the initiateSale request.
secureHash	Hash value	Alphanumeric	64	C	Check Hash Calculation for logic

Chapter 6: Authorize

The merchant needs to send request after verify OTP request is successful. The authorize request is a POST request.

<authorizeURI available in initiateSale Response>

6.1 Authorize Request Parameters

Will be sent as json request

Param	Description	Type	Size	Mandatory	Remarks
tranCtx	The transaction context generated by the PG	Alphanumeric	512	Yes	tranCtx sent in initiateSale Response

6.2 Authorize Response Parameters

Will be available as json response.

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure	Alphanumeric	4	Yes	000 and 0000 – Success R1000 – Request Initiated successfully (mostly used for UPI Initiation where the payment is out of band.) Any other value indicates failure.
respDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantId	Merchant account ID	Numeric	20	C	Echo of request field

aggregatorID	Merchant aggregator ID	Numeric	20	C	Echo of request field (if available request)
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	Echo of request field
txnID	The unique ref number generated by the PG	Numeric	24	C	The unique ref number generated by the PG
paymentDateTime	Authorization date time	Numeric	16	C	YYYYMMDDHHMISS
paymentID	The authorization/payment generated by the authorization system	Numeric	24	C	The authorization/payment generated by the authorization system
paymentMode	The payment mode used CARD, NB, UPI, Wallet	Alphanumeric	12	C	Available only to merchants who have opted for this. Determined using configuration or using the request url used.
paymentSubInstType	The payment sub instrument type. Will contain the bank name case of payment using NB case of card payment this will be either DC or CC.	Alphanumeric	64	C	The payment sub instrument type. Will contain the bank name case of payment using NB case of card payment this will be either DC or CC.
Amount	The amount paid.	Numeric	9,2	C	The amount paid.
txnChannel	The channel used for transactions (WEB)	Alphanumeric	5	C	For POS, this will be returned always for successful txns. If not available, it is to be treated WEB transaction.

customerMobileNo	The customer mobile num as sent by merchant	Alphanumeric	13	C	Echo of request field. Available based on configuration sale url used
customerEmailId	The emailID of the custom as sent by merchant	Alphanumeric (special characters like @, #, $, %, etc)	48	C	Echo of request field Available based on configuration sale url used
addlParam1	Additional info 1	Alphanumeric	64	C	Echo of request field
addlParam2	Additional info 2	Alphanumeric	64	C	Echo of request field
convenienceFee	Convenience fee charged customer	Numeric	9, 2	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter
serviceTax	Service tax	Numeric	9, 2	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter
cardNetwork	Card Network	Alphanumeric	12	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter
nwAuthRefNo	Network Auth ref No	Alpha	64	C	Currently it is only applicable for Rupay cards. This will be available if customer has opted for saveCar This value needs to be used when initiating tokenization with RuPay's Token Server.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Chapter 7: Authorization Redirect Request

The Merchant needs to redirect to the redirect URI in the following request format when showOTPCapturePage is 'N' is sale response.

<redirectURL available in Sale Response>?tranCtx=<tranCtx available in sale Response>

The payment response would be posted back to the merchants return URL (in form url encoded format) as form post.

7.1 Payment Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicate success/failure	Alphanumeric	4	Yes	000 and 0000 – Success R1000 – Request Initiated successful (mostly used for UPI Initiation where the payment is out band.) Any other value indicates failure.
respDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantId	Merchant account ID	Numeric	20	Yes	Echo of request field
aggregatorID	Merchant aggregator ID	Numeric	20	C	Echo of request field (if available in request)
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	Yes	Echo of request field
txnID	The unique ref number generated by the PG	Numeric	24	Yes	The unique ref number generated by the PG
paymentDateTime	Authorization date time	Numeric	14	Y	YYYYMMDDHHMISS
paymentID	The authorization / payment generated by the authorization system	Numeric	24	C	The authorization / payment generated by the authorization system
paymentMode	The payment mode used CARD, NB, Wallet, UPI, etc.	Alphanumeric	12	C	Available only for the merchants who have opted for this. Determined using configuration or using the sale request url used.

paymentSubInstType	The payment sub instrument type. Will contain the bank name in case of payment using NB. In case of card payment this field will be either DC or CC.	Alphanumeric	64	C	The payment sub instrument type. In case of UPI, the values will be: SAVING CREDIT PPIWALLET
Amount	The amount paid	Numeric	9,2	C	The amount paid
oth_charge	Charges applied for the transaction	Numeric	9,2	C	Charges applied for the transaction
txnChannel	The channel used for transactions (WEB)	Alphanumeric	5	C	Default, it is to be treated as WEB transaction.
customerMobileNo	The customer mobile number as sent by merchant	Alphanumeric	13	C	Echo of request field. Available based on configuration / sale used.
customerEmailID	The emailID of the customer as sent by merchant	Alphanumeric (special characters @, #, $, %, etc)	48	C	Echo of request field. Available based on configuration / sale used.
addlParam1	Additional info 1	Alphanumeric	64	C	Echo of request field
addlParam2	Additional info 2	Alphanumeric	64	C	Echo of request field
convenienceFee	Convenience fee charged to customer	Numeric	9,2	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter
serviceTax	Service tax	Numeric	9,2	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter
cardNetwork	Card Network	Alphanumeric	12	C	Applicable only if merchant has specified for this additional field in the returnURL addlResParams parameter

nwAuthRefNo	Network Auth ref No	Alpha	64	C	Currently only applicable for Rupay cards. This will be available if customs have opted for saveCard. This value needs to be used when initiating tokenization with RuPay's Toke Server.
panReferenceId	Pan Reference ID of the card number for this token is generated	Alpha	64	C	It will be present in response if tokenizeOnAuth was Y in the initiateSale request.
maskedCardNo	Masked Card number	Alpha	19	C	It will be present in response if tokenizeOnAuth was Y in the initiateSale request.
tokenReferenceId	Token reference Id to identify a token for a card number	Alphanumeric	64	C	It will be present in response if tokenizeOnAuth was Y in the initiateSale request.
tokenReferenceIdHash	Token reference id hash to validate the token reference id	Alphanumeric	64	C	It will be present in response if tokenizeOnAuth was Y in the initiateSale request.
cardExpiry	Card expiration (YYYYMM)	Numeric	6	C	It will be present in response if tokenizeOnAuth was Y in the initiateSale request.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Note: Only POST parameters are considered for secureHash calculation. Query parameters are not considered for secureHash calculation.

Sample Response form

```
<form id='myForm' name='myForm' action='${merchantReturnURL}'
method='post' enctype="application/x-www-form-urlencoded">

<input type="hidden" name="responseCode" value="000" />

<input type="hidden" name="respDescription" value="SUCCESS" />

<input type="hidden" name="merchantId" value="M000001" />

<input type="hidden" name="merchantTxnNo" value="M0099999221" />

<input type="hidden" name="txnID" value="T1472640294491" />

<input type="hidden" name="paymentDateTime" value="20160831041454" />

<input type="hidden" name="paymentID" value="006503" />

<input type="hidden" name="secureHash"
value="39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2"/>

</form>
```

Chapter 8: Payment Advice

In case merchant wants payment status to be updated to its system, Transaction Gateway can push the status of the payment. Payment advice is same as payment response but only used by the payment gateway to inform the merchant system of a later change in transaction status which can occur after the online transaction has been completed. This will be a server-to-server API call (not involving the browser). Merchant has to expose a URL for consuming the payment advice. The parameters will be sent as POST request, and the parameters will be same as that used for the online payment response.

Any response with http status code of 200 is considered as successful delivery of the advice. Advice can be configured to be retried in case of unsuccessful delivery (non 200 http status code).

Note: The addlResParams if specified in returnURL are only used for redirection parameters and not used for payment advice.

Payment advice message by default would be posted to the advice url of the merchant with content- type of “application/x-www-form-urlencoded”. In this format the request body would contain all the parameters in name value pairs. The merchant server can handle this in the same manner how it handles any form post.

responseCode=0000&respDescription=Transaction%20successful&merchantId=T_05022&merch antTxnNo=
638948982&txnID=T002473066701&paymentDateTime=20210817060032&paymentID=

In case the merchant has opted for json format (during merchant onboarding). The same advice above would be sent in json format. For json message, the content type would be “application/json”

{
"responseCode":"0000", "respDescription":"Transaction successful", "merchantId":"T_05022", "merchantTxnNo":"638948982", "txnID":"T002473066701", "paymentDateTime":"202108170 60032", "paymentID":"700788003737",

Any response with http status code of 200 is taken as a successful response.

Chapter 9: Settlement Advice

Settlement advice will be a server-to-server API call initiated by the system. Merchant must expose a URL for consuming the settlement advice. The parameters will be sent as POST request (with json data in POST body).

9.1 Settlement Advice Request Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
aggregatorID	Merchant aggregator	Alphanumeric	20	C	Echo of request field (if available in original payment request)
merchantId	Merchant account ID	Alphanumeric	20	Yes	Merchant account ID
merchantTxnNo	Merchant Txn ref Num	Alphanumeric	20	Yes	Echo of request field, the merchant txn reference no. sent by the merchant while initiating the payment request. For payment against invoices (orders created in ICICI Bank system), this field will be an auto generated field.
invoiceNos	List of Invoices (comm separated) for which t payment was done	Alphanumeric	160	C	Echo of request field. In case of payment against multiple invoices, this field will contain a separated coma list of invoice reference nos.
paymentMode	The payment mode/type used for the payment	Alphanumeric	32	C	e.g., CARD, NB, Wallet, UPI

paymentSubInstType	The sub type for the payment mode used.	Alphanumeric	32	C	If paymentMode is CARD then possible values would be DC, CC. For other payment modes it will be NA (Not Applicable).
txnChannel	The txn channel used (Applicable only for CARD)	Alphanumeric	32	C	Default value is WEB.
txnAmount	Transaction amount	Amount	9,2	C	Applicable only if the charges are paid by Merchant & certified to receive this field
txnCharges	Applicable only if the charges are paid by Merchant & certified to receive this field	Amount	9,2	C	Applicable only if the charges are paid by Merchant & certified to receive this field
serviceTax	Applicable only if the charges are paid by Merchant and certified to receive this field.	Amount	9,2	C	Applicable only if the charges are paid by Merchant and certified to receive this field.
settlementID	The settlementID/credit reference no linked to invoice settlement	Alphanumeric	32	Yes	The settlementID/credit reference no linked to invoice settlement.
settlementDate	Settlement Date	Alphanumeric	8	Yes	YYYYMMDD
settlementAccount	Settlement Account	Alphanumeric	21	Yes	Available only if the merchant has certified to receive this field.
settlementAccountIFSC	Settlement Account IFSC Code	Alphanumeric	8	Yes	Available only if the merchant has certified to receive this field.
settledAmount	Settlement Amount	Amount	9,2	Yes	Available only if the merchant has certified to receive this field.

cardNetwork	Card network	Alpha	8	Yes	Available only if the merchant has certified to receive this field and the paymentMode is Card. Possible values are VISA / MasterCard / AMEX / RUPAY
addlParam1	Additional Param sent initial sale request	Alphanumeric	64	C	Echo of request field (if present in request)
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Request would be in json format. Sample request is given below.

{

“aggregatorID”: “A001”,

“merchantId”: “123243”,

“merchantTxnNo”: ”RF12937”,

“invoiceNos” : “343223”,

“settlementID”: ”A00121-20171101-010”,

“settlementDate”: ”20171101”,

“paymentMode”: ”card”,

“paymentSubInstType”: ”DC”,

“cardNetwork”: “VISA”,

“txnChannel”: ”WEB”,

“secureHash”:
“39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”

}

Any response with http status code of 200 is taken as a successful response.

Chapter 10: Generate QR

10.1 Generate QR Request Parameters

Below are the field details for GenerateQR Request Parameters:

Parameter	Description	Type	Size	Mandatory	Remarks
merchantd	Merchant account ID	Numeric	12	Yes	Merchant account ID
merchanRefNo	Txn ref Number	Alphanumeric	12	Yes	Unique ref no to identify the request.
amount	Transaction amount	Numeric	9,2	Yes	9 significant and decimal/precision e.g., nnnnnnnnn.nn
currency	Transaction Currency Code	Numeric	3	Yes	356
emailID	Email ID of customer	Alphanumeric (special characters @, #, $, %, etc)	36	Yes	In case Customer email ID is not available, send guest@ICICIBank.com
mobileNo	Customer Mobile No	Numeric	15	No	Customer Mobile No
invoiceNo	Merchant Invoice No	Alphanumeric	32	C	Merchant Invoice No
requestType	Request Type	Alphanumeric	12	C	Applicable values is “UPIQR”
aggregatorID	Merchant Aggregator ID	Alphanumeric	20	C	Only applicable for Aggregator’s
taxableValue	Taxable amount	Numeric	9,2	C	Taxable amount

gstIn		Alphanumeric	15	C	GSTIN of the merchant. Required if gst details are passed on by the merchant.
gst		Numeric	9,2	C	The GST amount calculated by the merchant
cgst		Numeric	9,2	C	The CGST amount
sgst		Numeric	9,2	C	The SGST amount
Igst		Numeric	9,2	C	The IGST amount
cess		Numeric	9,2	C	CESS amount
gstIncentive		Numeric	9,2	C	GST Incentive
gstPercentage		Numeric	2	C	GST Percentage used.
customerID	Customer ID	Alphanumeric	15	No	-
customerN	Customer Name	Alphanumeric	45	No	-
invoiceDate	Invoice Date	Numeric	8	No	YYYYMMDD
accountNo		Alphanumeric	16	No	For Broker integration: If a merchant needs to validate the account from which payment is made. If not sent, then the registered account details of customerID would be used.

accountIFSC		Alphanumeric	12	No	For Broker integration: The IFSC Code of the accountNo. If not sent, then the registered account details of customerID would be used.
udfFields	UDFFields Json Object to send user defined fields	Json		No	UDFFields Json Object to send user defined fields
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic.

UDF Fields Json Object

Parameter	Description	Type	Size	Mandatory	Remarks
udf1	User Defined Field	Alphanumeric	128	No	User Defined Field
udf2	User Defined Field	Alphanumeric	128	No	User Defined Field
udf3	User Defined Field	Alphanumeric	128	No	User Defined Field
udf4	User Defined Field	Alphanumeric	128	No	User Defined Field
udf5	User Defined Field	Alphanumeric	128	No	User Defined Field
udf6	User Defined Field	Alphanumeric	128	No	User Defined Field
udf7	User Defined Field	Alphanumeric	128	No	User Defined Field
udf8	User Defined Field	Alphanumeric	128	No	User Defined Field
udf9	User Defined Field	Alphanumeric	128	No	User Defined Field
udf10	User Defined Field	Alphanumeric	128	No	User Defined Field
udf11	User Defined Field	Alphanumeric	128	No	User Defined Field
udf12	User Defined Field	Alphanumeric	128	No	User Defined Field

udf13	User Defined Field	Alphanumeric	128	No	User Defined Field
udf14	User Defined Field	Alphanumeric	128	No	User Defined Field
udf15	User Defined Field	Alphanumeric	128	No	User Defined Field

10.2 Generate QR Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
returnCode	Return code indicating success/failure of the generation request	Numeric	3	Yes	200 – Success Any other value failure.
responseDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantID	Merchant account ID	Alphanumeric	20	Yes	Echo of request field
aggregatorID	Merchant account ID	Alphanumeric	20	C	Echo of request field
merchantRefNo	Merchant Txn ref Number	Alphanumeric	12	C	Echo of request field
upiQR	Generated UPI QR String	Alphanumeric	NA	C	Generated UPI QR String

Sample Request of Generate QR request

```
curl --location 'https://pgpayuat.icicibank.com/tsp/pg/api/generateQR' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'merchantId=T_S00067' \
--data-urlencode 'merchantRefNo=208850085911' \
--data-urlencode 'amount=40' \
--data-urlencode 'currency=356' \
--data-urlencode 'mobileNo=8208191623' \
--data-urlencode 'emailID=test@gmail.com' \
--data-urlencode 'requestType=UPIQR' \
--data-urlencode 'customerID=CSDRR1' \
--data-urlencode 'invoiceDate=20251008' \
--data-urlencode
'secureHash=5c860cb28cb5a0e94911cb9759f1d39cf5fbb73388499d7783480d7da510f730' \
--data-urlencode 'accountNo=001701378981' \
--data-urlencode 'accountIFSC=ICIC0000017' \
--data-urlencode 'aggregatorID=J_D0001'
```

Sample Response (json) of Generate QR request

{"respHeader":{"returnCode":200,"desc":"Success","upiRespDesc":"SUC"},"respBody":{"merchantID":"T_S00067","aggregatorID":"J_D0001","merchantRefNo":"208850085911","bharatQR":null,"upiQR":"upi://pay?pa=phicomm@icici&pn=Saavn Media&mc=3018&tr=1773361794809801&am=40.00&cu=INR&invoiceDate=2025-10-08T00:00:00+05:30","expiry":null,"serviceChargeUPI":"0","serviceChargeBharatQR":null}}

Chapter 11: Refund/Auth/Void

11.1 Refund/Auth/Void Request Parameters

This is a server-to-server API Call which uses POST method with content type as "application/x- www- form-urlencoded"

Parameter	Description	Type	Size	Mandatory	Remarks
merchantID	Merchant account ID	Alphanumeric	20	Yes	Echo of request field
aggregatorID	Aggregator ID	Alphanumeric	20	C	Required if the original txn was initiated from Aggregator
merchantTxnNo	Txn ref Number	Alphanumeric	20	Yes	The new reference No. for this request.
originalTxnNo	Original txn refNo	Alphanumeric	20	yes	The reference No. of the initial transaction for which the refund/auth/void is initiated.
amount	Amount to be authorized or refunded to the customer	Numeric	9,2	Yes	9 significant and 2 decimal/precision. This cannot be more than the original transaction amount. This field should be set to 0 for void.
transactionType	Type of Transaction REFUND	Alpha	6	Yes	Type of REFUND transactions
addlParam1	Additional info 1	Alphanumeric	64	No	Additional information.

addlParam2	Additional info 2	Alphanumeric	64	No	Additional information.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

11.2 Refund/Auth/Void Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure	Numeric	3	Yes	000 – Success Failure for any other value.
respDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantId	Merchant account ID	Alphanumeric	20	C	Echo of request field
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	Echo of request field
txnID	The unique ref number generated by the PG	Numeric	24	C	The unique ref number generated by the PG
paymentDateTime	Authorization date time	Numeric	14	C	YYYYMMDDHHMISS
txnAuthID	The authorization / payment ID generated by the authorization system	Alphanumeric	24	C	The authorization / payment ID generated by the authorization system
addlParam1	Additional info 1	Alphanumeric	64	C	Echo of request field

addlParam2	Additional info 2	Alphanumeric	64	C	Echo of request field
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation in Appendix

Chapter 12: Transaction Status

12.1 Transaction Status Request Parameters

This is a server-to-server API Call which uses POST method with content type as "application/x-www- form-urlencoded".

Parameter	Description	Type	Size	Mandatory	Remarks
merchantID	Merchant account ID	Alphanumeric	20	Yes	Merchant account ID
aggregatorID	Aggregator ID	Alphanumeric	20	C	Required if the original txn was initiated from Aggregator
merchantTxnNo	Txn ref Number	Alphanumeric	20	Yes	Same as originalTxnNo.
originalTxnNo	Original Txn ref Number	Alphanumeric	20	Yes	The original refNo for which status is requested.
transactionType	Type of Transaction STATUS	Alpha	6	Yes	Type of transaction (Status)
oth_charge	Charges applied on the transaction	Numeric	9,2	C	Charges applied on the transaction
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

12.2 Transaction Status Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure of the transaction status request	Alphanumeric	4	Yes	000 / 0000 – Success Any other value indicates status request failure / original transaction not found. For status of the original txn always check txnStatus and txnResponseCode.
respDescription	Description of failure	Alphanumeric	45	Yes	Ignore for success response.
merchantID	Merchant account ID	Numeric	20	Yes	Echo of request field
aggregatorID	Merchant Aggregator ID	Numeric	20	C	Echo of request field
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	Echo of request field
txnStatus	Status of original txn	ENUM	3	Yes	REQ – Request received and in process SUC – Transaction Successful REJ – Transaction Rejected ERR – Error in transaction process
txnResponseCode	The response code for the original txn	Alphanumeric	24	Yes	Original txn response code. 000 / 0000 – Success Any other value indicates failure.
txnRespDescription	Response description for original txn	Alphanumeric	24	Yes	Response description for original txn

txnID	The unique ref number generated by the gateway	Alphanumeric	24	Yes	System generated Transaction ID
paymentDateTime	Authorization date time	Numeric	14	Yes	YYYYMMDDHHMISS
txnAuthID	The authorization / payment ID generated by the authorization system	Numeric	24	C	The auth ID generated by the bank.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Sample Transaction Status Check Request

```
curl --location &#39;https://pgpayuat.icicibank.com/tsp/pg/api/command&#39; \
--header &#39;Content-Type: application/x-www-form-urlencoded&#39; \
--data-urlencode &#39;merchantId=T_S00067&#39; \
--data-urlencode &#39;merchantTxnNo=Test03102025&#39; \
--data-urlencode &#39;originalTxnNo=7700206371536&#39; \
--data-urlencode &#39;transactionType=STATUS&#39; \
--data-urlencode
&#39;secureHash=8dead97d14d846cbb5674a46385675d242dbb35e54b37e423f241cbca85519f6&#
39; \
--data-urlencode &#39;addlParam1=Additional Information&#39;
```

Sample Transaction Status Check Response

{"txnRespDescription":"Transaction successful","secureHash":"2e2f67b7038a6f86d8383b59f8b7c6bf443b71d783212e9a29b6dc09abfbef12","amount":"550.00","txnResponseCode":"0000","txnAuthID":"811069696857","authCode":"7700201930022","respDescription":"Request processed successfully","paymentMode":"UPI","customerEmailID":"guest@icici.com","TransmissionDateTime":"20251003155304","oth_charge":false,"paymentInstId":"9552012231@upi","responseCode":"000","customerMobileNo":"7912403781","txnStatus":"SUC","merchantId":"T_S00067","merchantTxnNo":"7700206371536","addlParam1":"Additional Information","paymentDateTime":"20251003155335","txnID":"7700206371536"}

Chapter 13: Settlement Status

13.1 Settlement Status Request Parameters

Settlement status API should be used only to check the settlement status of the transaction and never used for checking the payment status of original transaction. The payment transaction gets reflected in settlement only after the settlement cycle which might take anywhere up to 12hrs.

This is a server-to-server API Call which uses POST method with content type as "application/x- www- form-urlencoded".

Parameter	Description	Type	Size	Mandatory	Remarks
merchantID	Merchant account ID	Alphanumeric	20	Yes	Merchant ID of original transaction.
aggregatorID	Aggregator ID	Alphanumeric	20	C	Aggregator ID of original transaction.
originalTxnNo	Original Txn ref Number	Alphanumeric	20	Yes	The original merchant refNo for which status requested.
transactionType	Type of Transaction SETTLSTATUS	Alpha	11	Yes	Type of Transaction SETTLSTATUS
SecureHash	Hash value	Alphanumeric	64	Yes	Check appendix for hash logic

13.2 Settlement Status Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
responseCode	Response code indicating success/failure of the transaction status request	Alphanumeric	4	Yes	000 / 0000 – Success Any other value indicates request failure / transaction found in settlement system. For settlement status of the t always check settlementStatus.
respDescription	Description of settlement status	Alphanumeric	45	Yes	Ignore for success response.
merchantId	Merchant account ID	Numeric	20	Yes	Echo of request field
aggregatorID	Merchant Aggregator ID	Numeric	20	C	Echo of request field
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	Yes	Echo of request field
settlementStatus	Status of settlement	Alpha	3	Yes	NSD – Not yet settled STD – Settled
txnStatus	Status of original txn	Alpha	3	Yes	REQ – Request received and process SUC – Transaction Successful REJ – Transaction Rejected ERR – Error in transaction process
txnResponseCode	The response code for the original txn	Alpha	4	Yes	Original txn response code. 000 / 0000 – Success Any other value indicates failure.

txnID	The unique ref number generated by the gateway	Alphanumeric	24	Yes	The unique ref number generated by the gateway.
settlementID	Settlement ID/UTR No.	Alphanumeric	24	C	Settlement ID for merchant or service provider. Valid only if settled.
settlementDate	Date of settlement	Numeric	8	C	YYYYMMDD Valid only if settled.
txnAmount	The transaction amount	Numeric	9,2	C	Applicable only if the charges are paid by the merchant and certified to receive this field.
txnCharges	Total charges	Numeric	9,2	C	Charges including tax
serviceTax	Service tax paid	Numeric	9,2	C	Applicable only if the charges are paid by the merchant and certified to receive this field.
settledAmount	Amount settled	Numeric	9,2	C	The amount settled for this transaction
settlementAccount	Account No	Alphanumeric	24	C	Account no to which the txn been settled into
settlementAccountIFSC	IFSC Code of the account	Alphanumeric	11	C	The IFSC Code of account No.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Chapter 14: Settlement Summary Request Parameters

14.1 Settlement Summary Request Parameters

Settlement status API should be used only to check the settlement status of the transaction and never used for checking the payment status of original transaction. The payment transaction gets reflected in settlement only after the settlement cycle which might take anywhere upto 12hrs.

Parameter	Description	Type	Size	Mandatory	Remarks
merchantID	Merchant account ID	Alphanumeric	20	Yes	Either of merchantID or aggregatorID should be present
aggregatorID	Aggregator ID	Alphanumeric	20	C	Echo of request field.
settlementDate	Settlement Date	Alphanumeric	8	Yes	YYYYMMDD
transactionType	Type of Transaction SETTLEMENTSUMMARY	Alphanumeric	17	Yes	Type of transaction SETTLEMENTSUMMARY
secureHash	Hash value	Alphanumeric	64	No	Check Hash calculation for logic

This is a server-to-server API Call which uses POST method with content type as "application/x- www- form-urlencoded”

14.2 Settlement Summary Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
error_code	Response code	Alphanumeric	4	Yes	000 / 0000 – Success Any other value indicates request failure / transaction n found in settlement system. For settlement status of the txn always check settlementStatus
merchantId	Merchant account	Alphanumeric	20	Yes	Echo of request field
aggregatorID	Merchant Aggregator ID	Alphanumeric	20	C	Echo of request field
settlementDate	Settlement Date	Alphanumeric	12	C	Echo of request field
Payouts	All the settlement performed on the settlement Date	Alphanumeric	12	C	All the settlement performed on the settlement Date
account_no	Account number where the amount settled	Alphanumeric	32	Yes	Account number where the amount settled
ifsc_code	IFSC code of the account number	Alphanumeric	32	Yes	IFSC code of the account number
pay_amount	Amount settled	Numeric	9,2	Yes	Amount settled
settlementID	Settlement id	Alphanumeric	32	Yes	Settlement ID for merchant o service provider
settlement_currency	Settlement Currency	Numeric	3	Yes	356
trans_currency	Settlement Currency	Numeric	3	Yes	356

utr_no	UTR number	Alphanumeric	24	Yes	UTR number of the transfer.
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Chapter 15: Settlement Details Request Parameters

15.1 Settlement Details Request Parameters

This API needs to be called after settlement summary API for each settlementID received in the response. This API provides details of all the transactions that were settled under a particular settlementID. If there are more than 100 transactions settled under a particular settlementID then one API call will return only 100 transactions. Another API call with the same settlementID and passing the last transaction id needs to be made to get next set of 100 transactions and so on to get all transactions under that settlementID.

This is a server-to-server API Call which uses POST method with content type as "application/json".

Parameter	Description	Type	Size	Mandatory	Remarks
merchantID	Merchant account ID	Alphanumeric	20	Yes	Either of merchantID OR aggregatorID should be present
aggregatorID	Aggregator ID	Alphanumeric	20	C	Either of merchantID OR aggregatorID should be present
providerID	Service provider ID	Alphanumeric	14	C	If the settlement id is for service provider
settlementID	SettlementID	Alphanumeric	32	Yes	Settlement ID
lastTxnID	Last txnid from the previous request.	Alphanumeric	32	No	Last transaction ID
secureHash	Hash value	Alphanumeric	64	No	Check Hash Calculation for logic

Settlement Details request API:

```
curl --location 'https://pgpayuat.icicibank.com/tsp/pg/api/settlementDetails' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'merchantId=T_03342' \
```

```
--data-urlencode 'settlementID=T03342000280190' \
--data-urlencode
'secureHash=180c2507bf70e81594075e916f874b2ba1ef1842a09612458452f3f7539e4239' \
--data-urlencode 'lastTxnID='
```

15.2 Settlement Details Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
error_code	Response code indicating success/failure of the request	Alphanumeric	4	Yes	000 / 0000 – Success Any other value indicates status req failure / original transaction not found. For status of the response always ch txnStatus and txnResponseCode
merchantID	Merchant account ID	Alphanumeric	20	Yes	Echo of request field
lasttxnID	Last txnid in the response	Alphanumeric	32	No	Last txnid in the response
Payouts					
merchantID	Merchant account ID	Alphanumeric	20	Yes	merchantID or providerID will be available
providerID	Service Provider	Alphanumeric	32	C	Either merchantID or providerID will be available
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	C	Merchant Txn ref Number
settlementStatus	Settlement status the transaction	Alpha	3	C	NSD – Not yet settled STD – Settled
txnStatus	Status of the original transact	Alpha	3	C	REQ – Request received and in pro SUC – Transaction Successful REJ – Transaction Rejected ERR – Error in transaction process
txnResponseCode	Txn response code	Alphanumeric	4	C	Original txn response code. 000 / 0000 – Success Any other value indicates failure.

txnID	Transaction ID generate PG	Alphanumeric	24	C	Transaction ID generate PG
paymentID	The authorization payment ID generated by the authorization system	Alphanumeric	24	C	The authorization payment ID generated by the authorization system
settlementAccount	Account number where the transaction was settled	Alphanumeric	21	Yes	Account number where the transaction was settled
settlementAccountIFSC	IFSC code of the account number	Alphanumeric	11	Yes	IFSC code of the account number
txnAmount	Transaction amount	Numeric	9,2	Yes	Transaction amount
txnCharges	Total charges	Numeric	9,2	C	Only available in case of merchant settlement
serviceTax	Service tax paid	Numeric	9,2	C	Only available in case of merchant settlement
settledAmount	Amount settled in the account	Numeric	9,2	Yes	Amount settled with merchant/service provider
utr_no	Utr number of the transfer	Alphanumeric	24	Yes	Utr number of the transfer
settlementDate	Date on which settlement was done	Alphanumeric	12	Yes	YYYYMMDD
transmissionDateTime	Time at which transaction was executed	Alphanumeric	12	Yes	YYYYMMDD
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation for logic

Settlement Details response API:

{"error_code":"000","merchantID":"T_03342","count":7,"Payouts":[{"merchantID":"T_03342","merchantTxnNo":"77563","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499484","paymentID":"10520592231","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 12:56:06"},{"merchantID":"T_03342","merchantTxnNo":"13689","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499495","paymentID":"906554130018","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 13:02:45"},{"merchantID":"T_03342","merchantTxnNo":"5761","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499497","paymentID":"83946778663","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 13:05:39"},{"merchantID":"T_03342","merchantTxnNo":"733A","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499508","paymentID":"90930961981","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 13:17:39"},{"merchantID":"T_03342","merchantTxnNo":"7318A","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499510","paymentID":"15684915903","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 13:27:58"},{"merchantID":"T_03342","merchantTxnNo":"1256A","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201499517","paymentID":"186648344624","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"100.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"100.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-07-28 13:37:07"},{"merchantID":"T_03342","merchantTxnNo":"1597169707","settlementStatus":"SETTLED","txnStatus":"SUC","txnResponseCode":"0","txnID":"7700201925306","paymentID":"54472510906","settlementAccount":"629405033171","settlementAccountIFSC":"ICIC0000011","txnAmount":"10000.00","serviceTax":"0.00","txnCharges":"0.00","settledAmount":"10000.00","utr_no":"T03342000280190","settlementDate":"28-07-2025","transmissionDateTime":"2025-09-25 18:46:20"}],"secureHash":"6971b3a706ed2dc46adecb21810ebb7df85ffabce9506e7cde13ca0b6c7b2efa"}

Chapter 16: Get Card Bin

16.1 Get Card Bin Request Parameters

To get the card Bank Identification Number (BIN) details stored in the Payment Gateway

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant id	Alphanumeric	20	Yes	System generated
requestId	Unique request ID	Alphanumeric	12	Yes	Unique request ID
requestedAt	Date time when the request was initiated	Alphanumeric	14	Yes	YYYYMMDDHHMMSS The requestDateTime should be in UTC and the value cannot be older than 30 mins of current time.
cardNo	Card bin or the card number	Alphanumeric	20	No	Card bin or the card number
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation v2 for the logic

This is a server-to-server API Call which uses POST method with content type as "application/json"

Sample Request body.

{
“merchantId”: “T_12345”, “requestId”: “00000000000003”,
“requestedAt” : “20230426123501”
“cardNo”: “400100007”,
“secureHash”:
“39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
}

16.2 Get Card Bin Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant id	Alphanumeric	20	Yes	Echoed from the request
network	Card network	Alphanumeric	45	Yes	Whether VISA, Rupay or MC
error_code	Response code	Alphanumeric	4	yes	0000 – success 5001 – if the bin is inactive 500 – Internal error
errorDescription	Response description	Alphanumeric	48	No	Only when the response is not successful
cardType	Type of the card	Alphanumeric	45	No	CC – credit card DC – debit card PP – prepaid card
domOrIntl	Whether the card is domestic or international	Alphanumeric	45	No	DOM – domestic card w.r.t. India INTL – international card w.r.t. India
prdType	Product type of the bin	Alphanumeric	45	No	Product type of the bin.

Sample response

{
“error_code”: “000”,
“errorDescription”: “Transaction successful”, “merchantId”: “123243”,
“network” : “343223” “cardType”: “SUC”,
“domOrIntl”: “000”,
“prdType”: “”

}

Chapter 17: UserCancel API

17.1 User Cancel Request Parameters

When a transaction is canceled by the end customer after a timeout, the merchant must call this API to mark the transaction as user canceled.

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant id	Alphanumeric	20	Yes	System provided.
aggregatorID	Merchant Aggregator ID	Alphanumeric	20	C	Only applicable for Aggregators
merchantTxnNo	Txn ref Number	Alphanumeric	20	Yes	Unique ref no to identify the request. Should have only alphanumeric characters. No other characters allowed.
cancellationCode	Error Code	Alphanumeric	20	Yes	Default = 020
cancellationDesc	Error Description	Alphanumeric	48	Yes	Default = Cancel By User
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation v2 for the logic

This is a server-to-server API Call which uses POST method with content type as "application/json"

API End Point :- /pg/api/userCancel

Sample Request body.

{
“merchantId”: “T_12345”, “aggregatorID”: “A_00001”, “merchantTxnNo” : “20230426123501”
“cancellationCode”: “020”, “cancellationDesc”: “Cancel By User”,
“secureHash”:
“39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
}

17.2 UserCancel API Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant account ID	Alphanumeric	20	Yes	Echo of request field
aggregatorID	Merchant aggregator ID	Alphanumeric	20	C	Echo of request field (if available in request)
merchantTxnNo	Merchant Txn ref Number	Alphanumeric	20	Yes	Echo of request field
respDescription	Response description	Alphanumeric	45	Yes	Response description
responseCode	Response Code	Alphanumeric	3	yes	
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation V2

Sample response.

{
“merchantId”: “T_12345”, “aggregatorID”: “A_00001”, “merchantTxnNo” : “20230426123501”
“cancellationCode”: “020”, “cancellationDesc”: “Cancel By User”,
“secureHash”: “39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
}

Chapter 18: Get Service Charges API

18.1 Get Service Charges Request Parameters

- It is used to calculate the Transactions charges in case customer payable.

Parameter	Description	Type	Size	Mandatory	Remarks
merchantId	Merchant id	Alphanumeric	20	Yes	System provided.
aggregatorID	Merchant Aggregator ID	Alphanumeric	20	C	Only applicable for Aggregators
merchantTxnNo	Txn ref Number	Alphanumeric	20	Yes	Unique ref no to identify the request. Should have only alphanumeric characters. No other characters allowed.
paymentMode	Payment mode	Alphanumeric	48	Yes	• CARD • NB • WALLET • UPI • AADHAAR
paymentOption Codes	Sub Payment mode	Alphanumeric	48	Yes	Available options under a select payment mode.
amount	Transaction amount	Numeric	9,2	Yes	9 significant and 2 decimal/precision e.g., nnnnnnnnn.nn
currencyCode	Transaction Currency	Numeric	3	Yes	356
secureHash	Hash value	Alphanumeric	64	Yes	Check Hash Calculation v2 for the logic

This is a server-to-server API Call which uses POST method with content type as "application/x- www- form-urlencoded”

Sample Request body.


```
  {
“respHeader” :
{ “responseCode”: “200”, “respDescription” : “OK”
},
“respBody”: {
“merchantId”: “T_12345”, “amount”: “100”,
“serviceCharge”: “11.80”
}
  }
```

18.2 Get Service Charges Response Parameters

Parameter	Description	Type	Size	Mandatory	Remarks
respHeader					
responseCode	Response code	Alphanumeric		Yes	200 in case of success
respDescription	Response description	Alphanumeric		Yes	OK in case of success
respBody					
merchantId	Merchant account ID	Alphanumeric	20	Yes	Echo of request field
amount	Amount	Numeric	9,2	Yes	Echo of request field
serviceCharge	Service charges calculated for the payment mode and sub payment mode	Numeric	9,2	Yes	Service charges including GST

Sample response.


```
{
“respHeader” :
{ “responseCode”: “200”, “respDescription” : “OK”
},
“respBody”: {
“merchantId”: “T_12345”, “amount”: “100”,
“serviceCharge”: “11.80”
}
  }
```

Sample HTML for Standard Mode Integration

Request Parameters HTTP- POST: https:// .co.in/Phiwebpay/v1.0/payments

```
<form id='myForm' name='myForm' action='${saleRequestURL}'
method='post' enctype="application/x-www-form-urlencoded">
        <input type="hidden" name="merchantID" value="M00001" />

        <input type="hidden" name="merchantTxnNo" value="M99887766" />

        <input type="hidden" name="amount" value="1000" />

        <input type="hidden" name="currencyCode" value="356" />

        <input type="hidden" name="payType" value="0" />

        <input type="hidden" name="customerEmailId" value="customer@email.com" />

        <input type="hidden" name="transactionType" value="SALE" />

        <input type="hidden" name="returnURL"
value="https://shoppingdomain.com/paymentResponseURL" />
        <input type="hidden" name="txnDate" value="20160803101010" />

        <input type="hidden" name="customerMobileNo" value="9123456789" />

        <input type="hidden" name="secureHash"
value="062f43817ff97eee69e89ff6d4ea283295db5d3f73a5c8addfa9012aed6aa995"/>

</form>
```

Sample HTML for Direct Mode Integration

```
<form id='myForm' name='myForm' action='${saleRequestURL}'
method='post' enctype="application/x-www-form-urlencoded">

    <input type="hidden" name="merchantID" value="M00001" />

    <input type="hidden" name="merchantTxnNo" value="M99887766" />

    <input type="hidden" name="amount" value="1000" />

    <input type="hidden" name="currencyCode" value="356" />

    <input type="hidden" name="payType" value="1" />

    <input type="hidden" name="customerEmailId" value="customer@email.com" />

    <input type="hidden" name="transactionType" value="SALE" />

    <input type="hidden" name="returnURL"
    value="https://shoppingdomain.com/paymentResponseURL" />

    <input type="hidden" name="txnDate" value="356" />

    <input type="hidden" name="customerMobileNo" value="9123456789" />

    <input type="hidden" name="cardNo" value="4111111111111111" />

    <input type="hidden" name="cardExp" value="202008" />

    <input type="hidden" name="nameOnCard" value="Customer Name" />

    <input type="hidden" name="cvv" value="123" />

    <input type="hidden" name="secureHash"
value="062f43817ff97eee69e89ff6d4ea283295db5d3f73a5c8addfa9012aed6aa995"    />

</form>
```

Payment Response

```
<form id='myForm' name='myForm' action='${merchantReturnURL}'
method='post' enctype="application/x-www-form-urlencoded">
        <input type="hidden" name="responseCode" value="000" />

        <input type="hidden" name="respDescription" value="SUCCESS" />

        <input type="hidden" name="merchantId" value="M000001" />

        <input type="hidden" name="merchantTxnNo" value="M0099999221" />

        <input type="hidden" name="txnID" value="T1472640294491" />

        <input type="hidden" name="paymentDateTime" value="20160831041454" />

        <input type="hidden" name="txnAuthID" value="006503" />

        <input type="hidden" name="secureHash"
value="39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2"     />
</form>
```

Refund/Auth Response

Sample response for refund/auth would be in json format. Sample response given below.

{
“responseCode”: “000”, “respDescription”: “”, “merchantId”: “123243”,
“merchantTxnNo” : “343223” “txnID”:”T20394302393”,
“paymentDateTime”: “20160803101010”,
“txnAuthID” : “28288”, “addlParam1” : “”,
“addlParam2” : “”,
“secureHash”: “39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
}

Transaction Status Response

Sample response for status would be in json format as given below.

{
“responseCode”: “000”, “respDescription”: “”, “merchantId”: “123243”,
“merchantTxnNo” : “343223” “txnStatus”: “SUC”, “txnResponseCode”: “000”, “txnRespDescription”: “”, “txnID”:”T20394302393”,
“paymentDateTime”: “20160803101010”,
“txnAuthID” : “28288”,
“secureHash”: “39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
}

Settlement Status Response

Sample response for settlement status would be in json format. Sample response given below.


```
  {
      “responseCod
e”:          “000”,
“respDescription”:
“”,   “merchantId”:
“123243”,
      “aggregatorID”: “123243”,
      “merchantTxnNo” : “343223”
“settlementStatus”: “STD”,
“txnStatus”: “SUC”,
“txnResponseCode”: “0000”,
“txnID”:”T20394302393”,
      “settlementID” : “28288_20191010-001”,
“settlementDate”: “20160803”,
      “secureHash”:
“39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2”
  }
```

Hash Calculation

Step 1: Concatenate the parameter values (if not null and not an empty string) in ascending order of parameter names. E.g., if param1 = “abc”, param2 = “xyz” and name = ”aa” then the concatenated value would be “aaabcxyz” (i.e., value of name + value of param1 + value of param2).

Step 2: Use HMAC function to calculate the hash. The algorithm used should be SHA256. The key used should be the key shared with the merchant/pg by ICICI Bank.

Step 3: Convert the result to HEX format.

Step 4: Convert the HEX format to lowercase and send it in secureHash parameter. E.g., if result of step 3 is “FEAB12CD” then convert it to “feab12cd”. This step can be skipped if the result of step 3 is already in lowercase.

Hash Logic: Merchant has to generate to a secure hash at their end for the response parameter that is being received in the callback URL. Accordingly, match it with the securehash that is received in the response callback.

Note 1: Don’t ignore any parameters which are part of a response or request for hash calculation, even if the parameter is not part of published spec. Parameters which are not part of specs can be ignored for business processing but not for hash calculation. One can ignore only those parameters which are null or have empty values for hash calculation.

Note 2: The hash calculation logic is available in V1 and V2. For APIs where the version is not specified, it is assumed to be Hash Calc V1.

Java example for HMAC

```
public static String hmacDigest(String msg, String keyString)
{ String digest = null;
try {
SecretKeySpec key = new SecretKeySpec((keyString).getBytes("UTF-8"), “HmacSHA256”);
Mac mac = Mac.getInstance(“HmacSHA256”);
mac.init(key);
byte[] bytes = mac.doFinal(msg.getBytes("ASCII"));
StringBuffer hash = new StringBuffer();
for (int i = 0; i <bytes.length; i++) {
String hex = Integer.toHexString(0xFF & bytes[i]);
if (hex.length() == 1) {
hash.append('0');
}
97Interface Specifications Document
hash.append(hex);
}
```

```
digest = hash.toString();
} catch (UnsupportedEncodingException e) {
} catch (InvalidKeyException e) {
} catch (NoSuchAlgorithmException e) {
}
return digest;
}
```

Java sample for server-to-server API call (HTTPS Post)

```
// HTTP POST request
public void sendPost()throws Exception {
String url="https://abc.example.com/someoperation"; URL obj=newURL(url);
HttpsURLConnection con =(HttpsURLConnection)obj.openConnection();
//add request header con.setRequestMethod("POST"); con.setRequestProperty("Content-Type",
"application/x-www-form-urlencoded");
String
urlParams="merchantId=12321&merchantTxnNo=38928332&transactionType=REFUND&secureHa
sh
=39867b8ef38a2853aacb84bbf5f927a72b27bdb301365245564f012d20dbc2f2";
// Send post request con.setDoOutput(true); con.setDoInput(true);
DataOutputStreamwr=newDataOutputStream(con.getOutputStream()); wr.writeBytes(urlParams);
wr.flush();
wr.close();
System.out.println("Sending POST request to URL : "+url);

intresponseCode=con.getResponseCode(); System.out.println("Post parameters : "+urlParameters);

BufferedReader in
=newBufferedReader( newInputStreamReader(con.ge tInputStream())); String inputLine;
StringBuffer response =newStringBuffer(); while((inputLine=in.readLine())!= null){
response.append(inputLine);
}
in.close();
//print result System.out.println(response.toString());
```

Hash Calculation (v2)

Applicable for json requests/responses

Step 1: Convert the json request/response to string (e.g., JSON.stringify(jsonObject)). The json request has to be a minified json and not a formatted json.

Step 2: Use the output of step 1 to calculate the hash. Use HMAC function to calculate the hash. The algorithm used should be SHA256. The key used should be the key shared with the merchant/pg by ICICI Bank.

Step 3: Convert the result to HEX format.

Step 4: Convert the HEX format to lowercase. E.g., if result of step 3 is “FEAB12CD” then convert it to “feab12cd”. This step can be skipped if the result of step 3 is already in lowercase.

Step 5: Send the value (step 4 result) in the custom http request header parameter “securehash” Note: Since request header names are case insensitive the parameter name is “securehash” (all in lower case)

Java example for HMAC

Please Note: If user is using the UDF parameters, then the clear text json packet of udf parameter value need to append with the other parameter to generate the secure hash.

```
public static String hmacDigest(String msg, String keyString)
{ String digest = null;
try {
SecretKeySpec key = new SecretKeySpec((keyString).getBytes("UTF-8"), “HmacSHA256”);
Mac mac = Mac.getInstance(“HmacSHA256”);
mac.init(key);
byte[] bytes = mac.doFinal(msg.getBytes("ASCII"));
StringBuffer hash = new StringBuffer();
for (int i = 0; i <bytes.length; i++) {
String hex = Integer.toHexString(0xFF & bytes[i]);
if (hex.length() == 1) {
hash.append('0');
}
97Interface Specifications Document
hash.append(hex);
}
digest = hash.toString();
} catch (UnsupportedEncodingException e) {
} catch (InvalidKeyException e) {
} catch (NoSuchAlgorithmException e) {
}
return digest;
}
```

Sample API Request and Response

Standard Method

1. Initiate sale Request (Standard Method PayType = 0)


```
{
    "merchantId": "T_S00067",
    "merchantTxnNo": "Test03102025111",
    //"aggregatorID" : "A100000000007064",
    "amount": "550.00",
    "currencyCode": "356",
    "payType": "0",
    "customerEmailID": "guest@icici.com",
    "transactionType": "SALE",
    "returnURL": "https://pgpayuat.icicibank.com/tsp/pg/api/merchant",
    "txnDate": "20251003123421",
    "secureHash":
"720406455a8631f5c55caf8fabbbd11f49615e4167c0c7b9ff61f0262292656f",
    "customerMobileNo": "7912403781",
    "addlParam1": "Additional Information",
    "addlParam2" : "Additional Information"
}
```


Initiate sale Response (Standard Method PayType = 0)

{"responseCode":"R1000","merchantId":"T_S00067","aggregatorID":null,"merchantTxnNo":"Test03102025111","redirectURI":"https://pgpayuat.icicibank.com/tsp/pg/api/v2/authRedirect","showOTPCapturePage":"N","generateOTPURI":null,"verifyOTPURI":null,"authorizeURI":null,"tranCtx":"Rb2fa698c-e1bd-41fc-b4c5-5b5cda1a2c53","secureHash":"da3e83172b3717be0e3c294157eda2b250a419251bf11010b496640b7775cd49"}

Direct Method

2. Initiate sale Request (Direct Method PayTyp e = 1)

```
{
    "merchantId": "T_S00067",
    "merchantTxnNo": "Test202510030141",
    "amount": "500.00",
    "currencyCode": "356",
    "payType": "1",
    "transactionType": "SALE",
    "customerUPIAlias" : "test@okicici",
    "paymentMode" : "UPI",
    "paymentDateTime" : "20251003161835",
    "customerEmailID": "guest@icici.com",
    "customerName" : "Test",
    "returnURL": "https://pgpayuat.icicibank.com/tsp/pg/api/merchant",
    "txnDate": "20251003123421",
    "secureHash":
"80e41869ee210badf95ea0e91c1cfd4a23d640240d8fbdc79681fefaff8c04a8",
    "customerMobileNo": "8901278901",
    "addlParam1": "Additional Information",
    "addlParam2" : "Additional Information"
}
```

Initiate sale Response (Direct Method PayType = 1)

{"responseCode":"R1000","merchantId":"T_S0001","aggregatorID":"J_D0001","merchantTxnNo":"Test0310202511","redirectURI":"https://pgpayuat.icicibank.com/tsp/pg/api/v2/authRedirect","showOTPCapturePage":"N","generateOTPURI":null,"verifyOTPURI":null,"authorizeURI":null,"tranCtx":"R5bfa541a-9e0e-469c-92d9-e12b89b717cc","secureHash":"4f4f1c96141401bb96acea6b662de5304429f11b9491f87bbfb0d2426f9ee3df"}

---

3. Transaction Refund Request

```
curl --location 'https://pgpayuat.icicibank.com/tsp/pg/api/command' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'merchantId=T_S00067' \
--data-urlencode 'transactionType=REFUND' \
--data-urlencode 'merchantTxnNo=Test03102025' \
--data-urlencode 'originalTxnNo=7700206371536' \
--data-urlencode 'amount=150.00' \
--data-urlencode
'secureHash=90a84da8a87c0433625016af74001e88ccf00ede8f3ded30a486c4463b774bd5' \
--data-urlencode 'addlParam1=Additional Information'
```

Transaction Refund Response

{"secureHash":"87b6d49a2ceb1dc54352bd6d0851f07ee28213614c693274d32cc8a5f33b478d","respDescription":"Request processed successfully","merchantId":"T_S00067","merchantTxnNo":"Test03102025","addlParam1":"Additional Information","txnID":"7700206371606","responseCode":"R1000"}

---

4. Transaction Status Check Request

```
curl --location 'https://pgpayuat.icicibank.com/tsp/pg/api/command' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'merchantId=T_S00067' \
--data-urlencode 'merchantTxnNo=Test03102025' \
--data-urlencode 'originalTxnNo=7700206371536' \
--data-urlencode 'transactionType=STATUS' \
--data-urlencode
'secureHash=8dead97d14d846cbb5674a46385675d242dbb35e54b37e423f241cbca85519f6' \
--data-urlencode 'addlParam1=Additional Information'
```

Transaction Status Check Response

{"txnRespDescription":"Transaction successful","secureHash":"2e2f67b7038a6f86d8383b59f8b7c6bf443b71d783212e9a29b6dc09abfbef12","amount":"550.00","txnResponseCode":"0000","txnAuthID":"811069696857","authCode":"7700201930022","respDescription":"Request processed successfully","paymentMode":"UPI","customerEmailID":"guest@icici.com","TransmissionDateTime":"20251003155304","oth_charge":false,"paymentInstId":"9552012231@upi","responseCode":"000","customerMobileNo":"7912403781","txnStatus":"SUC","merchantId":"T_S00067","merchantTxnNo":"7700206371536","addlParam1":"Additional Information","paymentDateTime":"20251003155335","txnID":"7700206371536"}

URLs

Test Environment URLS

Sale
https://pgpayuat.icicibank.com/tsp/pg/api/v2/initiateSale

Refund/StatusCheck
https://pgpayuat.icicibank.com/tsp/pg/api/command

GenerateQR UAT
https://pgpayuat.icicibank.com/tsp/pg/api/generateQR

Settlement Details
https://pgpayuat.icicibank.com/tsp/pg/api/settlementDetails

Settlement Summary
https://pgpayuat.icicibank.com/tsp/pg/api/command

User Cancelation API
https://pgpayuat.icicibank.com/tsp/pg/api/userCancel

Production URLs

Sale
https://pgpay.icicibank.com/pg/api/v2/initiateSale

Refund/Void/StatusCheck
https://pgpay.icicibank.com/pg/api/command

GenerateQR:
https://pgpay.icicibank.com/pg/api/generateQR

Settlement Details:
https://pgpay.icicibank.com/pg/api/settlementDetails

Settlement Summary
https://pgpay.icicibank.com/pg/api/command

User Cancelation API
https://pgpay.icicibank.com/pg/api/userCancel