

---

# DBMS Short Revision Notes

Sourabh Aggarwal

Compiled on January 4, 2019

## Contents

### 1 Intro

#### 1 Intro

Database is simply a collection of related info.  
Create Read (Retrieve) Update Delete (CRUD)

Two types of Databases:-

- Relational Databases (SQL): Organize data into one or more tables, each table has columns and rows and a unique key identifies each row.
- Non Relational (noSQL / not just SQL): Organize data is anything but a traditional table. Like key value stores, Documents (JSON), Graphs, etc.

Relational database management systems (RDBMS): softwares which help users create and maintain a a relational database. Ex: mySQL

Schema: Is just an overall structure of our database, columns, their types etc.

SQL (Standard Query Language): Standardized language for interacting with RDBMS. It's basically 4 types of languages in one:

- Data Query Language (DQL)
- Data Definition Language (schemas etc.)
- Data Control Language (permissions etc.)
- Data Manipulation Language (update etc.)

Queries are requests made to the database management systems for specific information.

Primary Key: Column which uniquely identifies each row. (It cannot contain NULL values.) Tables are limited to ONE primary key each.

Surrogate key: Primary key which has no inference, just a random no.

Natural Key: Aadhaar no., etc. which have real world inference/mapping. (it is a primary key)

Composite Key: Key which requires 2 or more attributes, Primary key can be a composite key.

Foreign Key: Attribute which will link us to another database table. Foreign key stores primary key of a row of another database table. A particular table can have more than one foreign key. And it can have NULL values. Primary key could be a composite of foreign keys.

Code written

```
create database girrafe;
```

```
INT -- whole numbers
```

```
DECIMAL(M, N) -- M is the total no. of digits and N is the no. of digits after the decimal point.
```

```
VARCHAR(1) -- String of length 1.
```

```
BLOB -- Binary Large Object
```

```
DATE -- 'YYYY-MM-DD'
```

```
TIMESTAMP -- 'YYYY-MM-DD HH:MM:SS'
```

```
CREATE TABLE student (  
    student_id INT PRIMARY KEY,  
    name VARCHAR (30),  
    major VARCHAR (20)  
);
```

```
DESCRIBE student; -- Describes our table
```

```
DROP TABLE student; -- Deletes our table
```

```
ALTER TABLE student ADD gpa DECIMAL (3, 2); -- Add a column to our table
```

```
ALTER TABLE student DROP COLUMN gpa; -- drops our gpa column
```

```
SELECT * FROM student; -- show all rows
```

```
INSERT INTO student VALUES (1, 'Jack', 'Biology'); -- add this row, parameters should be given in order
```

```
INSERT INTO student (student_id, name) VALUES (2, 'Kate'); --  
Now we need not include 'major', it will show 'NULL' in major now.
```

```
UPDATE student  
SET major = 'Bio'
```

```
WHERE major = 'Biology'; -- other operators are <> (not equal),
> (greater), <, >=, <=. our target is to update the major name
to Bio in case the major name is Biology
-- Or we could have done WHERE student_id > 3;
-- Or SET major = 'Biochemistry'
-- WHERE major = 'Bio' OR major = 'Chemistry';
-- SET name = 'Tom', major = 'undecided'
-- WHERE student_id = 1;
-- Note: If we remove WHERE then it will affect all of the rows.
DELETE FROM student -- if we put semicolon at the end of this
statement then it will delete all of the rows in the table
WHERE name = 'Tom' AND major = 'undecided';
-----
SELECT name, major
FROM student; -- now we will get only two columns name, major
--
SELECT name, major
FROM student
ORDER by name DESC; -- will give the entries in the descending
order of names. If we remove DESC then it will be order by
ascending order. btw ASC can as well be used instead.
-- ORDER by major, student_id DESC; -- will order by major and
in case there is a tie then they will be ordered by descending
student_id.
-- We can add LIMIT 2; this would give us only 2 entries.
SELECT name, major
FROM student
WHERE name IN ('Claire', 'Kate', 'Mike') AND student_id > 2; --
IN checks for set membership
```

# Company Database

Employee

emp_id	first_name	last_name	birth_date	sex	salary	super_id	branch_id
100	David	Wallace	1967-11-17	M	250,000	NULL	1
101	Jan	Levinson	1961-05-11	F	110,000	100	1
102	Michael	Scott	1964-03-15	M	75,000	100	2
103	Angela	Martin	1971-06-25	F	63,000	102	2
104	Kelly	Kapoor	1980-02-05	F	55,000	102	2
105	Stanley	Hudson	1958-02-19	M	69,000	102	2
106	Josh	Porter	1969-09-05	M	78,000	100	3
107	Andy	Bernard	1973-07-22	M	65,000	106	3
108	Jim	Halpert	1978-10-01	M	71,000	106	3

Branch

branch_id	branch_name	mgr_id	mgr_start_date
1	Corporate	100	2006-02-09
2	Scranton	102	1992-04-06
3	Stamford	106	1998-02-13

Works\_With

emp_id	client_id	total_sales
105	400	55,000
102	401	267,000
108	402	22,500
107	403	5,000
108	403	12,000
105	404	33,000
107	405	26,000
102	406	15,000
105	406	130,000

Client

client_id	client_name	branch_id
400	Dunmore Highschool	2
401	Lackawana Country	2
402	FedEx	3
403	John Daly Law, LLC	3
404	Scranton Whitepages	2
405	Times Newspaper	3
406	FedEx	2

Branch Supplier

branch_id	supplier_name	supply_type
2	Hammer Mill	Paper
2	Uni-ball	Writing Utensils
3	Patriot Paper	Paper
2	J.T. Forms & Labels	Custom Forms
3	Uni-ball	Writing Utensils
3	Hammer Mill	Paper
3	Stamford Lables	Custom Forms

Labels

	Primary Key
	Foreign Key
	Attribute

```
CREATE TABLE employee (
    emp_id INT PRIMARY KEY,
    first_name VARCHAR(40),
    last_name VARCHAR(40),
    birth_day DATE,
    sex VARCHAR(1),
    salary INT,
    super_id INT,
    branch_id INT
);
```

```
CREATE TABLE branch (
    branch_id INT PRIMARY KEY,
    branch_name VARCHAR(40),
```

```
mgr_id INT,
mgr_start_date DATE,
FOREIGN KEY(mgr_id) REFERENCES employee(emp_id) ON DELETE SET
NULL
);
```

```
ALTER TABLE employee
ADD FOREIGN KEY(branch_id)
REFERENCES branch(branch_id)
ON DELETE SET NULL;
```

```
ALTER TABLE employee
ADD FOREIGN KEY(super_id)
REFERENCES employee(emp_id)
ON DELETE SET NULL;
```

```
CREATE TABLE client (
    client_id INT PRIMARY KEY,
    client_name VARCHAR(40),
    branch_id INT,
    FOREIGN KEY(branch_id) REFERENCES branch(branch_id) ON DELETE
SET NULL
);
```

```
CREATE TABLE works_with (
    emp_id INT,
    client_id INT,
    total_sales INT,
    PRIMARY KEY(emp_id, client_id),
    FOREIGN KEY(emp_id) REFERENCES employee(emp_id) ON DELETE
CASCADE,
    FOREIGN KEY(client_id) REFERENCES client(client_id) ON DELETE
CASCADE
);
```

```
CREATE TABLE branch_supplier (
    branch_id INT,
    supplier_name VARCHAR(40),
    supply_type VARCHAR(40),
    PRIMARY KEY(branch_id, supplier_name),
    FOREIGN KEY(branch_id) REFERENCES branch(branch_id) ON DELETE
CASCADE
);
```

```
--
-----
-- Corporate
INSERT INTO employee VALUES(100, 'David', 'Wallace',
'1967-11-17', 'M', 250000, NULL, NULL);
```

```
INSERT INTO branch VALUES(1, 'Corporate', 100, '2006-02-09');
```

```
UPDATE employee
SET branch_id = 1
WHERE emp_id = 100;
```

```
INSERT INTO employee VALUES(101, 'Jan', 'Levinson',
'1961-05-11', 'F', 110000, 100, 1);
```

```
-- Scranton
INSERT INTO employee VALUES(102, 'Michael', 'Scott',
'1964-03-15', 'M', 75000, 100, NULL);
```

```
INSERT INTO branch VALUES(2, 'Scranton', 102, '1992-04-06');
```

```
UPDATE employee
SET branch_id = 2
WHERE emp_id = 102;
```

```
INSERT INTO employee VALUES(103, 'Angela', 'Martin',
'1971-06-25', 'F', 63000, 102, 2);
INSERT INTO employee VALUES(104, 'Kelly', 'Kapoor',
'1980-02-05', 'F', 55000, 102, 2);
INSERT INTO employee VALUES(105, 'Stanley', 'Hudson',
'1958-02-19', 'M', 69000, 102, 2);
```

```
-- Stamford
INSERT INTO employee VALUES(106, 'Josh', 'Porter',
'1969-09-05', 'M', 78000, 100, NULL);
```

```
INSERT INTO branch VALUES(3, 'Stamford', 106, '1998-02-13');
```

```
UPDATE employee  
SET branch_id = 3  
WHERE emp_id = 106;
```

```
INSERT INTO employee VALUES(107, 'Andy', 'Bernard',  
'1973-07-22', 'M', 65000, 106, 3);  
INSERT INTO employee VALUES(108, 'Jim', 'Halpert',  
'1978-10-01', 'M', 71000, 106, 3);
```

```
-- BRANCH SUPPLIER
```

```
INSERT INTO branch_supplier VALUES(2, 'Hammer Mill', 'Paper');  
INSERT INTO branch_supplier VALUES(2, 'Uni-ball', 'Writing  
Utensils');  
INSERT INTO branch_supplier VALUES(3, 'Patriot Paper',  
'Paper');  
INSERT INTO branch_supplier VALUES(2, 'J.T. Forms & Labels',  
'Custom Forms');  
INSERT INTO branch_supplier VALUES(3, 'Uni-ball', 'Writing  
Utensils');  
INSERT INTO branch_supplier VALUES(3, 'Hammer Mill', 'Paper');  
INSERT INTO branch_supplier VALUES(3, 'Stamford Lables',  
'Custom Forms');
```

```
-- CLIENT
```

```
INSERT INTO client VALUES(400, 'Dunmore Highschool', 2);  
INSERT INTO client VALUES(401, 'Lackawana Country', 2);  
INSERT INTO client VALUES(402, 'FedEx', 3);  
INSERT INTO client VALUES(403, 'John Daly Law, LLC', 3);  
INSERT INTO client VALUES(404, 'Scranton Whitepages', 2);  
INSERT INTO client VALUES(405, 'Times Newspaper', 3);  
INSERT INTO client VALUES(406, 'FedEx', 2);
```

```
-- WORKS_WITH
```

```
INSERT INTO works_with VALUES(105, 400, 55000);  
INSERT INTO works_with VALUES(102, 401, 267000);  
INSERT INTO works_with VALUES(108, 402, 22500);  
INSERT INTO works_with VALUES(107, 403, 5000);  
INSERT INTO works_with VALUES(108, 403, 12000);  
INSERT INTO works_with VALUES(105, 404, 33000);  
INSERT INTO works_with VALUES(107, 405, 26000);  
INSERT INTO works_with VALUES(102, 406, 15000);  
INSERT INTO works_with VALUES(105, 406, 130000);
```

```
-- Find all employees
```

```
SELECT *  
FROM employee;
```

```
-- Find all clients
```

```
SELECT *  
FROM clients;
```

```
-- Find all employees ordered by salary
```

```
SELECT *  
from employee  
ORDER BY salary ASC/DESC;
```

```
-- Find all employees ordered by sex then name
```

```
SELECT *  
from employee  
ORDER BY sex, name;
```

```
-- Find the first 5 employees in the table
```

```
SELECT *  
from employee  
LIMIT 5;
```

```
-- Find the first and last names of all employees
```

```
SELECT first_name, employee.last_name  
FROM employee;
```

```
-- Find the forename and surnames names of all employees
```

```
SELECT first_name AS forename, employee.last_name AS surname  
FROM employee;
```

```
-- Find out all the different genders
```

```
SELECT DISINCT sex  
FROM employee;
```

```
-- Find all male employees
```

```
SELECT *  
FROM employee  
WHERE sex = 'M';
```

```
-- Find all employees at branch 2
```

```
SELECT *  
FROM employee  
WHERE branch_id = 2;
```

```
-- Find all employee's id's and names who were born after 1969
```

```
SELECT emp_id, first_name, last_name  
FROM employee  
WHERE birth_day >= 1970-01-01;
```

```
-- Find all female employees at branch 2
```

```
SELECT *  
FROM employee  
WHERE branch_id = 2 AND sex = 'F';
```

```
-- Find all employees who are female & born after 1969 or who  
make over 80000
```

```
SELECT *  
FROM employee  
WHERE (birth_day >= '1970-01-01' AND sex = 'F') OR salary >  
80000;
```

```
-- Find all employees born between 1970 and 1975
```

```
SELECT *  
FROM employee  
WHERE birth_day BETWEEN '1970-01-01' AND '1975-01-01';
```

```
-- Find all employees named Jim, Michael, Johnny or David
```

```
SELECT *  
FROM employee  
WHERE first_name IN ('Jim', 'Michael', 'Johnny', 'David');
```

```
-- Functions
```

```
-- Find the number of employees
```

```
SELECT COUNT(super_id)  
FROM employee;
```

```
-- Find the average of all employee's salaries
```

```
SELECT AVG(salary)  
FROM employee;
```

```
-- Find the sum of all employee's salaries
```

```
SELECT SUM(salary)  
FROM employee;
```

```
-- Aggregation.
```

```
-- Find out how many males and females there are
```

```
SELECT COUNT(sex), sex  
FROM employee  
GROUP BY sex
```

```
-- Find the total sales of each salesman
```

```
SELECT SUM(total_sales), emp_id  
FROM works_with  
GROUP BY client_id;
```

```
-- Find the total amount of money spent by each client
```

```
SELECT SUM(total_sales), client_id  
FROM works_with  
GROUP BY client_id;
```

```
-- Wildcards
```

```
-- % = any # characters, _ = one character
```

```
-- Find any client's who are an LLC
```

```
SELECT *  
FROM client  
WHERE client_name LIKE '%LLC';
```

```
-- Find any branch suppliers who are in the label business
```

```
SELECT *  
FROM branch_supplier  
WHERE supplier_name LIKE '% Label%';
```

```
-- Find any employee born on the 10th day of the month
```

```
SELECT *
```

```

FROM employee
WHERE birth_day LIKE '____10%';

-- Find any clients who are schools
SELECT *
FROM client
WHERE client_name LIKE '%Highschool%';

-- Union

-- Find a list of employee and branch names
SELECT employee.first_name AS Employee_Branch_Names
FROM employee
UNION
SELECT branch.branch_name
FROM branch;

-- Find a list of all clients & branch suppliers' names
SELECT client.client_name AS Non-Employee_Entities,
client.branch_id AS Branch_ID
FROM client
UNION -- both above and below thing should have same number of
columns and same data type respectively
SELECT branch_supplier.supplier_name, branch_supplier.branch_id
FROM branch_supplier;

-- JOINS (used to combine rows from two or more tables based on
the related columns)

-- Add the extra branch
INSERT INTO branch VALUES(4, "Buffalo", NULL, NULL);

-- Find all branches and the names of their managers
SELECT employee.emp_id, employee.first_name, branch.branch_name
FROM employee
JOIN branch -- LEFT JOIN (when we use LEFT JOIN all the rows
from the left table gets included as well, similarly for RIGHT
JOIN), RIGHT JOIN (we added buffalo just so that we can see
difference in case of RIGHT JOIN)
ON employee.emp_id = branch.mgr_id;

-- nested queries

-- Find names of all employees who have sold over 50,000
SELECT employee.first_name, employee.last_name
FROM employee
WHERE employee.emp_id IN (SELECT works_with.emp_id -- note
that first sql will execute the part which is inside "()"
FROM works_with
WHERE works_with.total_sales >
50000);

-- Find all clients who are handles by the branch that Michael
Scott manages
-- Assume you know Michael's ID
SELECT client.client_id, client.client_name
FROM client
WHERE client.branch_id = (SELECT branch.branch_id
FROM branch
WHERE branch.mgr_id = 102);

-- Find all clients who are handles by the branch that Michael
Scott manages
-- Assume you DONT'T know Michael's ID
SELECT client.client_id, client.client_name
FROM client
WHERE client.branch_id = (SELECT branch.branch_id
FROM branch
WHERE branch.mgr_id = (SELECT
employee.emp_id
FROM employee
WHERE
employee.first_name
= 'Michael'
AND
employee.last_name
= 'Scott'
LIMIT 1));

-- Find the names of employees who work with clients handled by
the scranton branch

```

```

SELECT employee.first_name, employee.last_name
FROM employee
WHERE employee.emp_id IN (
SELECT works_with.emp_id
FROM works_with
)
AND employee.branch_id = 2;

-- Find the names of all clients who have spent more than
100,000 dollars
SELECT client.client_name
FROM client
WHERE client.client_id IN (
SELECT client_id
FROM (
SELECT
SUM(works_with.total_sales) AS
totals, client_id
FROM works_with
GROUP BY client_id) AS
total_client_sales
WHERE totals > 100000
);

-- deleting entries in the table when they have foreign keys
associated to them
-- ON DELETE NULL means that say if we delete Michael Scott then
second entry in the branch table will get mgr_id set to NULL
whereas in ON DELETE CASCADE the entire row will get deleted in
branch table. Use ON DELETE CASCADE when that foreign key is
very important like say it forms a primary key.

-- CREATE
-- TRIGGER `event_name` BEFORE/AFTER INSERT/UPDATE/DELETE
-- ON `database`.`table`
-- FOR EACH ROW BEGIN
-- -- trigger body
-- -- this code is applied to every
-- -- inserted/updated/deleted row
-- END;

CREATE TABLE trigger_test (
message VARCHAR(100)
);

DELIMITER $$ -- changing delimiter from semicolon to ll as we
will be using semicolon inside and we don't want sql to think
that when we put semicolon we are done with our trigger
CREATE
TRIGGER my_trigger BEFORE INSERT
ON employee
FOR EACH ROW BEGIN -- for each new item that is inserted
INSERT INTO trigger_test VALUES('added new employee');
END$$
DELIMITER ; -- changing delimiter back to semi colon.
INSERT INTO employee
VALUES(109, 'Oscar', 'Martinez', '1968-02-19', 'M', 69000, 106,
3);

DELIMITER $$
CREATE
TRIGGER my_trigger BEFORE INSERT
ON employee
FOR EACH ROW BEGIN
INSERT INTO trigger_test VALUES(NEW.first_name);
END$$
DELIMITER ;
INSERT INTO employee
VALUES(110, 'Kevin', 'Malone', '1978-02-19', 'M', 69000, 106,
3);

DELIMITER $$
CREATE
TRIGGER my_trigger BEFORE INSERT
ON employee
FOR EACH ROW BEGIN
IF NEW.sex = 'M' THEN

```

```

        INSERT INTO trigger_test VALUES('added male
        employee');
    ELSEIF NEW.sex = 'F' THEN
        INSERT INTO trigger_test VALUES('added female');
    ELSE
        INSERT INTO trigger_test VALUES('added other
        employee');
    END IF;
END$$
DELIMITER ;
INSERT INTO employee
VALUES(111, 'Pam', 'Beesly', '1988-02-19', 'F', 69000, 106, 3);

DROP TRIGGER my_trigger;

```

Entity = An object we want to model and store information about  
 Attributes = Specific pieces of information about an entity  
 Composite attribute = An attribute that can be broken up into sub attributes  
 Multi-valued attribute = An attribute that can have more than one value (like same student can have more than one club but only one GPA)  
 Derived Attribute = An attribute that can be derived from the other attributes.  
 ER = Entity Relationship defines a relationship between two entities.  
 Relationship Attribute = An attribute about the relationship