

# Research Report - Spectral Clustering

Sourabh Antani  
supervisor  
Dr. Yunkai Zhou

Mathematics Department,  
Southern Methodist University

June 3, 2021

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - *k*-means [Macqueen, 1967] [Lloyd 1982]

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - $k$ -means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - *k*-means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]
  - Mean-shift [Cheng 1995]

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - $k$ -means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]
  - Mean-shift [Cheng 1995]
  - DBSCAN [Ester et al. 1996]

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - $k$ -means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]
  - Mean-shift [Cheng 1995]
  - DBSCAN [Ester et al. 1996]
- Linear Algebra based

# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - $k$ -means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]
  - Mean-shift [Cheng 1995]
  - DBSCAN [Ester et al. 1996]
- Linear Algebra based
  - Non-Negative Matrix Factorization [Lawton et al. 1971] [Paatero et al. 1991] [Ding et al. 2005]



# Clustering Algorithms

Below are some examples of clustering algorithms used in practice, aside from spectral clustering.

- Euclidean distance and spatial density based:
  - $k$ -means [Macqueen, 1967] [Lloyd 1982]
  - BIRCH (Balanced Iterative Reducing and Clustering using Hierarchies) [Zhang et al. 1996]
  - Mean-shift [Cheng 1995]
  - DBSCAN [Ester et al. 1996]
- Linear Algebra based
  - Non-Negative Matrix Factorization [Lawton et al. 1971] [Paatero et al. 1991] [Ding et al. 2005]
  - PCA Based clustering [Zhang et al. 2018]

# Spectral Clustering

## Graph Laplacian - Construction

- Given an undirected graph,  $\mathbf{G} = (\mathbf{V}, \mathbf{E})$  with set of vertices  $\mathbf{V} = \{\mathbf{v}_1, \dots, \mathbf{v}_n\}$  and  $\mathbf{E}$  set of weighted edges. The weight of the edge between  $v_i$  and  $v_j$ , denoted by  $w_{ij}$  is assigned based on the 'similarity' between the data-points  $v_i$  and  $v_j$ . For example, if the similarity function chosen is a Gaussian kernel and the data that these vertices represent are scalars  $x_i$  and  $x_j$ , then
$$w_{ij} = e^{-|x_i - x_j|^2 / 2}$$

# Spectral Clustering

## Graph Laplacian - Construction

- Given an undirected graph,  $\mathbf{G} = (\mathbf{V}, \mathbf{E})$  with set of vertices  $\mathbf{V} = \{\mathbf{v}_1, \dots, \mathbf{v}_n\}$  and  $\mathbf{E}$  set of weighted edges. The weight of the edge between  $v_i$  and  $v_j$ , denoted by  $w_{ij}$  is assigned based on the 'similarity' between the data-points  $v_i$  and  $v_j$ . For example, if the similarity function chosen is a Gaussian kernel and the data that these vertices represent are scalars  $x_i$  and  $x_j$ , then
$$w_{ij} = e^{-|x_i - x_j|^2 / 2}$$
- Construct the Weighted adjacency matrix  $\mathbf{W} = (w_{ij})_{i,j=1,\dots,n}$  and Degree matrix  $\mathbf{D} = \text{diag}(d_1, \dots, d_n)$  where  $d_i = \sum_{j=1}^n w_{ij}$  is called Degree of a vertex  $v_i$ .

# Spectral Clustering

## Graph Laplacian - Construction

- Given an undirected graph,  $\mathbf{G} = (\mathbf{V}, \mathbf{E})$  with set of vertices  $\mathbf{V} = \{\mathbf{v}_1, \dots, \mathbf{v}_n\}$  and  $\mathbf{E}$  set of weighted edges. The weight of the edge between  $v_i$  and  $v_j$ , denoted by  $w_{ij}$  is assigned based on the 'similarity' between the data-points  $v_i$  and  $v_j$ . For example, if the similarity function chosen is a Gaussian kernel and the data that these vertices represent are scalars  $x_i$  and  $x_j$ , then
$$w_{ij} = e^{-|x_i - x_j|^2 / 2}$$
- Construct the Weighted adjacency matrix  $\mathbf{W} = (w_{ij})_{i,j=1,\dots,n}$  and Degree matrix  $\mathbf{D} = \text{diag}(d_1, \dots, d_n)$  where  $d_i = \sum_{j=1}^n w_{ij}$  is called Degree of a vertex  $v_i$ .
- Graph Laplacian is defined as  $L = D - W$

# Spectral Clustering

## Graph Laplacian - Construction

- Given an undirected graph,  $\mathbf{G} = (\mathbf{V}, \mathbf{E})$  with set of vertices  $\mathbf{V} = \{\mathbf{v}_1, \dots, \mathbf{v}_n\}$  and  $\mathbf{E}$  set of weighted edges. The weight of the edge between  $v_i$  and  $v_j$ , denoted by  $w_{ij}$  is assigned based on the 'similarity' between the data-points  $v_i$  and  $v_j$ . For example, if the similarity function chosen is a Gaussian kernel and the data that these vertices represent are scalars  $x_i$  and  $x_j$ , then
$$w_{ij} = e^{-|x_i - x_j|^2 / 2}$$
- Construct the Weighted adjacency matrix  $\mathbf{W} = (w_{ij})_{i,j=1,\dots,n}$  and Degree matrix  $\mathbf{D} = \text{diag}(d_1, \dots, d_n)$  where  $d_i = \sum_{j=1}^n w_{ij}$  is called Degree of a vertex  $v_i$ .
- Graph Laplacian is defined as  $L = D - W$
- A fully connected graph can be made sparse by converting it into a  $k$ -nearest neighbor or an  $\epsilon$ -neighborhood graph.

# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)

# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)
- Normalized Symmetric Graph Laplacian [Chung, 1997]
  - $L_{sym} = D^{-1/2} L D^{-1/2} = I - D^{-1/2} W D^{-1/2}$  (Symmetric)

# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)
- Normalized Symmetric Graph Laplacian [Chung, 1997]
  - $L_{sym} = D^{-1/2} L D^{-1/2} = I - D^{-1/2} W D^{-1/2}$  (Symmetric)
- Normalized Random Walk Graph Laplacian [Chung 1997]
  - $L_{rw} = D^{-1} L = I - D^{-1} W$  (Not-Symmetric)



# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)
- Normalized Symmetric Graph Laplacian [Chung, 1997]
  - $L_{sym} = D^{-1/2} L D^{-1/2} = I - D^{-1/2} W D^{-1/2}$  (Symmetric)
- Normalized Random Walk Graph Laplacian [Chung 1997]
  - $L_{rw} = D^{-1} L = I - D^{-1} W$  (Not-Symmetric)
- The eigenpair  $(\lambda, u)$  of  $L_{rw}$  solve  $Lu = \lambda Du$  and in this case  $D^{1/2}u$  is eigenvector of  $L_{sym}$  with eigenvalue  $\lambda$ .

# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)
- Normalized Symmetric Graph Laplacian [Chung, 1997]
  - $L_{sym} = D^{-1/2} L D^{-1/2} = I - D^{-1/2} W D^{-1/2}$  (Symmetric)
- Normalized Random Walk Graph Laplacian [Chung 1997]
  - $L_{rw} = D^{-1} L = I - D^{-1} W$  (Not-Symmetric)
- The eigenpair  $(\lambda, u)$  of  $L_{rw}$  solve  $Lu = \lambda Du$  and in this case  $D^{1/2}u$  is eigenvector of  $L_{sym}$  with eigenvalue  $\lambda$ .
- All Laplacians are Positive-semidefinite, hence have non-Negative Real-Valued Eigenvalues

# Spectral Clustering

Graph Laplacian - Types and Properties [Luxburg, 2007]

- Unnormalized Graph Laplacian [Mohar, 1991], [Mohar, 1997]
  - $L = D - W$  (Symmetric)
- Normalized Symmetric Graph Laplacian [Chung, 1997]
  - $L_{sym} = D^{-1/2} L D^{-1/2} = I - D^{-1/2} W D^{-1/2}$  (Symmetric)
- Normalized Random Walk Graph Laplacian [Chung 1997]
  - $L_{rw} = D^{-1} L = I - D^{-1} W$  (Not-Symmetric)
- The eigenpair  $(\lambda, u)$  of  $L_{rw}$  solve  $Lu = \lambda Du$  and in this case  $D^{1/2}u$  is eigenvector of  $L_{sym}$  with eigenvalue  $\lambda$ .
- All Laplacians are Positive-semidefinite, hence have non-Negative Real-Valued Eigenvalues
- 0 is an eigenvalue with multiplicity equal to number of connected components

# Spectral Clustering

## Graph Cuts

- The goal of clustering is to maximize the similarity within cluster and minimize the similarity between clusters.

# Spectral Clustering

## Graph Cuts

- The goal of clustering is to maximize the similarity within cluster and minimize the similarity between clusters.
- Minimizing the between cluster similarity equals to minimizing the objective function

$$\text{cut}(A_1, \dots, A_k) := \frac{1}{2} \sum_{i=1}^k W(A_i, \bar{A}_i), \quad \text{where } W(A, B) = \sum_{i \in A, j \in B} w_{ij}, \bar{A} = V \setminus A$$

# Spectral Clustering

## Graph Cuts

- The goal of clustering is to maximize the similarity within cluster and minimize the similarity between clusters.
- Minimizing the between cluster similarity equals to minimizing the objective function

$$\text{cut}(A_1, \dots, A_k) := \frac{1}{2} \sum_{i=1}^k W(A_i, \bar{A}_i), \quad \text{where } W(A, B) = \sum_{i \in A, j \in B} w_{ij}, \bar{A} = V \setminus A$$

- To maximize the within-cluster similarity, we define two objective functions

$$\text{RatioCut}(A_1, \dots, A_k) = \frac{1}{2} \sum_{i=1}^k \frac{W(A_i, \bar{A}_i)}{|A_i|} = \sum_{i=1}^k \frac{\text{cut}(A_i, \bar{A}_i)}{|A_i|} \text{ [Hagen, Kahng, 1992]}$$

$$\text{Ncut}(A_1, \dots, A_k) = \frac{1}{2} \sum_{i=1}^k \frac{W(A_i, \bar{A}_i)}{\text{vol}(A_i)} = \sum_{i=1}^k \frac{\text{cut}(A_i, \bar{A}_i)}{\text{vol}(A_i)} \text{ [Shi, Malik, 2000]}$$

# Spectral Clustering

Algorithms - Unnormalized Spectral Clustering - Hagen & Kahng (1992)

**Input:** Similarity matrix  $S \in \mathbb{R}^{n \times n}$ , number  $k$  of clusters to construct.

**begin**

Construct a similarity graph and its weighted adjacency matrix  $W$  according to the chosen similarity function

Compute the unnormalized Laplacian  $L$

Compute the first  $k$  eigenvectors  $u_1, \dots, u_k$  of  $L$

Let  $U \in \mathbb{R}^{n \times k}$  be the matrix containing the vectors  $u_1, \dots, u_k$  as columns

For  $i = 1, \dots, n$ , let  $y_i \in \mathbb{R}^k$  be the vector corresponding to the  $i^{\text{th}}$  row of  $U$

Cluster the points  $(y_i), i = 1, \dots, n$  in  $\mathbb{R}^k$  with the k-means algorithm into clusters  $C_1, \dots, C_k$

**end**

**Output:** Clusters  $A_1, \dots, A_k$  with  $A_i = \{x_j | y_j \in C_i\}$

# Spectral Clustering

Algorithms - Normalized Spectral Clustering - Shi & Malik (2000)

*This algorithm uses generalized eigenvectors of  $L$ , which are the eigenvectors of normalized random-walk Laplacian  $L_{rw} = D^{-1}L$*

**Input:** Similarity matrix  $S \in \mathbb{R}^{n \times n}$ , number  $k$  of clusters to construct

**begin**

Construct a similarity graph and its weighted adjacency matrix  $W$  according to the chosen similarity function

Compute the unnormalized Laplacian  $L$ .

Compute the first  $k$  generalized eigenvectors  $u_1, \dots, u_k$  of generalized eigenproblem  $Lu = \lambda Du$ .

Let  $U \in \mathbb{R}^{n \times k}$  be the matrix containing the vectors  $u_1, \dots, u_k$  as columns.

For  $i = 1, \dots, n$ , let  $y_i \in \mathbb{R}^k$  be the vector corresponding to the  $i^{th}$  row of  $U$ .

Cluster the points  $(y_i), i = 1, \dots, n$  in  $\mathbb{R}^k$  with the k-means algorithm into clusters  $C_1, \dots, C_k$ .

**end**

**Output:** Clusters  $A_1, \dots, A_k$  with  $A_i = \{x_j | y_j \in C_i\}$



# Spectral Clustering

Algorithms - Normalized Spectral Clustering - Ng, Jordan & Weiss (2002)

*This algorithm uses the eigenvectors of normalized symmetric Laplacian  $L_{sym} = D^{-1/2}LD^{-1/2}$ . Note that if  $D^{1/2}u$  is an eigenvector of  $L_{sym}$  if  $u$  is an eigenvector of  $L$  hence an additional normalization step is needed.*

**Input:** Similarity matrix  $S \in \mathbb{R}^{n \times n}$ , number  $k$  of clusters to construct.

**begin**

Construct a similarity graph and its weighted adjacency matrix  $W$  according to the chosen similarity function

Compute the normalized Laplacian  $L_{sym}$

Compute the first  $k$  eigenvectors  $u_1, \dots, u_k$  of  $L_{sym}$

Let  $U \in \mathbb{R}^{n \times k}$  be the matrix containing the vectors  $u_1, \dots, u_k$  as columns

Form the matrix  $T \in \mathbb{R}^{n \times k}$  from  $U$  by normalizing the norm to 1,

$$t_{ij} = u_{ij} / (\sum_k u_{ik}^2)^{1/2}$$

For  $i = 1, \dots, n$ , let  $y_i \in \mathbb{R}^k$  be the vector corresponding to the  $i^{th}$  row of  $U$


Cluster the points  $(y_i), i = 1, \dots, n$  in  $\mathbb{R}^k$  with the k-means algorithm into clusters  $C_1, \dots, C_k$

**end**

**Output:** Clusters  $A_1, \dots, A_k$  with  $A_i = \{x_j | y_j \in C_i\}$





# Numerical Experiments

Mixture of 4 Gaussians in  $\mathbb{R}^1$ . Similarity function:  $e^{-|x_i - x_j|^2/2}$




# Numerical Experiments

1351 Points in  $\mathbb{R}^2$ . Similarity function:  $\|x - y\|_2^{-1}$




# Numerical Experiments

Image Classification. Similarity function:  $\|\mathbf{v}_i \circ \mathbf{v}_j\|_1$



(a) Weighted Adjacency Matrix




(b) Clustering Result


**Figure:** 2000 images from MNIST data-set were clustered into 10 clusters. (b) shows first 10 images in each cluster with one row per cluster

# Numerical Experiments

Image Classification. Similarity function:  $\|v_i - v_j\|_2^{-1}$



(a) Weighted Adjacency Matrix




(b) Clustering Result


**Figure:** 2000 images from MNIST data-set were clustered into 10 clusters. (b) shows first 10 images in each cluster with one row per cluster

# Numerical Experiments

Image Classification. Similarity function: number of pixels that either 0 or non-zero in both  $\mathbf{v}_i$  &  $\mathbf{v}_j$



(a) Weighted Adjacency Matrix




(b) Clustering Result

Figure: 2000 images from MNIST data-set were clustered into 10 clusters. (b) shows first 10 images in each cluster with one row per cluster

# Numerical Experiments

Image Classification. Doubling the number of clusters to capture handwriting style differences



(a) Similarity function:  $\|\mathbf{v}_i \circ \mathbf{v}_j\|_1$



(b) Similarity function:  $\|\mathbf{v}_i - \mathbf{v}_j\|_2^{-1}$

**Figure:** 2000 images from MNIST data-set were clustered into 20 clusters, showing first 10 images in each cluster with one row per cluster.

# Compressive Spectral Clustering

[Tremblay et al. 2016]

Challenges with Spectral Clustering: Eigenvector computation, Cold-restart, expensive  $k$ -means due to high dimensionality.



# Compressive Spectral Clustering

[Tremblay et al. 2016]

Challenges with Spectral Clustering: Eigenvector computation, Cold-restart, expensive  $k$ -means due to high dimensionality.

- Sample  $\mathcal{O}(\log(k))$  randomly filtered signals on the graph to serve as feature vectors instead of eigenvectors
  - Estimate  $k^{\text{th}}$  eigenvalue per [Napoli 2013]
  - Approximate the action of a low-pass filter  $H$  that selects the first  $k$  eigenvectors on the graph Laplacian
  - Generate  $\mathcal{O}(\log(k))$  Gaussian signals, filtered by  $H$  to generate feature vectors  $\mathbf{f}_i$

# Compressive Spectral Clustering

[Tremblay et al. 2016]

Challenges with Spectral Clustering: Eigenvector computation, Cold-restart, expensive  $k$ -means due to high dimensionality.

- Sample  $\mathcal{O}(\log(k))$  randomly filtered signals on the graph to serve as feature vectors instead of eigenvectors
  - Estimate  $k^{\text{th}}$  eigenvalue per [Napoli 2013]
  - Approximate the action of a low-pass filter  $H$  that selects the first  $k$  eigenvectors on the graph Laplacian
  - Generate  $\mathcal{O}(\log(k))$  Gaussian signals, filtered by  $H$  to generate feature vectors  $\mathbf{f}_i$
- Clustering random subset of  $\mathcal{O}(k \log(k))$  nodes using random feature vectors

# Compressive Spectral Clustering

[Tremblay et al. 2016]

Challenges with Spectral Clustering: Eigenvector computation, Cold-restart, expensive  $k$ -means due to high dimensionality.

- Sample  $\mathcal{O}(\log(k))$  randomly filtered signals on the graph to serve as feature vectors instead of eigenvectors
  - Estimate  $k^{\text{th}}$  eigenvalue per [Napoli 2013]
  - Approximate the action of a low-pass filter  $H$  that selects the first  $k$  eigenvectors on the graph Laplacian
  - Generate  $\mathcal{O}(\log(k))$  Gaussian signals, filtered by  $H$  to generate feature vectors  $\mathbf{f}_i$
- Clustering random subset of  $\mathcal{O}(k \log(k))$  nodes using random feature vectors
- Infer the cluster label of all  $N$  nodes by interpolating.

# Future Work

- Accelerated Eigensolvers
  - Accelerating Lanczos
  - Chebyshev-Davidson Methods [Zhou & Saad 2007] [Z. Wang, 2015]
  - Taking advantage of structure
- Detecting number of clusters adaptively.
- Hot-restart information from the pass with  $k$  clusters to bootstrap clustering process with  $k + l$  clusters
- Dimensionality reduction for  $k$ -means

Thank You!