

Main List Methods In python

No.	List method	Syntax	Simple meaning	Example
1	append()	list.append(value)	Adds 1 item at the end	a.append(50)
2	extend()	list.extend(iterable)	Adds multiple items at the end	a.extend([50, 60])
3	insert()	list.insert(index, value)	Adds an item at a specific index	a.insert(1, 50)
4	remove()	list.remove(value)	Removes the given value	a.remove(20)
5	pop()	list.pop(index)	Removes the item at the given index	a.pop(2)
6	clear()	list.clear()	Empties the entire list	a.clear()
7	index()	list.index(value)	Finds the index of a value	a.index(30)
8	count()	list.count(value)	Tells how many times a value occurs	a.count(10)
9	sort()	list.sort()	Arranges the list in ascending order	a.sort()
10	reverse()	list.reverse()	Reverses the current order of the list	a.reverse()
11	copy()	list.copy()	Creates a copy of the list	b = a.copy()

Special Dunder Method In Python List

No.	Dunder method	Syntax	Simple meaning	Example
1	<code>__len__()</code>	<code>def __len__(self)</code>	Runs when <code>len()</code> is called on the object	<code>len(obj)</code>
2	<code>__getitem__()</code>	<code>def __getitem__(self, key)</code>	Runs when an item is accessed by index or key	<code>obj[0]</code>
3	<code>__setitem__()</code>	<code>def __setitem__(self, key, value)</code>	Runs when an item is set by index or key	<code>obj[0] = 10</code>
4	<code>__delitem__()</code>	<code>def __delitem__(self, key)</code>	Runs when an item is deleted by index or key	<code>del obj[0]</code>
5	<code>__contains__()</code>	<code>def __contains__(self, item)</code>	Runs when the <code>in</code> keyword is used to check membership	<code>5 in obj</code>
6	<code>__add__()</code>	<code>def __add__(self, other)</code>	Runs when two objects are added with <code>+</code>	<code>obj1 + obj2</code>
7	<code>__mul__()</code>	<code>def __mul__(self, other)</code>	Runs when the object is multiplied with <code>*</code>	<code>obj * 3</code>
8	<code>__iter__()</code>	<code>def __iter__(self)</code>	Runs when the object is looped over, makes it iterable	<code>for x in obj</code>
9	<code>__eq__()</code>	<code>def __eq__(self, other)</code>	Runs when two objects are compared with <code>==</code>	<code>obj1 == obj2</code>